



---

## HiPE

Copyright © 2006-2015 Ericsson AB. All Rights Reserved.  
HiPE 3.14  
December 18, 2015

---

**Copyright © 2006-2015 Ericsson AB. All Rights Reserved.**

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at <http://www.apache.org/licenses/LICENSE-2.0> Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License. Ericsson AB. All Rights Reserved..

**December 18, 2015**



---

# 1 Reference Manual

---

# HiPE

---

## Application

The normal way to native-compile an Erlang module using HiPE is to include the atom `native` in the Erlang compiler options, as in:

```
1> c(my_module, [native]).
```

Options to the HiPE compiler are then passed as follows:

```
1> c(my_module, [native,{hipe,Options}]).
```

For on-line help in the Erlang shell, call `hipe:help()`. Details on HiPE compiler options are given by `hipe:help_options()`.

## SEE ALSO

*c(3)*, *compile(3)*