libcaca

0.99.beta16

Generated by Doxygen 1.7.6.1

Tue Feb 28 2012 10:23:48

pt3em

Contents

1 libcaca Documentation **1**

1.1 Introduction 1

1.2 Developer's documentation 1

1.3 User's documentation 2

1.4 Misc 2

1.5 License 2

2 Libcaca authors **2**

3 Libcaca news **3**

3.1 Changes between 0.9.beta16 and 0.99.beta15 3

3.2 Changes between 0.9.beta15 and 0.99.beta14 3

3.3 Changes between 0.9.beta14 and 0.99.beta13 3

3.4 Changes between 0.9.beta13 and 0.99.beta12 3

3.5 Changes between 0.9.beta12 and 0.99.beta11 4

3.6 Changes between 0.9.beta11 and 0.99.beta10 4

3.7 Changes between 0.9.beta10 and 0.99.beta9 4

3.8 Changes between 0.9.beta9 and 0.99.beta8 4

3.9 Changes between 0.9.beta8 and 0.99.beta7 5

3.10 Changes between 0.9.beta7 and 0.99.beta6 5

3.11 Changes between 0.9.beta6 and 0.99.beta5 5

3.12 Changes between 0.9.beta5 and 0.99.beta4 5

3.13 Changes between 0.9.beta4 and 0.99.beta3 5

3.14 Changes between 0.9.beta3 and 0.99.beta2 6

3.15 Changes between 0.9.beta2 and 0.99.beta1 6

3.16 Changes between 0.9 and 0.99.beta1 6

3.17 Changes between 0.8 and 0.9 7

3.18 Changes between 0.7 and 0.8 7

3.19 Changes between 0.6 and 0.7 7

3.20 Changes between 0.5 and 0.6 7

3.21 Changes between 0.4 and 0.5 7

pt3em

3.22 Changes between 0.3 and 0.4 . . . 8
3.23 Changes between 0.2 and 0.3 . . . 8
3.24 Changes between 0.1 and 0.2 . . . 8
3.25 New in 0.1 . . . 8

4 Libcaca thanks **9**
4.1 Bugfixes and improvements . . . 9
4.2 Reused code . . . 9
4.3 Porters and packagers . . . 9

5 The libcaca canvas format (version 1) **9**

6 The libcaca font format (version 1) **10**

7 Migrating from libcaca 0.x to the 1.0 API **11**
7.1 Overview . . . 12
7.2 Migration strategy . . . 12
7.3 Function equivalence list . . . 13
7.3.1 Basic functions . . . 13
7.3.2 Event handling . . . 13
7.3.3 Character printing . . . 14
7.3.4 Primitives drawing . . . 14
7.3.5 Mathematical functions . . . 15
7.3.6 Sprite handling . . . 15
7.3.7 Bitmap handling . . . 15
7.4 Compilation . . . 16

8 Libcaca coding style **16**
8.1 General guidelines . . . 16
8.2 C coding style . . . 16
8.3 C++ coding style . . . 17

9 A libcaca tutorial **17**

10 Libcaca environment variables **18**

pt3em

11 Libcaca ruby bindings **19**

11.1 Libcaca Ruby API 19

12 Module Documentation **22**

12.1 libcaca attribute definitions 22

12.1.1 Detailed Description 23

12.1.2 Define Documentation 23

12.2 libcaca basic functions 26

12.2.1 Detailed Description 26

12.2.2 Function Documentation 26

12.3 libcaca canvas drawing 33

12.3.1 Detailed Description 33

12.3.2 Define Documentation 34

12.3.3 Function Documentation 34

12.4 libcaca canvas transformation 41

12.4.1 Detailed Description 41

12.4.2 Function Documentation 41

12.5 libcaca attribute conversions 47

12.5.1 Detailed Description 47

12.5.2 Function Documentation 47

12.6 libcaca character set conversions 55

12.6.1 Detailed Description 55

12.6.2 Function Documentation 55

12.7 libcaca primitives drawing 59

12.7.1 Detailed Description 59

12.7.2 Function Documentation 60

12.8 libcaca canvas frame handling 68

12.8.1 Detailed Description 68

12.8.2 Function Documentation 68

12.9 libcaca bitmap dithering 73

12.9.1 Detailed Description 74

12.9.2 Function Documentation 74

12.10 libcaca font handling 85

pt3em
12.10.1 Detailed Description . . . 85
12.10.2 Function Documentation . . . 85
12.11 libcaca FIGfont handling . . . 90
12.11.1 Detailed Description . . . 90
12.12 libcaca file IO . . . 92
12.12.1 Detailed Description . . . 92
12.13 libcaca importers/exporters from/to various . . . 94
12.13.1 Detailed Description . . . 94
12.14 libcaca display functions . . . 96
12.14.1 Detailed Description . . . 96
12.14.2 Function Documentation . . . 97
12.15 libcaca event handling . . . 105
12.15.1 Detailed Description . . . 105
12.15.2 Function Documentation . . . 105

13 Data Structure Documentation **111**
13.1 caca_event Struct Reference . . . 111
13.1.1 Detailed Description . . . 111

14 File Documentation **111**
14.1 caca.h File Reference . . . 111
14.1.1 Detailed Description . . . 120
14.1.2 Define Documentation . . . 120
14.1.3 Typedef Documentation . . . 120
14.1.4 Enumeration Type Documentation . . . 121

1 libcaca Documentation

1.1 Introduction

libcaca is a graphics library that outputs text instead of pixels, so that it can work on older video cards or text terminals. It is not unlike the famous AAlib library. *libcaca* can use almost any virtual terminal to work, thus it should work on all Unix systems (including Mac OS X) using either the S-Lang library or the ncurses library, on DOS using the conio library, and on Windows systems using the native Win32 console, the conio library, or using S-Lang or ncurses (through Cygwin emulation). There is also a

pt3em
native X11 driver, and an OpenGL driver (through freeglut) that does not require a text terminal. For machines without a screen, the raw driver can be used to send the output to another machine, using for instance cacaserver.

libcaca is free software, released under the Do What The Fuck You Want To Public - License. This ensures that no one, not even the *libcaca* developers, will ever have anything to say about what you do with the software. It used to be licensed under the GNU Lesser General Public License, but that was not free enough.

1.2 Developer's documentation

The complete *libcaca* programming interface is available from the following header:

- caca.h

There is language-specific documentation for the various bindings:

- Libcaca ruby bindings

Some other topics are covered by specific sections:

- A libcaca tutorial
- Migrating from libcaca 0.x to the 1.0 API

There is also information specially targeted at *libcaca* developers:

- The libcaca font format (version 1)
- The libcaca canvas format (version 1)
- Libcaca coding style

1.3 User's documentation

- Libcaca environment variables

1.4 Misc

- Libcaca news
- Libcaca authors
- Libcaca thanks

pt3em

1.5 License

Permission is granted to copy, distribute and/or modify this document under the terms of the Do What The Fuck You Want To Public License, version 2 as published by Sam Hocevar. For details see http://sam.zoy.org/wtfpl/ .

2 Libcaca authors

Sam Hocevar <sam@zoy.org>

- main programmer

Jean-Yves Lamoureux <jylam@lnxscene.org>

- cacaball
- OpenGL driver
- Pypycaca Python wrapper
- exporters
- network driver
- C# bindings

John Beppu <beppu@lbox.org>

- Term::Caca Perl wrapper

Ben Wiley Sittler <bsittler@gmail.com>

- numerous bugfixes and enhancements

Pascal Terjan <pterjan@linuxfr.org>

- Ruby bindings

Daniele "Eriol" Tricoli <eriol@mornie.org>

- Python CTypes sample program

3 Libcaca news

3.1 Changes between 0.9.beta16 and 0.99.beta15

- many build fixes, especially for nonstandard platforms

pt3em

3.2 Changes between 0.9.beta15 and 0.99.beta14

- libcucul was merged back into libcaca for more clarity

3.3 Changes between 0.9.beta14 and 0.99.beta13

- internal FIGlet font support
- use C99 types in public headers
- runtime support for output drivers
- BBcode export support

3.4 Changes between 0.9.beta13 and 0.99.beta12

- device-dependent cursor support
- event API rewrite
- minor API improvements and extensions
- img2txt improvements
- Ruby bindings
- Massive C# bindings improvements
- Python sample code
- Visual Studio build solution

3.5 Changes between 0.9.beta12 and 0.99.beta11

- support for 90-degree canvas rotation
- better behaviour when trying to output Unicode on an ASCII terminal
- the built-in font now supports the Geometric Shapes, Halfwidth and Fullwidth - Forms and Miscellaneous Symbols Unicode blocks
- new rotozoom effect in cacademo
- Cocoa output driver for Mac OS X
- preliminary .NET bindings
- many bugfixes and documentation changes

pt3em

3.6 Changes between 0.9.beta11 and 0.99.beta10

- fixed compilation of the C++ bindings
- fixed bugs in cucul_import_memory(), cucul_set_canvas_size()
- implemented caca_set_display_title() for ncurses and S-Lang
- minor bugfixes

3.7 Changes between 0.9.beta10 and 0.99.beta9

- new debug mode
- blitting canvases now makes use of the canvas' handle coordinates
- import functions can read streamed data
- attribute to colorspace transformations
- added katakana and hiragana glyphs to the built-in font
- many bugfixes and documentation changes

3.8 Changes between 0.9.beta9 and 0.99.beta8

- support for blink, bold, italics and underline attributes
- allow to import and export zero-sized canvases
- fixed Imlib2 support in cacaview
- fixed buffer overlows in the file importer
- big documentation updates

3.9 Changes between 0.9.beta8 and 0.99.beta7

- allow to build the X11 and GL drivers as separate plugins
- support for fullwidth Unicode characters
- improved cucul_flip() and cucul_rotate()
- minor bugfixes and documentation updates

pt3em

3.10 Changes between 0.9.beta7 and 0.99.beta6

- transparency support in the UTF-8 importer and exporter
- optimised triangle fill routine
- updated C++ bindings

3.11 Changes between 0.9.beta6 and 0.99.beta5

- ANSI importer now handles transparency and UTF-8
- Unicode support was broken for about 10% of the set
- various memory leaks were fixed

3.12 Changes between 0.9.beta5 and 0.99.beta4

- implemented cucul_getchar() and cucul_get_color()
- handle transparency in the IRC export
- new cropping and expanding filters
- full Unicode support in the OpenGL driver
- portability fixes for 64-bit architectures, Win32 and MS-DOS
- all demos except cacafire were merged into cacademo

3.13 Changes between 0.9.beta4 and 0.99.beta3

- added a compatibility layer for pre-1.x libcaca applications
- fixed manpage generation
- minor bugfixes and documentation updates

3.14 Changes between 0.9.beta3 and 0.99.beta2

- libcaca functions use errno for error reporting
- updated C++ bindings
- minor improvements, bugfixes and documentation updates

pt3em

3.15 Changes between 0.9.beta2 and 0.99.beta1

- ANSI importer
- functions use errno for error reporting
- updated C++ bindings
- .NET bindings
- cacadraw, an ANSI viewer that will evolve into an editor
- Unicode input and output support for SLang and ncurses
- built-in fonts work on Win32

3.16 Changes between 0.9 and 0.99.beta1

- license switched to WTFPL
- libcaca was split into libcucul, a standalone text manipulation backend, and libcaca, the display and user input frontend
- Unicode support
- TrueColor (more than 16 colours) support
- Floyd-Steinberg dithering
- gamma correction
- export functions for HTML, IRC, ANSI, SVG, PostScript, TGA...
- builtin fonts for device-independent bitmap output
- various text transformation routines (rotation, horizontal flip...)
- OpenGL renderer
- kernel mode to build libcaca programs into a bootable x86 kernel
- cacaserver, a telnet server that can be hooked to libcaca applications
- img2irc, an image to IRC conversion utility

3.17 Changes between 0.8 and 0.9

- fix for a buffer overflow in the line rendering
- fixed resizing in the ncurses and slang drivers
- aspect ratio and finer zoom support in cacaview
- minor compilation fixes

pt3em

3.18 Changes between 0.7 and 0.8

- window resizing support
- native Win32 port
- autorepeat emulation in the ncurses and slang drivers
- support for more keycodes in the ncurses and slang drivers
- cacaplas, a plasma animation example
- cacamoir, a moire circles animation example
- MSVC project file

3.19 Changes between 0.6 and 0.7

- many bugfixes in the event handling
- cacaball, a metaball animation example

3.20 Changes between 0.5 and 0.6

- 30% speed increase in the bitmap rendering routine
- mouse support and various speed optimisations in the X11 driver
- X11 is now the preferred driver
- improved documentation
- minor bugfixes

3.21 Changes between 0.4 and 0.5

- palette optimisation for the S-Lang driver to work around the colour pair shortage bug
- minor compilation fix

pt3em

3.22 Changes between 0.3 and 0.4

- preliminary X11 graphics driver
- support for simultaneously compiled-in drivers
- honour the CACA_DRIVER, CACA_GEOMETRY and CACA_FONT environment variables
- more documentation

3.23 Changes between 0.2 and 0.3

- antialiasing support
- dithering, antialiasing and background mode can now be selected at runtime or in the environment using the CACA_BACKGROUND, CACA_DITHERING and CACA_ANTIALIASING variables
- alpha channel support in cacaview
- BMP loading support in cacaview even if Imlib2 is not present
- cacafire, a libcaca port of aafire

3.24 Changes between 0.1 and 0.2

- rendering now uses 256 colour pairs instead of 16
- mouse support for ncurses
- ncurses is now the preferred backend
- arbitrary color depth and bitmasks in the bitmap renderer
- cacaview, an image viewer based on libcaca

3.25 New in 0.1

- initial release
- slang, ncurses and conio drivers
- basic line, box, ellipse and triangle primitives
- colour bitmap blitting

pt3em

4 Libcaca thanks

4.1 Bugfixes and improvements

- Gildas Bazin <gbazin@netcourrier.com> - win32 driver improvements
- Jari Komppa <jari.komppa at gmail> - win32 speed improvements

4.2 Reused code

- Jan Hubicka <hubicka@freesoft.cz> - aafire
- Michele Bini <mibin@tin.it> - original SDL plasma
- Free Software Foundation, Inc. - multiboot.S

4.3 Porters and packagers

- Derk-Jan Hartman <thedj@users.sourceforge.net> - Gentoo ebuild file
- Ladislav Hagara <hgr@vabo.cz> - Source Mage spell
- Philip Balinov - Slackware package
- Richard Zidlicky <rz@linux-m68k.org> - rpm specfile
- Thomas Klausner <wiz@NetBSD.org> - NetBSD port maintainer
- Vincent Tantardini <vinc@FreeBSD-fr.org> - FreeBSD port maintainer

5 The libcaca canvas format (version 1)

All types are big endian.

```
struct
{
magic:
   uint8_t caca_header[2];    // "\xCA\xCA"
   uint8_t caca_file_type[2]; // "CV"

canvas_header:
   uint32_t control_size;     // Control size (canvas_data - canvas_header)
   uint32_t data_size;        // Data size (EOF - canvas_data)

   uint16_t version;          // Canvas format version
                              //  bit 0: set to 1 if canvas is compatible
```

```
pt3em
                              //         with version 1 of the format
                              //  bits 1-15: unused yet, must be 0

   uint32_t frames;           // Frame count

   uint16_t flags;            // Feature flags
                              //  bits 0-15: unused yet, must be 0

frame_info:
   struct
   {
      uint32_t width;         // Frame width
      uint32_t height;        // Frame height
      uint32_t duration;      // Frame duration in milliseconds, 0 to
                              // not specify a duration
      uint32_t attr;          // Graphics context attribute
      int32_t cursor_x;       // Cursor X coordinate
      int32_t cursor_y;       // Cursor Y coordinate
      int32_t handle_x;       // Handle X coordinate
      int32_t handle_y;       // Handle Y coordinate
   }
   frame_list[frames];

control_extension_1:
control_extension_2:
   ...
control_extension_N:
   ...                        // reserved for future use

canvas_data:
   uint8_t data[data_size];   // canvas data

data_extension_1:
data_extension_2:
   ...
data_extension_N:
   ...                        // reserved for future use
};
```

6 The libcaca font format (version 1)

All types are big endian.

```
struct
{
magic:
   uint8_t caca_header[2];    // "\xCA\xCA"
   uint8_t caca_file_type[2]; // "FT"

font_header:
   uint32_t control_size;     // Control size (font_data - font_header)
   uint32_t data_size;        // Data size (EOF - font_data)

   uint16_t version;          // Font format version
                              //  bit 0: set to 1 if font is compatible
                              //         with version 1 of the format
                              //  bits 1-15: unused yet, must be 0
```

```
pt3em
   uint16_t blocks;           // Number of blocks in the font
   uint32_t glyphs;           // Total number of glyphs in the font

   uint16_t bpp;              // Bits per pixel for glyph data (valid
                              // Values are 1, 2, 4 and 8)
   uint16_t width;            // Standard glyph width
   uint16_t height;           // Standard glyph height
   uint16_t maxwidth;         // Maximum glyph width
   uint16_t maxheight;        // Maximum glyph height

   uint16_t flags;            // Feature flags
                              //  bit 0: set to 1 if font is fixed width
                              //  bits 1-15: unused yet, must be 0

block_info:
   struct
   {
      uint32_t start;         // Unicode index of the first glyph
      uint32_t stop;          // Unicode index of the last glyph + 1
      uint32_t index;         // Glyph info index of the first glyph
   }
   block_list[blocks];

glyph_info:
   struct
   {
      uint16_t width;         // Glyph width in pixels
      uint16_t height;        // Glyph height in pixels
      uint32_t data_offset;   // Offset (starting from data) to the data
                              // for the first character
   }
   glyph_list[glyphs];

control_extension_1:
control_extension_2:
   ...
control_extension_N:
   ...                        // reserved for future use

font_data:
   uint8_t data[data_size];   // glyph data

data_extension_1:
data_extension_2:
   ...
data_extension_N:
   ...                        // reserved for future use
};
```

7 Migrating from libcaca 0.x to the 1.0 API

This section will guide you through the migration of a *libcaca* 0.x application to the latest API version.

pt3em

7.1 Overview

The most important change in the 1.0 API of *libcaca* is the object-oriented design. See these two examples for a rough idea of what changed:

pt3em

```
#include <caca.h>

/* libcaca program - 0.x API */
int main(void)
{
    /* Initialise libcaca */
    caca_init();
    /* Set window title */
    caca_set_window_title("Window");
    /* Choose drawing colours */
    caca_set_color(CACA_COLOR_BLACK,
                   CACA_COLOR_WHITE);
    /* Draw a string at (0, 0) */
    caca_putstr(0, 0, "Hello world!");
    /* Refresh display */
    caca_refresh();
    /* Wait for a key press event */
    caca_wait_event(CACA_EVENT_KEY_PRESS);
    /* Clean up library */
    caca_end();

    return 0;
}
```

pt3em

```
#include <caca.h>

/* libcaca program - 1.0 API */
int main(void)
{
    /* Initialise libcaca */
    caca_canvas_t *cv;
    caca_display_t *dp;
    dp = caca_create_display(cv);
    cv = caca_get_canvas(dp);
    /* Set window title */
    caca_set_display_title(dp, "Window");
    /* Choose drawing colours */
    caca_set_color_ansi(cv, CACA_BLACK,
                        CACA_WHITE);
    /* Draw a string at (0, 0) */
    caca_put_str(cv, 0, 0, "Hello world!");
    /* Refresh display */
    caca_refresh_display();
    /* Wait for a key press event */
    caca_get_event(dp, CACA_EVENT_KEY_PRESS,
                   NULL, -1);
    /* Clean up library */
    caca_free_display(dp);

    return 0;
}
```

Note the following important things:

- Functions now take an object handle as their first argument.
- All input/output functions start with **caca_** and all drawing and text handling functions start with **caca_** .

7.2 Migration strategy

You have two ways to migrate your application to use *libcaca* 1.x:

- Port your code using the function equivalence list. This is the preferred way because new functions are thread safe and offer much more features to both the programmer and the end user.
- Use the legacy compatibility layer.

Using the compatibility layer is as easy as adding the following three lines:

pt3em

pt3em	pt3em

`#include <caca.h>`
 	
`/* libcaca program - 0.x API */`
`...`
	`#include <caca.h>`
	`#ifdef CACA_API_VERSION_1`
	`#  include <caca0.h>`
	`#endif`
	
	`/* libcaca program - 0.x API */`
	`...`

7.3 Function equivalence list

7.3.1 Basic functions

- **caca_init()**: use caca_create_canvas() to create a *libcaca* canvas, followed by caca_create_display() to attach a *libcaca* display to it.
- **caca_set_delay()**: use caca_set_display_time().
- **caca_get_feature()**: deprecated.
- **caca_set_feature()**: deprecated, see caca_set_dither_antialias(), caca_set_dither_color() and caca_set_dither_mode() instead.
- **caca_get_feature_name()**: deprecated, see caca_get_dither_mode_list(), caca_get_dither_antialias_list() and caca_get_dither_color_list() instead.
- **caca_get_rendertime()**: use caca_get_display_time().
- **caca_get_width()**: use caca_get_canvas_width().
- **caca_get_height()**: use caca_get_canvas_height().
- **caca_set_window_title()**: use caca_set_display_title().
- **caca_get_window_width()**: use caca_get_display_width().
- **caca_get_window_height()**: use caca_get_display_height().
- **caca_refresh()**: use caca_refresh_display().
- **caca_end()**: use caca_free_display() to detach the *libcaca* display, followed by caca_free_canvas() to free the underlying *libcaca* canvas.

7.3.2 Event handling

- **caca_get_event()**: unchanged, but the event information retrieval changed a lot.
- **caca_wait_event()**: use caca_get_event() with a `timeout` argument of **-1**.
- **caca_get_mouse_x()**: unchanged.
- **caca_get_mouse_y()**: unchanged.

pt3em

7.3.3 Character printing

- **caca_set_color()**: use caca_set_color_ansi() or caca_set_color_argb().
- **caca_get_fg_color()**: use caca_get_attr().
- **caca_get_bg_color()**: use caca_get_attr().
- **caca_get_color_name()**: this function is now deprecated due to major uselessness.
- **caca_putchar()**: use caca_put_char().
- **caca_putstr()**: use caca_put_str().
- **caca_printf()**: use caca_printf().
- **caca_clear()**: use caca_clear_canvas().

7.3.4 Primitives drawing

These functions are almost unchanged, except for Unicode support and the fact that they now act on a given canvas.

- **caca_draw_line()**: use caca_draw_line().
- **caca_draw_polyline()**: use caca_draw_polyline().
- **caca_draw_thin_line()**: use caca_draw_thin_line().
- **caca_draw_thin_polyline()**: use caca_draw_thin_polyline().
- **caca_draw_circle()**: use caca_draw_circle().
- **caca_draw_ellipse()**: use caca_draw_ellipse().
- **caca_draw_thin_ellipse()**: use caca_draw_thin_ellipse().
- **caca_fill_ellipse()**: use caca_fill_ellipse().
- **caca_draw_box()**: use caca_draw_box().
- **caca_draw_thin_box()**: use caca_draw_thin_box() or caca_draw_cp437_box().
- **caca_fill_box()**: use caca_fill_box().
- **caca_draw_triangle()**: use caca_draw_triangle().
- **caca_draw_thin_triangle()**: use caca_draw_thin_triangle().
- **caca_fill_triangle()**: use caca_fill_triangle().

pt3em

7.3.5 Mathematical functions

- **caca_rand()**: use caca_rand(). The second argument is different, make sure you take that into account.
- **caca_sqrt()**: this function is now deprecated, use your system's **sqrt()** call instead.

7.3.6 Sprite handling

The newly introduced canvases can have several frames. Sprites are hence completely deprecated.

- **caca_load_sprite()**: use caca_import_file().
- **caca_get_sprite_frames()**: use caca_get_frame_count().
- **caca_get_sprite_width()**: use caca_get_canvas_width().
- **caca_get_sprite_height()**: use caca_get_canvas_height().
- **caca_get_sprite_dx()**: use caca_get_canvas_handle_x().
- **caca_get_sprite_dy()**: use caca_get_canvas_handle_y().
- **caca_draw_sprite()**: use caca_set_frame() and caca_blit().
- **caca_free_sprite()**: use caca_free_canvas().

7.3.7 Bitmap handling

Bitmaps have been renamed to dithers, because these objects do not in fact store any pixels, they just have information on how bitmaps will be dithered.

- **caca_create_bitmap()**: use caca_create_dither().
- **caca_set_bitmap_palette()**: use caca_set_dither_palette().
- **caca_draw_bitmap()**: use caca_dither_bitmap().
- **caca_free_bitmap()**: use caca_free_dither().

pt3em

7.4 Compilation

The `caca-config` utility is deprecated in favour of the standard `pkg-config` interface:

```
gcc -c foobar.c -o foobar.o `pkg-config --cflags caca`
gcc foobar.o -o foobar `pkg-config --libs caca`
```

`caca-config` is still provided as a convenience tool but may be removed in the future.

8 Libcaca coding style

8.1 General guidelines

A pretty safe rule of thumb is: look at what has already been done and try to do the same.

- Tabulations should be avoided and replaced with *eight* spaces.
- Indentation is generally 4 spaces.
- Lines should wrap at most at 79 characters.
- Do not leave whitespace at the end of lines.
- Do not use multiple spaces for anything else than indentation.
- Code qui fait des warnings == code de porc == deux baffes dans ta gueule

8.2 C coding style

Try to use short names whenever possible (`i` for indices, `w` for width, `cv` for canvas...). Macros are always uppercase, variable and function names are always lowercase. Use the underscore to separate words within names:

```
#define BROKEN 0
#define MAX(x, y) ((x > y) ? (x) : (y))

unsigned int x, y, w, h;
char *font_name;
void frobulate_every_three_seconds(void);
```

`const` is a *suffix*. It's `char const *foo`, not `const char *foo`.

Use spaces after commas and between operators. Do not use spaces after an opening parenthesis or before a closing one:

```
pt3em
```

```
a += 2;
b = (a * (c + d));
x = min(x1, x2, x3);
```

Do not put a space between functions and the corresponding opening parenthesis:

```
int function(int);

if(a == b)
    return;
```

Do not put parentheses around return values:

```
return a + (b & x) + d[10];
```

Opening braces should be on a line of their own, aligned with the current block. Braces are optional for one-liners:

```
int function(int a)
{
    if(a & 0x84)
        return a;

    if(a < 0)
    {
        return -a;
    }
    else
    {
        a /= 2;

        switch(a)
        {
            case 0:
            case 1:
                return -1;
                break;
            default:
                return a;
        }
    }
}
```

8.3 C++ coding style

Nothing here yet.

9 A libcaca tutorial

First, a very simple working program, to check for basic libcaca functionalities.

```
pt3em

#include <caca.h>

int main(void)
{
    caca_canvas_t *cv; caca_display_t *dp; caca_event_t ev;

    dp = caca_create_display(NULL);
    if(!dp) return 1;
    cv = caca_get_canvas(dp);

    caca_set_display_title(dp, "Hello!");
    caca_set_color_ansi(cv, CACA_BLACK, CACA_WHITE);
    caca_put_str(cv, 0, 0, "This is a message");
    caca_refresh_display(dp);
    caca_get_event(dp, CACA_EVENT_KEY_PRESS, &ev, -1);
    caca_free_display(dp);

    return 0;
}
```

What does it do?

- Create a display. Physically, the display is either a window or a context in a terminal (ncurses, slang) or even the whole screen (VGA).
- Get the display's associated canvas. A canvas is the surface where everything happens: writing characters, sprites, strings, images... It is unavoidable. Here the size of the canvas is set by the display.
- Set the display's window name (only available in windowed displays, does nothing otherwise).
- Set the current canvas colours to black background and white foreground.
- Write the string "This is a message" using the current colors onto the canvas.
- Refresh the display.
- Wait for an event of type "CACA_EVENT_KEY_PRESS".
- Free the display (release memory). Since it was created together with the display, the canvas will be automatically freed as well.

You can then compile this code on an UNIX-like system using the following comman (requiring pkg-config and gcc):

```
gcc `pkg-config --libs --cflags caca` example.c -o example
```

10 Libcaca environment variables

Some environment variables can be used to change the behaviour of *libcaca* without having to modify the program which uses them. These variables are:

pt3em

- **CACA_DRIVER:** set the backend video driver. In order of preference:
  - `conio` uses the DOS conio.h interface.
  - `ncurses` uses the ncurses library.
  - `slang` uses the S-Lang library.
  - `x11` uses the native X11 driver.
  - `gl` uses freeglut and opengl libraries.
  - `raw` outputs to the standard output instead of rendering the canvas. This is can be used together with cacaserver.

- **CACA_GEOMETRY:** set the video display size. The format of this variable must be `XxY`, with `X` and `Y` being integer values. This option currently works with the raw, X11 and GL drivers.

- **CACA_FONT:** set the rendered font. The format of this variable is implementation dependent, but since it currently only works with the X11 driver, an X11 font name such as `fixed` or `5x7` is expected.

11 Libcaca ruby bindings

There is no real documentation yet for the Ruby binding but `methods` on any object should help you :)

I tried to follow Ruby spirit meaning that :

- most of the methods return self
- the methods set_foo with only an argument are also available as foo= (returning the value instead of self)
- the methods originally named get_foo are available only as foo

For the list of methods and some sample code, read:

Libcaca Ruby API

11.1 Libcaca Ruby API

Theclasses available for libcaca are :

- **Caca::Canvas** : functions that have a caca_canvas_t∗ as first argument
- **Caca::Dither** : functions that have a caca_dither_t∗ as first argument
- **Caca::Font** : functions that have a caca_font_t∗ as first argument (The constructor can currently only accept the name of a builtin font)

pt3em

- **Caca::Display**
- **Caca::Event**
- **Caca::Event::Key**
- **Caca::Event::Key::Press**
- **Caca::Event::Key::Release**
- **Caca::Event::Mouse**
- **Caca::Event::Mouse::Press**
- **Caca::Event::Mouse::Release**
- **Caca::Event::Mouse::Motion**
- **Caca::Event::Resize**
- **Caca::Event::Quit**

Thecharacter set conversion functions are not available yet in the binding.

```
$irb -rcaca
irb(main):001:0>class Object
irb(main):002:1>def Object.my_instance_methods
irb(main):003:2>instance_methods.sort - ancestors[1].instance_methods
irb(main):004:2>end
irb(main):005:1>def Object.my_methods
irb(main):006:2>methods.sort - ancestors[1].methods
irb(main):007:2>end
irb(main):008:1>end


irb(main):009:0>Caca.constants
=>["BROWN", "BOLD", "GREEN", "LIGHTMAGENTA", "LIGHTBLUE", "BLINK",
"MAGENTA","DEFAULT", "TRANSPARENT", "BLUE", "LIGHTRED", "DARKGRAY",
"UNDERLINE","RED", "WHITE", "BLACK", "LIGHTCYAN", "LIGHTGRAY",
"ITALICS","CYAN", "YELLOW", "LIGHTGREEN", "Canvas", "Dither", "Font"]


irb(main):010:0>Caca.my_methods
=>["version"]


irb(main):011:0>Caca::Canvas.my_methods
=>["export_list", "import_list"]


irb(main):012:0>Caca::Canvas.my_instance_methods
=>["attr=", "blit", "clear", "create_frame", "cursor_x", "cursor_y",
"dither_bitmap","draw_box", "draw_circle", "draw_cp437_box", "draw_ellipse",
"draw_line","draw_polyline", "draw_thin_box", "draw_thin_ellipse",
"draw_thin_line","draw_thin_polyline", "draw_thin_triangle",
"draw_triangle","export_memory", "fill_box", "fill_ellipse",
"fill_triangle","flip", "flop", "frame=", "frame_count", "frame_name",
"frame_name=","free_frame", "get_attr", "get_char", "gotoxy",
"handle_x","handle_y", "height", "height=", "import_file",
"import_memory","invert", "printf", "put_attr", "put_char", "put_str",
```

```
pt3em
"rotate_180","rotate_left", "rotate_right", "set_attr",
"set_boundaries","set_color_ansi", "set_color_argb", "set_frame",
"set_frame_name","set_handle", "set_height", "set_size", "set_width",
"stretch_left","stretch_right", "width", "width="]


irb(main):013:0>Caca::Font.my_methods
=>["list"]


irb(main):014:0>Caca::Font.my_instance_methods
=>["blocks", "height", "width"]


irb(main):015:0>Caca::Dither.my_instance_methods
=>["algorithm=", "algorithm_list", "antialias=", "antialias_list",
"brightness=","charset=", "charset_list", "color=", "color_list",
"contrast=","gamma=", "palette=", "set_algorithm", "set_antialias",
"set_brightness","set_charset", "set_color", "set_contrast",
"set_gamma","set_palette"]


irb(main):010:0>Caca::Display.my_instance_methods
=>["canvas", "get_event", "height", "mouse=", "mouse_x", "mouse_y", "refresh",
"set_mouse","set_time", "set_title", "time", "time=", "title=", "width"]


irb(main):011:0>Caca::Event.constants
=>["Key", "Quit", "TYPE", "Mouse", "Resize"]


irb(main):012:0>Caca::Event.my_instance_methods
=>["quit?"]


irb(main):013:0>Caca::Event::Key.my_instance_methods
=>["ch", "utf32", "utf8"]


irb(main):014:0>Caca::Event::Mouse.my_instance_methods
=>["button", "x", "y"]


irb(main):015:0>Caca::Event::Resize.my_instance_methods
=>["w", "h"]


$ruby -rcaca -e 'c=Caca::Canvas.new(6, 3).fill_box(0,0,2,2,"#"[0]);
c2=Caca::Canvas.new(1,1).put_str(0,0,"x"); c.blit(1,1,c2); puts
c.export_memory("irc")'
###
#x#
###


$ruby -e 'puts Caca::Canvas.new(6,3).draw_thin_polyline([[0,0], [0,2],
[5,2],[0,0]]).export_memory("irc")'
-.
|`.
----`-


$ruby -rcaca -e 'p Caca::Canvas.export_list'
[["caca","native libcaca format"], ["ansi", "ANSI"], ["utf8", "UTF-8
withANSI escape codes"], ["utf8cr", "UTF-8 with ANSI escape codes and
MS-DOS\\r"], ["html", "HTML"], ["html3", "backwards-compatible HTML"],
["irc","IRC with mIRC colours"], ["ps", "PostScript document"], ["svg",
"SVGvector image"], ["tga", "TGA image"]]
```

```
pt3em


$ruby -rcaca -e 'p Caca::Font.list'
["Monospace9", "Monospace Bold 12"]


require'caca'
c= Caca::Canvas.new(20,10)
c.put_str(2,3, "plop!")
c.draw_thin_polyline([[0,0],[0,2], [5,2], [0,0]])
d= Caca::Display.new(c)
d.title= "Test !"
d.refresh

#Redefine Event::Key#quit? so that q, Q, and Esc become exit keys
moduleCaca
class Event::Key
def quit?
"qQ^[".split('').member?(@ch.chr)
end
end
end

while((e= d.get_event(Caca::Event, -1)) && ! e.quit?)
p e
d.refresh
end
```

12 Module Documentation

12.1 libcaca attribute definitions

Defines

- #define CACA_BLACK 0x00
- #define CACA_BLUE 0x01
- #define CACA_GREEN 0x02
- #define CACA_CYAN 0x03
- #define CACA_RED 0x04
- #define CACA_MAGENTA 0x05
- #define CACA_BROWN 0x06
- #define CACA_LIGHTGRAY 0x07
- #define CACA_DARKGRAY 0x08
- #define CACA_LIGHTBLUE 0x09
- #define CACA_LIGHTGREEN 0x0a
- #define CACA_LIGHTCYAN 0x0b
- #define CACA_LIGHTRED 0x0c
- #define CACA_LIGHTMAGENTA 0x0d
- #define CACA_YELLOW 0x0e
- #define CACA_WHITE 0x0f
- #define CACA_DEFAULT 0x10
- #define CACA_TRANSPARENT 0x20

pt3em

- #define CACA_BOLD 0x01
- #define CACA_ITALICS 0x02
- #define CACA_UNDERLINE 0x04
- #define CACA_BLINK 0x08

12.1.1 Detailed Description

Colours and styles that can be used with caca_set_attr().

12.1.2 Define Documentation

12.1.2.1 #define CACA_BLACK 0x00

The colour index for black.

Referenced by caca_attr_to_ansi(), caca_attr_to_argb64(), caca_attr_to_rgb12_bg(), and caca_dither_bitmap().

12.1.2.2 #define CACA_BLUE 0x01

The colour index for blue.

12.1.2.3 #define CACA_GREEN 0x02

The colour index for green.

12.1.2.4 #define CACA_CYAN 0x03

The colour index for cyan.

12.1.2.5 #define CACA_RED 0x04

The colour index for red.

12.1.2.6 #define CACA_MAGENTA 0x05

The colour index for magenta.

12.1.2.7 #define CACA_BROWN 0x06

The colour index for brown.

12.1.2.8 #define CACA_LIGHTGRAY 0x07

The colour index for light gray.

Referenced by caca_attr_to_ansi(), caca_attr_to_argb64(), and caca_attr_to_rgb12_fg().

pt3em

12.1.2.9 #define CACA_DARKGRAY 0x08

The colour index for dark gray.

12.1.2.10 #define CACA_LIGHTBLUE 0x09

The colour index for blue.

12.1.2.11 #define CACA_LIGHTGREEN 0x0a

The colour index for light green.

12.1.2.12 #define CACA_LIGHTCYAN 0x0b

The colour index for light cyan.

12.1.2.13 #define CACA_LIGHTRED 0x0c

The colour index for light red.

12.1.2.14 #define CACA_LIGHTMAGENTA 0x0d

The colour index for light magenta.

12.1.2.15 #define CACA_YELLOW 0x0e

The colour index for yellow.

12.1.2.16 #define CACA_WHITE 0x0f

The colour index for white.

12.1.2.17 #define CACA_DEFAULT 0x10

The output driver's default colour.

Referenced by caca_attr_to_argb64(), caca_attr_to_rgb12_bg(), caca_attr_to_rgb12_-fg(), and caca_create_canvas().

12.1.2.18 #define CACA_TRANSPARENT 0x20

The transparent colour.

Referenced by caca_attr_to_argb64(), caca_attr_to_rgb12_bg(), caca_attr_to_rgb12_-fg(), and caca_create_canvas().

12.1.2.19 #define CACA_BOLD 0x01

The style mask for bold.

pt3em

12.1.2.20 #define CACA_ITALICS 0x02

The style mask for italics.

12.1.2.21 #define CACA_UNDERLINE 0x04

The style mask for underline.

12.1.2.22 #define CACA_BLINK 0x08

The style mask for blink.

pt3em

12.2 libcaca basic functions

Functions

- __extern caca_canvas_t * caca_create_canvas (int, int)
  Initialise a libcaca canvas.
- __extern int caca_manage_canvas (caca_canvas_t *, int(*)(void *), void *)
  Manage a canvas.
- __extern int caca_unmanage_canvas (caca_canvas_t *, int(*)(void *), void *)
  Unmanage a canvas.
- __extern int caca_set_canvas_size (caca_canvas_t *, int, int)
  Resize a canvas.
- __extern int caca_get_canvas_width (caca_canvas_t const *)
  Get the canvas width.
- __extern int caca_get_canvas_height (caca_canvas_t const *)
  Get the canvas height.
- __extern uint8_t const * caca_get_canvas_chars (caca_canvas_t const *)
  Get the canvas character array.
- __extern uint8_t const * caca_get_canvas_attrs (caca_canvas_t const *)
  Get the canvas attribute array.
- __extern int caca_free_canvas (caca_canvas_t *)
  Uninitialise libcaca.
- __extern int caca_rand (int, int)
  Generate a random integer within a range.
- __extern char const * caca_get_version (void)
  Return the libcaca version.

12.2.1 Detailed Description

These functions provide the basic *libcaca* routines for library initialisation, system information retrieval and configuration.

12.2.2 Function Documentation

12.2.2.1 __extern caca_canvas_t* caca_create_canvas (int *width*, int *height*)

Initialise internal *libcaca* structures and the backend that will be used for subsequent graphical operations. It must be the first *libcaca* function to be called in a function. caca_free_canvas() should be called at the end of the program to free all allocated resources.

Both the cursor and the canvas' handle are initialised at the top-left corner.

If an error occurs, NULL is returned and **errno** is set accordingly:

pt3em

- EINVAL Specified width or height is invalid.
- ENOMEM Not enough memory for the requested canvas size.

pt3em**Parameters**

pt3em*width*	pt3emThe desired canvas width
pt3em*height*	pt3emThe desired canvas height

pt3em**Returns**

A libcaca canvas handle upon success, NULL if an error occurred.

References CACA_DEFAULT, caca_set_color_ansi(), and CACA_TRANSPARENT.

Referenced by caca_create_display_with_driver(), and caca_set_canvas_boundaries().

12.2.2.2 __extern int caca_manage_canvas (caca_canvas_t * *cv*, int(*)(void *) *callback*, void * *p*)

Lock a canvas to prevent it from being resized. If non-NULL, the *callback* function pointer will be called upon each *caca_set_canvas_size* call and if the returned value is zero, the canvas resize request will be denied.

This function is only useful for display drivers such as the *libcaca* library.

If an error occurs, -1 is returned and **errno** is set accordingly:

- EBUSY The canvas is already being managed.

pt3em**Parameters**

pt3em*cv*	pt3emA libcaca canvas.
pt3em *callback*	pt3emAn optional callback function pointer.
pt3em*p*	pt3emThe argument to be passed to *callback*.

pt3em

pt3emReturns

0 in case of success, -1 if an error occurred.

Referenced by caca_create_display_with_driver().

12.2.2.3 extern int caca_unmanage_canvas (caca_canvas_t * *cv*, int(*)(void *) *callback*, void * *p*)

Unlock a canvas previously locked by caca_manage_canvas(). For safety reasons, the callback and callback data arguments must be the same as for the caca_manage_canvas() call.

This function is only useful for display drivers such as the *libcaca* library.

If an error occurs, -1 is returned and **errno** is set accordingly:

- EINVAL The canvas is not managed, or the callback arguments do not match.

pt3emParameters

pt3em	pt3em*cv*	pt3emA libcaca canvas.
	pt3em *callback*	pt3emThe *callback* argument previously passed to caca_manage_canvas().
	pt3em*p*	pt3emThe *p* argument previously passed to caca_manage_canvas().

pt3emReturns

0 in case of success, -1 if an error occurred.

Referenced by caca_create_display_with_driver(), and caca_free_display().

12.2.2.4 extern int caca_set_canvas_size (caca_canvas_t * *cv*, int *width*, int *height*)

Set the canvas' width and height, in character cells.

The contents of the canvas are preserved to the extent of the new canvas size. Newly allocated character cells at the right and/or at the bottom of the canvas are filled with spaces.

If as a result of the resize the cursor coordinates fall outside the new canvas boundaries, they are readjusted. For instance, if the current X cursor coordinate is 11 and the requested width is 10, the new X cursor coordinate will be 10.

It is an error to try to resize the canvas if an output driver has been attached to the canvas using caca_create_display(). You need to remove the output driver using caca_free_display() before you can change the canvas size again. However, the caca output driver can cause a canvas resize through user interaction. See the caca_event() documentation for more about this.

pt3em

If an error occurs, -1 is returned and **errno** is set accordingly:

- `EINVAL` Specified width or height is invalid.
- `EBUSY` The canvas is in use by a display driver and cannot be resized.
- `ENOMEM` Not enough memory for the requested canvas size. If this happens, the canvas handle becomes invalid and should not be used.

pt3em**Parameters**

pt3em	pt3em*cv*	pt3emA libcaca canvas.
	pt3em*width*	pt3emThe desired canvas width.
	pt3em*height*	pt3emThe desired canvas height.

pt3em**Returns**

0 in case of success, -1 if an error occurred.

12.2.2.5 __extern int **caca_get_canvas_width** (**caca_canvas_t const** * ***cv***)

Return the current canvas' width, in character cells.

This function never fails.

pt3em**Parameters**

pt3em	pt3em*cv*	pt3emA libcaca canvas.

pt3em**Returns**

The canvas width.

Referenced by caca_get_mouse_x().

12.2.2.6 __extern int **caca_get_canvas_height** (**caca_canvas_t const** * ***cv***)

Returns the current canvas' height, in character cells.

This function never fails.

pt3em**Parameters**

pt3em	pt3em*cv*	pt3emA libcaca canvas.

pt3em

pt3emReturns

The canvas height.

Referenced by caca_get_mouse_y().

12.2.2.7 __extern uint8_t const* caca_get_canvas_chars (caca_canvas_t const * *cv*)

Return the current canvas' internal character array. The array elements consist in native endian 32-bit Unicode values as returned by caca_get_char().

This function is only useful for display drivers such as the *libcaca* library.

This function never fails.

pt3emParameters

pt3empt3em*cv*	pt3emA libcaca canvas.

pt3emReturns

The canvas character array.

12.2.2.8 __extern uint8_t const* caca_get_canvas_attrs (caca_canvas_t const * *cv*)

Returns the current canvas' internal attribute array. The array elements consist in native endian 32-bit attribute values as returned by caca_get_attr().

This function is only useful for display drivers such as the *libcaca* library.

This function never fails.

pt3emParameters

pt3empt3em*cv*	pt3emA libcaca canvas.

pt3emReturns

The canvas attribute array.

12.2.2.9 __extern int caca_free_canvas (caca_canvas_t * *cv*)

Free all resources allocated by caca_create_canvas(). After this function has been called, no other *libcaca* functions may be used unless a new call to caca_create_canvas() is done.

If an error occurs, -1 is returned and **errno** is set accordingly:

- EBUSY The canvas is in use by a display driver and cannot be freed.

pt3em

pt3emParameters

pt3empt3em*cv*	pt3emA libcaca canvas.

pt3emReturns

0 in case of success, -1 if an error occurred.

Referenced by caca_create_display_with_driver(), and caca_free_display().

12.2.2.10 __extern int caca_rand (int *min*, int *max*)

Generate a random integer within the given range.

This function never fails.

pt3emParameters

pt3empt3em*min*	pt3emThe lower bound of the integer range.
pt3em*max*	pt3emThe upper bound of the integer range.

pt3emReturns

A random integer comprised between `min` and `max` - 1 (inclusive).

12.2.2.11 __extern char const* caca_get_version (void)

Return a read-only string with the *libcaca* version information.

This function never fails.

pt3emReturns

The *libcaca* version information.

pt3em

pt3em

12.3 libcaca canvas drawing

Defines

- #define CACA_MAGIC_FULLWIDTH 0x000ffffe

Functions

- __extern int caca_gotoxy (caca_canvas_t *, int, int)

  Set cursor position.
- __extern int caca_get_cursor_x (caca_canvas_t const *)

  Get X cursor position.
- __extern int caca_get_cursor_y (caca_canvas_t const *)

  Get Y cursor position.
- __extern int caca_put_char (caca_canvas_t *, int, int, uint32_t)

  Print an ASCII or Unicode character.
- __extern uint32_t caca_get_char (caca_canvas_t const *, int, int)

  Get the Unicode character at the given coordinates.
- __extern int caca_put_str (caca_canvas_t *, int, int, char const *)

  Print a string.
- __extern int caca_printf (caca_canvas_t *, int, int, char const *,...)

  Print a formated string.
- __extern int caca_clear_canvas (caca_canvas_t *)

  Clear the canvas.
- __extern int caca_set_canvas_handle (caca_canvas_t *, int, int)

  Set cursor handle.
- __extern int caca_get_canvas_handle_x (caca_canvas_t const *)

  Get X handle position.
- __extern int caca_get_canvas_handle_y (caca_canvas_t const *)

  Get Y handle position.
- __extern int caca_blit (caca_canvas_t *, int, int, caca_canvas_t const *, caca_canvas_t const *)

  Blit a canvas onto another one.
- __extern int caca_set_canvas_boundaries (caca_canvas_t *, int, int, int, int)

  Set a canvas' new boundaries.

12.3.1 Detailed Description

These functions provide low-level character printing routines and higher level graphics functions.

pt3em

12.3.2 Define Documentation

12.3.2.1 #define CACA_MAGIC_FULLWIDTH 0x000ffffe

Used to indicate that the previous character was a fullwidth glyph.

Referenced by caca_blit(), caca_flip(), caca_put_attr(), caca_put_char(), and caca_rotate_180().

12.3.3 Function Documentation

12.3.3.1 __extern int caca_gotoxy (caca_canvas_t * *cv,* int *x,* int *y*)

Put the cursor at the given coordinates. Functions making use of the cursor will use the new values. Setting the cursor position outside the canvas is legal but the cursor will not be shown.

This function never fails.

pt3em**Parameters**

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.
	pt3em*x*	pt3emX cursor coordinate.
	pt3em*y*	pt3emY cursor coordinate.

pt3em**Returns**

This function always returns 0.

12.3.3.2 __extern int caca_get_cursor_x (caca_canvas_t const * *cv*)

Retrieve the X coordinate of the cursor's position.

This function never fails.

pt3em**Parameters**

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.

pt3em**Returns**

The cursor's X coordinate.

12.3.3.3 __extern int caca_get_cursor_y (caca_canvas_t const * *cv*)

Retrieve the Y coordinate of the cursor's position.

pt3em

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.

pt3emReturns

The cursor's Y coordinate.

12.3.3.4 __extern int caca_put_char (caca_canvas_t * *cv*, int *x*, int *y*, uint32_t *ch*)

Print an ASCII or Unicode character at the given coordinates, using the default foreground and background colour values.

If the coordinates are outside the canvas boundaries, nothing is printed. If a fullwidth Unicode character gets overwritten, its remaining visible parts are replaced with spaces. If the canvas' boundaries would split the fullwidth character in two, a space is printed instead.

The behaviour when printing non-printable characters or invalid UTF-32 characters is undefined. To print a sequence of bytes forming an UTF-8 character instead of an UTF-32 character, use the caca_put_str() function.

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.
	pt3em*x*	pt3emX coordinate.
	pt3em*y*	pt3emY coordinate.
	pt3em*ch*	pt3emThe character to print.

pt3emReturns

This function always returns 0.

References CACA_MAGIC_FULLWIDTH, and caca_utf32_is_fullwidth().

Referenced by caca_dither_bitmap(), caca_draw_cp437_box(), caca_draw_thin_box(), caca_fill_box(), caca_fill_triangle(), and caca_put_str().

12.3.3.5 __extern uint32_t caca_get_char (caca_canvas_t const * *cv*, int *x*, int *y*)

Get the ASCII or Unicode value of the character at the given coordinates. If the value is less or equal to 127 (0x7f), the character can be printed as ASCII. Otherise, it must be handled as a UTF-32 value.

If the coordinates are outside the canvas boundaries, a space (0x20) is returned.

pt3em

A special exception is when CACA_MAGIC_FULLWIDTH is returned. This value is guaranteed not to be a valid Unicode character, and indicates that the character at the left of the requested one is a fullwidth character.

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.
	pt3em*x*	pt3emX coordinate.
	pt3em*y*	pt3emY coordinate.

pt3emReturns

This function always returns 0.

12.3.3.6 __extern int caca_put_str (caca_canvas_t * *cv*, int *x*, int *y*, char const * *s*)

Print an UTF-8 string at the given coordinates, using the default foreground and background values. The coordinates may be outside the canvas boundaries (eg. a negative Y coordinate) and the string will be cropped accordingly if it is too long.

See caca_put_char() for more information on how fullwidth characters are handled when overwriting each other or at the canvas' boundaries.

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.
	pt3em*x*	pt3emX coordinate.
	pt3em*y*	pt3emY coordinate.
	pt3em*s*	pt3emThe string to print.

pt3emReturns

This function always returns 0.

References caca_put_char(), caca_utf32_is_fullwidth(), and caca_utf8_to_utf32().

Referenced by caca_printf().

12.3.3.7 __extern int caca_printf (caca_canvas_t * *cv*, int *x*, int *y*, char const * *format*, ...)

Format a string at the given coordinates, using the default foreground and background values. The coordinates may be outside the canvas boundaries (eg. a negative Y coordinate) and the string will be cropped accordingly if it is too long. The syntax of the format string is the same as for the C printf() function.

pt3em

This function never fails.

pt3em**Parameters**

pt3em pt3em*cv*	pt3emA handle to the libcaca canvas.
pt3em*x*	pt3emX coordinate.
pt3em*y*	pt3emY coordinate.
pt3em*format*	pt3emThe format string to print.
pt3em...	pt3emArguments to the format string.

pt3em**Returns**

This function always returns 0.

References caca_put_str().

12.3.3.8 __extern int **caca_clear_canvas** (**caca_canvas_t** ∗ ***cv***)

Clear the canvas using the current foreground and background colours.

This function never fails.

pt3em**Parameters**

pt3em pt3em*cv*	pt3emThe canvas to clear.

pt3em**Returns**

This function always returns 0.

12.3.3.9 __extern int **caca_set_canvas_handle** (**caca_canvas_t** ∗ ***cv,*** **int** ***x,*** **int** ***y***)

Set the canvas' handle. Blitting functions will use the handle value to put the canvas at the proper coordinates.

This function never fails.

pt3em**Parameters**

pt3em pt3em*cv*	pt3emA handle to the libcaca canvas.
pt3em*x*	pt3emX handle coordinate.
pt3em*y*	pt3emY handle coordinate.

pt3em**Returns**

This function always returns 0.

pt3em

12.3.3.10 __extern int caca_get_canvas_handle_x (caca_canvas_t const * *cv*)

Retrieve the X coordinate of the canvas' handle.

This function never fails.

pt3em**Parameters**

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.

pt3em**Returns**

The canvas' handle's X coordinate.

12.3.3.11 __extern int caca_get_canvas_handle_y (caca_canvas_t const * *cv*)

Retrieve the Y coordinate of the canvas' handle.

This function never fails.

pt3em**Parameters**

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.

pt3em**Returns**

The canvas' handle's Y coordinate.

12.3.3.12 __extern int caca_blit (caca_canvas_t * *dst,* int *x,* int *y,* caca_canvas_t const * *src,* caca_canvas_t const * *mask*)

Blit a canvas onto another one at the given coordinates. An optional mask canvas can be used.

If an error occurs, -1 is returned and **errno** is set accordingly:

- `EINVAL` A mask was specified but the mask size and source canvas size do not match.

pt3em**Parameters**

pt3em	pt3em*dst*	pt3emThe destination canvas.
	pt3em*x*	pt3emX coordinate.
	pt3em*y*	pt3emY coordinate.
	pt3em*src*	pt3emThe source canvas.
	pt3em*mask*	pt3emThe mask canvas.

pt3em

pt3em**Returns**

0 in case of success, -1 if an error occurred.

References CACA_MAGIC_FULLWIDTH.

Referenced by caca_set_canvas_boundaries().

12.3.3.13 __extern int **caca_set_canvas_boundaries** (**caca_canvas_t** * ***cv***, **int** ***x***, **int** ***y***, **int** ***w***, **int** ***h***)

Set new boundaries for a canvas. This function can be used to crop a canvas, to expand it or for combinations of both actions. All frames are affected by this function.

If an error occurs, -1 is returned and **errno** is set accordingly:

- `EINVAL` Specified width or height is invalid.
- `EBUSY` The canvas is in use by a display driver and cannot be resized.
- `ENOMEM` Not enough memory for the requested canvas size. If this happens, the canvas handle becomes invalid and should not be used.

pt3em**Parameters**

pt3em	pt3em*cv*	pt3emThe canvas to crop.
	pt3em*x*	pt3emX coordinate of the top-left corner.
	pt3em*y*	pt3emY coordinate of the top-left corner.
	pt3em*w*	pt3emThe width of the cropped area.
	pt3em*h*	pt3emThe height of the cropped area.

pt3em**Returns**

0 in case of success, -1 if an error occurred.

References caca_blit(), caca_create_canvas(), caca_create_frame(), caca_get_frame_count(), and caca_set_frame().

pt3em

pt3em

12.4 libcaca canvas transformation

Functions

- __extern int caca_invert (caca_canvas_t *)
  Invert a canvas' colours.
- __extern int caca_flip (caca_canvas_t *)
  Flip a canvas horizontally.
- __extern int caca_flop (caca_canvas_t *)
  Flip a canvas vertically.
- __extern int caca_rotate_180 (caca_canvas_t *)
  Rotate a canvas.
- __extern int caca_rotate_left (caca_canvas_t *)
  Rotate a canvas, 90 degrees counterclockwise.
- __extern int caca_rotate_right (caca_canvas_t *)
  Rotate a canvas, 90 degrees counterclockwise.
- __extern int caca_stretch_left (caca_canvas_t *)
  Rotate and stretch a canvas, 90 degrees counterclockwise.
- __extern int caca_stretch_right (caca_canvas_t *)
  Rotate and stretch a canvas, 90 degrees clockwise.

12.4.1 Detailed Description

These functions perform horizontal and vertical canvas flipping.

12.4.2 Function Documentation

12.4.2.1 __extern int caca_invert (caca_canvas_t * *cv*)

Invert a canvas' colours (black becomes white, red becomes cyan, etc.) without changing the characters in it.

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emThe canvas to invert.

pt3emReturns

This function always returns 0.

pt3em

12.4.2.2 __extern int caca_flip (caca_canvas_t * cv)

Flip a canvas horizontally, choosing characters that look like the mirrored version wherever possible. Some characters will stay unchanged by the process, but the operation is guaranteed to be involutive: performing it again gives back the original canvas.

This function never fails.

pt3emParameters

pt3em	pt3emcv	pt3emThe canvas to flip.

pt3emReturns

This function always returns 0.

References CACA_MAGIC_FULLWIDTH.

12.4.2.3 __extern int caca_flop (caca_canvas_t * cv)

Flip a canvas vertically, choosing characters that look like the mirrored version wherever possible. Some characters will stay unchanged by the process, but the operation is guaranteed to be involutive: performing it again gives back the original canvas.

This function never fails.

pt3emParameters

pt3em	pt3emcv	pt3emThe canvas to flop.

pt3emReturns

This function always returns 0.

12.4.2.4 __extern int caca_rotate_180 (caca_canvas_t * cv)

Apply a 180-degree transformation to a canvas, choosing characters that look like the upside-down version wherever possible. Some characters will stay unchanged by the process, but the operation is guaranteed to be involutive: performing it again gives back the original canvas.

This function never fails.

pt3emParameters

pt3em	pt3emcv	pt3emThe canvas to rotate.

pt3em

pt3emReturns

This function always returns 0.

References CACA_MAGIC_FULLWIDTH.

12.4.2.5 __extern int caca_rotate_left (caca_canvas_t * *cv*)

Apply a 90-degree transformation to a canvas, choosing characters that look like the rotated version wherever possible. Characters cells are rotated two-by-two. Some characters will stay unchanged by the process, some others will be replaced by close equivalents. Fullwidth characters at odd horizontal coordinates will be lost. The operation is not guaranteed to be reversible at all.

Note that the width of the canvas is divided by two and becomes the new height. Height is multiplied by two and becomes the new width. If the original width is an odd number, the division is rounded up.

If an error occurs, -1 is returned and **errno** is set accordingly:

- EBUSY The canvas is in use by a display driver and cannot be rotated.
- ENOMEM Not enough memory to allocate the new canvas size. If this happens, the previous canvas handle is still valid.

pt3emParameters

pt3em	pt3em*cv*	pt3emThe canvas to rotate left.

pt3emReturns

0 in case of success, -1 if an error occurred.

12.4.2.6 __extern int caca_rotate_right (caca_canvas_t * *cv*)

Apply a 90-degree transformation to a canvas, choosing characters that look like the rotated version wherever possible. Characters cells are rotated two-by-two. Some characters will stay unchanged by the process, some others will be replaced by close equivalents. Fullwidth characters at odd horizontal coordinates will be lost. The operation is not guaranteed to be reversible at all.

Note that the width of the canvas is divided by two and becomes the new height. Height is multiplied by two and becomes the new width. If the original width is an odd number, the division is rounded up.

If an error occurs, -1 is returned and **errno** is set accordingly:

- EBUSY The canvas is in use by a display driver and cannot be rotated.

pt3em

- ENOMEM Not enough memory to allocate the new canvas size. If this happens, the previous canvas handle is still valid.

pt3emParameters

pt3em	pt3emcv	pt3emThe canvas to rotate right.

pt3emReturns

0 in case of success, -1 if an error occurred.

12.4.2.7 __extern int caca_stretch_left (caca_canvas_t * cv)

Apply a 90-degree transformation to a canvas, choosing characters that look like the rotated version wherever possible. Some characters will stay unchanged by the process, some others will be replaced by close equivalents. Fullwidth characters will be lost. The operation is not guaranteed to be reversible at all.

Note that the width and height of the canvas are swapped, causing its aspect ratio to look stretched.

If an error occurs, -1 is returned and **errno** is set accordingly:

- EBUSY The canvas is in use by a display driver and cannot be rotated.
- ENOMEM Not enough memory to allocate the new canvas size. If this happens, the previous canvas handle is still valid.

pt3emParameters

pt3em	pt3emcv	pt3emThe canvas to rotate left.

pt3emReturns

0 in case of success, -1 if an error occurred.

12.4.2.8 __extern int caca_stretch_right (caca_canvas_t * cv)

Apply a 270-degree transformation to a canvas, choosing characters that look like the rotated version wherever possible. Some characters will stay unchanged by the process, some others will be replaced by close equivalents. Fullwidth characters will be lost. The operation is not guaranteed to be reversible at all.

Note that the width and height of the canvas are swapped, causing its aspect ratio to look stretched.

If an error occurs, -1 is returned and **errno** is set accordingly:

pt3em

- EBUSY The canvas is in use by a display driver and cannot be rotated.
- ENOMEM Not enough memory to allocate the new canvas size. If this happens, the previous canvas handle is still valid.

pt3emParameters

pt3empt3em*cv*	pt3emThe canvas to rotate right.

pt3emReturns

0 in case of success, -1 if an error occurred.

pt3em

pt3em

12.5 libcaca attribute conversions

Functions

- __extern uint32_t caca_get_attr (caca_canvas_t const *, int, int)
  Get the text attribute at the given coordinates.
- __extern int caca_set_attr (caca_canvas_t *, uint32_t)
  Set the default character attribute.
- __extern int caca_put_attr (caca_canvas_t *, int, int, uint32_t)
  Set the character attribute at the given coordinates.
- __extern int caca_set_color_ansi (caca_canvas_t *, uint8_t, uint8_t)
  Set the default colour pair for text (ANSI version).
- __extern int caca_set_color_argb (caca_canvas_t *, uint16_t, uint16_t)
  Set the default colour pair for text (truecolor version).
- __extern uint8_t caca_attr_to_ansi (uint32_t)
  Get DOS ANSI information from attribute.
- __extern uint8_t caca_attr_to_ansi_fg (uint32_t)
  Get ANSI foreground information from attribute.
- __extern uint8_t caca_attr_to_ansi_bg (uint32_t)
  Get ANSI background information from attribute.
- __extern uint16_t caca_attr_to_rgb12_fg (uint32_t)
  Get 12-bit RGB foreground information from attribute.
- __extern uint16_t caca_attr_to_rgb12_bg (uint32_t)
  Get 12-bit RGB background information from attribute.
- __extern void caca_attr_to_argb64 (uint32_t, uint8_t[8])
  Get 64-bit ARGB information from attribute.

12.5.1 Detailed Description

These functions perform conversions between attribute values.

12.5.2 Function Documentation

12.5.2.1 __extern uint32_t caca_get_attr (caca_canvas_t const * *cv*, int *x*, int *y*)

Get the internal *libcaca* attribute value of the character at the given coordinates. The attribute value has 32 significant bits, organised as follows from MSB to LSB:

- 3 bits for the background alpha
- 4 bits for the background red component
- 4 bits for the background green component

pt3em

- 3 bits for the background blue component
- 3 bits for the foreground alpha
- 4 bits for the foreground red component
- 4 bits for the foreground green component
- 3 bits for the foreground blue component
- 4 bits for the bold, italics, underline and blink flags

If the coordinates are outside the canvas boundaries, the current attribute is returned.

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.
	pt3em*x*	pt3emX coordinate.
	pt3em*y*	pt3emY coordinate.

pt3emReturns

The requested attribute.

Referenced by caca_dither_bitmap().

12.5.2.2 __extern int caca_set_attr (caca_canvas_t * *cv*, uint32_t *attr*)

Set the default character attribute for drawing. Attributes define foreground and background colour, transparency, bold, italics and underline styles, as well as blink. String functions such as caca_printf() and graphical primitive functions such as caca_draw_line() will use this attribute.

The value of *attr* is either:

- a 32-bit integer as returned by caca_get_attr(), in which case it also contains colour information,
- a combination (bitwise OR) of style values (*CACA_UNDERLINE*, *CACA_BLINK*, *CACA_BOLD* and *CACA_ITALICS*), in which case setting the attribute does not modify the current colour information.

To retrieve the current attribute value, use caca_get_attr(-1,-1).

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.
	pt3em*attr*	pt3emThe requested attribute value.

pt3em

pt3emReturns

This function always returns 0.

Referenced by caca_dither_bitmap().

12.5.2.3 __extern int caca_put_attr (caca_canvas_t * cv, int x, int y, uint32_t attr)

Set the character attribute, without changing the character's value. If the character at the given coordinates is a fullwidth character, both cells' attributes are replaced.

The value of *attr* is either:

- a 32-bit integer as returned by caca_get_attr(), in which case it also contains colour information,
- a combination (bitwise OR) of style values (*CACA_UNDERLINE*, *CACA_BLINK*, *CACA_BOLD* and *CACA_ITALICS*), in which case setting the attribute does not modify the current colour information.

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.
	pt3em*x*	pt3emX coordinate.
	pt3em*y*	pt3emY coordinate.
	pt3em*attr*	pt3emThe requested attribute value.

pt3emReturns

This function always returns 0.

References CACA_MAGIC_FULLWIDTH.

12.5.2.4 __extern int caca_set_color_ansi (caca_canvas_t * cv, uint8_t fg, uint8_t bg)

Set the default ANSI colour pair for text drawing. String functions such as caca_printf() and graphical primitive functions such as caca_draw_line() will use these attributes.

Color values are those defined in caca.h, such as CACA_RED or CACA_TRANSPARENT.

If an error occurs, 0 is returned and **errno** is set accordingly:

- `EINVAL` At least one of the colour values is invalid.

pt3em

pt3emParameters

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.
	pt3em*fg*	pt3emThe requested ANSI foreground colour.
	pt3em*bg*	pt3emThe requested ANSI background colour.

pt3emReturns

0 in case of success, -1 if an error occurred.

Referenced by caca_create_canvas(), and caca_dither_bitmap().

12.5.2.5 __extern int caca_set_color_argb (caca_canvas_t * *cv*, uint16_t *fg*, uint16_t *bg*)

Set the default ARGB colour pair for text drawing. String functions such as caca_printf() and graphical primitive functions such as caca_draw_line() will use these attributes.

Colors are 16-bit ARGB values, each component being coded on 4 bits. For instance, 0xf088 is solid dark cyan (A=15 R=0 G=8 B=8), and 0x8fff is white with 50% alpha (A=8 R=15 G=15 B=15).

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.
	pt3em*fg*	pt3emThe requested ARGB foreground colour.
	pt3em*bg*	pt3emThe requested ARGB background colour.

pt3emReturns

This function always returns 0.

12.5.2.6 __extern uint8_t caca_attr_to_ansi (uint32_t *attr*)

Get the ANSI colour pair for a given attribute. The returned value is an 8-bit value whose higher 4 bits are the background colour and lower 4 bits are the foreground colour.

If the attribute has ARGB colours, the nearest colour is used. Special attributes such as *CACA_DEFAULT* and *CACA_TRANSPARENT* are not handled and are both replaced with *CACA_LIGHTGRAY* for the foreground colour and *CACA_BLACK* for the background colour.

This function never fails. If the attribute value is outside the expected 32-bit range, higher order bits are simply ignored.

pt3em

pt3emParameters

pt3empt3em*attr*	pt3emThe requested attribute value.

pt3emReturns

The corresponding DOS ANSI value.

References CACA_BLACK, and CACA_LIGHTGRAY.

12.5.2.7 __extern uint8_t caca_attr_to_ansi_fg (uint32_t *attr*)

Get the ANSI foreground colour value for a given attribute. The returned value is either one of the *CACA_RED*, *CACA_BLACK* etc. predefined colours, or the special value *CACA_DEFAULT* meaning the media's default foreground value, or the special value *CACA_TRANSPARENT*.

If the attribute has ARGB colours, the nearest colour is returned.

This function never fails. If the attribute value is outside the expected 32-bit range, higher order bits are simply ignored.

pt3emParameters

pt3empt3em*attr*	pt3emThe requested attribute value.

pt3emReturns

The corresponding ANSI foreground value.

12.5.2.8 __extern uint8_t caca_attr_to_ansi_bg (uint32_t *attr*)

Get the ANSI background colour value for a given attribute. The returned value is either one of the *CACA_RED*, *CACA_BLACK* etc. predefined colours, or the special value *CACA_DEFAULT* meaning the media's default background value, or the special value *CACA_TRANSPARENT*.

If the attribute has ARGB colours, the nearest colour is returned.

This function never fails. If the attribute value is outside the expected 32-bit range, higher order bits are simply ignored.

pt3emParameters

pt3empt3em*attr*	pt3emThe requested attribute value.

pt3em

pt3emReturns

The corresponding ANSI background value.

12.5.2.9 __extern uint16_t caca_attr_to_rgb12_fg (uint32_t *attr*)

Get the 12-bit foreground colour value for a given attribute. The returned value is a native-endian encoded integer with each red, green and blue values encoded on 8 bits in the following order:

- 8-11 most significant bits: red
- 4-7 most significant bits: green
- least significant bits: blue

This function never fails. If the attribute value is outside the expected 32-bit range, higher order bits are simply ignored.

pt3emParameters

pt3empt3em*attr*	pt3emThe requested attribute value.

pt3emReturns

The corresponding 12-bit RGB foreground value.

References CACA_DEFAULT, CACA_LIGHTGRAY, and CACA_TRANSPARENT.

12.5.2.10 __extern uint16_t caca_attr_to_rgb12_bg (uint32_t *attr*)

Get the 12-bit background colour value for a given attribute. The returned value is a native-endian encoded integer with each red, green and blue values encoded on 8 bits in the following order:

- 8-11 most significant bits: red
- 4-7 most significant bits: green
- least significant bits: blue

This function never fails. If the attribute value is outside the expected 32-bit range, higher order bits are simply ignored.

pt3emParameters

pt3empt3em*attr*	pt3emThe requested attribute value.

pt3em

pt3emReturns

The corresponding 12-bit RGB background value.

References CACA_BLACK, CACA_DEFAULT, and CACA_TRANSPARENT.

12.5.2.11 __extern void caca_attr_to_argb64 (uint32_t *attr,* uint8_t *argb[8]*)

Get the 64-bit colour and alpha values for a given attribute. The values are written as 8-bit integers in the *argb* array in the following order:

- *argb*[0]: background alpha value
- *argb*[1]: background red value
- *argb*[2]: background green value
- *argb*[3]: background blue value
- *argb*[4]: foreground alpha value
- *argb*[5]: foreground red value
- *argb*[6]: foreground green value
- *argb*[7]: foreground blue value

This function never fails. If the attribute value is outside the expected 32-bit range, higher order bits are simply ignored.

pt3emParameters

pt3empt3em*attr*	pt3emThe requested attribute value.
pt3em*argb*	pt3emAn array of 8-bit integers.

References CACA_BLACK, CACA_DEFAULT, CACA_LIGHTGRAY, and CACA_TRANSPARENT.

Referenced by caca_render_canvas().

pt3em

pt3em

12.6 libcaca character set conversions

Functions

- __extern uint32_t caca_utf8_to_utf32 (char const *, size_t *)

  Convert a UTF-8 character to UTF-32.
- __extern size_t caca_utf32_to_utf8 (char *, uint32_t)

  Convert a UTF-32 character to UTF-8.
- __extern uint8_t caca_utf32_to_cp437 (uint32_t)

  Convert a UTF-32 character to CP437.
- __extern uint32_t caca_cp437_to_utf32 (uint8_t)

  Convert a CP437 character to UTF-32.
- __extern char caca_utf32_to_ascii (uint32_t)

  Convert a UTF-32 character to ASCII.
- __extern int caca_utf32_is_fullwidth (uint32_t)

  Tell whether a UTF-32 character is fullwidth.

12.6.1 Detailed Description

These functions perform conversions between usual character sets.

12.6.2 Function Documentation

12.6.2.1 __extern uint32_t caca_utf8_to_utf32 (char const * *s*, size_t * *bytes*)

Convert a UTF-8 character read from a string and return its value in the UTF-32 character set. If the second argument is not null, the total number of read bytes is written in it.

If a null byte was reached before the expected end of the UTF-8 sequence, this function returns zero and the number of read bytes is set to zero.

This function never fails, but its behaviour with illegal UTF-8 sequences is undefined.

pt3emParameters

pt3em pt3em*s*	pt3emA string containing the UTF-8 character.
pt3em*bytes*	pt3emA pointer to a size_t to store the number of bytes in the character, or NULL.

pt3em

pt3emReturns

The corresponding UTF-32 character, or zero if the character is incomplete.

Referenced by caca_put_str().

12.6.2.2 __extern size_t caca_utf32_to_utf8 (char * *buf,* uint32_t *ch*)

Convert a UTF-32 character read from a string and write its value in the UTF-8 character set into the given buffer.

This function never fails, but its behaviour with illegal UTF-32 characters is undefined.

pt3emParameters

pt3em	pt3em*buf*	pt3emA pointer to a character buffer where the UTF-8 sequence will be written.
	pt3em*ch*	pt3emThe UTF-32 character.

pt3emReturns

The number of bytes written.

12.6.2.3 __extern uint8_t caca_utf32_to_cp437 (uint32_t *ch*)

Convert a UTF-32 character read from a string and return its value in the CP437 character set, or "?" if the character has no equivalent.

This function never fails.

pt3emParameters

pt3em	pt3em*ch*	pt3emThe UTF-32 character.

pt3emReturns

The corresponding CP437 character, or "?" if not representable.

12.6.2.4 __extern uint32_t caca_cp437_to_utf32 (uint8_t *ch*)

Convert a CP437 character read from a string and return its value in the UTF-32 character set, or zero if the character is a CP437 control character.

This function never fails.

pt3em

pt3emParameters

pt3empt3em*ch*	pt3emThe CP437 character.

pt3emReturns

The corresponding UTF-32 character, or zero if not representable.

12.6.2.5 __extern char caca_utf32_to_ascii (uint32_t *ch*)

Convert a UTF-32 character into an ASCII character. When no equivalent exists, a graphically close equivalent is sought.

This function never fails, but its behaviour with illegal UTF-32 characters is undefined.

pt3emParameters

pt3empt3em*ch*	pt3emThe UTF-32 character.

pt3emReturns

The corresponding ASCII character, or a graphically close equivalent if found, or "?" if not representable.

12.6.2.6 __extern int caca_utf32_is_fullwidth (uint32_t *ch*)

Check whether the given UTF-32 character should be printed at twice the normal width (fullwidth characters). If the character is unknown or if its status cannot be decided, it is treated as a standard-width character.

This function never fails.

pt3emParameters

pt3empt3em*ch*	pt3emThe UTF-32 character.

pt3emReturns

1 if the character is fullwidth, 0 otherwise.

Referenced by caca_put_char(), and caca_put_str().

pt3em

pt3em

12.7 libcaca primitives drawing

Functions

- __extern int caca_draw_line (caca_canvas_t *, int, int, int, int, uint32_t)

  Draw a line on the canvas using the given character.
- __extern int caca_draw_polyline (caca_canvas_t *, int const x[], int const y[], int, uint32_t)

  Draw a polyline.
- __extern int caca_draw_thin_line (caca_canvas_t *, int, int, int, int)

  Draw a thin line on the canvas, using ASCII art.
- __extern int caca_draw_thin_polyline (caca_canvas_t *, int const x[], int const y[], int)

  Draw an ASCII art thin polyline.
- __extern int caca_draw_circle (caca_canvas_t *, int, int, int, uint32_t)

  Draw a circle on the canvas using the given character.
- __extern int caca_draw_ellipse (caca_canvas_t *, int, int, int, int, uint32_t)

  Draw an ellipse on the canvas using the given character.
- __extern int caca_draw_thin_ellipse (caca_canvas_t *, int, int, int, int)

  Draw a thin ellipse on the canvas.
- __extern int caca_fill_ellipse (caca_canvas_t *, int, int, int, int, uint32_t)

  Fill an ellipse on the canvas using the given character.
- __extern int caca_draw_box (caca_canvas_t *, int, int, int, int, uint32_t)

  Draw a box on the canvas using the given character.
- __extern int caca_draw_thin_box (caca_canvas_t *, int, int, int, int)

  Draw a thin box on the canvas.
- __extern int caca_draw_cp437_box (caca_canvas_t *, int, int, int, int)

  Draw a box on the canvas using CP437 characters.
- __extern int caca_fill_box (caca_canvas_t *, int, int, int, int, uint32_t)

  Fill a box on the canvas using the given character.
- __extern int caca_draw_triangle (caca_canvas_t *, int, int, int, int, int, int, uint32_t)

  Draw a triangle on the canvas using the given character.
- __extern int caca_draw_thin_triangle (caca_canvas_t *, int, int, int, int, int, int)

  Draw a thin triangle on the canvas.
- __extern int caca_fill_triangle (caca_canvas_t *, int, int, int, int, int, int, uint32_t)

  Fill a triangle on the canvas using the given character.

12.7.1 Detailed Description

These functions provide routines for primitive drawing, such as lines, boxes, triangles and ellipses.

pt3em

12.7.2 Function Documentation

12.7.2.1 __extern int caca_draw_line (caca_canvas_t * cv, int x1, int y1, int x2, int y2, uint32_t ch)

This function never fails.

pt3emParameters

pt3em	pt3emcv	pt3emThe handle to the libcaca canvas.
	pt3emx1	pt3emX coordinate of the first point.
	pt3emy1	pt3emY coordinate of the first point.
	pt3emx2	pt3emX coordinate of the second point.
	pt3emy2	pt3emY coordinate of the second point.
	pt3emch	pt3emUTF-32 character to be used to draw the line.

pt3emReturns

This function always returns 0.

Referenced by caca_draw_box(), caca_draw_triangle(), and caca_fill_ellipse().

12.7.2.2 __extern int caca_draw_polyline (caca_canvas_t * cv, int const x[], int const y[], int n, uint32_t ch)

Draw a polyline on the canvas using the given character and coordinate arrays. The first and last points are not connected, hence in order to draw a polygon you need to specify the starting point at the end of the list as well.

This function never fails.

pt3emParameters

pt3em	pt3emcv	pt3emThe handle to the libcaca canvas.
	pt3emx	pt3emArray of X coordinates. Must have n + 1 elements.
	pt3emy	pt3emArray of Y coordinates. Must have n + 1 elements.
	pt3emn	pt3emNumber of lines to draw.
	pt3emch	pt3emUTF-32 character to be used to draw the lines.

pt3em

pt3emReturns

This function always returns 0.

12.7.2.3 __extern int caca_draw_thin_line (caca_canvas_t * cv, int x1, int y1, int x2, int y2)

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emThe handle to the libcaca canvas.
	pt3em*x1*	pt3emX coordinate of the first point.
	pt3em*y1*	pt3emY coordinate of the first point.
	pt3em*x2*	pt3emX coordinate of the second point.
	pt3em*y2*	pt3emY coordinate of the second point.

pt3emReturns

This function always returns 0.

Referenced by caca_draw_thin_triangle().

12.7.2.4 __extern int caca_draw_thin_polyline (caca_canvas_t * cv, int const x[], int const y[], int n)

Draw a thin polyline on the canvas using the given coordinate arrays and with ASCII art. The first and last points are not connected, so in order to draw a polygon you need to specify the starting point at the end of the list as well.

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emThe handle to the libcaca canvas.
	pt3em*x*	pt3emArray of X coordinates. Must have n + 1 elements.
	pt3em*y*	pt3emArray of Y coordinates. Must have n + 1 elements.
	pt3em*n*	pt3emNumber of lines to draw.

pt3emReturns

This function always returns 0.

12.7.2.5 __extern int caca_draw_circle (caca_canvas_t * cv, int x, int y, int r, uint32_t ch)

This function never fails.

pt3em

pt3emParameters

pt3em	pt3em*cv*	pt3emThe handle to the libcaca canvas.
	pt3em*x*	pt3emCenter X coordinate.
	pt3em*y*	pt3emCenter Y coordinate.
	pt3em*r*	pt3emCircle radius.
	pt3em*ch*	pt3emUTF-32 character to be used to draw the circle outline.

pt3emReturns

This function always returns 0.

12.7.2.6 __extern int caca_draw_ellipse (caca_canvas_t * *cv*, int *xo*, int *yo*, int *a*, int *b*, uint32_t *ch*)

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emThe handle to the libcaca canvas.
	pt3em*xo*	pt3emCenter X coordinate.
	pt3em*yo*	pt3emCenter Y coordinate.
	pt3em*a*	pt3emEllipse X radius.
	pt3em*b*	pt3emEllipse Y radius.
	pt3em*ch*	pt3emUTF-32 character to be used to draw the ellipse outline.

pt3emReturns

This function always returns 0.

12.7.2.7 __extern int caca_draw_thin_ellipse (caca_canvas_t * *cv*, int *xo*, int *yo*, int *a*, int *b*)

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emThe handle to the libcaca canvas.
	pt3em*xo*	pt3emCenter X coordinate.
	pt3em*yo*	pt3emCenter Y coordinate.
	pt3em*a*	pt3emEllipse X radius.
	pt3em*b*	pt3emEllipse Y radius.

pt3em

pt3em**Returns**

This function always returns 0.

12.7.2.8 __extern int **caca_fill_ellipse** (**caca_canvas_t** * *cv*, **int** *xo*, **int** *yo*, **int** *a*, **int** *b*, **uint32_t** *ch*)

This function never fails.

pt3em**Parameters**

pt3em	pt3em*cv*	pt3emThe handle to the libcaca canvas.
	pt3em*xo*	pt3emCenter X coordinate.
	pt3em*yo*	pt3emCenter Y coordinate.
	pt3em*a*	pt3emEllipse X radius.
	pt3em*b*	pt3emEllipse Y radius.
	pt3em*ch*	pt3emUTF-32 character to be used to fill the ellipse.

pt3em**Returns**

This function always returns 0.

References caca_draw_line().

12.7.2.9 __extern int **caca_draw_box** (**caca_canvas_t** * *cv*, **int** *x*, **int** *y*, **int** *w*, **int** *h*, **uint32_t** *ch*)

This function never fails.

pt3em**Parameters**

pt3em	pt3em*cv*	pt3emThe handle to the libcaca canvas.
	pt3em*x*	pt3emX coordinate of the upper-left corner of the box.
	pt3em*y*	pt3emY coordinate of the upper-left corner of the box.
	pt3em*w*	pt3emWidth of the box.
	pt3em*h*	pt3emHeight of the box.
	pt3em*ch*	pt3emUTF-32 character to be used to draw the box.

pt3em

pt3emReturns

This function always returns 0.

References caca_draw_line().

12.7.2.10 __extern int caca_draw_thin_box (caca_canvas_t * *cv*, int *x*, int *y*, int *w*, int *h*)

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emThe handle to the libcaca canvas.
	pt3em*x*	pt3emX coordinate of the upper-left corner of the box.
	pt3em*y*	pt3emY coordinate of the upper-left corner of the box.
	pt3em*w*	pt3emWidth of the box.
	pt3em*h*	pt3emHeight of the box.

pt3emReturns

This function always returns 0.

References caca_put_char().

12.7.2.11 __extern int caca_draw_cp437_box (caca_canvas_t * *cv*, int *x*, int *y*, int *w*, int *h*)

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emThe handle to the libcaca canvas.
	pt3em*x*	pt3emX coordinate of the upper-left corner of the box.
	pt3em*y*	pt3emY coordinate of the upper-left corner of the box.
	pt3em*w*	pt3emWidth of the box.
	pt3em*h*	pt3emHeight of the box.

pt3em

pt3emReturns

This function always returns 0.

References caca_put_char().

12.7.2.12 __extern int caca_fill_box (caca_canvas_t * *cv,* int *x,* int *y,* int *w,* int *h,* uint32_t *ch*)

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emThe handle to the libcaca canvas.
	pt3em*x*	pt3emX coordinate of the upper-left corner of the box.
	pt3em*y*	pt3emY coordinate of the upper-left corner of the box.
	pt3em*w*	pt3emWidth of the box.
	pt3em*h*	pt3emHeight of the box.
	pt3em*ch*	pt3emUTF-32 character to be used to draw the box.

pt3emReturns

This function always returns 0.

References caca_put_char().

12.7.2.13 __extern int caca_draw_triangle (caca_canvas_t * *cv,* int *x1,* int *y1,* int *x2,* int *y2,* int *x3,* int *y3,* uint32_t *ch*)

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emThe handle to the libcaca canvas.
	pt3em*x1*	pt3emX coordinate of the first point.
	pt3em*y1*	pt3emY coordinate of the first point.
	pt3em*x2*	pt3emX coordinate of the second point.
	pt3em*y2*	pt3emY coordinate of the second point.
	pt3em*x3*	pt3emX coordinate of the third point.
	pt3em*y3*	pt3emY coordinate of the third point.
	pt3em*ch*	pt3emUTF-32 character to be used to draw the triangle outline.

pt3emReturns

This function always returns 0.

References caca_draw_line().

pt3em

12.7.2.14 __extern int caca_draw_thin_triangle (caca_canvas_t * cv, int x1, int y1, int x2, int y2, int x3, int y3)

This function never fails.

pt3emParameters

pt3em	pt3emcv	pt3emThe handle to the libcaca canvas.
	pt3emx1	pt3emX coordinate of the first point.
	pt3emy1	pt3emY coordinate of the first point.
	pt3emx2	pt3emX coordinate of the second point.
	pt3emy2	pt3emY coordinate of the second point.
	pt3emx3	pt3emX coordinate of the third point.
	pt3emy3	pt3emY coordinate of the third point.

pt3emReturns

This function always returns 0.

References caca_draw_thin_line().

12.7.2.15 __extern int caca_fill_triangle (caca_canvas_t * cv, int x1, int y1, int x2, int y2, int x3, int y3, uint32_t ch)

This function never fails.

pt3emParameters

pt3em	pt3emcv	pt3emThe handle to the libcaca canvas.
	pt3emx1	pt3emX coordinate of the first point.
	pt3emy1	pt3emY coordinate of the first point.
	pt3emx2	pt3emX coordinate of the second point.
	pt3emy2	pt3emY coordinate of the second point.
	pt3emx3	pt3emX coordinate of the third point.
	pt3emy3	pt3emY coordinate of the third point.
	pt3emch	pt3emUTF-32 character to be used to fill the triangle.

pt3emReturns

This function always returns 0.

References caca_fill_triangle(), and caca_put_char().

Referenced by caca_fill_triangle().

pt3em

pt3em

12.8 libcaca canvas frame handling

Functions

- __extern int caca_get_frame_count (caca_canvas_t const *)
  Get the number of frames in a canvas.
- __extern int caca_set_frame (caca_canvas_t *, int)
  Activate a given canvas frame.
- __extern char const * caca_get_frame_name (caca_canvas_t const *)
  Get the current frame's name.
- __extern int caca_set_frame_name (caca_canvas_t *, char const *)
  Set the current frame's name.
- __extern int caca_create_frame (caca_canvas_t *, int)
  Add a frame to a canvas.
- __extern int caca_free_frame (caca_canvas_t *, int)
  Remove a frame from a canvas.

12.8.1 Detailed Description

These functions provide high level routines for canvas frame insertion, removal, copying etc.

12.8.2 Function Documentation

12.8.2.1 __extern int caca_get_frame_count (caca_canvas_t const * *cv*)

Return the current canvas' frame count.

This function never fails.

pt3emParameters

pt3empt3em*cv*	pt3emA libcaca canvas

pt3emReturns

The frame count

Referenced by caca_set_canvas_boundaries().

12.8.2.2 __extern int caca_set_frame (caca_canvas_t * *cv*, int *id*)

Set the active canvas frame. All subsequent drawing operations will be performed on that frame. The current painting context set by caca_set_attr() is inherited.

pt3em

If the frame index is outside the canvas' frame range, nothing happens.

If an error occurs, -1 is returned and **errno** is set accordingly:

- `EINVAL` Requested frame is out of range.

pt3emParameters

pt3em	pt3em*cv*	pt3emA libcaca canvas
	pt3em*id*	pt3emThe canvas frame to activate

pt3emReturns

0 in case of success, -1 if an error occurred.

Referenced by caca_set_canvas_boundaries().

12.8.2.3 __extern char const* caca_get_frame_name (caca_canvas_t const * *cv*)

Return the current frame's name. The returned string is valid until the frame is deleted or caca_set_frame_name() is called to change the frame name again.

This function never fails.

pt3emParameters

pt3em	pt3em*cv*	pt3emA libcaca canvas.

pt3emReturns

The current frame's name.

12.8.2.4 __extern int caca_set_frame_name (caca_canvas_t * *cv*, char const * *name*)

Set the current frame's name. Upon creation, a frame has a default name of "`frame#xxxxxxxx`" where `xxxxxxxx` is a self-incrementing hexadecimal number.

If an error occurs, -1 is returned and **errno** is set accordingly:

- `ENOMEM` Not enough memory to allocate new frame.

pt3emParameters

pt3em	pt3em*cv*	pt3emA libcaca canvas.
	pt3em*name*	pt3emThe name to give to the current frame.

pt3em

pt3emReturns

0 in case of success, -1 if an error occurred.

12.8.2.5 __extern int caca_create_frame (caca_canvas_t * cv, int id)

Create a new frame within the given canvas. Its contents and attributes are copied from the currently active frame.

The frame index indicates where the frame should be inserted. Valid values range from 0 to the current canvas frame count. If the frame index is greater than or equals the current canvas frame count, the new frame is appended at the end of the canvas. If the frame index is less than zero, the new frame is inserted at index 0.

The active frame does not change, but its index may be renumbered due to the insertion.

If an error occurs, -1 is returned and **errno** is set accordingly:

- ENOMEM Not enough memory to allocate new frame.

pt3emParameters

pt3em	pt3em*cv*	pt3emA libcaca canvas
	pt3em*id*	pt3emThe index where to insert the new frame

pt3emReturns

0 in case of success, -1 if an error occurred.

Referenced by caca_set_canvas_boundaries().

12.8.2.6 __extern int caca_free_frame (caca_canvas_t * cv, int id)

Delete a frame from a given canvas.

The frame index indicates the frame to delete. Valid values range from 0 to the current canvas frame count minus 1. If the frame index is greater than or equals the current canvas frame count, the last frame is deleted.

If the active frame is deleted, frame 0 becomes the new active frame. Otherwise, the active frame does not change, but its index may be renumbered due to the deletion.

If an error occurs, -1 is returned and **errno** is set accordingly:

- EINVAL Requested frame is out of range, or attempt to delete the last frame of the canvas.

pt3em

pt3emParameters

pt3empt3em*cv*	pt3emA libcaca canvas
pt3em*id*	pt3emThe index of the frame to delete

pt3emReturns

0 in case of success, -1 if an error occurred.

pt3em

pt3em

12.9 libcaca bitmap dithering

Functions

- __extern caca_dither_t * caca_create_dither (int, int, int, int, uint32_t, uint32_t, uint32_t, uint32_t)

  Create an internal dither object.
- __extern int caca_set_dither_palette (caca_dither_t *, uint32_t r[], uint32_t g[], uint32_t b[], uint32_t a[])

  Set the palette of an 8bpp dither object.
- __extern int caca_set_dither_brightness (caca_dither_t *, float)

  Set the brightness of a dither object.
- __extern float caca_get_dither_brightness (caca_dither_t const *)

  Get the brightness of a dither object.
- __extern int caca_set_dither_gamma (caca_dither_t *, float)

  Set the gamma of a dither object.
- __extern float caca_get_dither_gamma (caca_dither_t const *)

  Get the gamma of a dither object.
- __extern int caca_set_dither_contrast (caca_dither_t *, float)

  Set the contrast of a dither object.
- __extern float caca_get_dither_contrast (caca_dither_t const *)

  Get the contrast of a dither object.
- __extern int caca_set_dither_antialias (caca_dither_t *, char const *)

  Set dither antialiasing.
- __extern char const *const * caca_get_dither_antialias_list (caca_dither_t const *)

  Get available antialiasing methods.
- __extern char const * caca_get_dither_antialias (caca_dither_t const *)

  Get current antialiasing method.
- __extern int caca_set_dither_color (caca_dither_t *, char const *)

  Choose colours used for dithering.
- __extern char const *const * caca_get_dither_color_list (caca_dither_t const *)

  Get available colour modes.
- __extern char const * caca_get_dither_color (caca_dither_t const *)

  Get current colour mode.
- __extern int caca_set_dither_charset (caca_dither_t *, char const *)

  Choose characters used for dithering.
- __extern char const *const * caca_get_dither_charset_list (caca_dither_t const *)

  Get available dither character sets.
- __extern char const * caca_get_dither_charset (caca_dither_t const *)

pt3em

Get current character set.

- __extern int caca_set_dither_algorithm (caca_dither_t ∗, char const ∗)

  Set dithering algorithm.

- __extern char const ∗const ∗ caca_get_dither_algorithm_list (caca_dither_t const ∗)

  Get dithering algorithms.

- __extern char const ∗ caca_get_dither_algorithm (caca_dither_t const ∗)

  Get current dithering algorithm.

- __extern int caca_dither_bitmap (caca_canvas_t ∗, int, int, int, int, caca_dither_t const ∗, void ∗)

  Dither a bitmap on the canvas.

- __extern int caca_free_dither (caca_dither_t ∗)

  Free the memory associated with a dither.

12.9.1 Detailed Description

These functions provide high level routines for dither allocation and rendering.

12.9.2 Function Documentation

12.9.2.1 __extern **caca_dither_t**∗ **caca_create_dither** (**int** *bpp,* **int** *w,* **int** *h,* **int** *pitch,* **uint32_t** *rmask,* **uint32_t** *gmask,* **uint32_t** *bmask,* **uint32_t** *amask*)

Create a dither structure from its coordinates (depth, width, height and pitch) and pixel mask values. If the depth is 8 bits per pixel, the mask values are ignored and the colour palette should be set using the caca_set_dither_palette() function. For depths greater than 8 bits per pixel, a zero alpha mask causes the alpha values to be ignored.

If an error occurs, NULL is returned and **errno** is set accordingly:

- `EINVAL` Requested width, height, pitch or bits per pixel value was invalid.
- `ENOMEM` Not enough memory to allocate dither structure.

pt3em**Parameters**

pt3empt3em*bpp*	pt3emBitmap depth in bits per pixel.
pt3em*w*	pt3emBitmap width in pixels.
pt3em*h*	pt3emBitmap height in pixels.
pt3em*pitch*	pt3emBitmap pitch in bytes.
pt3em*rmask*	pt3emBitmask for red values.
pt3em*gmask*	pt3emBitmask for green values.
pt3em*bmask*	pt3emBitmask for blue values.
pt3em*amask*	pt3emBitmask for alpha values.

pt3em

pt3em**Returns**

Dither object upon success, NULL if an error occurred.

12.9.2.2 __extern int **caca_set_dither_palette** (**caca_dither_t** * *d,* **uint32_t** *red[],* **uint32_t** *green[],* **uint32_t** *blue[],* **uint32_t** *alpha[]*)

Set the palette of an 8 bits per pixel bitmap. Values should be between 0 and 4095 (0xfff).

If an error occurs, -1 is returned and **errno** is set accordingly:

- `EINVAL` Dither bits per pixel value is not 8, or one of the pixel values was outside the range 0 - 4095.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.
pt3em*red*	pt3emArray of 256 red values.
pt3em*green*	pt3emArray of 256 green values.
pt3em*blue*	pt3emArray of 256 blue values.
pt3em*alpha*	pt3emArray of 256 alpha values.

pt3em**Returns**

0 in case of success, -1 if an error occurred.

12.9.2.3 __extern int **caca_set_dither_brightness** (**caca_dither_t** * *d,* **float** *brightness*)

Set the brightness of dither.

If an error occurs, -1 is returned and **errno** is set accordingly:

- `EINVAL` Brightness value was out of range.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.
pt3em *brightness*	pt3embrightness value.

pt3em**Returns**

0 in case of success, -1 if an error occurred.

pt3em

12.9.2.4 __extern float **caca_get_dither_brightness** (**caca_dither_t** const * *d*)

Get the brightness of the given dither object.

This function never fails.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.

pt3em**Returns**

Brightness value.

12.9.2.5 __extern int **caca_set_dither_gamma** (**caca_dither_t** * *d,* float *gamma*)

Set the gamma of the given dither object. A negative value causes colour inversion.

If an error occurs, -1 is returned and **errno** is set accordingly:

- `EINVAL` Gamma value was out of range.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.
pt3em *gamma*	pt3emGamma value.

pt3em**Returns**

0 in case of success, -1 if an error occurred.

12.9.2.6 __extern float **caca_get_dither_gamma** (**caca_dither_t** const * *d*)

Get the gamma of the given dither object.

This function never fails.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.

pt3em**Returns**

Gamma value.

pt3em

12.9.2.7 __extern int **caca_set_dither_contrast** (**caca_dither_t** ∗ ***d,*** **float** ***contrast***)

Set the contrast of dither.

If an error occurs, -1 is returned and **errno** is set accordingly:

- `EINVAL` Contrast value was out of range.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.
pt3em *contrast*	pt3emcontrast value.

pt3em**Returns**

0 in case of success, -1 if an error occurred.

12.9.2.8 __extern float **caca_get_dither_contrast** (**caca_dither_t** const ∗ ***d***)

Get the contrast of the given dither object.

This function never fails.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.

pt3em**Returns**

Contrast value.

12.9.2.9 __extern int **caca_set_dither_antialias** (**caca_dither_t** ∗ ***d,*** **char** const ∗ ***str***)

Tell the renderer whether to antialias the dither. Antialiasing smoothens the rendered image and avoids the commonly seen staircase effect.

- `"none"`: no antialiasing.
- `"prefilter"` or `"default"`: simple prefilter antialiasing. This is the default value.

If an error occurs, -1 is returned and **errno** is set accordingly:

- `EINVAL` Invalid antialiasing mode.

pt3em

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.
pt3em*str*	pt3emA string describing the antialiasing method that will be used for the dithering.

pt3em**Returns**

0 in case of success, -1 if an error occurred.

12.9.2.10 __extern char const* const* caca_get_dither_antialias_list (caca_dither_t const * *d*)

Return a list of available antialiasing methods for a given dither. The list is a NULL-terminated array of strings, interleaving a string containing the internal value for the antialiasing method to be used with caca_set_dither_antialias(), and a string containing the natural language description for that antialiasing method.

This function never fails.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.

pt3em**Returns**

An array of strings.

12.9.2.11 __extern char const* caca_get_dither_antialias (caca_dither_t const * *d*)

Return the given dither's current antialiasing method.

This function never fails.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.

pt3em**Returns**

A static string.

12.9.2.12 __extern int caca_set_dither_color (caca_dither_t * *d,* char const * *str*)

Tell the renderer which colours should be used to render the bitmap. Valid values for `str` are:

pt3em

- `"mono"`: use light gray on a black background.
- `"gray"`: use white and two shades of gray on a black background.
- `"8"`: use the 8 ANSI colours on a black background.
- `"16"`: use the 16 ANSI colours on a black background.
- `"fullgray"`: use black, white and two shades of gray for both the characters and the background.
- `"full8"`: use the 8 ANSI colours for both the characters and the background.
- `"full16"` or `"default"`: use the 16 ANSI colours for both the characters and the background. This is the default value.

If an error occurs, -1 is returned and **errno** is set accordingly:

- `EINVAL` Invalid colour set.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.
pt3em*str*	pt3emA string describing the colour set that will be used for the dithering.

pt3em**Returns**

0 in case of success, -1 if an error occurred.

12.9.2.13 __extern char const* const* caca_get_dither_color_list (caca_dither_t const * *d*)

Return a list of available colour modes for a given dither. The list is a NULL-terminated array of strings, interleaving a string containing the internal value for the colour mode, to be used with caca_set_dither_color(), and a string containing the natural language description for that colour mode.

This function never fails.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.

pt3em**Returns**

An array of strings.

pt3em

12.9.2.14 __extern char const* caca_get_dither_color (caca_dither_t const * *d*)

Return the given dither's current colour mode.

This function never fails.

pt3em**Parameters**

pt3em	pt3em*d*	pt3emDither object.

pt3em**Returns**

A static string.

12.9.2.15 __extern int caca_set_dither_charset (caca_dither_t * *d,* char const * *str*)

Tell the renderer which characters should be used to render the dither. Valid values for `str` are:

- `"ascii"` or `"default"`: use only ASCII characters. This is the default value.
- `"shades"`: use Unicode characters "U+2591 LIGHT SHADE", "U+2592 MEDIUM SHADE" and "U+2593 DARK SHADE". These characters are also present in the CP437 codepage available on DOS and VGA.
- `"blocks"`: use Unicode quarter-cell block combinations. These characters are only found in the Unicode set.

If an error occurs, -1 is returned and **errno** is set accordingly:

- `EINVAL` Invalid character set.

pt3em**Parameters**

pt3em	pt3em*d*	pt3emDither object.
	pt3em*str*	pt3emA string describing the characters that need to be used for the dithering.

pt3em**Returns**

0 in case of success, -1 if an error occurred.

12.9.2.16 __extern char const* const* caca_get_dither_charset_list (caca_dither_t const * *d*)

Return a list of available character sets for a given dither. The list is a NULL-terminated array of strings, interleaving a string containing the internal value for the character set,

pt3em
to be used with caca_set_dither_charset(), and a string containing the natural language description for that character set.

This function never fails.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.

pt3em**Returns**

An array of strings.

12.9.2.17 __extern char const* caca_get_dither_charset (caca_dither_t const * *d*)

Return the given dither's current character set.

This function never fails.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.

pt3em**Returns**

A static string.

12.9.2.18 __extern int caca_set_dither_algorithm (caca_dither_t * *d*, char const * *str*)

Tell the renderer which dithering algorithm should be used. Dithering is necessary because the picture being rendered has usually far more colours than the available palette. Valid values for `str` are:

- `"none"`: no dithering is used, the nearest matching colour is used.
- `"ordered2"`: use a 2x2 Bayer matrix for dithering.
- `"ordered4"`: use a 4x4 Bayer matrix for dithering.
- `"ordered8"`: use a 8x8 Bayer matrix for dithering.
- `"random"`: use random dithering.
- `"fstein"`: use Floyd-Steinberg dithering. This is the default value.

If an error occurs, -1 is returned and **errno** is set accordingly:

- `EINVAL` Unknown dithering mode.

pt3em

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.
pt3em*str*	pt3emA string describing the algorithm that needs to be used for the dithering.

pt3em**Returns**

0 in case of success, -1 if an error occurred.

12.9.2.19 __extern char const* const* caca_get_dither_algorithm_list (caca_dither_t const * *d*)

Return a list of available dithering algorithms for a given dither. The list is a NULL-terminated array of strings, interleaving a string containing the internal value for the dithering algorithm, to be used with caca_set_dither_dithering(), and a string containing the natural language description for that algorithm.

This function never fails.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.

pt3em**Returns**

An array of strings.

12.9.2.20 __extern char const* caca_get_dither_algorithm (caca_dither_t const * *d*)

Return the given dither's current dithering algorithm.

This function never fails.

pt3em**Parameters**

pt3em pt3em*d*	pt3emDither object.

pt3em

pt3em**Returns**

A static string.

12.9.2.21 __extern int **caca_dither_bitmap** (**caca_canvas_t** * ***cv*,** **int** ***x*,** **int** ***y*,** **int** ***w*,** **int** ***h*,** **caca_dither_t const** * ***d*,** **void** * ***pixels***)

Dither a bitmap at the given coordinates. The dither can be of any size and will be stretched to the text area.

This function never fails.

pt3em**Parameters**

pt3em	pt3em*cv*	pt3emA handle to the libcaca canvas.
	pt3em*x*	pt3emX coordinate of the upper-left corner of the drawing area.
	pt3em*y*	pt3emY coordinate of the upper-left corner of the drawing area.
	pt3em*w*	pt3emWidth of the drawing area.
	pt3em*h*	pt3emHeight of the drawing area.
	pt3em*d*	pt3emDither object to be drawn.
	pt3em*pixels*	pt3emBitmap's pixels.

pt3em**Returns**

This function always returns 0.

References CACA_BLACK, caca_get_attr(), caca_put_char(), caca_set_attr(), and caca_set_color_ansi().

12.9.2.22 __extern int **caca_free_dither** (**caca_dither_t** * ***d***)

Free the memory allocated by caca_create_dither().

This function never fails.

pt3em**Parameters**

pt3em	pt3em*d*	pt3emDither object.

pt3em**Returns**

This function always returns 0.

pt3em

pt3em

12.10 libcaca font handling

Functions

- __extern caca_font_t * caca_load_font (void const *, size_t)
  Load a font from memory for future use.
- __extern char const *const * caca_get_font_list (void)
  Get available builtin fonts.
- __extern int caca_get_font_width (caca_font_t const *)
  Get a font's standard glyph width.
- __extern int caca_get_font_height (caca_font_t const *)
  Get a font's standard glyph height.
- __extern uint32_t const * caca_get_font_blocks (caca_font_t const *)
  Get a font's list of supported glyphs.
- __extern int caca_render_canvas (caca_canvas_t const *, caca_font_t const *, void *, int, int, int)
  Render the canvas onto an image buffer.
- __extern int caca_free_font (caca_font_t *)
  Free a font structure.

12.10.1 Detailed Description

These functions provide font handling routines and high quality canvas to bitmap rendering.

12.10.2 Function Documentation

12.10.2.1 __extern caca_font_t* caca_load_font (void const * *data*, size_t *size*)

This function loads a font and returns a handle to its internal structure. The handle can then be used with caca_render_canvas() for bitmap output.

Internal fonts can also be loaded: if `size` is set to 0, `data` must be a string containing the internal font name.

If `size` is non-zero, the `size` bytes of memory at address `data` are loaded as a font. This memory are must not be freed by the calling program until the font handle has been freed with caca_free_font().

If an error occurs, NULL is returned and **errno** is set accordingly:

- `ENOENT` Requested built-in font does not exist.
- `EINVAL` Invalid font data in memory area.
- `ENOMEM` Not enough memory to allocate font structure.

pt3em

pt3em**Parameters**

pt3em pt3em*data*	pt3emThe memory area containing the font or its name.
pt3em*size*	pt3emThe size of the memory area, or 0 if the font name is given.

pt3em**Returns**

A font handle or NULL in case of error.

References caca_load_font().

Referenced by caca_load_font().

12.10.2.2 __extern char const* const* caca_get_font_list (void)

Return a list of available builtin fonts. The list is a NULL-terminated array of strings.

This function never fails.

pt3em**Returns**

An array of strings.

12.10.2.3 __extern int caca_get_font_width (caca_font_t const * *f*)

Return the standard value for the current font's glyphs. Most glyphs in the font will have this width, except fullwidth characters.

This function never fails.

pt3em**Parameters**

pt3em pt3em*f*	pt3emThe font, as returned by caca_load_font()

pt3em**Returns**

The standard glyph width.

12.10.2.4 __extern int caca_get_font_height (caca_font_t const * *f*)

Returns the standard value for the current font's glyphs. Most glyphs in the font will have this height.

This function never fails.

pt3em**Parameters**

pt3em

pt3em pt3emf	pt3emThe font, as returned by caca_load_font()

pt3emReturns

The standard glyph height.

12.10.2.5 __extern uint32_t const* caca_get_font_blocks (caca_font_t const * f)

This function returns the list of Unicode blocks supported by the given font. The list is a zero-terminated list of indices. Here is an example:

```
{
   0x0000, 0x0080,   // Basic latin: A, B, C, a, b, c
   0x0080, 0x0100,   // Latin-1 supplement: "A, 'e, ^u
   0x0530, 0x0590,   // Armenian
   0x0000, 0x0000,   // END
};
```

This function never fails.

pt3emParameters

pt3em pt3emf	pt3emThe font, as returned by caca_load_font()

pt3emReturns

The list of Unicode blocks supported by the font.

12.10.2.6 __extern int caca_render_canvas (caca_canvas_t const * cv, caca_font_t const * f, void * buf, int width, int height, int pitch)

This function renders the given canvas on an image buffer using a specific font. The pixel format is fixed (32-bit ARGB, 8 bits for each component).

The required image width can be computed using caca_get_canvas_width() and caca_get_font_width(). The required height can be computed using caca_get_canvas_height() and caca_get_font_height().

Glyphs that do not fit in the image buffer are currently not rendered at all. They may be cropped instead in future versions.

If an error occurs, -1 is returned and **errno** is set accordingly:

- EINVAL Specified width, height or pitch is invalid.

pt3emParameters

pt3empt3emcv	pt3emThe canvas to render

pt3em

pt3em*f*	pt3emThe font, as returned by caca_load_font()
pt3em*buf*	pt3emThe image buffer
pt3em*width*	pt3emThe width (in pixels) of the image buffer
pt3em*height*	pt3emThe height (in pixels) of the image buffer
pt3em*pitch*	pt3emThe pitch (in bytes) of an image buffer line.

pt3emReturns

0 in case of success, -1 if an error occurred.

References caca_attr_to_argb64().

12.10.2.7 __extern int caca_free_font (caca_font_t * *f*)

This function frees all data allocated by caca_load_font(). The font structure is no longer usable by other libcaca functions. Once this function has returned, the memory area that was given to caca_load_font() can be freed.

This function never fails.

pt3emParameters

pt3em	pt3em*f*	pt3emThe font, as returned by caca_load_font()

pt3emReturns

This function always returns 0.

pt3em

pt3em

12.11 libcaca FIGfont handling

Functions

- __extern int **caca_canvas_set_figfont** (caca_canvas_t *, char const *)
- __extern int **caca_put_figchar** (caca_canvas_t *, uint32_t)
- __extern int **caca_flush_figlet** (caca_canvas_t *)

12.11.1 Detailed Description

These functions provide FIGlet and TOIlet font handling routines.

pt3em

pt3em

12.12 libcaca file IO

Functions

- __extern caca_file_t * **caca_file_open** (char const *, const char *)
- __extern int **caca_file_close** (caca_file_t *)
- __extern uint64_t **caca_file_tell** (caca_file_t *)
- __extern size_t **caca_file_read** (caca_file_t *, void *, size_t)
- __extern size_t **caca_file_write** (caca_file_t *, const void *, size_t)
- __extern char * **caca_file_gets** (caca_file_t *, char *, int)
- __extern int **caca_file_eof** (caca_file_t *)

12.12.1 Detailed Description

These functions allow to read and write files in a platform-independent way.

pt3em

pt3em

12.13 libcaca importers/exporters from/to various

Functions

- __extern ssize_t **caca_import_memory** (caca_canvas_t *, void const *, size_t, char const *)
- __extern ssize_t **caca_import_file** (caca_canvas_t *, char const *, char const *)
- __extern char const *const * **caca_get_import_list** (void)
- __extern void * **caca_export_memory** (caca_canvas_t const *, char const *, size_t *)
- __extern char const *const * **caca_get_export_list** (void)

12.13.1 Detailed Description

formats

These functions import various file formats into a new canvas, or export the current canvas to various text formats.

pt3em

pt3em

12.14 libcaca display functions

Functions

- __extern caca_display_t * caca_create_display (caca_canvas_t *)

  Attach a caca graphical context to a caca canvas.
- __extern caca_display_t * caca_create_display_with_driver (caca_canvas_t *, char const *)

  Attach a specific caca graphical context to a caca canvas.
- __extern char const *const * caca_get_display_driver_list (void)

  Get available display drivers.
- __extern char const * caca_get_display_driver (caca_display_t *)

  Return a caca graphical context's current output driver.
- __extern int caca_set_display_driver (caca_display_t *, char const *)

  Set the output driver.
- __extern int caca_free_display (caca_display_t *)

  Detach a caca graphical context from a caca backend context.
- __extern caca_canvas_t * caca_get_canvas (caca_display_t *)

  Get the canvas attached to a caca graphical context.
- __extern int caca_refresh_display (caca_display_t *)

  Flush pending changes and redraw the screen.
- __extern int caca_set_display_time (caca_display_t *, int)

  Set the refresh delay.
- __extern int caca_get_display_time (caca_display_t const *)

  Get the display's average rendering time.
- __extern int caca_get_display_width (caca_display_t const *)

  Get the display width.
- __extern int caca_get_display_height (caca_display_t const *)

  Get the display height.
- __extern int caca_set_display_title (caca_display_t *, char const *)

  Set the display title.
- __extern int caca_set_mouse (caca_display_t *, int)

  Show or hide the mouse pointer.
- __extern int caca_set_cursor (caca_display_t *, int)

  Show or hide the cursor.

12.14.1 Detailed Description

These functions provide the basic *libcaca* routines for display initialisation, system information retrieval and configuration.

pt3em

12.14.2 Function Documentation

12.14.2.1 __extern caca_display_t* caca_create_display (caca_canvas_t * *cv*)

Create a graphical context using device-dependent features (ncurses for terminals, an X11 window, a DOS command window...) that attaches to a libcaca canvas. Everything that gets drawn in the libcaca canvas can then be displayed by the libcaca driver.

If no caca canvas is provided, a new one is created. Its handle can be retrieved using caca_get_canvas() and it is automatically destroyed when caca_free_display() is called.

See also caca_create_display_with_driver().

If an error occurs, NULL is returned and **errno** is set accordingly:

- ENOMEM Not enough memory.
- ENODEV Graphical device could not be initialised.

pt3emParameters

pt3em	pt3em*cv*	pt3emThe caca canvas or NULL to create a canvas automatically.

pt3emReturns

The caca graphical context or NULL if an error occurred.

References caca_create_display_with_driver().

12.14.2.2 __extern caca_display_t* caca_create_display_with_driver (caca_canvas_t * *cv*, char const * *driver*)

Create a graphical context using device-dependent features (ncurses for terminals, an X11 window, a DOS command window...) that attaches to a libcaca canvas. Everything that gets drawn in the libcaca canvas can then be displayed by the libcaca driver.

If no caca canvas is provided, a new one is created. Its handle can be retrieved using caca_get_canvas() and it is automatically destroyed when caca_free_display() is called.

If no driver name is provided, *libcaca* will try to autodetect the best output driver it can.

See also caca_create_display().

If an error occurs, NULL is returned and **errno** is set accordingly:

- ENOMEM Not enough memory.
- ENODEV Graphical device could not be initialised.

pt3em

pt3em**Parameters**

pt3em	pt3em*cv*	pt3emThe caca canvas or NULL to create a canvas automatically.
	pt3em*driver*	pt3emA string describing the desired output driver or NULL to choose the best driver automatically.

pt3em**Returns**

The caca graphical context or NULL if an error occurred.

References caca_create_canvas(), caca_free_canvas(), caca_manage_canvas(), and caca_unmanage_canvas().

Referenced by caca_create_display().

12.14.2.3 __extern char const* const* caca_get_display_driver_list (void)

Return a list of available display drivers. The list is a NULL-terminated array of strings, interleaving a string containing the internal value for the display driver, and a string containing the natural language description for that driver.

This function never fails.

pt3em**Returns**

An array of strings.

12.14.2.4 __extern char const* caca_get_display_driver (caca_display_t * *dp*)

Return the given display's current output driver.

This function never fails.

pt3em**Parameters**

pt3em	pt3em*dp*	pt3emThe caca display.

pt3em**Returns**

A static string.

12.14.2.5 __extern int caca_set_display_driver (caca_display_t * *dp*, char const * *driver*)

Dynamically change the given display's output driver.

FIXME: decide what to do in case of failure

pt3em

pt3emParameters

pt3empt3em*dp*	pt3emThe caca display.
pt3em*driver*	pt3emA string describing the desired output driver or NULL to choose the best driver automatically.

pt3emReturns

0 in case of success, -1 if an error occurred.

12.14.2.6 extern int caca_free_display (caca_display_t * *dp*)

Detach a graphical context from its caca backend and destroy it. The libcaca canvas continues to exist and other graphical contexts can be attached to it afterwards.

If the caca canvas was automatically created by caca_create_display(), it is automatically destroyed and any handle to it becomes invalid.

This function never fails.

pt3emParameters

pt3empt3em*dp*	pt3emThe libcaca graphical context.

pt3emReturns

This function always returns 0.

References caca_free_canvas(), and caca_unmanage_canvas().

12.14.2.7 extern caca_canvas_t* caca_get_canvas (caca_display_t * *dp*)

Return a handle on the *caca_canvas_t* object that was either attached or created by caca_create_display().

This function never fails.

pt3emParameters

pt3empt3em*dp*	pt3emThe libcaca graphical context.

pt3em

pt3emReturns

The libcaca canvas.

12.14.2.8 __extern int caca_refresh_display (caca_display_t * dp)

Flush all graphical operations and print them to the display device. Nothing will show on the screen until this function is called.

If caca_set_display_time() was called with a non-zero value, caca_refresh_display() will use that value to achieve constant framerate: if two consecutive calls to caca_refresh_display() are within a time range shorter than the value set with caca_set_display_time(), the second call will be delayed before performing the screen refresh.

This function never fails.

pt3emParameters

pt3empt3em*dp*	pt3emThe libcaca display context.

pt3emReturns

This function always returns 0.

12.14.2.9 __extern int caca_set_display_time (caca_display_t * dp, int usec)

Set the refresh delay in microseconds. The refresh delay is used by caca_refresh_display() to achieve constant framerate. See the caca_refresh_display() documentation for more details.

If the argument is zero, constant framerate is disabled. This is the default behaviour.

If an error occurs, -1 is returned and **errno** is set accordingly:

- `EINVAL` Refresh delay value is invalid.

pt3emParameters

pt3empt3em*dp*	pt3emThe libcaca display context.
pt3em*usec*	pt3emThe refresh delay in microseconds.

pt3em

pt3emReturns

0 upon success, -1 if an error occurred.

12.14.2.10 __extern int caca_get_display_time (caca_display_t const * dp)

Get the average rendering time, which is the average measured time between two caca_refresh_display() calls, in microseconds. If constant framerate was activated by calling caca_set_display_time(), the average rendering time will be close to the requested delay even if the real rendering time was shorter.

This function never fails.

pt3emParameters

pt3empt3em*dp*	pt3emThe libcaca display context.

pt3emReturns

The render time in microseconds.

12.14.2.11 __extern int caca_get_display_width (caca_display_t const * dp)

If libcaca runs in a window, get the usable window width. This value can be used for aspect ratio calculation. If libcaca does not run in a window or if there is no way to know the font size, most drivers will assume a 6x10 font is being used. Note that the units are not necessarily pixels.

This function never fails.

pt3emParameters

pt3empt3em*dp*	pt3emThe libcaca display context.

pt3emReturns

The display width.

12.14.2.12 __extern int caca_get_display_height (caca_display_t const * dp)

If libcaca runs in a window, get the usable window height. This value can be used for aspect ratio calculation. If libcaca does not run in a window or if there is no way to know the font size, assume a 6x10 font is being used. Note that the units are not necessarily pixels.

This function never fails.

pt3em

pt3em**Parameters**

pt3empt3em*dp*	pt3emThe libcaca display context.

pt3em**Returns**

The display height.

12.14.2.13 __extern int **caca_set_display_title** (**caca_display_t** ∗ ***dp,*** **char const** ∗ ***title***)

If libcaca runs in a window, try to change its title. This works with the ncurses, S-Lang, OpenGL, X11 and Win32 drivers.

If an error occurs, -1 is returned and **errno** is set accordingly:

- ENOSYS Display driver does not support setting the window title.

pt3em**Parameters**

pt3empt3em*dp*	pt3emThe libcaca display context.
pt3em*title*	pt3emThe desired display title.

pt3em**Returns**

0 upon success, -1 if an error occurred.

12.14.2.14 __extern int **caca_set_mouse** (**caca_display_t** ∗ ***dp,*** **int** ***flag***)

Show or hide the mouse pointer. This function works with the ncurses, S-Lang and X11 drivers.

If an error occurs, -1 is returned and **errno** is set accordingly:

- ENOSYS Display driver does not support hiding the mouse pointer.

pt3em**Parameters**

pt3empt3em*dp*	pt3emThe libcaca display context.
pt3em*flag*	pt3em0 hides the pointer, 1 shows the system's default pointer (usually an arrow). Other values are reserved for future use.

pt3em

pt3em**Returns**

0 upon success, -1 if an error occurred.

12.14.2.15 __extern int **caca_set_cursor** (**caca_display_t** * *dp,* **int** *flag*)

Show or hide the cursor, for devices that support such a feature.

If an error occurs, -1 is returned and **errno** is set accordingly:

- `ENOSYS` Display driver does not support showing the cursor.

pt3em**Parameters**

pt3em	pt3em*dp*	pt3emThe libcaca display context.
	pt3em*flag*	pt3em0 hides the cursor, 1 shows the system's default cursor (usually a white rectangle). Other values are reserved for future use.

pt3em**Returns**

0 upon success, -1 if an error occurred.

pt3em

pt3em

12.15 libcaca event handling

Functions

- __extern int caca_get_event (caca_display_t *, int, caca_event_t *, int)
  Get the next mouse or keyboard input event.
- __extern int caca_get_mouse_x (caca_display_t const *)
  Return the X mouse coordinate.
- __extern int caca_get_mouse_y (caca_display_t const *)
  Return the Y mouse coordinate.
- __extern enum caca_event_type caca_get_event_type (caca_event_t const *)
  Return an event's type.
- __extern int caca_get_event_key_ch (caca_event_t const *)
  Return a key press or key release event's value.
- __extern uint32_t caca_get_event_key_utf32 (caca_event_t const *)
  Return a key press or key release event's Unicode value.
- __extern int caca_get_event_key_utf8 (caca_event_t const *, char *)
  Return a key press or key release event's UTF-8 value.
- __extern int caca_get_event_mouse_button (caca_event_t const *)
  Return a mouse press or mouse release event's button.
- __extern int caca_get_event_mouse_x (caca_event_t const *)
  Return a mouse motion event's X coordinate.
- __extern int caca_get_event_mouse_y (caca_event_t const *)
  Return a mouse motion event's Y coordinate.
- __extern int caca_get_event_resize_width (caca_event_t const *)
  Return a resize event's display width value.
- __extern int caca_get_event_resize_height (caca_event_t const *)
  Return a resize event's display height value.

12.15.1 Detailed Description

These functions handle user events such as keyboard input and mouse clicks.

12.15.2 Function Documentation

12.15.2.1 __extern int caca_get_event (caca_display_t * *dp*, int *event_mask*, caca_event_t * *ev*, int *timeout*)

Poll the event queue for mouse or keyboard events matching the event mask and return the first matching event. Non-matching events are discarded. If `event_mask` is zero, the function returns immediately.

pt3em

The timeout value tells how long this function needs to wait for an event. A value of zero returns immediately and the function returns zero if no more events are pending in the queue. A negative value causes the function to wait indefinitely until a matching event is received.

If not null, `ev` will be filled with information about the event received. If null, the function will return but no information about the event will be sent.

This function never fails.

pt3em**Parameters**

pt3em pt3em*dp*	pt3emThe libcaca graphical context.
pt3em *event_mask*	pt3emBitmask of requested events.
pt3em *timeout*	pt3emA timeout value in microseconds, -1 for blocking behaviour
pt3em*ev*	pt3emA pointer to a caca_event structure, or NULL.

pt3em**Returns**

1 if a matching event was received, or 0 if the wait timeouted.

References CACA_EVENT_NONE.

12.15.2.2 __extern int **caca_get_mouse_x** (**caca_display_t** const * *dp*)

Return the X coordinate of the mouse position last time it was detected. This function is not reliable if the ncurses or S-Lang drivers are being used, because mouse position is only detected when the mouse is clicked. Other drivers such as X11 work well.

This function never fails.

pt3em**Parameters**

pt3em pt3em*dp*	pt3emThe libcaca graphical context.

pt3em**Returns**

The X mouse coordinate.

References caca_get_canvas_width().

12.15.2.3 __extern int **caca_get_mouse_y** (**caca_display_t** const * *dp*)

Return the Y coordinate of the mouse position last time it was detected. This function is not reliable if the ncurses or S-Lang drivers are being used, because mouse position is only detected when the mouse is clicked. Other drivers such as X11 work well.

This function never fails.

pt3em

pt3em**Parameters**

pt3em	pt3em*dp*	pt3emThe libcaca graphical context.

pt3em**Returns**

The Y mouse coordinate.

References caca_get_canvas_height().

12.15.2.4 __extern enum caca_event_type caca_get_event_type (caca_event_t const * *ev*)

Return the type of an event. This function may always be called on an event after caca_get_event() was called, and its return value indicates which other functions may be called:

- `CACA_EVENT_NONE`: no other function may be called.
- `CACA_EVENT_KEY_PRESS`, `CACA_EVENT_KEY_RELEASE`: caca_get_event_key_ch(), caca_get_event_key_utf32() and caca_get_event_key_utf8() may be called.
- `CACA_EVENT_MOUSE_PRESS`, `CACA_EVENT_MOUSE_RELEASE`: caca_get_event_mouse_button() may be called.
- `CACA_EVENT_MOUSE_MOTION`: caca_get_event_mouse_x() and caca_get_event_mouse_y() may be called.
- `CACA_EVENT_RESIZE`: caca_get_event_resize_width() and caca_get_event_resize_height() may be called.
- `CACA_EVENT_QUIT`: no other function may be called.

This function never fails.

pt3em**Parameters**

pt3em	pt3em*ev*	pt3emThe libcaca event.

pt3em**Returns**

The event's type.

12.15.2.5 __extern int caca_get_event_key_ch (caca_event_t const * *ev*)

Return either the ASCII value for an event's key, or if the key is not an ASCII character, an appropriate *enum caca_key* value.

pt3em

This function never fails, but must only be called with a valid event of type CACA_EVENT_KEY_PRESS or CACA_EVENT_KEY_RELEASE, or the results will be undefined. See caca_get_event_type() for more information.

pt3em**Parameters**

pt3em	pt3em*ev*	pt3emThe libcaca event.

pt3em**Returns**

The key value.

12.15.2.6 __extern uint32_t caca_get_event_key_utf32 (caca_event_t const * *ev*)

Return the UTF-32/UCS-4 value for an event's key if it resolves to a printable character.

This function never fails, but must only be called with a valid event of type CACA_EVENT_KEY_PRESS or CACA_EVENT_KEY_RELEASE, or the results will be undefined. See caca_get_event_type() for more information.

pt3em**Parameters**

pt3em	pt3em*ev*	pt3emThe libcaca event.

pt3em**Returns**

The key's Unicode value.

12.15.2.7 __extern int caca_get_event_key_utf8 (caca_event_t const * *ev*, char * *utf8*)

Write the UTF-8 value for an event's key if it resolves to a printable character. Up to 6 UTF-8 bytes and a null termination are written.

This function never fails, but must only be called with a valid event of type CACA_EVENT_KEY_PRESS or CACA_EVENT_KEY_RELEASE, or the results will be undefined. See caca_get_event_type() for more information.

pt3em**Parameters**

pt3em	pt3em*ev*	pt3emThe libcaca event.

pt3em**Returns**

This function always returns 0.

pt3em

12.15.2.8 __extern int caca_get_event_mouse_button (caca_event_t const * *ev*)

Return the mouse button index for an event.

This function never fails, but must only be called with a valid event of type `CACA_EVENT_MOUSE_PRESS` or `CACA_EVENT_MOUSE_RELEASE`, or the results will be undefined. See caca_get_event_type() for more information.

pt3em**Parameters**

pt3em	pt3em*ev*	pt3emThe libcaca event.

pt3em**Returns**

The event's mouse button.

12.15.2.9 __extern int caca_get_event_mouse_x (caca_event_t const * *ev*)

Return the X coordinate for a mouse motion event.

This function never fails, but must only be called with a valid event of type `CACA_EVENT_MOUSE_MOTION`, or the results will be undefined. See caca_get_event_type() for more information.

pt3em**Parameters**

pt3em	pt3em*ev*	pt3emThe libcaca event.

pt3em**Returns**

The event's X mouse coordinate.

12.15.2.10 __extern int caca_get_event_mouse_y (caca_event_t const * *ev*)

Return the Y coordinate for a mouse motion event.

This function never fails, but must only be called with a valid event of type `CACA_EVENT_MOUSE_MOTION`, or the results will be undefined. See caca_get_event_type() for more information.

pt3em**Parameters**

pt3em	pt3em*ev*	pt3emThe libcaca event.

pt3em

pt3em**Returns**

The event's Y mouse coordinate.

12.15.2.11 __extern int caca_get_event_resize_width (caca_event_t const * *ev*)

Return the width value for a display resize event.

This function never fails, but must only be called with a valid event of type `CACA_EVENT_RESIZE`, or the results will be undefined. See caca_get_event_type() for more information.

pt3em**Parameters**

pt3em pt3em*ev*	pt3emThe libcaca event.

pt3em**Returns**

The event's new display width value.

12.15.2.12 __extern int caca_get_event_resize_height (caca_event_t const * *ev*)

Return the height value for a display resize event.

This function never fails, but must only be called with a valid event of type `CACA_EVENT_RESIZE`, or the results will be undefined. See caca_get_event_type() for more information.

pt3em**Parameters**

pt3em pt3em*ev*	pt3emThe libcaca event.

pt3em**Returns**

The event's new display height value.

pt3em

13 Data Structure Documentation

13.1 caca_event Struct Reference

Handling of user events.

Data Fields

- enum caca_event_type **type**
- union {
  struct {
  int **x**
  int **y**
  int **button**
  } **mouse**
  struct {
  int **w**
  int **h**
  } **resize**
  struct {
  int **ch**
  uint32_t **utf32**
  char **utf8** [8]
  } **key**
  } **data**

- uint8_t **padding** [16]

13.1.1 Detailed Description

This structure is filled by caca_get_event() when an event is received. It is an opaque structure that should only be accessed through caca_event_get_type() and similar functions. The struct members may no longer be directly accessible in future versions.

14 File Documentation

14.1 caca.h File Reference

The *libcaca* public header.

pt3em

Data Structures

- struct caca_event

  Handling of user events.

Defines

- #define CACA_API_VERSION_1
- #define CACA_BLACK 0x00
- #define CACA_BLUE 0x01
- #define CACA_GREEN 0x02
- #define CACA_CYAN 0x03
- #define CACA_RED 0x04
- #define CACA_MAGENTA 0x05
- #define CACA_BROWN 0x06
- #define CACA_LIGHTGRAY 0x07
- #define CACA_DARKGRAY 0x08
- #define CACA_LIGHTBLUE 0x09
- #define CACA_LIGHTGREEN 0x0a
- #define CACA_LIGHTCYAN 0x0b
- #define CACA_LIGHTRED 0x0c
- #define CACA_LIGHTMAGENTA 0x0d
- #define CACA_YELLOW 0x0e
- #define CACA_WHITE 0x0f
- #define CACA_DEFAULT 0x10
- #define CACA_TRANSPARENT 0x20
- #define CACA_BOLD 0x01
- #define CACA_ITALICS 0x02
- #define CACA_UNDERLINE 0x04
- #define CACA_BLINK 0x08
- #define CACA_MAGIC_FULLWIDTH 0x000ffffe

Typedefs

- typedef struct caca_canvas caca_canvas_t
- typedef struct caca_dither caca_dither_t
- typedef struct caca_font caca_font_t
- typedef struct caca_file caca_file_t
- typedef struct caca_display caca_display_t
- typedef struct caca_event caca_event_t

pt3em

Enumerations

- enum caca_event_type { CACA_EVENT_NONE = 0x0000, CACA_EVENT_KEY_PRESS = 0x0001, CACA_EVENT_KEY_RELEASE = 0x0002, CACA_EVENT_MOUSE_PRESS = 0x0004, CACA_EVENT_MOUSE_RELEASE = 0x0008, CACA_EVENT_MOUSE_MOTION = 0x0010, CACA_EVENT_RESIZE = 0x0020, CACA_EVENT_QUIT = 0x0040, CACA_EVENT_ANY = 0xffff }

  User event type enumeration.
- enum caca_key { CACA_KEY_UNKNOWN = 0x00, CACA_KEY_CTRL_A = 0x01, CACA_KEY_CTRL_B = 0x02, CACA_KEY_CTRL_C = 0x03, CACA_KEY_CTRL_D = 0x04, CACA_KEY_CTRL_E = 0x05, CACA_KEY_CTRL_F = 0x06, CACA_KEY_CTRL_G = 0x07, CACA_KEY_BACKSPACE = 0x08, CACA_KEY_TAB = 0x09, CACA_KEY_CTRL_J = 0x0a, CACA_KEY_CTRL_K = 0x0b, CACA_KEY_CTRL_L = 0x0c, CACA_KEY_RETURN = 0x0d, CACA_KEY_CTRL_N = 0x0e, CACA_KEY_CTRL_O = 0x0f, CACA_KEY_CTRL_P = 0x10, CACA_KEY_CTRL_Q = 0x11, CACA_KEY_CTRL_R = 0x12, CACA_KEY_PAUSE = 0x13, CACA_KEY_CTRL_T = 0x14, CACA_KEY_CTRL_U = 0x15, CACA_KEY_CTRL_V = 0x16, CACA_KEY_CTRL_W = 0x17, CACA_KEY_CTRL_X = 0x18, CACA_KEY_CTRL_Y = 0x19, CACA_KEY_CTRL_Z = 0x1a, CACA_KEY_ESCAPE = 0x1b, CACA_KEY_DELETE = 0x7f, CACA_KEY_UP = 0x111, CACA_KEY_DOWN = 0x112, CACA_KEY_LEFT = 0x113, CACA_KEY_RIGHT = 0x114, CACA_KEY_INSERT = 0x115, CACA_KEY_HOME = 0x116, CACA_KEY_END = 0x117, CACA_KEY_PAGEUP = 0x118, CACA_KEY_PAGEDOWN = 0x119, CACA_KEY_F1 = 0x11a, CACA_KEY_F2 = 0x11b, CACA_KEY_F3 = 0x11c, CACA_KEY_F4 = 0x11d, CACA_KEY_F5 = 0x11e, CACA_KEY_F6 = 0x11f, CACA_KEY_F7 = 0x120, CACA_KEY_F8 = 0x121, CACA_KEY_F9 = 0x122, CACA_KEY_F10 = 0x123, CACA_KEY_F11 = 0x124, CACA_KEY_F12 = 0x125, CACA_KEY_F13 = 0x126, CACA_KEY_F14 = 0x127, CACA_KEY_F15 = 0x128 }

  Special key values.

Functions

- __extern caca_canvas_t * caca_create_canvas (int, int)

  Initialise a libcaca canvas.
- __extern int caca_manage_canvas (caca_canvas_t *, int(*)(void *), void *)

  Manage a canvas.
- __extern int caca_unmanage_canvas (caca_canvas_t *, int(*)(void *), void *)

  Unmanage a canvas.
- __extern int caca_set_canvas_size (caca_canvas_t *, int, int)

  Resize a canvas.
- __extern int caca_get_canvas_width (caca_canvas_t const *)

  Get the canvas width.
- __extern int caca_get_canvas_height (caca_canvas_t const *)

pt3em

Get the canvas height.

- __extern uint8_t const * caca_get_canvas_chars (caca_canvas_t const *)

  Get the canvas character array.
- __extern uint8_t const * caca_get_canvas_attrs (caca_canvas_t const *)

  Get the canvas attribute array.
- __extern int caca_free_canvas (caca_canvas_t *)

  Uninitialise libcaca.
- __extern int caca_rand (int, int)

  Generate a random integer within a range.
- __extern char const * caca_get_version (void)

  Return the libcaca version.
- __extern int caca_gotoxy (caca_canvas_t *, int, int)

  Set cursor position.
- __extern int caca_get_cursor_x (caca_canvas_t const *)

  Get X cursor position.
- __extern int caca_get_cursor_y (caca_canvas_t const *)

  Get Y cursor position.
- __extern int caca_put_char (caca_canvas_t *, int, int, uint32_t)

  Print an ASCII or Unicode character.
- __extern uint32_t caca_get_char (caca_canvas_t const *, int, int)

  Get the Unicode character at the given coordinates.
- __extern int caca_put_str (caca_canvas_t *, int, int, char const *)

  Print a string.
- __extern int caca_printf (caca_canvas_t *, int, int, char const *,...)

  Print a formated string.
- __extern int caca_clear_canvas (caca_canvas_t *)

  Clear the canvas.
- __extern int caca_set_canvas_handle (caca_canvas_t *, int, int)

  Set cursor handle.
- __extern int caca_get_canvas_handle_x (caca_canvas_t const *)

  Get X handle position.
- __extern int caca_get_canvas_handle_y (caca_canvas_t const *)

  Get Y handle position.
- __extern int caca_blit (caca_canvas_t *, int, int, caca_canvas_t const *, caca_-canvas_t const *)

  Blit a canvas onto another one.
- __extern int caca_set_canvas_boundaries (caca_canvas_t *, int, int, int, int)

  Set a canvas' new boundaries.
- __extern int caca_invert (caca_canvas_t *)

  Invert a canvas' colours.
- __extern int caca_flip (caca_canvas_t *)

  Flip a canvas horizontally.

pt3em

- __extern int caca_flop (caca_canvas_t *)

  Flip a canvas vertically.
- __extern int caca_rotate_180 (caca_canvas_t *)

  Rotate a canvas.
- __extern int caca_rotate_left (caca_canvas_t *)

  Rotate a canvas, 90 degrees counterclockwise.
- __extern int caca_rotate_right (caca_canvas_t *)

  Rotate a canvas, 90 degrees counterclockwise.
- __extern int caca_stretch_left (caca_canvas_t *)

  Rotate and stretch a canvas, 90 degrees counterclockwise.
- __extern int caca_stretch_right (caca_canvas_t *)

  Rotate and stretch a canvas, 90 degrees clockwise.
- __extern uint32_t caca_get_attr (caca_canvas_t const *, int, int)

  Get the text attribute at the given coordinates.
- __extern int caca_set_attr (caca_canvas_t *, uint32_t)

  Set the default character attribute.
- __extern int caca_put_attr (caca_canvas_t *, int, int, uint32_t)

  Set the character attribute at the given coordinates.
- __extern int caca_set_color_ansi (caca_canvas_t *, uint8_t, uint8_t)

  Set the default colour pair for text (ANSI version).
- __extern int caca_set_color_argb (caca_canvas_t *, uint16_t, uint16_t)

  Set the default colour pair for text (truecolor version).
- __extern uint8_t caca_attr_to_ansi (uint32_t)

  Get DOS ANSI information from attribute.
- __extern uint8_t caca_attr_to_ansi_fg (uint32_t)

  Get ANSI foreground information from attribute.
- __extern uint8_t caca_attr_to_ansi_bg (uint32_t)

  Get ANSI background information from attribute.
- __extern uint16_t caca_attr_to_rgb12_fg (uint32_t)

  Get 12-bit RGB foreground information from attribute.
- __extern uint16_t caca_attr_to_rgb12_bg (uint32_t)

  Get 12-bit RGB background information from attribute.
- __extern void caca_attr_to_argb64 (uint32_t, uint8_t[8])

  Get 64-bit ARGB information from attribute.
- __extern uint32_t caca_utf8_to_utf32 (char const *, size_t *)

  Convert a UTF-8 character to UTF-32.
- __extern size_t caca_utf32_to_utf8 (char *, uint32_t)

  Convert a UTF-32 character to UTF-8.
- __extern uint8_t caca_utf32_to_cp437 (uint32_t)

  Convert a UTF-32 character to CP437.
- __extern uint32_t caca_cp437_to_utf32 (uint8_t)

  Convert a CP437 character to UTF-32.

pt3em

- __extern char caca_utf32_to_ascii (uint32_t)

  Convert a UTF-32 character to ASCII.
- __extern int caca_utf32_is_fullwidth (uint32_t)

  Tell whether a UTF-32 character is fullwidth.
- __extern int caca_draw_line (caca_canvas_t *, int, int, int, int, uint32_t)

  Draw a line on the canvas using the given character.
- __extern int caca_draw_polyline (caca_canvas_t *, int const x[], int const y[], int, uint32_t)

  Draw a polyline.
- __extern int caca_draw_thin_line (caca_canvas_t *, int, int, int, int)

  Draw a thin line on the canvas, using ASCII art.
- __extern int caca_draw_thin_polyline (caca_canvas_t *, int const x[], int const y[], int)

  Draw an ASCII art thin polyline.
- __extern int caca_draw_circle (caca_canvas_t *, int, int, int, uint32_t)

  Draw a circle on the canvas using the given character.
- __extern int caca_draw_ellipse (caca_canvas_t *, int, int, int, int, uint32_t)

  Draw an ellipse on the canvas using the given character.
- __extern int caca_draw_thin_ellipse (caca_canvas_t *, int, int, int, int)

  Draw a thin ellipse on the canvas.
- __extern int caca_fill_ellipse (caca_canvas_t *, int, int, int, int, uint32_t)

  Fill an ellipse on the canvas using the given character.
- __extern int caca_draw_box (caca_canvas_t *, int, int, int, int, uint32_t)

  Draw a box on the canvas using the given character.
- __extern int caca_draw_thin_box (caca_canvas_t *, int, int, int, int)

  Draw a thin box on the canvas.
- __extern int caca_draw_cp437_box (caca_canvas_t *, int, int, int, int)

  Draw a box on the canvas using CP437 characters.
- __extern int caca_fill_box (caca_canvas_t *, int, int, int, int, uint32_t)

  Fill a box on the canvas using the given character.
- __extern int caca_draw_triangle (caca_canvas_t *, int, int, int, int, int, int, uint32_t)

  Draw a triangle on the canvas using the given character.
- __extern int caca_draw_thin_triangle (caca_canvas_t *, int, int, int, int, int, int)

  Draw a thin triangle on the canvas.
- __extern int caca_fill_triangle (caca_canvas_t *, int, int, int, int, int, int, uint32_t)

  Fill a triangle on the canvas using the given character.
- __extern int caca_get_frame_count (caca_canvas_t const *)

  Get the number of frames in a canvas.
- __extern int caca_set_frame (caca_canvas_t *, int)

  Activate a given canvas frame.
- __extern char const * caca_get_frame_name (caca_canvas_t const *)

pt3em

Get the current frame's name.

- __extern int caca_set_frame_name (caca_canvas_t *, char const *)

  Set the current frame's name.
- __extern int caca_create_frame (caca_canvas_t *, int)

  Add a frame to a canvas.
- __extern int caca_free_frame (caca_canvas_t *, int)

  Remove a frame from a canvas.
- __extern caca_dither_t * caca_create_dither (int, int, int, int, uint32_t, uint32_t, uint32_t, uint32_t)

  Create an internal dither object.
- __extern int caca_set_dither_palette (caca_dither_t *, uint32_t r[], uint32_t g[], uint32_t b[], uint32_t a[])

  Set the palette of an 8bpp dither object.
- __extern int caca_set_dither_brightness (caca_dither_t *, float)

  Set the brightness of a dither object.
- __extern float caca_get_dither_brightness (caca_dither_t const *)

  Get the brightness of a dither object.
- __extern int caca_set_dither_gamma (caca_dither_t *, float)

  Set the gamma of a dither object.
- __extern float caca_get_dither_gamma (caca_dither_t const *)

  Get the gamma of a dither object.
- __extern int caca_set_dither_contrast (caca_dither_t *, float)

  Set the contrast of a dither object.
- __extern float caca_get_dither_contrast (caca_dither_t const *)

  Get the contrast of a dither object.
- __extern int caca_set_dither_antialias (caca_dither_t *, char const *)

  Set dither antialiasing.
- __extern char const *const * caca_get_dither_antialias_list (caca_dither_t const *)

  Get available antialiasing methods.
- __extern char const * caca_get_dither_antialias (caca_dither_t const *)

  Get current antialiasing method.
- __extern int caca_set_dither_color (caca_dither_t *, char const *)

  Choose colours used for dithering.
- __extern char const *const * caca_get_dither_color_list (caca_dither_t const *)

  Get available colour modes.
- __extern char const * caca_get_dither_color (caca_dither_t const *)

  Get current colour mode.
- __extern int caca_set_dither_charset (caca_dither_t *, char const *)

  Choose characters used for dithering.
- __extern char const *const * caca_get_dither_charset_list (caca_dither_t const *)

pt3em

Get available dither character sets.

- __extern char const * caca_get_dither_charset (caca_dither_t const *)

  Get current character set.
- __extern int caca_set_dither_algorithm (caca_dither_t *, char const *)

  Set dithering algorithm.
- __extern char const *const * caca_get_dither_algorithm_list (caca_dither_t const *)

  Get dithering algorithms.
- __extern char const * caca_get_dither_algorithm (caca_dither_t const *)

  Get current dithering algorithm.
- __extern int caca_dither_bitmap (caca_canvas_t *, int, int, int, int, caca_dither_t const *, void *)

  Dither a bitmap on the canvas.
- __extern int caca_free_dither (caca_dither_t *)

  Free the memory associated with a dither.
- __extern caca_font_t * caca_load_font (void const *, size_t)

  Load a font from memory for future use.
- __extern char const *const * caca_get_font_list (void)

  Get available builtin fonts.
- __extern int caca_get_font_width (caca_font_t const *)

  Get a font's standard glyph width.
- __extern int caca_get_font_height (caca_font_t const *)

  Get a font's standard glyph height.
- __extern uint32_t const * caca_get_font_blocks (caca_font_t const *)

  Get a font's list of supported glyphs.
- __extern int caca_render_canvas (caca_canvas_t const *, caca_font_t const *, void *, int, int, int)

  Render the canvas onto an image buffer.
- __extern int caca_free_font (caca_font_t *)

  Free a font structure.
- __extern int **caca_canvas_set_figfont** (caca_canvas_t *, char const *)
- __extern int **caca_put_figchar** (caca_canvas_t *, uint32_t)
- __extern int **caca_flush_figlet** (caca_canvas_t *)
- __extern caca_file_t * **caca_file_open** (char const *, const char *)
- __extern int **caca_file_close** (caca_file_t *)
- __extern uint64_t **caca_file_tell** (caca_file_t *)
- __extern size_t **caca_file_read** (caca_file_t *, void *, size_t)
- __extern size_t **caca_file_write** (caca_file_t *, const void *, size_t)
- __extern char * **caca_file_gets** (caca_file_t *, char *, int)
- __extern int **caca_file_eof** (caca_file_t *)
- __extern ssize_t **caca_import_memory** (caca_canvas_t *, void const *, size_t, char const *)
- __extern ssize_t **caca_import_file** (caca_canvas_t *, char const *, char const *)

pt3em

- __extern char const ∗const ∗ **caca_get_import_list** (void)
- __extern void ∗ **caca_export_memory** (caca_canvas_t const ∗, char const ∗, size_t ∗)
- __extern char const ∗const ∗ **caca_get_export_list** (void)
- __extern caca_display_t ∗ caca_create_display (caca_canvas_t ∗)

  Attach a caca graphical context to a caca canvas.
- __extern caca_display_t ∗ caca_create_display_with_driver (caca_canvas_t ∗, char const ∗)

  Attach a specific caca graphical context to a caca canvas.
- __extern char const ∗const ∗ caca_get_display_driver_list (void)

  Get available display drivers.
- __extern char const ∗ caca_get_display_driver (caca_display_t ∗)

  Return a caca graphical context's current output driver.
- __extern int caca_set_display_driver (caca_display_t ∗, char const ∗)

  Set the output driver.
- __extern int caca_free_display (caca_display_t ∗)

  Detach a caca graphical context from a caca backend context.
- __extern caca_canvas_t ∗ caca_get_canvas (caca_display_t ∗)

  Get the canvas attached to a caca graphical context.
- __extern int caca_refresh_display (caca_display_t ∗)

  Flush pending changes and redraw the screen.
- __extern int caca_set_display_time (caca_display_t ∗, int)

  Set the refresh delay.
- __extern int caca_get_display_time (caca_display_t const ∗)

  Get the display's average rendering time.
- __extern int caca_get_display_width (caca_display_t const ∗)

  Get the display width.
- __extern int caca_get_display_height (caca_display_t const ∗)

  Get the display height.
- __extern int caca_set_display_title (caca_display_t ∗, char const ∗)

  Set the display title.
- __extern int caca_set_mouse (caca_display_t ∗, int)

  Show or hide the mouse pointer.
- __extern int caca_set_cursor (caca_display_t ∗, int)

  Show or hide the cursor.
- __extern int caca_get_event (caca_display_t ∗, int, caca_event_t ∗, int)

  Get the next mouse or keyboard input event.
- __extern int caca_get_mouse_x (caca_display_t const ∗)

  Return the X mouse coordinate.
- __extern int caca_get_mouse_y (caca_display_t const ∗)

  Return the Y mouse coordinate.
- __extern enum caca_event_type caca_get_event_type (caca_event_t const ∗)

  Return an event's type.

pt3em

- __extern int caca_get_event_key_ch (caca_event_t const *)

  Return a key press or key release event's value.
- __extern uint32_t caca_get_event_key_utf32 (caca_event_t const *)

  Return a key press or key release event's Unicode value.
- __extern int caca_get_event_key_utf8 (caca_event_t const *, char *)

  Return a key press or key release event's UTF-8 value.
- __extern int caca_get_event_mouse_button (caca_event_t const *)

  Return a mouse press or mouse release event's button.
- __extern int caca_get_event_mouse_x (caca_event_t const *)

  Return a mouse motion event's X coordinate.
- __extern int caca_get_event_mouse_y (caca_event_t const *)

  Return a mouse motion event's Y coordinate.
- __extern int caca_get_event_resize_width (caca_event_t const *)

  Return a resize event's display width value.
- __extern int caca_get_event_resize_height (caca_event_t const *)

  Return a resize event's display height value.

14.1.1 Detailed Description

pt3em**Version**

Id

pt3em**Author**

Sam Hocevar <sam@zoy.org> This header contains the public types and functions that applications using *libcaca* may use.

14.1.2 Define Documentation

14.1.2.1 #define CACA_API_VERSION_1

libcaca API version

14.1.3 Typedef Documentation

14.1.3.1 typedef struct caca_canvas caca_canvas_t

libcaca canvas

14.1.3.2 typedef struct caca_dither caca_dither_t

dither structure

pt3em

14.1.3.3 typedef struct caca_font caca_font_t

font structure

14.1.3.4 typedef struct caca_file caca_file_t

file handle structure

14.1.3.5 typedef struct caca_display caca_display_t

libcaca display context

14.1.3.6 typedef struct caca_event caca_event_t

libcaca event structure

14.1.4 Enumeration Type Documentation

14.1.4.1 enum caca_event_type

This enum serves two purposes:

- Build listening masks for caca_get_event().
- Define the type of a *caca_event_t*.

pt3emEnumerator:

CACA_EVENT_NONE No event.

CACA_EVENT_KEY_PRESS A key was pressed.

CACA_EVENT_KEY_RELEASE A key was released.

CACA_EVENT_MOUSE_PRESS A mouse button was pressed.

CACA_EVENT_MOUSE_RELEASE A mouse button was released.

CACA_EVENT_MOUSE_MOTION The mouse was moved.

CACA_EVENT_RESIZE The window was resized.

CACA_EVENT_QUIT The user requested to quit.

CACA_EVENT_ANY Bitmask for any event.

14.1.4.2 enum caca_key

Special key values returned by caca_get_event() for which there is no printable ASCII equivalent.

pt3emEnumerator:

CACA_KEY_UNKNOWN Unknown key.

pt3em

CACA_KEY_CTRL_A The Ctrl-A key.

CACA_KEY_CTRL_B The Ctrl-B key.

CACA_KEY_CTRL_C The Ctrl-C key.

CACA_KEY_CTRL_D The Ctrl-D key.

CACA_KEY_CTRL_E The Ctrl-E key.

CACA_KEY_CTRL_F The Ctrl-F key.

CACA_KEY_CTRL_G The Ctrl-G key.

CACA_KEY_BACKSPACE The backspace key.

CACA_KEY_TAB The tabulation key.

CACA_KEY_CTRL_J The Ctrl-J key.

CACA_KEY_CTRL_K The Ctrl-K key.

CACA_KEY_CTRL_L The Ctrl-L key.

CACA_KEY_RETURN The return key.

CACA_KEY_CTRL_N The Ctrl-N key.

CACA_KEY_CTRL_O The Ctrl-O key.

CACA_KEY_CTRL_P The Ctrl-P key.

CACA_KEY_CTRL_Q The Ctrl-Q key.

CACA_KEY_CTRL_R The Ctrl-R key.

CACA_KEY_PAUSE The pause key.

CACA_KEY_CTRL_T The Ctrl-T key.

CACA_KEY_CTRL_U The Ctrl-U key.

CACA_KEY_CTRL_V The Ctrl-V key.

CACA_KEY_CTRL_W The Ctrl-W key.

CACA_KEY_CTRL_X The Ctrl-X key.

CACA_KEY_CTRL_Y The Ctrl-Y key.

CACA_KEY_CTRL_Z The Ctrl-Z key.

CACA_KEY_ESCAPE The escape key.

CACA_KEY_DELETE The delete key.

CACA_KEY_UP The up arrow key.

CACA_KEY_DOWN The down arrow key.

CACA_KEY_LEFT The left arrow key.

CACA_KEY_RIGHT The right arrow key.

CACA_KEY_INSERT The insert key.

CACA_KEY_HOME The home key.

CACA_KEY_END The end key.

CACA_KEY_PAGEUP The page up key.

CACA_KEY_PAGEDOWN The page down key.

pt3em

CACA_KEY_F1 The F1 key.

CACA_KEY_F2 The F2 key.

CACA_KEY_F3 The F3 key.

CACA_KEY_F4 The F4 key.

CACA_KEY_F5 The F5 key.

CACA_KEY_F6 The F6 key.

CACA_KEY_F7 The F7 key.

CACA_KEY_F8 The F8 key.

CACA_KEY_F9 The F9 key.

CACA_KEY_F10 The F10 key.

CACA_KEY_F11 The F11 key.

CACA_KEY_F12 The F12 key.

CACA_KEY_F13 The F13 key.

CACA_KEY_F14 The F14 key.

CACA_KEY_F15 The F15 key.