# glucat

0.8.2

Generated by Doxygen 1.8.14

# Contents


**1 Namespace Index** **1**

1.1 Namespace List . . . . . 1

**2 Hierarchical Index** **3**

2.1 Class Hierarchy . . . . . 3

**3 Class Index** **5**

3.1 Class List . . . . . 5

**4 File Index** **7**

4.1 File List . . . . . 7

**5 Namespace Documentation** **9**

5.1 cga3 Namespace Reference . . . . . 9

5.1.1 Detailed Description . . . . . 9

5.1.2 Function Documentation . . . . . 9

5.1.2.1 agc3() . . . . . 9

5.1.2.2 cga3() . . . . . 10

5.1.2.3 cga3std() . . . . . 10

5.2 glucat Namespace Reference . . . . . 10

5.2.1 Typedef Documentation . . . . . 21

5.2.1.1 index_t . . . . . 21

5.2.1.2 intfn . . . . . 22

5.2.1.3 intintfn . . . . . 22

5.2.1.4 set_value_t . . . . . 22

5.2.2 Enumeration Type Documentation . . . 22
5.2.2.1 precision_t . . . 22
5.2.3 Function Documentation . . . 23
5.2.3.1 _GLUCAT_CTAssert() [1/3] . . . 23
5.2.3.2 _GLUCAT_CTAssert() [2/3] . . . 23
5.2.3.3 _GLUCAT_CTAssert() [3/3] . . . 23
5.2.3.4 abs() . . . 23
5.2.3.5 acos() [1/2] . . . 24
5.2.3.6 acos() [2/2] . . . 24
5.2.3.7 acosh() [1/2] . . . 24
5.2.3.8 acosh() [2/2] . . . 25
5.2.3.9 asin() [1/2] . . . 25
5.2.3.10 asin() [2/2] . . . 25
5.2.3.11 asinh() [1/2] . . . 26
5.2.3.12 asinh() [2/2] . . . 26
5.2.3.13 atan() [1/2] . . . 26
5.2.3.14 atan() [2/2] . . . 27
5.2.3.15 atanh() [1/2] . . . 27
5.2.3.16 atanh() [2/2] . . . 27
5.2.3.17 cascade_log() . . . 28
5.2.3.18 check_complex() . . . 28
5.2.3.19 clifford_exp() . . . 28
5.2.3.20 compare() . . . 29
5.2.3.21 complexifier() . . . 29
5.2.3.22 conj() . . . 29
5.2.3.23 cos() [1/2] . . . 30
5.2.3.24 cos() [2/2] . . . 30
5.2.3.25 cosh() . . . 30
5.2.3.26 crd_of_mult() [1/2] . . . 31
5.2.3.27 crd_of_mult() [2/2] . . . 31

5.2.3.28 db_sqrt() . . . 31
5.2.3.29 db_step() . . . 31
5.2.3.30 elliptic() . . . 32
5.2.3.31 even() . . . 32
5.2.3.32 exp() [1/2] . . . 32
5.2.3.33 exp() [2/2] . . . 33
5.2.3.34 fast() . . . 33
5.2.3.35 folded_dim() . . . 33
5.2.3.36 imag() . . . 34
5.2.3.37 inv() . . . 34
5.2.3.38 inverse_gray() . . . 34
5.2.3.39 inverse_reversed_gray() . . . 34
5.2.3.40 involute() . . . 35
5.2.3.41 log() [1/4] . . . 35
5.2.3.42 log() [2/4] . . . 35
5.2.3.43 log() [3/4] . . . 36
5.2.3.44 log() [4/4] . . . 36
5.2.3.45 log2() . . . 36
5.2.3.46 matrix_log() . . . 37
5.2.3.47 matrix_sqrt() . . . 37
5.2.3.48 max_abs() . . . 37
5.2.3.49 max_pos() . . . 38
5.2.3.50 min_neg() . . . 38
5.2.3.51 norm() . . . 38
5.2.3.52 odd() . . . 38
5.2.3.53 offset_level() . . . 39
5.2.3.54 operator &() [1/8] . . . 39
5.2.3.55 operator &() [2/8] . . . 39
5.2.3.56 operator &() [3/8] . . . 39
5.2.3.57 operator &() [4/8] . . . 40

5.2.3.58 operator &() [5/8] . . . 40
5.2.3.59 operator &() [6/8] . . . 40
5.2.3.60 operator &() [7/8] . . . 40
5.2.3.61 operator &() [8/8] . . . 41
5.2.3.62 operator"!=() [1/3] . . . 41
5.2.3.63 operator"!=() [2/3] . . . 41
5.2.3.64 operator"!=() [3/3] . . . 41
5.2.3.65 operator%() [1/3] . . . 42
5.2.3.66 operator%() [2/3] . . . 42
5.2.3.67 operator%() [3/3] . . . 42
5.2.3.68 operator∗() [1/6] . . . 43
5.2.3.69 operator∗() [2/6] . . . 43
5.2.3.70 operator∗() [3/6] . . . 43
5.2.3.71 operator∗() [4/6] . . . 44
5.2.3.72 operator∗() [5/6] . . . 44
5.2.3.73 operator∗() [6/6] . . . 44
5.2.3.74 operator+() [1/3] . . . 44
5.2.3.75 operator+() [2/3] . . . 45
5.2.3.76 operator+() [3/3] . . . 45
5.2.3.77 operator-() [1/3] . . . 45
5.2.3.78 operator-() [2/3] . . . 45
5.2.3.79 operator-() [3/3] . . . 46
5.2.3.80 operator/() [1/5] . . . 46
5.2.3.81 operator/() [2/5] . . . 46
5.2.3.82 operator/() [3/5] . . . 47
5.2.3.83 operator/() [4/5] . . . 47
5.2.3.84 operator/() [5/5] . . . 47
5.2.3.85 operator<<() [1/4] . . . 47
5.2.3.86 operator<<() [2/4] . . . 48
5.2.3.87 operator<<() [3/4] . . . 48

5.2.3.88 operator<<() [4/4] . . . 48
5.2.3.89 operator>>() [1/3] . . . 48
5.2.3.90 operator>>() [2/3] . . . 49
5.2.3.91 operator>>() [3/3] . . . 49
5.2.3.92 operator^() [1/4] . . . 49
5.2.3.93 operator^() [2/4] . . . 49
5.2.3.94 operator^() [3/4] . . . 50
5.2.3.95 operator^() [4/4] . . . 50
5.2.3.96 operator"|() [1/4] . . . 50
5.2.3.97 operator"|() [2/4] . . . 50
5.2.3.98 operator"|() [3/4] . . . 51
5.2.3.99 operator"|() [4/4] . . . 51
5.2.3.100 outer_pow() . . . 51
5.2.3.101 pade_approx() . . . 51
5.2.3.102 pade_log() . . . 52
5.2.3.103 pos_mod() . . . 52
5.2.3.104 pow() [1/2] . . . 52
5.2.3.105 pow() [2/2] . . . 53
5.2.3.106 pure() . . . 53
5.2.3.107 quad() . . . 53
5.2.3.108 real() . . . 53
5.2.3.109 reframe() . . . 54
5.2.3.110 reverse() . . . 54
5.2.3.111 scalar() . . . 54
5.2.3.112 sign_of_square() . . . 55
5.2.3.113 sin() [1/2] . . . 55
5.2.3.114 sin() [2/2] . . . 55
5.2.3.115 sinh() . . . 56
5.2.3.116 sqrt() [1/4] . . . 56
5.2.3.117 sqrt() [2/4] . . . 56

5.2.3.118 sqrt() [3/4] . . . 57
5.2.3.119 sqrt() [4/4] . . . 57
5.2.3.120 star() [1/3] . . . 57
5.2.3.121 star() [2/3] . . . 57
5.2.3.122 star() [3/3] . . . 58
5.2.3.123 tan() [1/2] . . . 58
5.2.3.124 tan() [2/2] . . . 58
5.2.3.125 tanh() . . . 59
5.2.3.126 to_demote() . . . 59
5.2.3.127 to_promote() . . . 59
5.2.3.128 try_catch() [1/2] . . . 59
5.2.3.129 try_catch() [2/2] . . . 60
5.2.3.130 vector_part() . . . 60
5.2.4 Variable Documentation . . . 60
5.2.4.1 BITS_PER_SET_VALUE . . . 60
5.2.4.2 DEFAULT_Basis_Max_Count . . . 60
5.2.4.3 DEFAULT_Div_Max_Steps . . . 61
5.2.4.4 DEFAULT_Fast_Size_Threshold . . . 61
5.2.4.5 DEFAULT_Function_Precision . . . 61
5.2.4.6 DEFAULT_HI . . . 61
5.2.4.7 DEFAULT_Inv_Fast_Dim_Threshold . . . 61
5.2.4.8 DEFAULT_Log_Max_Inner_Steps . . . 61
5.2.4.9 DEFAULT_Log_Max_Outer_Steps . . . 62
5.2.4.10 DEFAULT_Mult_Matrix_Threshold . . . 62
5.2.4.11 DEFAULT_Products_Size_Threshold . . . 62
5.2.4.12 DEFAULT_Sqrt_Max_Steps . . . 62
5.2.4.13 DEFAULT_TRUNCATION . . . 62
5.2.4.14 l_ln2 . . . 62
5.2.4.15 l_pi . . . 63
5.2.4.16 MS_PER_S . . . 63

5.3 glucat::gen Namespace Reference . . . 63
5.3.1 Typedef Documentation . . . 63
5.3.1.1 signature_t . . . 63
5.3.2 Variable Documentation . . . 64
5.3.2.1 offset_to_super . . . 64
5.4 glucat::matrix Namespace Reference . . . 64
5.4.1 Enumeration Type Documentation . . . 65
5.4.1.1 eig_case_t . . . 65
5.4.2 Function Documentation . . . 66
5.4.2.1 classify_eigenvalues() . . . 66
5.4.2.2 eigenvalues() . . . 66
5.4.2.3 inner() . . . 66
5.4.2.4 isnan() . . . 67
5.4.2.5 kron() . . . 67
5.4.2.6 mono_kron() . . . 67
5.4.2.7 mono_prod() . . . 67
5.4.2.8 nnz() . . . 68
5.4.2.9 nork() . . . 68
5.4.2.10 nork_range() . . . 68
5.4.2.11 norm_frob2() . . . 69
5.4.2.12 prod() . . . 69
5.4.2.13 signed_perm_nork() . . . 69
5.4.2.14 sparse_prod() . . . 69
5.4.2.15 to_lapack() . . . 70
5.4.2.16 trace() . . . 70
5.4.2.17 unit() . . . 70
5.5 glucat::timing Namespace Reference . . . 70
5.5.1 Function Documentation . . . 71
5.5.1.1 elapsed() . . . 71
5.5.2 Variable Documentation . . . 71

5.5.2.1 EXTRA_TRIALS . . . 71
5.5.2.2 MS_PER_CLOCK . . . 71
5.5.2.3 MS_PER_SEC . . . 71
5.6 PyClical Namespace Reference . . . 72
5.6.1 Function Documentation . . . 72
5.6.1.1 _test() . . . 72
5.6.1.2 clifford_hidden_doctests() . . . 73
5.6.1.3 e() . . . 74
5.6.1.4 index_set_hidden_doctests() . . . 74
5.6.1.5 istpq() . . . 76
5.6.2 Variable Documentation . . . 76
5.6.2.1 __version__ . . . 76
5.6.2.2 cl . . . 76
5.6.2.3 fill . . . 76
5.6.2.4 i . . . 77
5.6.2.5 ist . . . 77
5.6.2.6 ixt . . . 77
5.6.2.7 nbar3 . . . 77
5.6.2.8 ninf3 . . . 77
5.6.2.9 obj . . . 78
5.6.2.10 pi . . . 78
5.6.2.11 tau . . . 78
5.7 std Namespace Reference . . . 78

**6 Class Documentation** **79**

6.1 glucat::basis_table< Scalar_T, LO, HI, Matrix_T > Class Template Reference . . . . . 79

6.1.1 Detailed Description . . . . . 80

6.1.2 Constructor & Destructor Documentation . . . . . 80

6.1.2.1 basis_table() [1/2] . . . . . 80

6.1.2.2 ~basis_table() . . . . . 80

6.1.2.3 basis_table() [2/2] . . . . . 81

6.1.3 Member Function Documentation . . . . . 81

6.1.3.1 basis() . . . . . 81

6.1.3.2 operator=() . . . . . 81

6.1.4 Friends And Related Function Documentation . . . . . 81

6.1.4.1 friend_for_private_destructor . . . . . 81

6.2 glucat::bool_to_type< truth_value > Class Template Reference . . . . . 82

6.2.1 Detailed Description . . . . . 82

6.2.2 Member Enumeration Documentation . . . . . 82

6.2.2.1 anonymous enum . . . . . 82

6.3 PyClical.clifford Class Reference . . . . . 83

6.3.1 Detailed Description . . . . . 84

6.3.2 Member Function Documentation . . . . . 84

6.3.2.1 __add__() . . . . . 85

6.3.2.2 __and__() . . . . . 85

6.3.2.3 __call__() . . . . . 85

6.3.2.4 __cinit__() . . . . . 86

6.3.2.5 __contains__() . . . . . 86

6.3.2.6 __dealloc__() . . . . . 86

6.3.2.7 __div__() . . . . . 87

6.3.2.8 __getitem__() . . . . . 87

6.3.2.9 __iadd__() . . . . . 87

6.3.2.10 __iand__() . . . . . 88

6.3.2.11 __idiv__() . . . . . 88

6.3.2.12 __imod__() . . . 88
6.3.2.13 __imul__() . . . 89
6.3.2.14 __ior__() . . . 89
6.3.2.15 __isub__() . . . 89
6.3.2.16 __iter__() . . . 90
6.3.2.17 __ixor__() . . . 90
6.3.2.18 __mod__() . . . 90
6.3.2.19 __mul__() . . . 91
6.3.2.20 __neg__() . . . 91
6.3.2.21 __or__() . . . 91
6.3.2.22 __pos__() . . . 92
6.3.2.23 __pow__() . . . 92
6.3.2.24 __repr__() . . . 92
6.3.2.25 __richcmp__() . . . 93
6.3.2.26 __str__() . . . 93
6.3.2.27 __sub__() . . . 93
6.3.2.28 __xor__() . . . 94
6.3.2.29 abs() . . . 94
6.3.2.30 conj() . . . 94
6.3.2.31 even() . . . 95
6.3.2.32 frame() . . . 95
6.3.2.33 inv() . . . 95
6.3.2.34 involute() . . . 96
6.3.2.35 isnan() . . . 96
6.3.2.36 max_abs() . . . 96
6.3.2.37 norm() . . . 97
6.3.2.38 odd() . . . 97
6.3.2.39 outer_pow() . . . 97
6.3.2.40 pow() . . . 98
6.3.2.41 pure() . . . 98

6.3.2.42 quad() . . . 98
6.3.2.43 reframe() . . . 99
6.3.2.44 reverse() . . . 99
6.3.2.45 scalar() . . . 99
6.3.2.46 truncated() . . . 100
6.3.2.47 vector_part() . . . 100
6.3.3 Member Data Documentation . . . 100
6.3.3.1 instance . . . 100
6.4 glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T > Class Template Reference . . . 101
6.4.1 Detailed Description . . . 103
6.4.2 Member Typedef Documentation . . . 103
6.4.2.1 index_set_t . . . 103
6.4.2.2 multivector_t . . . 103
6.4.2.3 pair_t . . . 103
6.4.2.4 scalar_t . . . 103
6.4.2.5 vector_t . . . 104
6.4.3 Constructor & Destructor Documentation . . . 104
6.4.3.1 ~clifford_algebra() . . . 104
6.4.4 Member Function Documentation . . . 104
6.4.4.1 classname() . . . 104
6.4.4.2 conj() . . . 104
6.4.4.3 even() . . . 105
6.4.4.4 frame() . . . 105
6.4.4.5 grade() . . . 105
6.4.4.6 inv() . . . 105
6.4.4.7 involute() . . . 105
6.4.4.8 isnan() . . . 106
6.4.4.9 max_abs() . . . 106
6.4.4.10 norm() . . . 106
6.4.4.11 odd() . . . 106

6.4.4.12 operator &=() . . . 106
6.4.4.13 operator%=() . . . 107
6.4.4.14 operator()() . . . 107
6.4.4.15 operator∗=() [1/2] . . . 107
6.4.4.16 operator∗=() [2/2] . . . 107
6.4.4.17 operator+=() [1/2] . . . 107
6.4.4.18 operator+=() [2/2] . . . 108
6.4.4.19 operator-() . . . 108
6.4.4.20 operator-=() . . . 108
6.4.4.21 operator/=() [1/2] . . . 108
6.4.4.22 operator/=() [2/2] . . . 108
6.4.4.23 operator==() [1/2] . . . 109
6.4.4.24 operator==() [2/2] . . . 109
6.4.4.25 operator[]() . . . 109
6.4.4.26 operator^=() . . . 109
6.4.4.27 operator"|=() . . . 109
6.4.4.28 outer_pow() . . . 110
6.4.4.29 pow() . . . 110
6.4.4.30 pure() . . . 110
6.4.4.31 quad() . . . 110
6.4.4.32 reverse() . . . 110
6.4.4.33 scalar() . . . 111
6.4.4.34 truncated() . . . 111
6.4.4.35 vector_part() [1/2] . . . 111
6.4.4.36 vector_part() [2/2] . . . 111
6.4.4.37 write() [1/2] . . . 111
6.4.4.38 write() [2/2] . . . 112
6.5 glucat::compare_types< LHS_T, RHS_T > Class Template Reference . . . 112
6.5.1 Detailed Description . . . 112
6.5.2 Member Enumeration Documentation . . . 112

6.5.2.1 anonymous enum . . . 112
6.6 glucat::compare_types< T, T > Class Template Reference . . . 113
6.6.1 Detailed Description . . . 113
6.6.2 Member Enumeration Documentation . . . 113
6.6.2.1 anonymous enum . . . 113
6.7 glucat::control_t Class Reference . . . 113
6.7.1 Detailed Description . . . 114
6.7.2 Constructor & Destructor Documentation . . . 115
6.7.2.1 control_t() [1/3] . . . 115
6.7.2.2 control_t() [2/3] . . . 115
6.7.2.3 ~control_t() . . . 115
6.7.2.4 control_t() [3/3] . . . 115
6.7.3 Member Function Documentation . . . 115
6.7.3.1 call() [1/2] . . . 116
6.7.3.2 call() [2/2] . . . 116
6.7.3.3 catch_exceptions() . . . 116
6.7.3.4 control() . . . 116
6.7.3.5 operator=() . . . 117
6.7.3.6 valid() . . . 117
6.7.3.7 verbose() . . . 117
6.7.4 Friends And Related Function Documentation . . . 117
6.7.4.1 friend_for_private_destructor . . . 117
6.7.5 Member Data Documentation . . . 117
6.7.5.1 m_catch_exceptions . . . 118
6.7.5.2 m_valid . . . 118
6.7.5.3 m_verbose_output . . . 118
6.8 glucat::CTAssertion< bool > Struct Template Reference . . . 118
6.8.1 Detailed Description . . . 119
6.9 glucat::CTAssertion< true > Struct Template Reference . . . 119
6.9.1 Detailed Description . . . 119

6.10 glucat::numeric_traits< Scalar_T >::demoted<> Struct Template Reference . . . . . 119
6.10.1 Detailed Description . . . . . 119
6.10.2 Member Typedef Documentation . . . . . 120
6.10.2.1 type [1/2] . . . . . 120
6.10.2.2 type [2/2] . . . . . 120
6.11 glucat::matrix::eig_genus< Matrix_T > Struct Template Reference . . . . . 120
6.11.1 Detailed Description . . . . . 121
6.11.2 Member Typedef Documentation . . . . . 121
6.11.2.1 Scalar_T . . . . . 121
6.11.3 Member Data Documentation . . . . . 121
6.11.3.1 m_eig_case . . . . . 121
6.11.3.2 m_safe_arg . . . . . 121
6.12 glucat::error< Class_T > Class Template Reference . . . . . 122
6.12.1 Detailed Description . . . . . 123
6.12.2 Constructor & Destructor Documentation . . . . . 123
6.12.2.1 error() [1/2] . . . . . 123
6.12.2.2 error() [2/2] . . . . . 123
6.12.3 Member Function Documentation . . . . . 123
6.12.3.1 classname() . . . . . 123
6.12.3.2 heading() . . . . . 124
6.12.3.3 print_error_msg() . . . . . 124
6.13 glucat::framed_multi< Scalar_T, LO, HI > Class Template Reference . . . . . 124
6.13.1 Detailed Description . . . . . 127
6.13.2 Member Typedef Documentation . . . . . 127
6.13.2.1 const_iterator . . . . . 128
6.13.2.2 error_t . . . . . 128
6.13.2.3 framed_multi_t . . . . . 128
6.13.2.4 framed_pair_t . . . . . 128
6.13.2.5 index_set_t . . . . . 128
6.13.2.6 iterator . . . . . 129

6.13.2.7 map_t . . . 129
6.13.2.8 matrix_multi_t . . . 129
6.13.2.9 matrix_t . . . 129
6.13.2.10 multivector_t . . . 129
6.13.2.11 scalar_t . . . 130
6.13.2.12 size_type . . . 130
6.13.2.13 sorted_map_t . . . 130
6.13.2.14 term_t . . . 130
6.13.2.15 var_term_t . . . 130
6.13.2.16 vector_t . . . 131
6.13.3 Constructor & Destructor Documentation . . . 131
6.13.3.1 ∼framed_multi() . . . 131
6.13.3.2 framed_multi() [1/15] . . . 131
6.13.3.3 framed_multi() [2/15] . . . 131
6.13.3.4 framed_multi() [3/15] . . . 132
6.13.3.5 framed_multi() [4/15] . . . 132
6.13.3.6 framed_multi() [5/15] . . . 132
6.13.3.7 framed_multi() [6/15] . . . 132
6.13.3.8 framed_multi() [7/15] . . . 133
6.13.3.9 framed_multi() [8/15] . . . 133
6.13.3.10 framed_multi() [9/15] . . . 133
6.13.3.11 framed_multi() [10/15] . . . 133
6.13.3.12 framed_multi() [11/15] . . . 134
6.13.3.13 framed_multi() [12/15] . . . 134
6.13.3.14 framed_multi() [13/15] . . . 134
6.13.3.15 framed_multi() [14/15] . . . 134
6.13.3.16 framed_multi() [15/15] . . . 135
6.13.4 Member Function Documentation . . . 135
6.13.4.1 centre_pm4_qp4() . . . 135
6.13.4.2 centre_pp4_qm4() . . . 135

6.13.4.3 centre_qp1_pm1() . . . 136
6.13.4.4 classname() . . . 136
6.13.4.5 divide() . . . 136
6.13.4.6 fast() . . . 137
6.13.4.7 fast_framed_multi() . . . 137
6.13.4.8 fast_matrix_multi() . . . 137
6.13.4.9 fold() . . . 138
6.13.4.10 nbr_terms() . . . 138
6.13.4.11 operator+=() . . . 138
6.13.4.12 random() . . . 138
6.13.4.13 unfold() . . . 139
6.13.5 Friends And Related Function Documentation . . . 139
6.13.5.1 exp . . . 139
6.13.5.2 framed_multi . . . 139
6.13.5.3 matrix_multi . . . 139
6.13.5.4 operator & . . . 140
6.13.5.5 operator% . . . 140
6.13.5.6 operator∗ . . . 140
6.13.5.7 operator/ . . . 140
6.13.5.8 operator<< [1/2] . . . 140
6.13.5.9 operator<< [2/2] . . . 141
6.13.5.10 operator>> . . . 141
6.13.5.11 operator^ . . . 141
6.13.5.12 operator" | . . . 141
6.13.5.13 star . . . 141
6.14 glucat::gen::generator_table< Matrix_T > Class Template Reference . . . 142
6.14.1 Detailed Description . . . 143
6.14.2 Constructor & Destructor Documentation . . . 143
6.14.2.1 generator_table() [1/2] . . . 143
6.14.2.2 ∼generator_table() . . . 143

6.14.2.3 generator_table() [2/2] . . . 144
6.14.3 Member Function Documentation . . . 144
6.14.3.1 gen_from_pm1_qm1() . . . 144
6.14.3.2 gen_from_pm4_qp4() . . . 144
6.14.3.3 gen_from_pp4_qm4() . . . 144
6.14.3.4 gen_from_qp1_pm1() . . . 145
6.14.3.5 gen_vector() . . . 145
6.14.3.6 generator() . . . 145
6.14.3.7 operator()() . . . 145
6.14.3.8 operator=() . . . 146
6.14.4 Friends And Related Function Documentation . . . 146
6.14.4.1 friend_for_private_destructor . . . 146
6.15 glucat::glucat_error Class Reference . . . 146
6.15.1 Detailed Description . . . 147
6.15.2 Constructor & Destructor Documentation . . . 147
6.15.2.1 glucat_error() . . . 147
6.15.2.2 ∼glucat_error() . . . 148
6.15.3 Member Function Documentation . . . 148
6.15.3.1 classname() . . . 148
6.15.3.2 heading() . . . 148
6.15.3.3 print_error_msg() . . . 148
6.15.4 Member Data Documentation . . . 148
6.15.4.1 name . . . 148
6.16 glucat::framed_multi< Scalar_T, LO, HI >::hash_size_t Class Reference . . . 149
6.16.1 Detailed Description . . . 149
6.16.2 Constructor & Destructor Documentation . . . 149
6.16.2.1 hash_size_t() . . . 149
6.16.3 Member Function Documentation . . . 149
6.16.3.1 operator()() . . . 149
6.16.4 Member Data Documentation . . . 150

6.16.4.1 n . . . 150
6.17 glucat::index_set< LO, HI > Class Template Reference . . . 150
6.17.1 Detailed Description . . . 153
6.17.2 Member Typedef Documentation . . . 153
6.17.2.1 bitset_t . . . 153
6.17.2.2 error_t . . . 153
6.17.2.3 index_pair_t . . . 154
6.17.2.4 index_set_t . . . 154
6.17.3 Constructor & Destructor Documentation . . . 154
6.17.3.1 index_set() [1/6] . . . 154
6.17.3.2 index_set() [2/6] . . . 154
6.17.3.3 index_set() [3/6] . . . 155
6.17.3.4 index_set() [4/6] . . . 155
6.17.3.5 index_set() [5/6] . . . 155
6.17.3.6 index_set() [6/6] . . . 155
6.17.4 Member Function Documentation . . . 156
6.17.4.1 BOOST_STATIC_ASSERT() . . . 156
6.17.4.2 classname() . . . 156
6.17.4.3 count() . . . 156
6.17.4.4 count_neg() . . . 156
6.17.4.5 count_pos() . . . 157
6.17.4.6 flip() [1/2] . . . 157
6.17.4.7 flip() [2/2] . . . 157
6.17.4.8 fold() [1/2] . . . 157
6.17.4.9 fold() [2/2] . . . 158
6.17.4.10 hash_fn() . . . 158
6.17.4.11 is_contiguous() . . . 158
6.17.4.12 lex_less_than() . . . 158
6.17.4.13 max() . . . 159
6.17.4.14 min() . . . 159

6.17.4.15 operator &=() . . . 159
6.17.4.16 operator"!=() . . . 159
6.17.4.17 operator< () . . . 160
6.17.4.18 operator==() . . . 160
6.17.4.19 operator[]() [1/2] . . . 160
6.17.4.20 operator[]() [2/2] . . . 160
6.17.4.21 operator^=() . . . 161
6.17.4.22 operator" |=() . . . 161
6.17.4.23 operator~() . . . 161
6.17.4.24 reset() [1/2] . . . 161
6.17.4.25 reset() [2/2] . . . 162
6.17.4.26 set() [1/3] . . . 162
6.17.4.27 set() [2/3] . . . 162
6.17.4.28 set() [3/3] . . . 162
6.17.4.29 sign_of_mult() . . . 163
6.17.4.30 sign_of_square() . . . 163
6.17.4.31 test() . . . 163
6.17.4.32 unfold() . . . 163
6.17.4.33 value_of_fold() . . . 164
6.17.5 Friends And Related Function Documentation . . . 164
6.17.5.1 compare . . . 164
6.17.5.2 operator & . . . 164
6.17.5.3 operator^ . . . 164
6.17.5.4 operator" | . . . 164
6.17.5.5 reference . . . 165
6.17.6 Member Data Documentation . . . 165
6.17.6.1 v_hi . . . 165
6.17.6.2 v_lo . . . 165
6.18 PyClical.index_set Class Reference . . . 165
6.18.1 Detailed Description . . . 166

6.18.2 Member Function Documentation . . . 167
6.18.2.1 __and__() . . . 167
6.18.2.2 __cinit__() . . . 167
6.18.2.3 __contains__() . . . 168
6.18.2.4 __dealloc__() . . . 168
6.18.2.5 __getitem__() . . . 168
6.18.2.6 __iand__() . . . 169
6.18.2.7 __invert__() . . . 169
6.18.2.8 __ior__() . . . 169
6.18.2.9 __iter__() . . . 170
6.18.2.10 __ixor__() . . . 170
6.18.2.11 __or__() . . . 170
6.18.2.12 __repr__() . . . 171
6.18.2.13 __richcmp__() . . . 171
6.18.2.14 __setitem__() . . . 171
6.18.2.15 __str__() . . . 172
6.18.2.16 __xor__() . . . 172
6.18.2.17 count() . . . 172
6.18.2.18 count_neg() . . . 173
6.18.2.19 count_pos() . . . 173
6.18.2.20 hash_fn() . . . 173
6.18.2.21 max() . . . 174
6.18.2.22 min() . . . 174
6.18.2.23 sign_of_mult() . . . 174
6.18.2.24 sign_of_square() . . . 175
6.18.3 Member Data Documentation . . . 175
6.18.3.1 instance . . . 175
6.19 glucat::index_set_hash< LO, HI > Class Template Reference . . . 175
6.19.1 Detailed Description . . . 176
6.19.2 Member Typedef Documentation . . . 176

6.19.2.1 index_set_t . . . 176
6.19.3 Member Function Documentation . . . 176
6.19.3.1 operator()() . . . 176
6.20 glucat::matrix_multi< Scalar_T, LO, HI > Class Template Reference . . . 177
6.20.1 Detailed Description . . . 180
6.20.2 Member Typedef Documentation . . . 180
6.20.2.1 basis_matrix_t . . . 180
6.20.2.2 error_t . . . 180
6.20.2.3 framed_multi_t . . . 181
6.20.2.4 index_set_t . . . 181
6.20.2.5 matrix_index_t . . . 181
6.20.2.6 matrix_multi_t . . . 181
6.20.2.7 matrix_t . . . 181
6.20.2.8 multivector_t . . . 182
6.20.2.9 orientation_t . . . 182
6.20.2.10 scalar_t . . . 182
6.20.2.11 term_t . . . 182
6.20.2.12 vector_t . . . 182
6.20.3 Constructor & Destructor Documentation . . . 183
6.20.3.1 ~matrix_multi() . . . 183
6.20.3.2 matrix_multi() [1/17] . . . 183
6.20.3.3 matrix_multi() [2/17] . . . 183
6.20.3.4 matrix_multi() [3/17] . . . 184
6.20.3.5 matrix_multi() [4/17] . . . 184
6.20.3.6 matrix_multi() [5/17] . . . 184
6.20.3.7 matrix_multi() [6/17] . . . 185
6.20.3.8 matrix_multi() [7/17] . . . 185
6.20.3.9 matrix_multi() [8/17] . . . 185
6.20.3.10 matrix_multi() [9/17] . . . 185
6.20.3.11 matrix_multi() [10/17] . . . 186

6.20.3.12 matrix_multi() [11/17] . . . 186
6.20.3.13 matrix_multi() [12/17] . . . 186
6.20.3.14 matrix_multi() [13/17] . . . 186
6.20.3.15 matrix_multi() [14/17] . . . 187
6.20.3.16 matrix_multi() [15/17] . . . 187
6.20.3.17 matrix_multi() [16/17] . . . 187
6.20.3.18 matrix_multi() [17/17] . . . 188
6.20.4 Member Function Documentation . . . 188
6.20.4.1 basis_element() . . . 188
6.20.4.2 classname() . . . 188
6.20.4.3 fast_framed_multi() . . . 189
6.20.4.4 fast_matrix_multi() . . . 189
6.20.4.5 operator+=() . . . 189
6.20.4.6 operator=() . . . 189
6.20.4.7 random() . . . 190
6.20.5 Friends And Related Function Documentation . . . 190
6.20.5.1 framed_multi . . . 190
6.20.5.2 matrix_log . . . 190
6.20.5.3 matrix_multi . . . 190
6.20.5.4 matrix_sqrt . . . 191
6.20.5.5 operator & . . . 191
6.20.5.6 operator% . . . 191
6.20.5.7 operator* . . . 191
6.20.5.8 operator/ . . . 191
6.20.5.9 operator<< [1/2] . . . 192
6.20.5.10 operator<< [2/2] . . . 192
6.20.5.11 operator>> . . . 192
6.20.5.12 operator^ . . . 192
6.20.5.13 operator"| . . . 192
6.20.5.14 reframe . . . 193

6.20.5.15 star . . . 193
6.20.6 Member Data Documentation . . . 193
6.20.6.1 m_frame . . . 193
6.20.6.2 m_matrix . . . 193
6.21 std::numeric_limits< glucat::framed_multi< Scalar_T, LO, HI > > Struct Template Reference . . . 194
6.21.1 Detailed Description . . . 194
6.22 std::numeric_limits< glucat::matrix_multi< Scalar_T, LO, HI > > Struct Template Reference . . . 195
6.22.1 Detailed Description . . . 195
6.23 glucat::numeric_traits< Scalar_T > Class Template Reference . . . 196
6.23.1 Detailed Description . . . 198
6.23.2 Member Function Documentation . . . 198
6.23.2.1 abs() . . . 198
6.23.2.2 acos() . . . 199
6.23.2.3 asin() . . . 199
6.23.2.4 atan() . . . 199
6.23.2.5 conj() . . . 199
6.23.2.6 cos() . . . 200
6.23.2.7 cosh() . . . 200
6.23.2.8 exp() . . . 200
6.23.2.9 fmod() . . . 200
6.23.2.10 imag() . . . 201
6.23.2.11 isInf() [1/3] . . . 201
6.23.2.12 isInf() [2/3] . . . 201
6.23.2.13 isInf() [3/3] . . . 201
6.23.2.14 isNaN() [1/3] . . . 202
6.23.2.15 isNaN() [2/3] . . . 202
6.23.2.16 isNaN() [3/3] . . . 202
6.23.2.17 isNaN_or_isInf() . . . 202
6.23.2.18 ln_2() [1/2] . . . 203
6.23.2.19 ln_2() [2/2] . . . 203

6.23.2.20 log() . . . 203
6.23.2.21 log2() . . . 203
6.23.2.22 NaN() . . . 204
6.23.2.23 pi() [1/2] . . . 204
6.23.2.24 pi() [2/2] . . . 204
6.23.2.25 pow() . . . 204
6.23.2.26 real() . . . 205
6.23.2.27 sin() . . . 205
6.23.2.28 sinh() . . . 205
6.23.2.29 sqrt() . . . 205
6.23.2.30 tan() . . . 206
6.23.2.31 tanh() . . . 206
6.23.2.32 to_double() . . . 206
6.23.2.33 to_int() . . . 206
6.23.2.34 to_scalar_t() [1/9] . . . 207
6.23.2.35 to_scalar_t() [2/9] . . . 207
6.23.2.36 to_scalar_t() [3/9] . . . 207
6.23.2.37 to_scalar_t() [4/9] . . . 207
6.23.2.38 to_scalar_t() [5/9] . . . 208
6.23.2.39 to_scalar_t() [6/9] . . . 208
6.23.2.40 to_scalar_t() [7/9] . . . 208
6.23.2.41 to_scalar_t() [8/9] . . . 208
6.23.2.42 to_scalar_t() [9/9] . . . 209
6.24 glucat::numeric_traits< Scalar_T >::promoted Struct Reference . . . 209
6.24.1 Detailed Description . . . 209
6.24.2 Member Typedef Documentation . . . 209
6.24.2.1 type . . . 209
6.25 glucat::random_generator< Scalar_T > Class Template Reference . . . 210
6.25.1 Detailed Description . . . 210
6.25.2 Constructor & Destructor Documentation . . . 211

6.25.2.1 random_generator() [1/2] . . . 211
6.25.2.2 random_generator() [2/2] . . . 211
6.25.2.3 ∼random_generator() . . . 211
6.25.3 Member Function Documentation . . . 211
6.25.3.1 generator() . . . 211
6.25.3.2 normal() . . . 212
6.25.3.3 operator=() . . . 212
6.25.3.4 uniform() . . . 212
6.25.4 Friends And Related Function Documentation . . . 212
6.25.4.1 friend_for_private_destructor . . . 212
6.25.5 Member Data Documentation . . . 212
6.25.5.1 normal_dist . . . 213
6.25.5.2 seed . . . 213
6.25.5.3 uint_gen . . . 213
6.25.5.4 uniform_dist . . . 213
6.26 glucat::index_set< LO, HI >::reference Class Reference . . . 214
6.26.1 Detailed Description . . . 215
6.26.2 Constructor & Destructor Documentation . . . 215
6.26.2.1 reference() [1/2] . . . 215
6.26.2.2 reference() [2/2] . . . 215
6.26.2.3 ∼reference() . . . 216
6.26.3 Member Function Documentation . . . 216
6.26.3.1 flip() . . . 216
6.26.3.2 operator bool() . . . 216
6.26.3.3 operator=() [1/2] . . . 216
6.26.3.4 operator=() [2/2] . . . 217
6.26.3.5 operator∼() . . . 217
6.26.4 Friends And Related Function Documentation . . . 217
6.26.4.1 index_set . . . 217
6.26.5 Member Data Documentation . . . 217

6.26.5.1 m_idx . . . 217
6.26.5.2 m_pst . . . 218
6.27 glucat::sorted_range< Map_T, Sorted_Map_T > Class Template Reference . . . 218
6.27.1 Detailed Description . . . 218
6.27.2 Member Typedef Documentation . . . 218
6.27.2.1 map_t . . . 219
6.27.2.2 sorted_iterator . . . 219
6.27.2.3 sorted_map_t . . . 219
6.27.3 Constructor & Destructor Documentation . . . 219
6.27.3.1 sorted_range() . . . 219
6.27.4 Member Data Documentation . . . 219
6.27.4.1 sorted_begin . . . 220
6.27.4.2 sorted_end . . . 220
6.28 glucat::sorted_range< Sorted_Map_T, Sorted_Map_T > Class Template Reference . . . 220
6.28.1 Detailed Description . . . 220
6.28.2 Member Typedef Documentation . . . 221
6.28.2.1 map_t . . . 221
6.28.2.2 sorted_iterator . . . 221
6.28.2.3 sorted_map_t . . . 221
6.28.3 Constructor & Destructor Documentation . . . 221
6.28.3.1 sorted_range() . . . 221
6.28.4 Member Data Documentation . . . 221
6.28.4.1 sorted_begin . . . 222
6.28.4.2 sorted_end . . . 222
6.29 glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_Max_Outer_↩ Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision > Struct Template Reference . . . 222
6.29.1 Detailed Description . . . 223
6.29.2 Member Enumeration Documentation . . . 223
6.29.2.1 anonymous enum . . . 223
6.29.2.2 anonymous enum . . . 223

6.29.2.3 anonymous enum . . . 224
6.29.2.4 anonymous enum . . . 224
6.29.2.5 anonymous enum . . . 225
6.29.2.6 anonymous enum . . . 225
6.29.2.7 anonymous enum . . . 226
6.29.2.8 anonymous enum . . . 226
6.29.2.9 anonymous enum . . . 226
6.29.3 Member Data Documentation . . . 227
6.29.3.1 function_precision . . . 227
6.30 glucat::framed_multi< Scalar_T, LO, HI >::var_term Class Reference . . . 227
6.30.1 Detailed Description . . . 228
6.30.2 Member Typedef Documentation . . . 229
6.30.2.1 var_pair_t . . . 229
6.30.3 Constructor & Destructor Documentation . . . 229
6.30.3.1 ~var_term() . . . 229
6.30.3.2 var_term() [1/2] . . . 229
6.30.3.3 var_term() [2/2] . . . 229
6.30.4 Member Function Documentation . . . 230
6.30.4.1 classname() . . . 230
6.30.4.2 operator*=() . . . 230

**7 File Documentation** **231**

7.1 glucat/clifford_algebra.h File Reference . . . 231

7.1.1 Macro Definition Documentation . . . 238

7.1.1.1 _GLUCAT_CLIFFORD_ALGEBRA_OPERATIONS . . . 238

7.2 glucat/clifford_algebra_imp.h File Reference . . . 238

7.3 glucat/errors.h File Reference . . . 245

7.4 glucat/errors_imp.h File Reference . . . 246

7.5 glucat/framed_multi.h File Reference . . . 246

7.5.1 Macro Definition Documentation . . . 249

7.5.1.1 _GLUCAT_MAP_IS_HASH . . . 249

7.6 glucat/framed_multi_imp.h File Reference . . . 249

7.6.1 Macro Definition Documentation . . . 251

7.6.1.1 _GLUCAT_HASH_N . . . 252

7.6.1.2 _GLUCAT_HASH_SIZE_T . . . 252

7.7 glucat/generation.h File Reference . . . 252

7.8 glucat/generation_imp.h File Reference . . . 254

7.9 glucat/global.h File Reference . . . 254

7.9.1 Macro Definition Documentation . . . 257

7.9.1.1 _GLUCAT_CTAssert . . . 257

7.10 glucat/glucat.h File Reference . . . 257

7.11 glucat/glucat_config.h File Reference . . . 258

7.11.1 Macro Definition Documentation . . . 259

7.11.1.1 GLUCAT_HAVE_INTTYPES_H . . . 259

7.11.1.2 GLUCAT_HAVE_MEMORY_H . . . 259

7.11.1.3 GLUCAT_HAVE_STDINT_H . . . 259

7.11.1.4 GLUCAT_HAVE_STDLIB_H . . . 260

7.11.1.5 GLUCAT_HAVE_STRING_H . . . 260

7.11.1.6 GLUCAT_HAVE_STRINGS_H . . . 260

7.11.1.7 GLUCAT_HAVE_SYS_STAT_H . . . 260

7.11.1.8 GLUCAT_HAVE_SYS_TYPES_H . . . 260

7.11.1.9 GLUCAT_HAVE_UNISTD_H . . . 260
7.11.1.10 GLUCAT_PACKAGE . . . 261
7.11.1.11 GLUCAT_PACKAGE_BUGREPORT . . . 261
7.11.1.12 GLUCAT_PACKAGE_NAME . . . 261
7.11.1.13 GLUCAT_PACKAGE_STRING . . . 261
7.11.1.14 GLUCAT_PACKAGE_TARNAME . . . 261
7.11.1.15 GLUCAT_PACKAGE_URL . . . 261
7.11.1.16 GLUCAT_PACKAGE_VERSION . . . 262
7.11.1.17 GLUCAT_STDC_HEADERS . . . 262
7.11.1.18 GLUCAT_VERSION . . . 262
7.12 glucat/glucat_imp.h File Reference . . . 262
7.13 glucat/index_set.h File Reference . . . 263
7.14 glucat/index_set_imp.h File Reference . . . 265
7.15 glucat/long_double.h File Reference . . . 266
7.16 glucat/matrix.h File Reference . . . 267
7.17 glucat/matrix_imp.h File Reference . . . 269
7.18 glucat/matrix_multi.h File Reference . . . 271
7.19 glucat/matrix_multi_imp.h File Reference . . . 274
7.20 glucat/portability.h File Reference . . . 276
7.20.1 Macro Definition Documentation . . . 277
7.20.1.1 _GLUCAT_ISINF . . . 277
7.20.1.2 _GLUCAT_ISNAN . . . 277
7.20.1.3 UBLAS_ABS . . . 278
7.20.1.4 UBLAS_SQRT . . . 278
7.21 glucat/qd.h File Reference . . . 278
7.22 glucat/random.h File Reference . . . 279
7.23 glucat/scalar.h File Reference . . . 280
7.24 glucat/scalar_imp.h File Reference . . . 282
7.25 pyclical/glucat.pxd File Reference . . . 283
7.26 pyclical/PyClical.cpp File Reference . . . 283

7.26.1 Macro Definition Documentation . . . 283
7.26.1.1 PY_SSIZE_T_CLEAN . . . 284
7.27 pyclical/PyClical.h File Reference . . . 284
7.27.1 Typedef Documentation . . . 285
7.27.1.1 Clifford . . . 285
7.27.1.2 IndexSet . . . 285
7.27.1.3 scalar_t . . . 285
7.27.1.4 String . . . 286
7.27.1.5 Tune_P . . . 286
7.27.2 Function Documentation . . . 286
7.27.2.1 clifford_to_repr() . . . 286
7.27.2.2 clifford_to_str() . . . 286
7.27.2.3 index_set_to_repr() . . . 287
7.27.2.4 index_set_to_str() . . . 287
7.27.2.5 PyFloat_FromDouble() . . . 287
7.27.3 Variable Documentation . . . 287
7.27.3.1 hi_ndx . . . 287
7.27.3.2 lo_ndx . . . 288
7.28 pyclical/PyClical.pxd File Reference . . . 288
7.29 pyclical/PyClical.pyx File Reference . . . 288
7.30 pyclical/PyClical_nocython.cpp File Reference . . . 289
7.30.1 Macro Definition Documentation . . . 289
7.30.1.1 PY_SSIZE_T_CLEAN . . . 289
7.31 test/control.h File Reference . . . 289
7.32 test/driver.h File Reference . . . 290
7.33 test/timing.h File Reference . . . 290
7.34 test/try_catch.h File Reference . . . 291
7.35 test/tuning.h File Reference . . . 292
7.35.1 Macro Definition Documentation . . . 293
7.35.1.1 __TEST_TUNING_DEFAULT_CONSTANT . . . 293

7.35.2 Typedef Documentation . . . 293
7.35.2.1 precision_t . . . 293
7.35.2.2 Tune_P . . . 293
7.35.3 Function Documentation . . . 293
7.35.3.1 __TEST_TUNING_DEFAULT_CONSTANT() [1/9] . . . 294
7.35.3.2 __TEST_TUNING_DEFAULT_CONSTANT() [2/9] . . . 294
7.35.3.3 __TEST_TUNING_DEFAULT_CONSTANT() [3/9] . . . 294
7.35.3.4 __TEST_TUNING_DEFAULT_CONSTANT() [4/9] . . . 294
7.35.3.5 __TEST_TUNING_DEFAULT_CONSTANT() [5/9] . . . 294
7.35.3.6 __TEST_TUNING_DEFAULT_CONSTANT() [6/9] . . . 294
7.35.3.7 __TEST_TUNING_DEFAULT_CONSTANT() [7/9] . . . 294
7.35.3.8 __TEST_TUNING_DEFAULT_CONSTANT() [8/9] . . . 295
7.35.3.9 __TEST_TUNING_DEFAULT_CONSTANT() [9/9] . . . 295
7.35.3.10 _GLUCAT_CTAssert() . . . 295
7.35.4 Variable Documentation . . . 295
7.35.4.1 Test_Tuning_Function_Precision . . . 295
7.35.4.2 Test_Tuning_Max_Threshold . . . 295
7.36 test/undefine.h File Reference . . . 295

**Index** **297**

# Chapter 1

# Namespace Index

## 1.1 Namespace List

Here is a list of all namespaces with brief descriptions:


cga3
    Definitions for 3D Conformal Geometric Algebra [DL] . . . . . 9
glucat . . . . . 10
glucat::gen . . . . . 63
glucat::matrix . . . . . 64
glucat::timing . . . . . 70
PyClical . . . . . 72
std . . . . . 78

# Chapter 2

# Hierarchical Index

## 2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:


bitset
  glucat::index_set< LO, HI > . . . 150
glucat::bool_to_type< truth_value > . . . 82
cdef
  PyClical.clifford . . . 83
  PyClical.index_set . . . 165
Clifford
  PyClical.clifford . . . 83
glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T > . . . 101
glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > > . . . 101
  glucat::framed_multi< Scalar_T, LO, HI > . . . 124
glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > > . . . 101
  glucat::matrix_multi< Scalar_T, LO, HI > . . . 177
glucat::compare_types< LHS_T, RHS_T > . . . 112
glucat::compare_types< T, T > . . . 113
glucat::control_t . . . 113
glucat::CTAssertion< bool > . . . 118
glucat::CTAssertion< true > . . . 119
glucat::numeric_traits< Scalar_T >::demoted<> . . . 119
glucat::matrix::eig_genus< Matrix_T > . . . 120
glucat::framed_multi< Scalar_T, LO, HI >::hash_size_t . . . 149
glucat::index_set_hash< LO, HI > . . . 175
IndexSet
  PyClical.index_set . . . 165
inline
  PyClical.clifford . . . 83
  PyClical.index_set . . . 165
logic_error
  glucat::glucat_error . . . 146
    glucat::error< Class_T > . . . 122
map
  glucat::basis_table< Scalar_T, LO, HI, Matrix_T > . . . 79
  glucat::gen::generator_table< Matrix_T > . . . 142
numeric_limits
  std::numeric_limits< glucat::framed_multi< Scalar_T, LO, HI > > . . . 194

std::numeric_limits< glucat::matrix_multi< Scalar_T, LO, HI > > . . . . . 195
glucat::numeric_traits< Scalar_T > . . . . . 196
obj
PyClical.clifford . . . . . 83
PyClical.index_set . . . . . 165
pair
glucat::framed_multi< Scalar_T, LO, HI >::var_term . . . . . 227
glucat::numeric_traits< Scalar_T >::promoted . . . . . 209
glucat::random_generator< Scalar_T > . . . . . 210
glucat::index_set< LO, HI >::reference . . . . . 214
glucat::sorted_range< Map_T, Sorted_Map_T > . . . . . 218
glucat::sorted_range< Sorted_Map_T, Sorted_Map_T > . . . . . 220
toClifford
PyClical.clifford . . . . . 83
toIndexSet
PyClical.index_set . . . . . 165
glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision > . . . . . 222
unordered_map
glucat::framed_multi< Scalar_T, LO, HI > . . . . . 124

# Chapter 3

# Class Index

## 3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:


glucat::basis_table< Scalar_T, LO, HI, Matrix_T >
: Table of basis elements used as a cache by basis_element() . . . 79
glucat::bool_to_type< truth_value >
: Bool to type . . . 82
PyClical.clifford . . . 83
glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >
: Clifford_algebra<> declares the operations of a Clifford algebra . . . 101
glucat::compare_types< LHS_T, RHS_T >
: Type comparison . . . 112
glucat::compare_types< T, T > . . . 113
glucat::control_t
: Parameters to control tests . . . 113
glucat::CTAssertion< bool >
: Compile time assertion . . . 118
glucat::CTAssertion< true > . . . 119
glucat::numeric_traits< Scalar_T >::demoted<>
: Demoted type for long double . . . 119
glucat::matrix::eig_genus< Matrix_T >
: Structure containing classification of eigenvalues . . . 120
glucat::error< Class_T >
: Specific exception class . . . 122
glucat::framed_multi< Scalar_T, LO, HI >
: A framed_multi<Scalar_T,LO,HI> is a framed approximation to a multivector . . . 124
glucat::gen::generator_table< Matrix_T >
: Table of generators for specific signatures . . . 142
glucat::glucat_error
: Abstract exception class . . . 146
glucat::framed_multi< Scalar_T, LO, HI >::hash_size_t . . . 149
glucat::index_set< LO, HI >
: Index set class based on std::bitset<> in Gnu standard C++ library . . . 150
PyClical.index_set . . . 165
glucat::index_set_hash< LO, HI > . . . 175
glucat::matrix_multi< Scalar_T, LO, HI >
: A matrix_multi<Scalar_T,LO,HI> is a matrix approximation to a multivector . . . 177
std::numeric_limits< glucat::framed_multi< Scalar_T, LO, HI > >
: Numeric limits for framed_multi inherit limits for the corresponding scalar type . . . 194

std::numeric_limits< glucat::matrix_multi< Scalar_T, LO, HI > >
Numeric limits for matrix_multi inherit limits for the corresponding scalar type . . . . . 195
glucat::numeric_traits< Scalar_T >
Extra traits which extend numeric limits . . . . . 196
glucat::numeric_traits< Scalar_T >::promoted
Promoted type . . . . . 209
glucat::random_generator< Scalar_T >
Random number generator with single instance per Scalar_T . . . . . 210
glucat::index_set< LO, HI >::reference
Index set member reference . . . . . 214
glucat::sorted_range< Map_T, Sorted_Map_T >
Sorted range for use with output . . . . . 218
glucat::sorted_range< Sorted_Map_T, Sorted_Map_T > . . . . . 220
glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis
Tuning policy . . . . . 222
glucat::framed_multi< Scalar_T, LO, HI >::var_term
Variable term . . . . . 227

# Chapter 4

# File Index

## 4.1 File List

Here is a list of all files with brief descriptions:


glucat/clifford_algebra.h . . . 231
glucat/clifford_algebra_imp.h . . . 238
glucat/errors.h . . . 245
glucat/errors_imp.h . . . 246
glucat/framed_multi.h . . . 246
glucat/framed_multi_imp.h . . . 249
glucat/generation.h . . . 252
glucat/generation_imp.h . . . 254
glucat/global.h . . . 254
glucat/glucat.h . . . 257
glucat/glucat_config.h . . . 258
glucat/glucat_imp.h . . . 262
glucat/index_set.h . . . 263
glucat/index_set_imp.h . . . 265
glucat/long_double.h . . . 266
glucat/matrix.h . . . 267
glucat/matrix_imp.h . . . 269
glucat/matrix_multi.h . . . 271
glucat/matrix_multi_imp.h . . . 274
glucat/portability.h . . . 276
glucat/qd.h . . . 278
glucat/random.h . . . 279
glucat/scalar.h . . . 280
glucat/scalar_imp.h . . . 282
pyclical/glucat.pxd . . . 283
pyclical/PyClical.cpp . . . 283
pyclical/PyClical.h . . . 284
pyclical/PyClical.pxd . . . 288
pyclical/PyClical.pyx . . . 288
pyclical/PyClical_nocython.cpp . . . 289
test/control.h . . . 289
test/driver.h . . . 290
test/timing.h . . . 290
test/try_catch.h . . . 291
test/tuning.h . . . 292
test/undefine.h . . . 295

# Chapter 5

# Namespace Documentation

## 5.1 cga3 Namespace Reference

Definitions for 3D Conformal Geometric Algebra [DL].

### Functions

- template<typename Multivector_T >
  Multivector_T cga3 (const Multivector_T &x)
  *Convert Euclidean 3D vector to Conformal Geometric Algebra null vector [DL (10.50)].*
- template<typename Multivector_T >
  Multivector_T cga3std (const Multivector_T &X)
  *Convert CGA3 null vector to standard Conformal Geometric Algebra null vector [DL (10.52)].*
- template<typename Multivector_T >
  Multivector_T agc3 (const Multivector_T &X)
  *Convert CGA3 null vector to Euclidean 3D vector [DL (10.50)].*

### 5.1.1 Detailed Description

Definitions for 3D Conformal Geometric Algebra [DL].

### 5.1.2 Function Documentation

#### 5.1.2.1 agc3()

```
template<typename Multivector_T >
Multivector_T cga3::agc3 (
            const Multivector_T & X )  [inline]
```

Convert CGA3 null vector to Euclidean 3D vector [DL (10.50)].

Definition at line 138 of file PyClical.h.

References cga3std(), PyClical::cl, and PyClical::ist.

#### 5.1.2.2 cga3()

```
template<typename Multivector_T >
Multivector_T cga3::cga3 (
            const Multivector_T & x )  [inline]
```

Convert Euclidean 3D vector to Conformal Geometric Algebra null vector [DL (10.50)].

Definition at line 115 of file PyClical.h.

References PyClical::cl, PyClical::ist, and PyClical::ninf3.

#### 5.1.2.3 cga3std()

```
template<typename Multivector_T >
Multivector_T cga3::cga3std (
            const Multivector_T & X )  [inline]
```

Convert CGA3 null vector to standard Conformal Geometric Algebra null vector [DL (10.52)].

Definition at line 126 of file PyClical.h.

References PyClical::cl, PyClical::ist, and PyClical::ninf3.

Referenced by agc3().

## 5.2 glucat Namespace Reference

### Namespaces

- gen
- matrix
- timing

### Classes

- class basis_table

  *Table of basis elements used as a cache by basis_element()*
- class bool_to_type

  *Bool to type.*
- class clifford_algebra

  *clifford_algebra<> declares the operations of a Clifford algebra*
- class compare_types

  *Type comparison.*
- class compare_types< T, T >
- class control_t

  *Parameters to control tests.*
- struct CTAssertion

*Compile time assertion.*

- struct CTAssertion< true >
- class error

  *Specific exception class.*
- class framed_multi

  *A framed_multi<Scalar_T,LO,HI> is a framed approximation to a multivector.*
- class glucat_error

  *Abstract exception class.*
- class index_set

  *Index set class based on std::bitset<> in Gnu standard C++ library.*
- class index_set_hash
- class matrix_multi

  *A matrix_multi<Scalar_T,LO,HI> is a matrix approximation to a multivector.*
- class numeric_traits

  *Extra traits which extend numeric limits.*
- class random_generator

  *Random number generator with single instance per Scalar_T.*
- class sorted_range

  *Sorted range for use with output.*
- class sorted_range< Sorted_Map_T, Sorted_Map_T >
- struct tuning

  *Tuning policy.*

## Typedefs

- typedef int index_t

  *Size of index_t should be enough to represent LO, HI.*
- typedef unsigned long set_value_t

  *Size of set_value_t should be enough to contain index_set<LO,HI>*
- typedef int(* intfn) ()

  *For exception catching: pointer to function returning int.*
- typedef int(* intintfn) (int)

  *For exception catching: pointer to function of int returning int.*

## Enumerations

- enum precision_t { precision_demoted, precision_same, precision_promoted }

  *Precision policy.*

## Functions

- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  bool operator!= (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Test for inequality of multivectors.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  bool operator!= (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar_T &scr)

  *Test for inequality of multivector and scalar.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  bool operator!= (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)

  *Test for inequality of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator+ (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar↩
  _T &scr)

  *Geometric sum of multivector and scalar.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator+ (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)

  *Geometric sum of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator+ (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Geometric sum.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator- (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar↩
  _T &scr)

  *Geometric difference of multivector and scalar.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator- (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)

  *Geometric difference of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator- (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Geometric difference.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator* (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar↩
  _T &scr)

  *Product of multivector and scalar.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator* (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)

  *Product of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator* (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Geometric product.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator^ (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Outer product.*

- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator & (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Inner product.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator% (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Left contraction.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T star (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Hestenes scalar product.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator/ (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar↩ _T &scr)

  *Quotient of multivector and scalar.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator/ (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)

  *Quotient of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator/ (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Geometric quotient.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator| (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Transformation via twisted adjoint action.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > inv (const Multivector< Scalar_T, LO, HI > &val)

  *Geometric multiplicative inverse.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > pow (const Multivector< Scalar_T, LO, HI > &lhs, int rhs)

  *Integer power of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > pow (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Multivector power of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > outer_pow (const Multivector< Scalar_T, LO, HI > &lhs, int rhs)

  *Outer product power of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T scalar (const Multivector< Scalar_T, LO, HI > &val)

  *Scalar part.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T real (const Multivector< Scalar_T, LO, HI > &val)

  *Real part: synonym for scalar part.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T imag (const Multivector< Scalar_T, LO, HI > &val)

  *Imaginary part: deprecated (always 0)*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > pure (const Multivector< Scalar_T, LO, HI > &val)

  *Pure part.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > even (const Multivector< Scalar_T, LO, HI > &val)

  *Even part.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > odd (const Multivector< Scalar_T, LO, HI > &val)

  *Odd part.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const std::vector< Scalar_T > vector_part (const Multivector< Scalar_T, LO, HI > &val)

  *Vector part of multivector, as a vector_t with respect to frame()*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > involute (const Multivector< Scalar_T, LO, HI > &val)

  *Main involution, each {i} is replaced by -{i} in each term, eg. {1}∗{2} -> (-{2})∗(-{1})*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > reverse (const Multivector< Scalar_T, LO, HI > &val)

  *Reversion, eg. {1}∗{2} -> {2}∗{1}.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > conj (const Multivector< Scalar_T, LO, HI > &val)

  *Conjugation, rev o invo == invo o rev.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T quad (const Multivector< Scalar_T, LO, HI > &val)

  *Scalar_T quadratic form == (rev(x)∗x)(0)*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T norm (const Multivector< Scalar_T, LO, HI > &val)

  *Scalar_T norm == sum of norm of coordinates.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T abs (const Multivector< Scalar_T, LO, HI > &val)

  *Absolute value == sqrt(norm)*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T max_abs (const Multivector< Scalar_T, LO, HI > &val)

  *Maximum of absolute values of components of multivector: multivector infinity norm.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > complexifier (const Multivector< Scalar_T, LO, HI > &val)

*Square root of -1 which commutes with all members of the frame of the given multivector.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > elliptic (const Multivector< Scalar_T, LO, HI > &val)
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > sqrt (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Square root of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > sqrt (const Multivector< Scalar_T, LO, HI > &val)

  *Square root of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > clifford_exp (const Multivector< Scalar_T, LO, HI > &val)

  *Exponential of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > log (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Natural logarithm of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > log (const Multivector< Scalar_T, LO, HI > &val)

  *Natural logarithm of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > cos (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Cosine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > cos (const Multivector< Scalar_T, LO, HI > &val)

  *Cosine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > acos (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse cosine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > acos (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse cosine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > cosh (const Multivector< Scalar_T, LO, HI > &val)

  *Hyperbolic cosine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > acosh (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse hyperbolic cosine of multivector with specified complexifier.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > acosh (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse hyperbolic cosine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > sin (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Sine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > sin (const Multivector< Scalar_T, LO, HI > &val)

  *Sine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > asin (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse sine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > asin (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse sine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > sinh (const Multivector< Scalar_T, LO, HI > &val)

  *Hyperbolic sine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > asinh (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse hyperbolic sine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > asinh (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse hyperbolic sine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > tan (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Tangent of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > tan (const Multivector< Scalar_T, LO, HI > &val)

  *Tangent of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > atan (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse tangent of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > atan (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse tangent of multivector.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > tanh (const Multivector< Scalar_T, LO, HI > &val)

  *Hyperbolic tangent of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > atanh (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse hyperbolic tangent of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > atanh (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse hyperbolic tangent of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > operator & (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Inner product.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  static void check_complex (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Check that i is a valid complexifier for val.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > operator* (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Geometric product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > operator^ (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Outer product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > operator & (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Inner product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > operator% (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Left contraction.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T star (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Hestenes scalar product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > operator/ (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Geometric quotient.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > operator| (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Transformation via twisted adjoint action.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  std::istream & operator>> (std::istream &s, framed_multi< Scalar_T, LO, HI > &val)

  *Read multivector from input.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  std::ostream & operator<< (std::ostream &os, const framed_multi< Scalar_T, LO, HI > &val)

*Write multivector to output.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  std::ostream & operator<< (std::ostream &os, const std::pair< const index_set< LO, HI >, Scalar_T > &term)

  *Write term to output.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > exp (const framed_multi< Scalar_T, LO, HI > &val)

  *Exponential of multivector.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  static Scalar_T crd_of_mult (const std::pair< const index_set< LO, HI >, Scalar_T > &lhs, const std::pair< const index_set< LO, HI >, Scalar_T > &rhs)

  *Coordinate of product of terms.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const std::pair< const index_set< LO, HI >, Scalar_T > operator* (const std::pair< const index_set< LO, HI >, Scalar_T > &lhs, const std::pair< const index_set< LO, HI >, Scalar_T > &rhs)

  *Product of terms.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > sqrt (const framed_multi< Scalar_T, LO, HI > &val, const framed_multi< Scalar_T, LO, HI > &i, bool prechecked)

  *Square root of multivector with specified complexifier.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > log (const framed_multi< Scalar_T, LO, HI > &val, const framed_multi< Scalar_T, LO, HI > &i, bool prechecked)

  *Natural logarithm of multivector with specified complexifier.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > operator & (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Inner product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  static Scalar_T crd_of_mult (const std::pair< const index_set< LO, HI >, Scalar_T > &lhs, const std::pair< const index_set< LO, HI >, Scalar_T > &rhs)

  *Coordinate of product of terms.*
- _GLUCAT_CTAssert (std::numeric_limits< unsigned char >::radix==2, CannotDetermineBitsPerChar) const index_t BITS_PER_CHAR

  *If radix of unsigned char is not 2, we can't easily determine number of bits from sizeof.*
- _GLUCAT_CTAssert (_GLUCAT_BITS_PER_ULONG==BITS_PER_SET_VALUE, BitsPerULongDoesNotMatchSetValueT) const index_t DEFAULT_LO

  *Default lowest index in an index set.*
- template<typename LHS_T , typename RHS_T >
  LHS_T pos_mod (LHS_T lhs, RHS_T rhs)

  *Modulo function which works reliably for lhs < 0.*
- template<const index_t LO, const index_t HI>
  const index_set< LO, HI > operator^ (const index_set< LO, HI > &lhs, const index_set< LO, HI > &rhs)

  *Symmetric set difference: exclusive or.*
- template<const index_t LO, const index_t HI>
  const index_set< LO, HI > operator & (const index_set< LO, HI > &lhs, const index_set< LO, HI > &rhs)

  *Set intersection: and.*
- template<const index_t LO, const index_t HI>
  const index_set< LO, HI > operator| (const index_set< LO, HI > &lhs, const index_set< LO, HI > &rhs)

  *Set union: or.*
- template<const index_t LO, const index_t HI>
  int compare (const index_set< LO, HI > &a, const index_set< LO, HI > &b)

  *"lexicographic compare" eg. {3,4,5} is less than {3,7,8}*

- _GLUCAT_CTAssert (sizeof(set_value_t) >=sizeof(std::bitset< DEFAULT_HI-DEFAULT_LO >), Default↩ _index_set_too_big_for_value) template< const index_t LO

  *Size of set_value_t should be enough to contain bitset<DEFAULT_HI-DEFAULT_LO>*
- const index_t HI std::ostream & operator<< (std::ostream &os, const index_set< LO, HI > &ist)

  *Write out index set.*
- template<const index_t LO, const index_t HI>
  std::istream & operator>> (std::istream &s, index_set< LO, HI > &ist)

  *Read in index set.*
- int sign_of_square (index_t j)

  *Square of generator {j}.*
- template<const index_t LO, const index_t HI>
  index_t min_neg (const index_set< LO, HI > &ist)

  *Minimum negative index, or 0 if none.*
- template<const index_t LO, const index_t HI>
  index_t max_pos (const index_set< LO, HI > &ist)

  *Maximum positive index, or 0 if none.*
- template<const index_t LO, const index_t HI>
  const index_set< LO, HI > operator & (const index_set< LO, HI > &lhs, const index_set< LO, HI > &rhs)

  *Set intersection: and.*
- static unsigned long inverse_reversed_gray (unsigned long x)

  *Inverse reversed Gray code.*
- static unsigned long inverse_gray (unsigned long x)

  *Inverse Gray code.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > operator* (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Geometric product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > operator^ (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Outer product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > operator & (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Inner product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > operator% (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Left contraction.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T star (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Hestenes scalar product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > operator/ (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Geometric quotient.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > operator| (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Transformation via twisted adjoint action.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  std::istream & operator>> (std::istream &s, matrix_multi< Scalar_T, LO, HI > &val)

  *Read multivector from input.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  std::ostream & operator<< (std::ostream &os, const matrix_multi< Scalar_T, LO, HI > &val)

  *Write multivector to output.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const index_set< LO, HI > reframe (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs, matrix_multi< Scalar_T, LO, HI > &lhs_reframed, matrix_multi< Scalar_T, LO, HI > &rhs_reframed)

  *Find a common frame for operands of a binary operator.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > sqrt (const matrix_multi< Scalar_T, LO, HI > &val, const matrix_multi< Scalar_T, LO, HI > &i, bool prechecked)

  *Square root of multivector with specified complexifier.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > matrix_sqrt (const matrix_multi< Scalar_T, LO, HI > &val, const matrix_multi< Scalar_T, LO, HI > &i)

  *Square root of multivector with specified complexifier.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > log (const matrix_multi< Scalar_T, LO, HI > &val, const matrix_multi< Scalar_T, LO, HI > &i, bool prechecked)

  *Natural logarithm of multivector with specified complexifier.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > matrix_log (const matrix_multi< Scalar_T, LO, HI > &val, const matrix_multi< Scalar_T, LO, HI > &i)

  *Natural logarithm of multivector with specified complexifier.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > exp (const matrix_multi< Scalar_T, LO, HI > &val)

  *Exponential of multivector.*
- index_t offset_level (const index_t p, const index_t q)

  *Determine the log2 dim corresponding to signature p, q.*
- template<typename Matrix_Index_T , const index_t LO, const index_t HI>
  static Matrix_Index_T folded_dim (const index_set< LO, HI > &sub)

  *Determine the matrix dimension of the fold of a subalegbra.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > operator & (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Inner product.*
- template<typename Multivector_T , typename Matrix_T , typename Basis_Matrix_T >
  static Multivector_T fast (const Matrix_T &X, index_t level)

  *Inverse generalized Fast Fourier Transform.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  static const matrix_multi< Scalar_T, LO, HI > pade_approx (const int array_size, const Scalar_T a[ ], const Scalar_T b[ ], const matrix_multi< Scalar_T, LO, HI > &X)

  *Pade' approximation.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  static void db_step (matrix_multi< Scalar_T, LO, HI > &M, matrix_multi< Scalar_T, LO, HI > &Y)

  *Single step of product form of Denman-Beavers square root iteration.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  static const matrix_multi< Scalar_T, LO, HI > db_sqrt (const matrix_multi< Scalar_T, LO, HI > &val)

  *Product form of Denman-Beavers square root iteration.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  static const matrix_multi< Scalar_T, LO, HI > pade_log (const matrix_multi< Scalar_T, LO, HI > &val)

  *Pade' approximation of log.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  static const matrix_multi< Scalar_T, LO, HI > cascade_log (const matrix_multi< Scalar_T, LO, HI > &val)

*Incomplete square root cascade and Pade' approximation of log.*

- template<typename Scalar_T >
  Scalar_T log2 (const Scalar_T &x)

  *Log base 2 of scalar.*
- template<typename Scalar_T >
  numeric_traits< Scalar_T >::promoted::type to_promote (const Scalar_T &val)

  *Cast to promote.*
- template<typename Scalar_T >
  numeric_traits< Scalar_T >::demoted::type to_demote (const Scalar_T &val)

  *Cast to demote.*
- int try_catch (intfn f)

  *Exception catching for functions returning int.*
- int try_catch (intintfn f, int arg)

  *Exception catching for functions of int returning int.*

## Variables

- const double MS_PER_S = 1000.0

  *Timing constant: deprecated here - moved to test/timing.h.*
- const index_t BITS_PER_SET_VALUE = std::numeric_limits<set_value_t>::digits

  *Number of bits in set_value_t.*
- const index_t DEFAULT_HI = index_t(BITS_PER_SET_VALUE / 2)

  *Default highest index in an index set.*
- const double DEFAULT_TRUNCATION = std::numeric_limits<float>::epsilon()

  *Default for truncation.*
- const unsigned int DEFAULT_Mult_Matrix_Threshold = 8
- const unsigned int DEFAULT_Div_Max_Steps = 4
- const unsigned int DEFAULT_Sqrt_Max_Steps = 256
- const unsigned int DEFAULT_Log_Max_Outer_Steps = 256
- const unsigned int DEFAULT_Log_Max_Inner_Steps = 32
- const unsigned int DEFAULT_Basis_Max_Count = 12
- const unsigned int DEFAULT_Fast_Size_Threshold = 1 << 6
- const unsigned int DEFAULT_Inv_Fast_Dim_Threshold = 1 << 3
- const unsigned int DEFAULT_Products_Size_Threshold = 1 << 22
- const precision_t DEFAULT_Function_Precision = precision_same
- static const long double l_pi = 3.14159265358979323846264338327950 29L
- static const long double l_ln2 = 0.69314718055994530941723212145817 66L

### 5.2.1 Typedef Documentation

#### 5.2.1.1 index_t

```
typedef int glucat::index_t
```

Size of index_t should be enough to represent LO, HI.

Definition at line 77 of file global.h.

#### 5.2.1.2 intfn

```
typedef int(* glucat::intfn) ()
```

For exception catching: pointer to function returning int.

Definition at line 37 of file try_catch.h.

#### 5.2.1.3 intintfn

```
typedef int(* glucat::intintfn) (int)
```

For exception catching: pointer to function of int returning int.

Definition at line 40 of file try_catch.h.

#### 5.2.1.4 set_value_t

```
typedef unsigned long glucat::set_value_t
```

Size of set_value_t should be enough to contain index_set<LO,HI>

Definition at line 79 of file global.h.

### 5.2.2 Enumeration Type Documentation

#### 5.2.2.1 precision_t

```
enum glucat::precision_t
```

Precision policy.

**Enumerator**

| | |
|---|---|
| precision_demoted | |
| precision_same | |
| precision_promoted | |

Definition at line 117 of file global.h.

### 5.2.3 Function Documentation

#### 5.2.3.1 _GLUCAT_CTAssert() [1/3]

```
glucat::_GLUCAT_CTAssert (
            std::numeric_limits< unsigned char >::radix  = =2,
            CannotDetermineBitsPerChar  ) const
```

If radix of unsigned char is not 2, we can't easily determine number of bits from sizeof.

Number of bits per char is used to determine number of bits in set_value_t

#### 5.2.3.2 _GLUCAT_CTAssert() [2/3]

```
glucat::_GLUCAT_CTAssert (
            _GLUCAT_BITS_PER_ULONG  = =BITS_PER_SET_VALUE,
            BitsPerULongDoesNotMatchSetValueT  ) const
```

Default lowest index in an index set.

#### 5.2.3.3 _GLUCAT_CTAssert() [3/3]

```
glucat::_GLUCAT_CTAssert (
            sizeof(set_value_t) >=sizeof(std::bitset< DEFAULT_HI-DEFAULT_LO >) ,
            Default_index_set_too_big_for_value  ) const
```

Size of set_value_t should be enough to contain bitset<DEFAULT_HI-DEFAULT_LO>

Write out index set

#### 5.2.3.4 abs()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
Scalar_T glucat::abs (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Absolute value == sqrt(norm)

Definition at line 491 of file clifford_algebra_imp.h.

References glucat::numeric_traits< Scalar_T >::sqrt().

Referenced by PyClical.clifford::abs(), acos(), asin(), glucat::matrix::classify_eigenvalues(), clifford_to_str(), glucat::framed_multi< Scalar_T, LO, HI >::framed_multi(), matrix_log(), and matrix_sqrt().

#### 5.2.3.5 acos() [1/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::acos (
            const Multivector< Scalar_T, LO, HI > & val,
            const Multivector< Scalar_T, LO, HI > & i,
            const bool prechecked = false )  [inline]
```

Inverse cosine of multivector with specified complexifier.

Definition at line 798 of file clifford_algebra_imp.h.

References abs(), acosh(), check_complex(), and PyClical::i.

Referenced by glucat::numeric_traits< Scalar_T >::acos(), and acos().

#### 5.2.3.6 acos() [2/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::acos (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Inverse cosine of multivector.

Definition at line 818 of file clifford_algebra_imp.h.

References acos(), and complexifier().

#### 5.2.3.7 acosh() [1/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::acosh (
            const Multivector< Scalar_T, LO, HI > & val,
            const Multivector< Scalar_T, LO, HI > & i,
            const bool prechecked = false )  [inline]
```

Inverse hyperbolic cosine of multivector with specified complexifier.

Definition at line 738 of file clifford_algebra_imp.h.

References check_complex(), PyClical::i, log(), norm(), and sqrt().

Referenced by acos(), and acosh().

#### 5.2.3.8 acosh() [2/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::acosh (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Inverse hyperbolic cosine of multivector.

Definition at line 758 of file clifford_algebra_imp.h.

References acosh(), and complexifier().

#### 5.2.3.9 asin() [1/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::asin (
            const Multivector< Scalar_T, LO, HI > & val,
            const Multivector< Scalar_T, LO, HI > & i,
            const bool prechecked = false )  [inline]
```

Inverse sine of multivector with specified complexifier.

Definition at line 905 of file clifford_algebra_imp.h.

References abs(), asinh(), check_complex(), and PyClical::i.

Referenced by glucat::numeric_traits< Scalar_T >::asin(), and asin().

#### 5.2.3.10 asin() [2/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::asin (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Inverse sine of multivector.

Definition at line 925 of file clifford_algebra_imp.h.

References asin(), and complexifier().

#### 5.2.3.11 asinh() [1/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::asinh (
            const Multivector< Scalar_T, LO, HI > & val,
            const Multivector< Scalar_T, LO, HI > & i,
            const bool prechecked = false )  [inline]
```

Inverse hyperbolic sine of multivector with specified complexifier.

Definition at line 845 of file clifford_algebra_imp.h.

References check_complex(), PyClical::i, log(), norm(), and sqrt().

Referenced by asin(), and asinh().

#### 5.2.3.12 asinh() [2/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::asinh (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Inverse hyperbolic sine of multivector.

Definition at line 865 of file clifford_algebra_imp.h.

References asinh(), and complexifier().

#### 5.2.3.13 atan() [1/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::atan (
            const Multivector< Scalar_T, LO, HI > & val,
            const Multivector< Scalar_T, LO, HI > & i,
            const bool prechecked = false )  [inline]
```

Inverse tangent of multivector with specified complexifier.

Definition at line 1005 of file clifford_algebra_imp.h.

References atanh(), check_complex(), PyClical::i, and scalar().

Referenced by glucat::numeric_traits< Scalar_T >::atan(), and atan().

#### 5.2.3.14 atan() [2/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::atan (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Inverse tangent of multivector.

Definition at line 1025 of file clifford_algebra_imp.h.

References atan(), and complexifier().

#### 5.2.3.15 atanh() [1/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::atanh (
            const Multivector< Scalar_T, LO, HI > & val,
            const Multivector< Scalar_T, LO, HI > & i,
            const bool prechecked = false )  [inline]
```

Inverse hyperbolic tangent of multivector with specified complexifier.

Definition at line 952 of file clifford_algebra_imp.h.

References check_complex(), PyClical::i, log(), and norm().

Referenced by atan(), and atanh().

#### 5.2.3.16 atanh() [2/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::atanh (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Inverse hyperbolic tangent of multivector.

Definition at line 969 of file clifford_algebra_imp.h.

References atanh(), and complexifier().

#### 5.2.3.17 cascade_log()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
static const matrix_multi<Scalar_T,LO,HI> glucat::cascade_log (
            const matrix_multi< Scalar_T, LO, HI > & val )  [static]
```

Incomplete square root cascade and Pade' approximation of log.

Definition at line 1976 of file matrix_multi_imp.h.

References db_step(), glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::isnan(), glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >::log_max_inner_steps, glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >::log_max_outer_steps, norm(), pade_log(), and pow().

Referenced by matrix_log().

#### 5.2.3.18 check_complex()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
static void glucat::check_complex (
            const Multivector< Scalar_T, LO, HI > & val,
            const Multivector< Scalar_T, LO, HI > & i,
            const bool prechecked = false )  [inline], [static]
```

Check that i is a valid complexifier for val.

Definition at line 566 of file clifford_algebra_imp.h.

References complexifier(), and PyClical::i.

Referenced by acos(), acosh(), asin(), asinh(), atan(), atanh(), cos(), log(), sin(), sqrt(), and tan().

#### 5.2.3.19 clifford_exp()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::clifford_exp (
            const Multivector< Scalar_T, LO, HI > & val )
```

Exponential of multivector.

Definition at line 604 of file clifford_algebra_imp.h.

References exp(), log2(), pow(), and scalar().

Referenced by exp().

#### 5.2.3.20 compare()

```
template<const index_t LO, const index_t HI>
int glucat::compare (
             const index_set< LO, HI > & a,
             const index_set< LO, HI > & b )  [inline]
```

"lexicographic compare" eg. {3,4,5} is less than {3,7,8}

Lexicographic ordering of two sets: -1 if a<b, +1 if a>b, 0 if a==b.

Definition at line 573 of file index_set_imp.h.

References glucat::index_set< LO, HI >::lex_less_than().

#### 5.2.3.21 complexifier()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::complexifier (
             const Multivector< Scalar_T, LO, HI > & val )
```

Square root of -1 which commutes with all members of the frame of the given multivector.

Definition at line 506 of file clifford_algebra_imp.h.

References pos_mod().

Referenced by acos(), acosh(), asin(), asinh(), atan(), atanh(), check_complex(), cos(), elliptic(), log(), sin(), sqrt(), and tan().

#### 5.2.3.22 conj()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::conj (
             const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Conjugation, rev o invo == invo o rev.

Definition at line 467 of file clifford_algebra_imp.h.

#### 5.2.3.23 cos() [1/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::cos (
            const Multivector< Scalar_T, LO, HI > & val,
            const Multivector< Scalar_T, LO, HI > & i,
            const bool prechecked = false )
```

Cosine of multivector with specified complexifier.

Definition at line 765 of file clifford_algebra_imp.h.

References check_complex(), exp(), PyClical::i, PyClical::pi, and scalar().

Referenced by glucat::numeric_traits< Scalar_T >::cos(), cos(), and tan().

#### 5.2.3.24 cos() [2/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::cos (
            const Multivector< Scalar_T, LO, HI > & val ) [inline]
```

Cosine of multivector.

Definition at line 789 of file clifford_algebra_imp.h.

References complexifier(), and cos().

#### 5.2.3.25 cosh()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::cosh (
            const Multivector< Scalar_T, LO, HI > & val ) [inline]
```

Hyperbolic cosine of multivector.

Definition at line 720 of file clifford_algebra_imp.h.

References exp(), and scalar().

Referenced by glucat::numeric_traits< Scalar_T >::cosh(), and tanh().

#### 5.2.3.26 crd_of_mult() [1/2]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
static Scalar_T glucat::crd_of_mult (
            const std::pair< const index_set< LO, HI >, Scalar_T > & lhs,
            const std::pair< const index_set< LO, HI >, Scalar_T > & rhs )  [inline], [static]
```

Coordinate of product of terms.

Referenced by operator &(), operator%(), operator∗(), and operator^().

#### 5.2.3.27 crd_of_mult() [2/2]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
static Scalar_T glucat::crd_of_mult (
            const std::pair< const index_set< LO, HI >, Scalar_T > & lhs,
            const std::pair< const index_set< LO, HI >, Scalar_T > & rhs )  [inline], [static]
```

Coordinate of product of terms.

Definition at line 1906 of file framed_multi_imp.h.

#### 5.2.3.28 db_sqrt()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
static const matrix_multi<Scalar_T,LO,HI> glucat::db_sqrt (
            const matrix_multi< Scalar_T, LO, HI > & val )  [static]
```

Product form of Denman-Beavers square root iteration.

Definition at line 1375 of file matrix_multi_imp.h.

References db_step(), norm(), pow(), and glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_↩ Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim↩ _Threshold, Products_Size_Threshold, Function_Precision >::sqrt_max_steps.

Referenced by matrix_sqrt().

#### 5.2.3.29 db_step()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
static void glucat::db_step (
            matrix_multi< Scalar_T, LO, HI > & M,
            matrix_multi< Scalar_T, LO, HI > & Y )  [inline], [static]
```

Single step of product form of Denman-Beavers square root iteration.

Definition at line 1362 of file matrix_multi_imp.h.

References inv().

Referenced by cascade_log(), and db_sqrt().

#### 5.2.3.30 elliptic()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::elliptic (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Square root of -1 which commutes with all members of the frame of the given multivector The name "elliptic" is now deprecated: use "complexifier" instead.

Definition at line 557 of file clifford_algebra_imp.h.

References complexifier().

#### 5.2.3.31 even()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::even (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Even part.

Definition at line 427 of file clifford_algebra_imp.h.

#### 5.2.3.32 exp() [1/2]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const framed_multi< Scalar_T, LO, HI > glucat::exp (
            const framed_multi< Scalar_T, LO, HI > & val )
```

Exponential of multivector.

Definition at line 1947 of file framed_multi_imp.h.

References clifford_exp(), glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, L↩
O, HI > >::frame(), glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_Max_Outer↩
_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products↩
_Size_Threshold, Function_Precision >::function_precision, glucat::clifford_algebra< Scalar_T, index_set< L↩
O, HI >, framed_multi< Scalar_T, LO, HI > >::isnan(), glucat::tuning< Mult_Matrix_Threshold, Div_Max_↩
Steps, Sqrt_Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold,
Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >::mult_matrix_threshold, precision_↩
demoted, precision_promoted, and scalar().

Referenced by clifford_exp(), cos(), cosh(), glucat::numeric_traits< Scalar_T >::exp(), exp(), matrix_log(), matrix↩
_sqrt(), pow(), PyClical.clifford::pow(), sin(), and sinh().

#### 5.2.3.33 exp() [2/2]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::exp (
            const matrix_multi< Scalar_T, LO, HI > & val )
```

Exponential of multivector.

Definition at line 2140 of file matrix_multi_imp.h.

References clifford_exp(), exp(), glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log↩ _Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >::function_precision, glucat::clifford_algebra< Scalar_T, index_↩ set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::isnan(), precision_demoted, precision_promoted, and scalar().

#### 5.2.3.34 fast()

```
template<typename Multivector_T , typename Matrix_T , typename Basis_Matrix_T >
static Multivector_T glucat::fast (
            const Matrix_T & X,
            index_t level )  [static]
```

Inverse generalized Fast Fourier Transform.

Definition at line 1083 of file matrix_multi_imp.h.

References glucat::matrix::signed_perm_nork().

#### 5.2.3.35 folded_dim()

```
template<typename Matrix_Index_T , const index_t LO, const index_t HI>
static Matrix_Index_T glucat::folded_dim (
            const index_set< LO, HI > & sub )  [inline], [static]
```

Determine the matrix dimension of the fold of a subalegbra.

Definition at line 91 of file matrix_multi_imp.h.

References glucat::index_set< LO, HI >::count_neg(), glucat::index_set< LO, HI >::count_pos(), and offset_↩ level().

#### 5.2.3.36 imag()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
Scalar_T glucat::imag (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Imaginary part: deprecated (always 0)

Definition at line 411 of file clifford_algebra_imp.h.

Referenced by glucat::matrix::classify_eigenvalues().

#### 5.2.3.37 inv()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::inv (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Geometric multiplicative inverse.

Definition at line 321 of file clifford_algebra_imp.h.

Referenced by db_step(), matrix_log(), and matrix_sqrt().

#### 5.2.3.38 inverse_gray()

```
static unsigned long glucat::inverse_gray (
            unsigned long x )  [inline], [static]
```

Inverse Gray code.

Definition at line 861 of file index_set_imp.h.

Referenced by glucat::index_set< LO, HI >::sign_of_mult().

#### 5.2.3.39 inverse_reversed_gray()

```
static unsigned long glucat::inverse_reversed_gray (
            unsigned long x )  [inline], [static]
```

Inverse reversed Gray code.

Definition at line 844 of file index_set_imp.h.

Referenced by glucat::index_set< LO, HI >::sign_of_mult().

#### 5.2.3.40 involute()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::involute (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Main involution, each {i} is replaced by -{i} in each term, eg. {1}∗{2} -> (-{2})∗(-{1})

Main involution, each {i} is replaced by -{i} in each term, eg. {1} ->-{1}.

Definition at line 451 of file clifford_algebra_imp.h.

#### 5.2.3.41 log() [1/4]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::log (
            const matrix_multi< Scalar_T, LO, HI > & val,
            const matrix_multi< Scalar_T, LO, HI > & i,
            bool prechecked )
```

Natural logarithm of multivector with specified complexifier.

Definition at line 2023 of file matrix_multi_imp.h.

References check_complex(), glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log↩_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >::function_precision, PyClical::i, glucat::clifford_algebra< Scalar↩_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::isnan(), matrix_log(), precision_demoted, and precision_promoted.

#### 5.2.3.42 log() [2/4]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const framed_multi< Scalar_T, LO, HI > glucat::log (
            const framed_multi< Scalar_T, LO, HI > & val,
            const framed_multi< Scalar_T, LO, HI > & i,
            bool prechecked )
```

Natural logarithm of multivector with specified complexifier.

Definition at line 1997 of file framed_multi_imp.h.

References check_complex(), PyClical::i, glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > >::isnan(), log(), PyClical::pi, and glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > >::scalar().

#### 5.2.3.43 log() [3/4]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::log (
            const Multivector< Scalar_T, LO, HI > & val,
            const Multivector< Scalar_T, LO, HI > & i,
            const bool prechecked = false )  [inline]
```

Natural logarithm of multivector with specified complexifier.

Definition at line 704 of file clifford_algebra_imp.h.

References PyClical::i.

Referenced by acosh(), asinh(), atanh(), glucat::numeric_traits< Scalar_T >::log(), log(), matrix_log(), glucat↩
::numeric_traits< Scalar_T >::NaN(), pow(), and PyClical.clifford::pow().

#### 5.2.3.44 log() [4/4]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::log (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Natural logarithm of multivector.

Definition at line 712 of file clifford_algebra_imp.h.

References complexifier(), and log().

#### 5.2.3.45 log2()

```
template<typename Scalar_T >
Scalar_T glucat::log2 (
            const Scalar_T & x )  [inline]
```

Log base 2 of scalar.

Definition at line 302 of file scalar.h.

References glucat::numeric_traits< Scalar_T >::log2().

Referenced by clifford_exp().

#### 5.2.3.46 matrix_log()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::matrix_log (
            const matrix_multi< Scalar_T, LO, HI > & val,
            const matrix_multi< Scalar_T, LO, HI > & i )
```

Natural logarithm of multivector with specified complexifier.

Definition at line 2064 of file matrix_multi_imp.h.

References abs(), glucat::matrix::both_eig_case, cascade_log(), glucat::matrix::classify_eigenvalues(), exp(), PyClical::i, inv(), glucat::matrix::isnan(), glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::isnan(), log(), glucat::matrix::eig_genus< Matrix_T >::m_eig_case, glucat::matrix::eig_genus< Matrix_T >::m_safe_arg, glucat::matrix::negative_eig_case, norm(), PyClical::pi, and glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::scalar().

Referenced by log().

#### 5.2.3.47 matrix_sqrt()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::matrix_sqrt (
            const matrix_multi< Scalar_T, LO, HI > & val,
            const matrix_multi< Scalar_T, LO, HI > & i )
```

Square root of multivector with specified complexifier.

Definition at line 1645 of file matrix_multi_imp.h.

References abs(), glucat::matrix::both_eig_case, glucat::matrix::classify_eigenvalues(), db_sqrt(), exp(), PyClical::i, inv(), glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::isnan(), glucat::matrix::eig_genus< Matrix_T >::m_eig_case, glucat::matrix::eig_genus< Matrix_T >::m_safe_arg, glucat::matrix::negative_eig_case, norm(), pade_approx(), glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::scalar(), and sqrt().

Referenced by sqrt().

#### 5.2.3.48 max_abs()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
Scalar_T glucat::max_abs (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Maximum of absolute values of components of multivector: multivector infinity norm.

Definition at line 499 of file clifford_algebra_imp.h.

#### 5.2.3.49 max_pos()

```
template<const index_t LO, const index_t HI>
index_t glucat::max_pos (
            const index_set< LO, HI > & ist )  [inline]
```

Maximum positive index, or 0 if none.

Definition at line 974 of file index_set_imp.h.

References PyClical::ist.

#### 5.2.3.50 min_neg()

```
template<const index_t LO, const index_t HI>
index_t glucat::min_neg (
            const index_set< LO, HI > & ist )  [inline]
```

Minimum negative index, or 0 if none.

Definition at line 967 of file index_set_imp.h.

References PyClical::ist.

#### 5.2.3.51 norm()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
Scalar_T glucat::norm (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Scalar_T norm == sum of norm of coordinates.

Definition at line 483 of file clifford_algebra_imp.h.

Referenced by acosh(), asinh(), atanh(), cascade_log(), glucat::matrix::classify_eigenvalues(), db_sqrt(), matrix_↩log(), and matrix_sqrt().

#### 5.2.3.52 odd()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::odd (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Odd part.

Definition at line 435 of file clifford_algebra_imp.h.

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::fast().

#### 5.2.3.53 offset_level()

```
index_t glucat::offset_level (
            const index_t p,
            const index_t q )  [inline]
```

Determine the log2 dim corresponding to signature p, q.

Definition at line 76 of file matrix_multi_imp.h.

References pos_mod().

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >::basis_element(), and folded_dim().

#### 5.2.3.54 operator &() [1/8]

```
template<const index_t LO, const index_t HI>
const index_set<LO,HI> glucat::operator& (
            const index_set< LO, HI > & lhs,
            const index_set< LO, HI > & rhs )  [inline]
```

Set intersection: and.

Definition at line 186 of file index_set_imp.h.

#### 5.2.3.55 operator &() [2/8]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi<Scalar_T,LO,HI> glucat::operator& (
            const matrix_multi< Scalar_T, LO, HI > & lhs,
            const matrix_multi< Scalar_T, LO, HI > & rhs )  [inline]
```

Inner product.

Definition at line 616 of file matrix_multi_imp.h.

#### 5.2.3.56 operator &() [3/8]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const framed_multi<Scalar_T,LO,HI> glucat::operator& (
            const framed_multi< Scalar_T, LO, HI > & lhs,
            const framed_multi< Scalar_T, LO, HI > & rhs )
```

Inner product.

Definition at line 601 of file framed_multi_imp.h.

References _GLUCAT_HASH_SIZE_T, crd_of_mult(), glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > >::frame(), and glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt↩ _Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_↩ Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >::products_size_threshold.

#### 5.2.3.57 operator &() [4/8]

```
template<const index_t LO, const index_t HI>
const index_set<LO,HI> glucat::operator& (
            const index_set< LO, HI > & lhs,
            const index_set< LO, HI > & rhs )  [inline]
```

Set intersection: and.

Definition at line 186 of file index_set_imp.h.

#### 5.2.3.58 operator &() [5/8]

```
template<template< typename, const index_t, const index_t > class Multivector, template<
typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO,
const index_t HI>
const Multivector<Scalar_T,LO,HI> glucat::operator& (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const RHS< Scalar_T, LO, HI > & rhs )  [inline]
```

Inner product.

Definition at line 228 of file clifford_algebra_imp.h.

#### 5.2.3.59 operator &() [6/8]

```
template<template< typename, const index_t, const index_t > class Multivector, template<
typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO,
const index_t HI>
const Multivector<Scalar_T,LO,HI> glucat::operator& (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const RHS< Scalar_T, LO, HI > & rhs )  [inline]
```

Inner product.

Definition at line 228 of file clifford_algebra_imp.h.

#### 5.2.3.60 operator &() [7/8]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const framed_multi<Scalar_T,LO,HI> glucat::operator& (
            const framed_multi< Scalar_T, LO, HI > & lhs,
            const framed_multi< Scalar_T, LO, HI > & rhs )
```

Inner product.

Definition at line 601 of file framed_multi_imp.h.

References _GLUCAT_HASH_SIZE_T, crd_of_mult(), glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > >::frame(), and glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt↩ _Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_↩ Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >::products_size_threshold.

#### 5.2.3.61 operator &() [8/8]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi<Scalar_T,LO,HI> glucat::operator& (
            const matrix_multi< Scalar_T, LO, HI > & lhs,
            const matrix_multi< Scalar_T, LO, HI > & rhs )  [inline]
```

Inner product.

Definition at line 616 of file matrix_multi_imp.h.

#### 5.2.3.62 operator"!=() [1/3]

```
template<template< typename, const index_t, const index_t > class Multivector, template<
typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO,
const index_t HI>
bool glucat::operator!= (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const RHS< Scalar_T, LO, HI > & rhs )  [inline]
```

Test for inequality of multivectors.

Definition at line 78 of file clifford_algebra_imp.h.

#### 5.2.3.63 operator"!=() [2/3]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
bool glucat::operator!= (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const Scalar_T & scr )  [inline]
```

Test for inequality of multivector and scalar.

Definition at line 86 of file clifford_algebra_imp.h.

#### 5.2.3.64 operator"!=() [3/3]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
bool glucat::operator!= (
            const Scalar_T & scr,
            const Multivector< Scalar_T, LO, HI > & rhs )  [inline]
```

Test for inequality of scalar and multivector.

Definition at line 94 of file clifford_algebra_imp.h.

#### 5.2.3.65 operator%() [1/3]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::operator% (
            const matrix_multi< Scalar_T, LO, HI > & lhs,
            const matrix_multi< Scalar_T, LO, HI > & rhs )  [inline]
```

Left contraction.

Definition at line 635 of file matrix_multi_imp.h.

#### 5.2.3.66 operator%() [2/3]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const framed_multi< Scalar_T, LO, HI > glucat::operator% (
            const framed_multi< Scalar_T, LO, HI > & lhs,
            const framed_multi< Scalar_T, LO, HI > & rhs )
```

Left contraction.

Definition at line 719 of file framed_multi_imp.h.

References _GLUCAT_HASH_SIZE_T, crd_of_mult(), glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > >::frame(), and glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt↩ _Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_↩ Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >::products_size_threshold.

#### 5.2.3.67 operator%() [3/3]

```
template<template< typename, const index_t, const index_t > class Multivector, template<
typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO,
const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator% (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const RHS< Scalar_T, LO, HI > & rhs )  [inline]
```

Left contraction.

Definition at line 243 of file clifford_algebra_imp.h.

#### 5.2.3.68 operator∗() [1/6]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::operator* (
            const matrix_multi< Scalar_T, LO, HI > & lhs,
            const matrix_multi< Scalar_T, LO, HI > & rhs )  [inline]
```

Geometric product.

Definition at line 547 of file matrix_multi_imp.h.

References glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::isnan(), glucat::matrix_multi< Scalar_T, LO, HI >::m_frame, glucat::matrix_multi< Scalar_T, LO, HI >::m_matrix, and reframe().

#### 5.2.3.69 operator∗() [2/6]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const framed_multi< Scalar_T, LO, HI > glucat::operator* (
            const framed_multi< Scalar_T, LO, HI > & lhs,
            const framed_multi< Scalar_T, LO, HI > & rhs )
```

Geometric product.

Definition at line 400 of file framed_multi_imp.h.

References _GLUCAT_HASH_SIZE_T, glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > >::frame(), glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > >::isnan(), and glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >::mult_matrix_threshold.

#### 5.2.3.70 operator∗() [3/6]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator* (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const Scalar_T & scr )  [inline]
```

Product of multivector and scalar.

Definition at line 172 of file clifford_algebra_imp.h.

#### 5.2.3.71 operator∗() [4/6]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator* (
            const Scalar_T & scr,
            const Multivector< Scalar_T, LO, HI > & rhs )  [inline]
```

Product of scalar and multivector.

Definition at line 183 of file clifford_algebra_imp.h.

#### 5.2.3.72 operator∗() [5/6]

```
template<template< typename, const index_t, const index_t > class Multivector, template<
typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO,
const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator* (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const RHS< Scalar_T, LO, HI > & rhs )  [inline]
```

Geometric product.

Definition at line 198 of file clifford_algebra_imp.h.

#### 5.2.3.73 operator∗() [6/6]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const std::pair< const index_set< LO, HI >, Scalar_T > glucat::operator* (
            const std::pair< const index_set< LO, HI >, Scalar_T > & lhs,
            const std::pair< const index_set< LO, HI >, Scalar_T > & rhs )  [inline]
```

Product of terms.

Definition at line 1914 of file framed_multi_imp.h.

References crd_of_mult().

#### 5.2.3.74 operator+() [1/3]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator+ (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const Scalar_T & scr )  [inline]
```

Geometric sum of multivector and scalar.

Definition at line 102 of file clifford_algebra_imp.h.

#### 5.2.3.75 operator+() [2/3]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator+ (
            const Scalar_T & scr,
            const Multivector< Scalar_T, LO, HI > & rhs )  [inline]
```

Geometric sum of scalar and multivector.

Definition at line 113 of file clifford_algebra_imp.h.

#### 5.2.3.76 operator+() [3/3]

```
template<template< typename, const index_t, const index_t > class Multivector, template<
typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO,
const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator+ (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const RHS< Scalar_T, LO, HI > & rhs )  [inline]
```

Geometric sum.

Definition at line 127 of file clifford_algebra_imp.h.

#### 5.2.3.77 operator-() [1/3]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator- (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const Scalar_T & scr )  [inline]
```

Geometric difference of multivector and scalar.

Definition at line 138 of file clifford_algebra_imp.h.

#### 5.2.3.78 operator-() [2/3]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator- (
            const Scalar_T & scr,
            const Multivector< Scalar_T, LO, HI > & rhs )  [inline]
```

Geometric difference of scalar and multivector.

Definition at line 149 of file clifford_algebra_imp.h.

#### 5.2.3.79 operator-() [3/3]

```
template<template< typename, const index_t, const index_t > class Multivector, template<
typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO,
const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator- (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const RHS< Scalar_T, LO, HI > & rhs )  [inline]
```

Geometric difference.

Definition at line 161 of file clifford_algebra_imp.h.

#### 5.2.3.80 operator/() [1/5]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::operator/ (
            const matrix_multi< Scalar_T, LO, HI > & lhs,
            const matrix_multi< Scalar_T, LO, HI > & rhs )
```

Geometric quotient.

Definition at line 668 of file matrix_multi_imp.h.

References glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size↩
_Threshold, Function_Precision >::div_max_steps, glucat::matrix::isnan(), glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::isnan(), glucat::matrix_multi< Scalar_T, LO, HI >::m_frame, and reframe().

#### 5.2.3.81 operator/() [2/5]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const framed_multi< Scalar_T, LO, HI > glucat::operator/ (
            const framed_multi< Scalar_T, LO, HI > & lhs,
            const framed_multi< Scalar_T, LO, HI > & rhs )  [inline]
```

Geometric quotient.

Definition at line 914 of file framed_multi_imp.h.

References glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > >↩
::frame().

#### 5.2.3.82 operator/() [3/5]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator/ (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const Scalar_T & scr )  [inline]
```

Quotient of multivector and scalar.

Definition at line 269 of file clifford_algebra_imp.h.

#### 5.2.3.83 operator/() [4/5]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator/ (
            const Scalar_T & scr,
            const Multivector< Scalar_T, LO, HI > & rhs )  [inline]
```

Quotient of scalar and multivector.

Definition at line 280 of file clifford_algebra_imp.h.

#### 5.2.3.84 operator/() [5/5]

```
template<template< typename, const index_t, const index_t > class Multivector, template<
typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO,
const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator/ (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const RHS< Scalar_T, LO, HI > & rhs )  [inline]
```

Geometric quotient.

Definition at line 295 of file clifford_algebra_imp.h.

#### 5.2.3.85 operator<<() [1/4]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
std::ostream & glucat::operator<< (
            std::ostream & os,
            const matrix_multi< Scalar_T, LO, HI > & val )  [inline]
```

Write multivector to output.

Definition at line 1025 of file matrix_multi_imp.h.

#### 5.2.3.86 operator<<() [2/4]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
std::ostream & glucat::operator<< (
            std::ostream & os,
            const framed_multi< Scalar_T, LO, HI > & val )
```

Write multivector to output.

Definition at line 1366 of file framed_multi_imp.h.

References glucat::sorted_range< Map_T, Sorted_Map_T >::sorted_begin, and glucat::sorted_range< Map_T, Sorted_Map_T >::sorted_end.

#### 5.2.3.87 operator<<() [3/4]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
std::ostream & glucat::operator<< (
            std::ostream & os,
            const std::pair< const index_set< LO, HI >, Scalar_T > & term )
```

Write term to output.

Definition at line 1398 of file framed_multi_imp.h.

References pow(), and glucat::numeric_traits< Scalar_T >::to_double().

#### 5.2.3.88 operator<<() [4/4]

```
std::ostream & glucat::operator<< (
            std::ostream & os,
            const index_set< LO, HI > & ist )
```

Write out index set.

Definition at line 611 of file index_set_imp.h.

References PyClical::i, and PyClical::ist.

#### 5.2.3.89 operator>>() [1/3]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
std::istream & glucat::operator>> (
            std::istream & s,
            matrix_multi< Scalar_T, LO, HI > & val )  [inline]
```

Read multivector from input.

Definition at line 1035 of file matrix_multi_imp.h.

#### 5.2.3.90 operator>>() [2/3]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
std::istream & glucat::operator>> (
             std::istream & s,
             framed_multi< Scalar_T, LO, HI > & val )
```

Read multivector from input.

Definition at line 1436 of file framed_multi_imp.h.

References PyClical::ist.

#### 5.2.3.91 operator>>() [3/3]

```
template<const index_t LO, const index_t HI>
std::istream & glucat::operator>> (
             std::istream & s,
             index_set< LO, HI > & ist )
```

Read in index set.

Definition at line 633 of file index_set_imp.h.

References PyClical::i, PyClical::ist, and glucat::index_set< LO, HI >::set().

#### 5.2.3.92 operator^() [1/4]

```
template<const index_t LO, const index_t HI>
const index_set< LO, HI > glucat::operator^ (
             const index_set< LO, HI > & lhs,
             const index_set< LO, HI > & rhs )  [inline]
```

Symmetric set difference: exclusive or.

Definition at line 161 of file index_set_imp.h.

#### 5.2.3.93 operator^() [2/4]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::operator^ (
             const matrix_multi< Scalar_T, LO, HI > & lhs,
             const matrix_multi< Scalar_T, LO, HI > & rhs )  [inline]
```

Outer product.

Definition at line 597 of file matrix_multi_imp.h.

#### 5.2.3.94 operator^() [3/4]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const framed_multi< Scalar_T, LO, HI > glucat::operator^ (
            const framed_multi< Scalar_T, LO, HI > & lhs,
            const framed_multi< Scalar_T, LO, HI > & rhs )
```

Outer product.

Definition at line 501 of file framed_multi_imp.h.

References _GLUCAT_HASH_SIZE_T, crd_of_mult(), glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > >::frame(), and glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt↩ _Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_↩ Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >::products_size_threshold.

#### 5.2.3.95 operator^() [4/4]

```
template<template< typename, const index_t, const index_t > class Multivector, template<
typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO,
const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator^ (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const RHS< Scalar_T, LO, HI > & rhs )  [inline]
```

Outer product.

Definition at line 213 of file clifford_algebra_imp.h.

#### 5.2.3.96 operator"|() [1/4]

```
template<const index_t LO, const index_t HI>
const index_set< LO, HI > glucat::operator| (
            const index_set< LO, HI > & lhs,
            const index_set< LO, HI > & rhs )  [inline]
```

Set union: or.

Definition at line 211 of file index_set_imp.h.

#### 5.2.3.97 operator"|() [2/4]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::operator| (
            const matrix_multi< Scalar_T, LO, HI > & lhs,
            const matrix_multi< Scalar_T, LO, HI > & rhs )  [inline]
```

Transformation via twisted adjoint action.

Definition at line 777 of file matrix_multi_imp.h.

References glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >↩ ::involute().

#### 5.2.3.98 operator" | () [3/4]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const framed_multi< Scalar_T, LO, HI > glucat::operator| (
            const framed_multi< Scalar_T, LO, HI > & lhs,
            const framed_multi< Scalar_T, LO, HI > & rhs )  [inline]
```

Transformation via twisted adjoint action.

Definition at line 940 of file framed_multi_imp.h.

References glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > >↩ ::involute().

#### 5.2.3.99 operator" | () [4/4]

```
template<template< typename, const index_t, const index_t > class Multivector, template<
typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO,
const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::operator| (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const RHS< Scalar_T, LO, HI > & rhs )  [inline]
```

Transformation via twisted adjoint action.

Definition at line 310 of file clifford_algebra_imp.h.

#### 5.2.3.100 outer_pow()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::outer_pow (
            const Multivector< Scalar_T, LO, HI > & lhs,
            int rhs )
```

Outer product power of multivector.

Definition at line 384 of file clifford_algebra_imp.h.

#### 5.2.3.101 pade_approx()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
static const matrix_multi<Scalar_T,LO,HI> glucat::pade_approx (
            const int array_size,
            const Scalar_T a[],
            const Scalar_T b[],
            const matrix_multi< Scalar_T, LO, HI > & X )  [inline], [static]
```

Pade' approximation.

Definition at line 1302 of file matrix_multi_imp.h.

References glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::isnan().

Referenced by matrix_sqrt(), and pade_log().

#### 5.2.3.102 pade_log()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
static const matrix_multi<Scalar_T,LO,HI> glucat::pade_log (
            const matrix_multi< Scalar_T, LO, HI > & val )  [static]
```

Pade' approximation of log.

Definition at line 1955 of file matrix_multi_imp.h.

References glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::isnan(), and pade_approx().

Referenced by cascade_log().

#### 5.2.3.103 pos_mod()

```
template<typename LHS_T , typename RHS_T >
LHS_T glucat::pos_mod (
            LHS_T lhs,
            RHS_T rhs )  [inline]
```

Modulo function which works reliably for lhs $< 0$.

Definition at line 187 of file global.h.

Referenced by complexifier(), glucat::matrix_multi< Scalar_T, LO, HI >::fast_framed_multi(), glucat::framed_multi< Scalar_T, LO, HI >::fast_matrix_multi(), glucat::gen::generator_table< Matrix_T >::gen_vector(), offset_level(), and glucat::gen::generator_table< Matrix_T >::operator()().

#### 5.2.3.104 pow() [1/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::pow (
            const Multivector< Scalar_T, LO, HI > & lhs,
            int rhs )
```

Integer power of multivector.

Definition at line 328 of file clifford_algebra_imp.h.

Referenced by cascade_log(), clifford_exp(), db_sqrt(), operator<<(), and glucat::numeric_traits< Scalar_T >↩ ::pow().

#### 5.2.3.105 pow() [2/2]

```
template<template< typename, const index_t, const index_t > class Multivector, template<
typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO,
const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::pow (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const RHS< Scalar_T, LO, HI > & rhs )  [inline]
```

Multivector power of multivector.

Definition at line 361 of file clifford_algebra_imp.h.

References exp(), and log().

#### 5.2.3.106 pure()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::pure (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Pure part.

Definition at line 419 of file clifford_algebra_imp.h.

#### 5.2.3.107 quad()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
Scalar_T glucat::quad (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Scalar_T quadratic form == (rev(x)∗x)(0)

Definition at line 475 of file clifford_algebra_imp.h.

#### 5.2.3.108 real()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
Scalar_T glucat::real (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Real part: synonym for scalar part.

Definition at line 400 of file clifford_algebra_imp.h.

Referenced by glucat::matrix::classify_eigenvalues().

#### 5.2.3.109 reframe()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const index_set< LO, HI > glucat::reframe (
            const matrix_multi< Scalar_T, LO, HI > & lhs,
            const matrix_multi< Scalar_T, LO, HI > & rhs,
            matrix_multi< Scalar_T, LO, HI > & lhs_reframed,
            matrix_multi< Scalar_T, LO, HI > & rhs_reframed )  [inline]
```

Find a common frame for operands of a binary operator.

Definition at line 350 of file matrix_multi_imp.h.

References glucat::matrix_multi< Scalar_T, LO, HI >::m_frame.

Referenced by operator*(), and operator/().

#### 5.2.3.110 reverse()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::reverse (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Reversion, eg. {1}*{2} -> {2}*{1}.

Definition at line 459 of file clifford_algebra_imp.h.

#### 5.2.3.111 scalar()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
Scalar_T glucat::scalar (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Scalar part.

Definition at line 392 of file clifford_algebra_imp.h.

Referenced by atan(), clifford_exp(), cos(), cosh(), exp(), glucat::framed_multi< Scalar_T, LO, HI >::fast(), sin(), sinh(), tan(), and tanh().

#### 5.2.3.112 sign_of_square()

```
int glucat::sign_of_square (
            index_t j )  [inline]
```

Square of generator {j}.

Square of generator index j.

Definition at line 960 of file index_set_imp.h.

#### 5.2.3.113 sin() [1/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::sin (
            const Multivector< Scalar_T, LO, HI > & val,
            const Multivector< Scalar_T, LO, HI > & i,
            const bool prechecked = false )
```

Sine of multivector with specified complexifier.

Definition at line 872 of file clifford_algebra_imp.h.

References check_complex(), exp(), PyClical::i, PyClical::pi, and scalar().

Referenced by glucat::numeric_traits< Scalar_T >::sin(), sin(), and tan().

#### 5.2.3.114 sin() [2/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::sin (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Sine of multivector.

Definition at line 896 of file clifford_algebra_imp.h.

References complexifier(), and sin().

#### 5.2.3.115 sinh()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::sinh (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Hyperbolic sine of multivector.

Definition at line 826 of file clifford_algebra_imp.h.

References exp(), and scalar().

Referenced by glucat::numeric_traits< Scalar_T >::sinh(), and tanh().

#### 5.2.3.116 sqrt() [1/4]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::sqrt (
            const matrix_multi< Scalar_T, LO, HI > & val,
            const matrix_multi< Scalar_T, LO, HI > & i,
            bool prechecked )
```

Square root of multivector with specified complexifier.

Definition at line 1600 of file matrix_multi_imp.h.

References check_complex(), glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log↩_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >::function_precision, PyClical::i, glucat::clifford_algebra< Scalar↩_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::isnan(), matrix_sqrt(), precision_demoted, and precision_promoted.

#### 5.2.3.117 sqrt() [2/4]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const framed_multi< Scalar_T, LO, HI > glucat::sqrt (
            const framed_multi< Scalar_T, LO, HI > & val,
            const framed_multi< Scalar_T, LO, HI > & i,
            bool prechecked )
```

Square root of multivector with specified complexifier.

Definition at line 1924 of file framed_multi_imp.h.

References check_complex(), PyClical::i, glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > >::isnan(), glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > >::scalar(), and sqrt().

#### 5.2.3.118 sqrt() [3/4]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::sqrt (
            const Multivector< Scalar_T, LO, HI > & val,
            const Multivector< Scalar_T, LO, HI > & i,
            const bool prechecked = false )  [inline]
```

Square root of multivector with specified complexifier.

Definition at line 589 of file clifford_algebra_imp.h.

References PyClical::i.

Referenced by acosh(), asinh(), matrix_sqrt(), glucat::framed_multi< Scalar_T, LO, HI >::random(), and sqrt().

#### 5.2.3.119 sqrt() [4/4]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::sqrt (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Square root of multivector.

Definition at line 597 of file clifford_algebra_imp.h.

References complexifier(), and sqrt().

#### 5.2.3.120 star() [1/3]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
Scalar_T glucat::star (
            const matrix_multi< Scalar_T, LO, HI > & lhs,
            const matrix_multi< Scalar_T, LO, HI > & rhs )  [inline]
```

Hestenes scalar product.

Definition at line 654 of file matrix_multi_imp.h.

#### 5.2.3.121 star() [2/3]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
Scalar_T glucat::star (
            const framed_multi< Scalar_T, LO, HI > & lhs,
            const framed_multi< Scalar_T, LO, HI > & rhs )
```

Hestenes scalar product.

Definition at line 855 of file framed_multi_imp.h.

#### 5.2.3.122 star() [3/3]

```
template<template< typename, const index_t, const index_t > class Multivector, template<
typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO,
const index_t HI>
Scalar_T glucat::star (
            const Multivector< Scalar_T, LO, HI > & lhs,
            const RHS< Scalar_T, LO, HI > & rhs )  [inline]
```

Hestenes scalar product.

Definition at line 258 of file clifford_algebra_imp.h.

#### 5.2.3.123 tan() [1/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::tan (
            const Multivector< Scalar_T, LO, HI > & val,
            const Multivector< Scalar_T, LO, HI > & i,
            const bool prechecked = false )  [inline]
```

Tangent of multivector with specified complexifier.

Definition at line 977 of file clifford_algebra_imp.h.

References check_complex(), cos(), PyClical::i, scalar(), and sin().

Referenced by glucat::numeric_traits< Scalar_T >::tan(), and tan().

#### 5.2.3.124 tan() [2/2]

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::tan (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Tangent of multivector.

Definition at line 996 of file clifford_algebra_imp.h.

References complexifier(), and tan().

#### 5.2.3.125 tanh()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const Multivector< Scalar_T, LO, HI > glucat::tanh (
            const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Hyperbolic tangent of multivector.

Definition at line 933 of file clifford_algebra_imp.h.

References cosh(), scalar(), and sinh().

Referenced by glucat::numeric_traits< Scalar_T >::tanh().

#### 5.2.3.126 to_demote()

```
template<typename Scalar_T >
numeric_traits<Scalar_T>::demoted::type glucat::to_demote (
            const Scalar_T & val )  [inline]
```

Cast to demote.

Definition at line 134 of file scalar_imp.h.

References glucat::numeric_traits< Scalar_T >::to_scalar_t().

#### 5.2.3.127 to_promote()

```
template<typename Scalar_T >
numeric_traits<Scalar_T>::promoted::type glucat::to_promote (
            const Scalar_T & val )  [inline]
```

Cast to promote.

Definition at line 124 of file scalar_imp.h.

References glucat::numeric_traits< Scalar_T >::to_scalar_t().

#### 5.2.3.128 try_catch() [1/2]

```
int glucat::try_catch (
            intfn f )
```

Exception catching for functions returning int.

Definition at line 49 of file try_catch.h.

References PyClical::e().

Referenced by glucat::control_t::call().

#### 5.2.3.129 try_catch() [2/2]

```
int glucat::try_catch (
             intintfn f,
             int arg )
```

Exception catching for functions of int returning int.

Definition at line 64 of file try_catch.h.

References PyClical::e().

#### 5.2.3.130 vector_part()

```
template<template< typename, const index_t, const index_t > class Multivector, typename Scalar↩
_T , const index_t LO, const index_t HI>
const std::vector< Scalar_T > glucat::vector_part (
             const Multivector< Scalar_T, LO, HI > & val )  [inline]
```

Vector part of multivector, as a vector_t with respect to frame()

Definition at line 443 of file clifford_algebra_imp.h.

### 5.2.4 Variable Documentation

#### 5.2.4.1 BITS_PER_SET_VALUE

```
const index_t glucat::BITS_PER_SET_VALUE = std::numeric_limits<set_value_t>::digits
```

Number of bits in set_value_t.

Definition at line 103 of file global.h.

#### 5.2.4.2 DEFAULT_Basis_Max_Count

```
const unsigned int glucat::DEFAULT_Basis_Max_Count = 12
```

Definition at line 130 of file global.h.

#### 5.2.4.3 DEFAULT_Div_Max_Steps

```
const unsigned int glucat::DEFAULT_Div_Max_Steps = 4
```

Definition at line 126 of file global.h.

#### 5.2.4.4 DEFAULT_Fast_Size_Threshold

```
const unsigned int glucat::DEFAULT_Fast_Size_Threshold = 1 << 6
```

Definition at line 131 of file global.h.

#### 5.2.4.5 DEFAULT_Function_Precision

```
const precision_t glucat::DEFAULT_Function_Precision = precision_same
```

Definition at line 134 of file global.h.

#### 5.2.4.6 DEFAULT_HI

```
const index_t glucat::DEFAULT_HI = index_t(BITS_PER_SET_VALUE / 2)
```

Default highest index in an index set.

Definition at line 111 of file global.h.

#### 5.2.4.7 DEFAULT_Inv_Fast_Dim_Threshold

```
const unsigned int glucat::DEFAULT_Inv_Fast_Dim_Threshold = 1 << 3
```

Definition at line 132 of file global.h.

#### 5.2.4.8 DEFAULT_Log_Max_Inner_Steps

```
const unsigned int glucat::DEFAULT_Log_Max_Inner_Steps = 32
```

Definition at line 129 of file global.h.

#### 5.2.4.9 DEFAULT_Log_Max_Outer_Steps

```
const unsigned int glucat::DEFAULT_Log_Max_Outer_Steps = 256
```

Definition at line 128 of file global.h.

#### 5.2.4.10 DEFAULT_Mult_Matrix_Threshold

```
const unsigned int glucat::DEFAULT_Mult_Matrix_Threshold = 8
```

Definition at line 125 of file global.h.

#### 5.2.4.11 DEFAULT_Products_Size_Threshold

```
const unsigned int glucat::DEFAULT_Products_Size_Threshold = 1 << 22
```

Definition at line 133 of file global.h.

#### 5.2.4.12 DEFAULT_Sqrt_Max_Steps

```
const unsigned int glucat::DEFAULT_Sqrt_Max_Steps = 256
```

Definition at line 127 of file global.h.

#### 5.2.4.13 DEFAULT_TRUNCATION

```
const double glucat::DEFAULT_TRUNCATION = std::numeric_limits<float>::epsilon()
```

Default for truncation.

Definition at line 114 of file global.h.

#### 5.2.4.14 l_ln2

```
const long double glucat::l_ln2 = 0.693147180559945309417232121458176 6L  [static]
```

Definition at line 41 of file long_double.h.

Referenced by glucat::numeric_traits< Scalar_T >::ln_2().

#### 5.2.4.15 l_pi

```
const long double glucat::l_pi = 3.14159265358979323846264338327950291L  [static]
```

Definition at line 40 of file long_double.h.

Referenced by glucat::numeric_traits< Scalar_T >::pi().

#### 5.2.4.16 MS_PER_S

```
const double glucat::MS_PER_S = 1000.0
```

Timing constant: deprecated here - moved to test/timing.h.

Definition at line 83 of file global.h.

## 5.3 glucat::gen Namespace Reference

### Classes

- class generator_table

  *Table of generators for specific signatures.*

### Typedefs

- typedef std::pair< index_t, index_t > signature_t

  *A signature is a pair of indices, p, q, with p == frame.max(), q == -frame.min()*

### Variables

- static const index_t offset_to_super [ ] = {0,-1, 0,-1,-2, 3, 2, 1}

  *Offsets between the current signature and that of the real superalgebra.*

### 5.3.1 Typedef Documentation

#### 5.3.1.1 signature_t

```
typedef std::pair<index_t, index_t> glucat::gen::signature_t
```

A signature is a pair of indices, p, q, with p == frame.max(), q == -frame.min()

Definition at line 43 of file generation.h.

### 5.3.2 Variable Documentation

#### 5.3.2.1 offset_to_super

```
const index_t glucat::gen::offset_to_super[ ] = {0,-1, 0,-1,-2, 3, 2, 1}  [static]
```

Offsets between the current signature and that of the real superalgebra.

Definition at line 81 of file generation.h.

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >::fast_framed_multi(), glucat::framed_multi< Scalar_T, LO, HI >::fast_matrix_multi(), and glucat::gen::generator_table< Matrix_T >::operator()().

## 5.4 glucat::matrix Namespace Reference

### Classes

- struct eig_genus

  *Structure containing classification of eigenvalues.*

### Enumerations

- enum eig_case_t { safe_eig_case, negative_eig_case, both_eig_case }

  *Classification of eigenvalues of a matrix.*

### Functions

- template<typename LHS_T , typename RHS_T >
  const RHS_T kron (const LHS_T &lhs, const RHS_T &rhs)

  *Kronecker tensor product of matrices - as per Matlab kron.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T mono_kron (const LHS_T &lhs, const RHS_T &rhs)

  *Sparse Kronecker tensor product of monomial matrices.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T nork (const LHS_T &lhs, const RHS_T &rhs, const bool mono=true)

  *Left inverse of Kronecker product.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T signed_perm_nork (const LHS_T &lhs, const RHS_T &rhs)

  *Left inverse of Kronecker product where lhs is a signed permutation matrix.*
- template<typename Matrix_T >
  Matrix_T::size_type nnz (const Matrix_T &m)

  *Number of non-zeros.*
- template<typename Matrix_T >
  bool isnan (const Matrix_T &m)

  *Not a Number.*

- template<typename Matrix_T >
  const Matrix_T unit (const typename Matrix_T::size_type n)

  *Unit matrix - as per Matlab eye.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T::expression_type mono_prod (const ublas::matrix_expression< LHS_T > &lhs, const ublas↩
  ::matrix_expression< RHS_T > &rhs)

  *Product of monomial matrices.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T::expression_type sparse_prod (const ublas::matrix_expression< LHS_T > &lhs, const ublas↩
  ::matrix_expression< RHS_T > &rhs)

  *Product of sparse matrices.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T::expression_type prod (const ublas::matrix_expression< LHS_T > &lhs, const ublas::matrix↩
  _expression< RHS_T > &rhs)

  *Product of matrices.*
- template<typename Scalar_T , typename LHS_T , typename RHS_T >
  Scalar_T inner (const LHS_T &lhs, const RHS_T &rhs)

  *Inner product: sum(x(i,j)∗y(i,j))/x.nrows()*
- template<typename Matrix_T >
  Matrix_T::value_type norm_frob2 (const Matrix_T &val)

  *Square of Frobenius norm.*
- template<typename Matrix_T >
  Matrix_T::value_type trace (const Matrix_T &val)

  *Matrix trace.*
- template<typename Matrix_T >
  ublas::vector< std::complex< double > > eigenvalues (const Matrix_T &val)

  *Eigenvalues of a matrix.*
- template<typename Matrix_T >
  eig_genus< Matrix_T > classify_eigenvalues (const Matrix_T &val)

  *Classify the eigenvalues of a matrix.*
- template<typename LHS_T , typename RHS_T >
  void nork_range (RHS_T &result, const typename LHS_T::const_iterator2 lhs_it2, const RHS_T &rhs, const typename RHS_T::size_type res_s1, const typename RHS_T::size_type res_s2)

  *Utility routine for nork: calculate result for a range of indices.*
- template<typename Matrix_T >
  static ublas::matrix< double, ublas::column_major > to_lapack (const Matrix_T &val)

  *Convert matrix to LAPACK format.*

## 5.4.1 Enumeration Type Documentation

### 5.4.1.1 eig_case_t

`enum glucat::matrix::eig_case_t`

Classification of eigenvalues of a matrix.

**Enumerator**

| | |
|---|---|
| safe_eig_case | |
| negative_eig_case | |
| both_eig_case | |

Definition at line 127 of file matrix.h.

### 5.4.2 Function Documentation

#### 5.4.2.1 classify_eigenvalues()

```
template<typename Matrix_T >
eig_genus< Matrix_T > glucat::matrix::classify_eigenvalues (
            const Matrix_T & val )
```

Classify the eigenvalues of a matrix.

Definition at line 526 of file matrix_imp.h.

References glucat::abs(), both_eig_case, eigenvalues(), glucat::imag(), glucat::matrix::eig_genus< Matrix_T >::m_eig_case, glucat::matrix::eig_genus< Matrix_T >::m_safe_arg, negative_eig_case, glucat::norm(), glucat::numeric_traits< Scalar_T >::pi(), PyClical::pi, glucat::real(), and safe_eig_case.

Referenced by glucat::matrix_log(), and glucat::matrix_sqrt().

#### 5.4.2.2 eigenvalues()

```
template<typename Matrix_T >
ublas::vector< std::complex< double > > glucat::matrix::eigenvalues (
            const Matrix_T & val )
```

Eigenvalues of a matrix.

Definition at line 493 of file matrix_imp.h.

References to_lapack().

Referenced by classify_eigenvalues().

#### 5.4.2.3 inner()

```
template<typename Scalar_T , typename LHS_T , typename RHS_T >
Scalar_T glucat::matrix::inner (
            const LHS_T & lhs,
            const RHS_T & rhs )
```

Inner product: sum(x(i,j)∗y(i,j))/x.nrows()

Inner product: sum(lhs(i,j)∗rhs(i,j))/lhs.nrows()

Definition at line 391 of file matrix_imp.h.

#### 5.4.2.4 isnan()

```
template<typename Matrix_T >
bool glucat::matrix::isnan (
             const Matrix_T & m )
```

Not a Number.

Definition at line 292 of file matrix_imp.h.

Referenced by glucat::matrix_log(), and glucat::operator/().

#### 5.4.2.5 kron()

```
template<typename LHS_T , typename RHS_T >
const RHS_T glucat::matrix::kron (
             const LHS_T & lhs,
             const RHS_T & rhs )
```

Kronecker tensor product of matrices - as per Matlab kron.

Definition at line 73 of file matrix_imp.h.

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::fast().

#### 5.4.2.6 mono_kron()

```
template<typename LHS_T , typename RHS_T >
const RHS_T glucat::matrix::mono_kron (
             const LHS_T & lhs,
             const RHS_T & rhs )
```

Sparse Kronecker tensor product of monomial matrices.

Definition at line 116 of file matrix_imp.h.

Referenced by glucat::gen::generator_table< Matrix_T >::gen_from_pm1_qm1().

#### 5.4.2.7 mono_prod()

```
template<typename LHS_T , typename RHS_T >
const RHS_T::expression_type glucat::matrix::mono_prod (
             const ublas::matrix_expression< LHS_T > & lhs,
             const ublas::matrix_expression< RHS_T > & rhs )
```

Product of monomial matrices.

Definition at line 326 of file matrix_imp.h.

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >::basis_element(), glucat::gen::generator_table< Matrix_T >::gen_from_pm4_qp4(), glucat::gen::generator_table< Matrix_T >::gen_from_pp4_qm4(), and glucat::gen::generator_table< Matrix_T >::gen_from_qp1_pm1().

#### 5.4.2.8 nnz()

```
template<typename Matrix_T >
Matrix_T::size_type glucat::matrix::nnz (
            const Matrix_T & m )
```

Number of non-zeros.

Definition at line 269 of file matrix_imp.h.

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::framed_multi().

#### 5.4.2.9 nork()

```
template<typename LHS_T , typename RHS_T >
const RHS_T glucat::matrix::nork (
            const LHS_T & lhs,
            const RHS_T & rhs,
            const bool mono = true )
```

Left inverse of Kronecker product.

Definition at line 188 of file matrix_imp.h.

References norm_frob2().

#### 5.4.2.10 nork_range()

```
template<typename LHS_T , typename RHS_T >
void glucat::matrix::nork_range (
            RHS_T & result,
            const typename LHS_T::const_iterator2 lhs_it2,
            const RHS_T & rhs,
            const typename RHS_T::size_type res_s1,
            const typename RHS_T::size_type res_s2 )
```

Utility routine for nork: calculate result for a range of indices.

Definition at line 155 of file matrix_imp.h.

References glucat::numeric_traits< Scalar_T >::to_scalar_t().

#### 5.4.2.11 norm_frob2()

```
template<typename Matrix_T >
Matrix_T::value_type glucat::matrix::norm_frob2 (
             const Matrix_T & val )
```

Square of Frobenius norm.

Definition at line 413 of file matrix_imp.h.

Referenced by nork().

#### 5.4.2.12 prod()

```
template<typename LHS_T , typename RHS_T >
const RHS_T::expression_type glucat::matrix::prod (
             const ublas::matrix_expression< LHS_T > & lhs,
             const ublas::matrix_expression< RHS_T > & rhs )  [inline]
```

Product of matrices.

Definition at line 373 of file matrix_imp.h.

#### 5.4.2.13 signed_perm_nork()

```
template<typename LHS_T , typename RHS_T >
const RHS_T glucat::matrix::signed_perm_nork (
             const LHS_T & lhs,
             const RHS_T & rhs )
```

Left inverse of Kronecker product where lhs is a signed permutation matrix.

Definition at line 237 of file matrix_imp.h.

Referenced by glucat::fast().

#### 5.4.2.14 sparse_prod()

```
template<typename LHS_T , typename RHS_T >
const RHS_T::expression_type glucat::matrix::sparse_prod (
             const ublas::matrix_expression< LHS_T > & lhs,
             const ublas::matrix_expression< RHS_T > & rhs )  [inline]
```

Product of sparse matrices.

Definition at line 362 of file matrix_imp.h.

#### 5.4.2.15 to_lapack()

```
template<typename Matrix_T >
static ublas::matrix<double, ublas::column_major> glucat::matrix::to_lapack (
            const Matrix_T & val )  [static]
```

Convert matrix to LAPACK format.

Definition at line 461 of file matrix_imp.h.

Referenced by eigenvalues().

#### 5.4.2.16 trace()

```
template<typename Matrix_T >
Matrix_T::value_type glucat::matrix::trace (
            const Matrix_T & val )
```

Matrix trace.

Definition at line 437 of file matrix_imp.h.

References glucat::numeric_traits< Scalar_T >::NaN().

#### 5.4.2.17 unit()

```
template<typename Matrix_T >
const Matrix_T glucat::matrix::unit (
            const typename Matrix_T::size_type n )  [inline]
```

Unit matrix - as per Matlab eye.

Definition at line 317 of file matrix_imp.h.

## 5.5 glucat::timing Namespace Reference

### Functions

- static double elapsed (clock_t cpu_time)

  *Elapsed time in milliseconds.*

### Variables

- const double MS_PER_SEC = 1000.0

  *Timing constant: milliseconds per second.*
- const double MS_PER_CLOCK = MS_PER_SEC / double(CLOCKS_PER_SEC)

  *Timing constant: milliseconds per clock.*
- const int EXTRA_TRIALS = 2

  *Timing constant: trial expansion factor.*

### 5.5.1 Function Documentation

#### 5.5.1.1 elapsed()

```
static double glucat::timing::elapsed (
            clock_t cpu_time )  [inline], [static]
```

Elapsed time in milliseconds.

Definition at line 51 of file timing.h.

References MS_PER_CLOCK.

### 5.5.2 Variable Documentation

#### 5.5.2.1 EXTRA_TRIALS

```
const int glucat::timing::EXTRA_TRIALS = 2
```

Timing constant: trial expansion factor.

Definition at line 45 of file timing.h.

#### 5.5.2.2 MS_PER_CLOCK

```
const double glucat::timing::MS_PER_CLOCK = MS_PER_SEC / double(CLOCKS_PER_SEC)
```

Timing constant: milliseconds per clock.

Definition at line 42 of file timing.h.

Referenced by elapsed().

#### 5.5.2.3 MS_PER_SEC

```
const double glucat::timing::MS_PER_SEC = 1000.0
```

Timing constant: milliseconds per second.

Definition at line 39 of file timing.h.

## 5.6 PyClical Namespace Reference

### Classes

- class clifford
- class index_set

### Functions

- def index_set_hidden_doctests ()
- def clifford_hidden_doctests ()
- def e (obj)
- def istpq (p, q)
- def _test ()

### Variables

- string __version__ = "0.8.2"
- obj
- i
- ixt
- fill
- float tau = atan(clifford(1.0)) * 8.0
- float pi = tau / 2.0
- cl = clifford
- ist = index_set
- def ninf3 = e(4) + e(-1)
- def nbar3 = e(4) - e(-1)

### 5.6.1 Function Documentation

#### 5.6.1.1 _test()

```
def PyClical._test ( )  [private]
```

Definition at line 1913 of file PyClical.pyx.

#### 5.6.1.2 clifford_hidden_doctests()

```
def PyClical.clifford_hidden_doctests ( )
```

Tests for functions that Doctest cannot see.

For clifford.__cinit__: Construct an object of type clifford.

```
>>> print clifford(2)
2
>>> print clifford(2L)
2
>>> print clifford(2.0)
2
>>> print clifford(1.0e-1)
0.1
>>> print clifford("2")
2
>>> print clifford("2{1,2,3}")
2{1,2,3}
>>> print clifford(clifford("2{1,2,3}"))
2{1,2,3}
>>> print clifford("-{1}")
-{1}
>>> print clifford(2,index_set({1,2}))
2{1,2}
>>> print clifford([2,3],index_set({1,2}))
2{1}+3{2}
>>> print clifford([1,2])
Traceback (most recent call last):
  ...
TypeError: Cannot initialize clifford object from <type 'list'>.
>>> print clifford(None)
Traceback (most recent call last):
  ...
TypeError: Cannot initialize clifford object from <type 'NoneType'>.
>>> print clifford(None,[1,2])
Traceback (most recent call last):
  ...
TypeError: Cannot initialize clifford object from (<type 'NoneType'>, <type 'list'>).
>>> print clifford([1,2],[1,2])
Traceback (most recent call last):
  ...
TypeError: Cannot initialize clifford object from (<type 'list'>, <type 'list'>).
>>> print clifford("")
Traceback (most recent call last):
  ...
ValueError: Cannot initialize clifford object from invalid string ''.
>>> print clifford("{")
Traceback (most recent call last):
  ...
ValueError: Cannot initialize clifford object from invalid string '{'.
>>> print clifford("{1")
Traceback (most recent call last):
  ...
ValueError: Cannot initialize clifford object from invalid string '{1'.
>>> print clifford("+")
Traceback (most recent call last):
  ...
ValueError: Cannot initialize clifford object from invalid string '+'.
>>> print clifford("-")
Traceback (most recent call last):
  ...
ValueError: Cannot initialize clifford object from invalid string '-'.
>>> print clifford("{1}+")
Traceback (most recent call last):
  ...
ValueError: Cannot initialize clifford object from invalid string '{1}+'.
```

For clifford.__richcmp__: Compare objects of type clifford.

```
>>> clifford("{1}") == clifford("1{1}")
True
>>> clifford("{1}") != clifford("1.0{1}")
False
>>> clifford("{1}") != clifford("1.0")
True
>>> clifford("{1,2}") == None
False
>>> clifford("{1,2}") != None
True
>>> None == clifford("{1,2}")
False
>>> None != clifford("{1,2}")
True
```

Definition at line 1243 of file PyClical.pyx.

#### 5.6.1.3 e()

```
def PyClical.e (
              obj )
```

```
Abbreviation for clifford(index_set(obj)).

>>> print e(1)
{1}
>>> print e(-1)
{-1}
>>> print e(0)
1
```

Definition at line 1887 of file PyClical.pyx.

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >.basis_element(), clifford_to_str(), glucat::framed_multi< Scalar_T, LO, HI >.framed_multi(), glucat::matrix_multi< Scalar_T, LO, HI >.matrix_multi(), and glucat.try_catch().

#### 5.6.1.4 index_set_hidden_doctests()

```
def PyClical.index_set_hidden_doctests ( )
```

```
Tests for functions that Doctest cannot see.

For index_set.__cinit__: Construct index_set.

>>> print index_set(1)
{1}
>>> print index_set({1,2})
{1,2}
>>> print index_set(index_set({1,2}))
{1,2}
>>> print index_set({1,2})
{1,2}
>>> print index_set({1,2,1})
{1,2}
>>> print index_set({1,2,1})
{1,2}
```

```
>>> print index_set("")
{}
>>> print index_set("{")
Traceback (most recent call last):
...
ValueError: Cannot initialize index_set object from invalid string '{'.
>>> print index_set("{1")
Traceback (most recent call last):
...
ValueError: Cannot initialize index_set object from invalid string '{1'.
>>> print index_set("{1,2,100}")
Traceback (most recent call last):
...
ValueError: Cannot initialize index_set object from invalid string '{1,2,100}'.
>>> print index_set({1,2,100})
Traceback (most recent call last):
...
IndexError: Cannot initialize index_set object from invalid set([1, 2, 100]).
>>> print index_set([1,2])
Traceback (most recent call last):
...
TypeError: Cannot initialize index_set object from <type 'list'>.

For index_set.__richcmp__: Compare two objects of class index_set.

>>> index_set(1) == index_set({1})
True
>>> index_set({1}) != index_set({1})
False
>>> index_set({1}) != index_set({2})
True
>>> index_set({1}) == index_set({2})
False
>>> index_set({1}) < index_set({2})
True
>>> index_set({1}) <= index_set({2})
True
>>> index_set({1}) > index_set({2})
False
>>> index_set({1}) >= index_set({2})
False
>>> None == index_set({1,2})
False
>>> None != index_set({1,2})
True
>>> None < index_set({1,2})
False
>>> None <= index_set({1,2})
False
>>> None > index_set({1,2})
False
>>> None >= index_set({1,2})
False
>>> index_set({1,2}) == None
False
>>> index_set({1,2}) != None
True
>>> index_set({1,2}) < None
False
>>> index_set({1,2}) <= None
False
>>> index_set({1,2}) > None
False
>>> index_set({1,2}) >= None
False
```

Definition at line 404 of file PyClical.pyx.

#### 5.6.1.5 istpq()

```
def PyClical.istpq (
              p,
              q )
```

```
Abbreviation for index_set({-q,...p}).
```

```
>>> print istpq(2,3)
{-3,-2,-1,1,2}
```

Definition at line 1900 of file PyClical.pyx.

### 5.6.2 Variable Documentation

#### 5.6.2.1 __version__

```
string PyClical.__version__ = "0.8.2"  [private]
```

Definition at line 32 of file PyClical.pyx.

#### 5.6.2.2 cl

```
PyClical.cl = clifford
```

Definition at line 1859 of file PyClical.pyx.

Referenced by cga3.agc3(), cga3.cga3(), and cga3.cga3std().

#### 5.6.2.3 fill

```
PyClical.fill
```

Definition at line 1815 of file PyClical.pyx.

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >.random(), and glucat::framed_multi< Scalar_T, LO, HI >.random().

#### 5.6.2.4 i

```
PyClical.i
```

Definition at line 1542 of file PyClical.pyx.

Referenced by glucat.acos(), glucat.acosh(), glucat.asin(), glucat.asinh(), glucat.atan(), glucat.atanh(), glucat.↩ check_complex(), glucat.cos(), glucat.log(), glucat.matrix_log(), glucat.matrix_sqrt(), glucat.operator<<(), glucat.↩ operator>>(), glucat.sin(), glucat.sqrt(), and glucat.tan().

#### 5.6.2.5 ist

```
PyClical.ist = index_set
```

Definition at line 1879 of file PyClical.pyx.

Referenced by cga3.agc3(), glucat::matrix_multi< Scalar_T, LO, HI >.basis_element(), glucat::framed_multi< Scalar_T, LO, HI >.centre_pm4_qp4(), glucat::framed_multi< Scalar_T, LO, HI >.centre_pp4_qm4(), glucat↩ ::framed_multi< Scalar_T, LO, HI >.centre_qp1_pm1(), cga3.cga3(), cga3.cga3std(), glucat::framed_multi< Scalar_T, LO, HI >.divide(), glucat::framed_multi< Scalar_T, LO, HI >.framed_multi(), index_set_to_repr(), index_set_to_str(), glucat::matrix_multi< Scalar_T, LO, HI >.matrix_multi(), glucat.max_pos(), glucat.min_neg(), glucat.operator<<(), and glucat.operator>>().

#### 5.6.2.6 ixt

```
PyClical.ixt
```

Definition at line 1815 of file PyClical.pyx.

#### 5.6.2.7 nbar3

```
def PyClical.nbar3 = e(4) - e(-1)
```

Definition at line 1910 of file PyClical.pyx.

#### 5.6.2.8 ninf3

```
def PyClical.ninf3 = e(4) + e(-1)
```

Definition at line 1909 of file PyClical.pyx.

Referenced by cga3.cga3(), and cga3.cga3std().

#### 5.6.2.9 obj

```
PyClical.obj
```

Definition at line 1542 of file PyClical.pyx.

#### 5.6.2.10 pi

```
float PyClical.pi = tau / 2.0
```

Definition at line 1857 of file PyClical.pyx.

Referenced by glucat::matrix.classify_eigenvalues(), glucat.cos(), glucat.log(), glucat.matrix_log(), and glucat.sin().

#### 5.6.2.11 tau

```
float PyClical.tau = atan(clifford(1.0)) * 8.0
```

Definition at line 1856 of file PyClical.pyx.

## 5.7 std Namespace Reference

### Classes

- struct numeric_limits< glucat::framed_multi< Scalar_T, LO, HI > >

  *Numeric limits for framed_multi inherit limits for the corresponding scalar type.*
- struct numeric_limits< glucat::matrix_multi< Scalar_T, LO, HI > >

  *Numeric limits for matrix_multi inherit limits for the corresponding scalar type.*

# Chapter 6

# Class Documentation

## 6.1 glucat::basis_table< Scalar_T, LO, HI, Matrix_T > Class Template Reference

Table of basis elements used as a cache by basis_element()

`#include <matrix_multi_imp.h>`

Inheritance diagram for glucat::basis_table< Scalar_T, LO, HI, Matrix_T >:




Collaboration diagram for glucat::basis_table< Scalar_T, LO, HI, Matrix_T >:



### Static Public Member Functions

- static basis_table & basis ()

  *Single instance of basis table.*

### Private Member Functions

- basis_table ()
- ~basis_table ()
- basis_table (const basis_table &)
- basis_table & operator= (const basis_table &)

### Friends

- class friend_for_private_destructor

## 6.1.1 Detailed Description

**template<typename Scalar_T, const index_t LO, const index_t HI, typename Matrix_T>**
**class glucat::basis_table< Scalar_T, LO, HI, Matrix_T >**

Table of basis elements used as a cache by basis_element()

Definition at line 1218 of file matrix_multi_imp.h.

## 6.1.2 Constructor & Destructor Documentation

### 6.1.2.1 basis_table() [1/2]

```
template<typename Scalar_T , const index_t LO, const index_t HI, typename Matrix_T >
glucat::basis_table< Scalar_T, LO, HI, Matrix_T >::basis_table ( )  [inline], [private]
```

Definition at line 1228 of file matrix_multi_imp.h.

### 6.1.2.2 ~basis_table()

```
template<typename Scalar_T , const index_t LO, const index_t HI, typename Matrix_T >
glucat::basis_table< Scalar_T, LO, HI, Matrix_T >::~basis_table ( )  [inline], [private]
```

Definition at line 1229 of file matrix_multi_imp.h.

#### 6.1.2.3 basis_table() [2/2]

```
template<typename Scalar_T , const index_t LO, const index_t HI, typename Matrix_T >
glucat::basis_table< Scalar_T, LO, HI, Matrix_T >::basis_table (
            const basis_table< Scalar_T, LO, HI, Matrix_T > &  )  [private]
```

### 6.1.3 Member Function Documentation

#### 6.1.3.1 basis()

```
template<typename Scalar_T , const index_t LO, const index_t HI, typename Matrix_T >
static basis_table& glucat::basis_table< Scalar_T, LO, HI, Matrix_T >::basis ( )  [inline],
[static]
```

Single instance of basis table.

Definition at line 1224 of file matrix_multi_imp.h.

#### 6.1.3.2 operator=()

```
template<typename Scalar_T , const index_t LO, const index_t HI, typename Matrix_T >
basis_table& glucat::basis_table< Scalar_T, LO, HI, Matrix_T >::operator= (
            const basis_table< Scalar_T, LO, HI, Matrix_T > &  )  [private]
```

### 6.1.4 Friends And Related Function Documentation

#### 6.1.4.1 friend_for_private_destructor

```
template<typename Scalar_T , const index_t LO, const index_t HI, typename Matrix_T >
friend class friend_for_private_destructor  [friend]
```

Friend declaration to avoid compiler warning: "... only defines a private destructor and has no friends" Ref: Carlos O'Ryan, ACE http://doc.ece.uci.edu

Definition at line 1236 of file matrix_multi_imp.h.

The documentation for this class was generated from the following file:

- glucat/matrix_multi_imp.h

## 6.2 glucat::bool_to_type< truth_value > Class Template Reference

Bool to type.

`#include <global.h>`

### Private Types

- enum { value = truth_value }

### 6.2.1 Detailed Description

**template<bool truth_value>**
**class glucat::bool_to_type< truth_value >**

Bool to type.

Definition at line 69 of file global.h.

### 6.2.2 Member Enumeration Documentation

#### 6.2.2.1 anonymous enum

```
template<bool truth_value>
anonymous enum  [private]
```

**Enumerator**

| | |
|---|---|
| value | |

Definition at line 72 of file global.h.

The documentation for this class was generated from the following file:

- glucat/global.h

## 6.3 PyClical.clifford Class Reference

Inheritance diagram for PyClical.clifford:




Collaboration diagram for PyClical.clifford:




### Public Member Functions

- def __cinit__ (self, other=0, ixt=None)
- def __dealloc__ (self)
- def __contains__ (self, x)
- def __iter__ (self)
- def reframe (self, ixt)
- def __richcmp__ (lhs, rhs, int, op)
- def __getitem__ (self, ixt)
- def __neg__ (self)
- def __pos__ (self)
- def __add__ (lhs, rhs)
- def __iadd__ (self, rhs)
- def __sub__ (lhs, rhs)
- def __isub__ (self, rhs)
- def __mul__ (lhs, rhs)
- def __imul__ (self, rhs)
- def __mod__ (lhs, rhs)
- def __imod__ (self, rhs)

- def __and__ (lhs, rhs)
- def __iand__ (self, rhs)
- def __xor__ (lhs, rhs)
- def __ixor__ (self, rhs)
- def __div__ (lhs, rhs)
- def __idiv__ (self, rhs)
- def inv (self)
- def __or__ (lhs, rhs)
- def __ior__ (self, rhs)
- def __pow__ (self, m, dummy)
- def pow (self, m)
- def outer_pow (self, m)
- def __call__ (self, grade)
- def scalar (self)
- def pure (self)
- def even (self)
- def odd (self)
- def vector_part (self, frm=None)
- def involute (self)
- def reverse (self)
- def conj (self)
- def quad (self)
- def norm (self)
- def abs (self)
- def max_abs (self)
- def truncated (self, limit)
- def isnan (self)
- def frame (self)
- def __repr__ (self)
- def __str__ (self)

### Public Attributes

- instance

### 6.3.1 Detailed Description

```
Python class clifford wraps C++ class Clifford.
```

Definition at line 532 of file PyClical.pyx.

### 6.3.2 Member Function Documentation

#### 6.3.2.1 __add__()

```
def PyClical.clifford.__add__ (
              lhs,
              rhs )
```

```
Geometric sum.
```

```
>>> print clifford(1) + clifford("{2}")
1+{2}
>>> print clifford("{1}") + clifford("{2}")
{1}+{2}
```

Definition at line 739 of file PyClical.pyx.

#### 6.3.2.2 __and__()

```
def PyClical.clifford.__and__ (
              lhs,
              rhs )
```

```
Inner product.
```

```
>>> print clifford("{1}") & clifford("{2}")
0
>>> print clifford(2) & clifford("{2}")
0
>>> print clifford("{1}") & clifford("{1}")
1
>>> print clifford("{1}") & clifford("{1,2}")
{2}
```

Definition at line 835 of file PyClical.pyx.

#### 6.3.2.3 __call__()

```
def PyClical.clifford.__call__ (
              self,
              grade )
```

```
Pure grade-vector part.
```

```
>>> print clifford("{1}")(1)
{1}
>>> print clifford("{1}")(0)
0
>>> print clifford("1+{1}+{1,2}")(0)
1
>>> print clifford("1+{1}+{1,2}")(1)
{1}
>>> print clifford("1+{1}+{1,2}")(2)
{1,2}
>>> print clifford("1+{1}+{1,2}")(3)
0
```

Definition at line 1019 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.4 __cinit__()

```
def PyClical.clifford.__cinit__ (
              self,
              other = 0,
              ixt = None )
```

```
Construct an object of type clifford.
```

```
>>> print clifford(2)
2
>>> print clifford(2L)
2
>>> print clifford(2.0)
2
>>> print clifford(1.0e-1)
0.1
>>> print clifford("2")
2
>>> print clifford("2{1,2,3}")
2{1,2,3}
>>> print clifford(clifford("2{1,2,3}"))
2{1,2,3}
>>> print clifford("-{1}")
-{1}
>>> print clifford(2,index_set({1,2}))
2{1,2}
>>> print clifford([2,3],index_set({1,2}))
2{1}+3{2}
```

Definition at line 563 of file PyClical.pyx.

#### 6.3.2.5 __contains__()

```
def PyClical.clifford.__contains__ (
              self,
              x )
```

```
Not applicable.
```

```
>>> x=clifford(index_set({-3,4,7})); -3 in x
Traceback (most recent call last):
  ...
TypeError: Not applicable.
```

Definition at line 626 of file PyClical.pyx.

#### 6.3.2.6 __dealloc__()

```
def PyClical.clifford.__dealloc__ (
              self )
```

```
Clean up by deallocating the instance of C++ class Clifford.
```

Definition at line 620 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.7 __div__()

```
def PyClical.clifford.__div__ (
              lhs,
              rhs )
```

Geometric quotient.

```
>>> print clifford("{1}") / clifford("{2}")
{1,2}
>>> print clifford(2) / clifford("{2}")
2{2}
>>> print clifford("{1}") / clifford("{1}")
1
>>> print clifford("{1}") / clifford("{1,2}")
-{2}
```

Definition at line 895 of file PyClical.pyx.

#### 6.3.2.8 __getitem__()

```
def PyClical.clifford.__getitem__ (
              self,
              ixt )
```

Subscripting: map from index set to scalar coordinate.

```
>>> clifford("{1}")[index_set(1)]
1.0
>>> clifford("{1}")[index_set({1})]
1.0
>>> clifford("{1}")[index_set({1,2})]
0.0
>>> clifford("2{1,2}")[index_set({1,2})]
2.0
```

Definition at line 706 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.9 __iadd__()

```
def PyClical.clifford.__iadd__ (
              self,
              rhs )
```

Geometric sum.

```
>>> x = clifford(1); x += clifford("{2}"); print x
1+{2}
```

Definition at line 750 of file PyClical.pyx.

#### 6.3.2.10 __iand__()

```
def PyClical.clifford.__iand__ (
              self,
              rhs )
```

Inner product.

```
>>> x = clifford("{1}"); x &= clifford("{2}"); print x
0
>>> x = clifford(2); x &= clifford("{2}"); print x
0
>>> x = clifford("{1}"); x &= clifford("{1}"); print x
1
>>> x = clifford("{1}"); x &= clifford("{1,2}"); print x
{2}
```

Definition at line 850 of file PyClical.pyx.

#### 6.3.2.11 __idiv__()

```
def PyClical.clifford.__idiv__ (
              self,
              rhs )
```

Geometric quotient.

```
>>> x = clifford("{1}"); x /= clifford("{2}"); print x
{1,2}
>>> x = clifford(2); x /= clifford("{2}"); print x
2{2}
>>> x = clifford("{1}"); x /= clifford("{1}"); print x
1
>>> x = clifford("{1}"); x /= clifford("{1,2}"); print x
-{2}
```

Definition at line 910 of file PyClical.pyx.

#### 6.3.2.12 __imod__()

```
def PyClical.clifford.__imod__ (
              self,
              rhs )
```

Contraction.

```
>>> x = clifford("{1}"); x %= clifford("{2}"); print x
0
>>> x = clifford(2); x %= clifford("{2}"); print x
2{2}
>>> x = clifford("{1}"); x %= clifford("{1}"); print x
1
>>> x = clifford("{1}"); x %= clifford("{1,2}"); print x
{2}
```

Definition at line 820 of file PyClical.pyx.

#### 6.3.2.13 __imul__()

```
def PyClical.clifford.__imul__ (
              self,
              rhs )
```

Geometric product.

```
>>> x = clifford(2); x *= clifford("{2}"); print x
2{2}
>>> x = clifford("{1}"); x *= clifford("{2}"); print x
{1,2}
>>> x = clifford("{1}"); x *= clifford("{1,2}"); print x
{2}
```

Definition at line 792 of file PyClical.pyx.

#### 6.3.2.14 __ior__()

```
def PyClical.clifford.__ior__ (
              self,
              rhs )
```

Transform left hand side, using right hand side as a transformation.

```
>>> x=clifford("{1,2}") * pi/2; y=clifford("{1}"); y|=x; print y
-{1}
>>> x=clifford("{1,2}") * pi/2; y=clifford("{1}"); y|=exp(x); print y
-{1}
```

Definition at line 949 of file PyClical.pyx.

#### 6.3.2.15 __isub__()

```
def PyClical.clifford.__isub__ (
              self,
              rhs )
```

Geometric difference.

```
>>> x = clifford(1); x -= clifford("{2}"); print x
1-{2}
```

Definition at line 770 of file PyClical.pyx.

#### 6.3.2.16 __iter__()

```
def PyClical.clifford.__iter__ (
              self )
```

Not applicable.

```
>>> for a in clifford(index_set({-3,4,7})): print a,
Traceback (most recent call last):
  ...
TypeError: Not applicable.
```

Definition at line 637 of file PyClical.pyx.

#### 6.3.2.17 __ixor__()

```
def PyClical.clifford.__ixor__ (
              self,
              rhs )
```

Outer product.

```
>>> x = clifford("{1}"); x ^= clifford("{2}"); print x
{1,2}
>>> x = clifford(2); x ^= clifford("{2}"); print x
2{2}
>>> x = clifford("{1}"); x ^= clifford("{1}"); print x
0
>>> x = clifford("{1}"); x ^= clifford("{1,2}"); print x
0
```

Definition at line 880 of file PyClical.pyx.

#### 6.3.2.18 __mod__()

```
def PyClical.clifford.__mod__ (
              lhs,
              rhs )
```

Contraction.

```
>>> print clifford("{1}") % clifford("{2}")
0
>>> print clifford(2) % clifford("{2}")
2{2}
>>> print clifford("{1}") % clifford("{1}")
1
>>> print clifford("{1}") % clifford("{1,2}")
{2}
```

Definition at line 805 of file PyClical.pyx.

#### 6.3.2.19 __mul__()

```
def PyClical.clifford.__mul__ (
              lhs,
              rhs )
```

Geometric product.

```
>>> print clifford("{1}") * clifford("{2}")
{1,2}
>>> print clifford(2) * clifford("{2}")
2{2}
>>> print clifford("{1}") * clifford("{1,2}")
{2}
```

Definition at line 779 of file PyClical.pyx.

#### 6.3.2.20 __neg__()

```
def PyClical.clifford.__neg__ (
              self )
```

Unary -.

```
>>> print -clifford("{1}")
-{1}
```

Definition at line 721 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.21 __or__()

```
def PyClical.clifford.__or__ (
              lhs,
              rhs )
```

Transform left hand side, using right hand side as a transformation.

```
>>> x=clifford("{1,2}") * pi/2; y=clifford("{1}"); print y|x
-{1}
>>> x=clifford("{1,2}") * pi/2; y=clifford("{1}"); print y|exp(x)
-{1}
```

Definition at line 938 of file PyClical.pyx.

#### 6.3.2.22 __pos__()

```
def PyClical.clifford.__pos__ (
              self )
```

```
Unary +.
```

```
>>> print +clifford("{1}")
{1}
```

Definition at line 730 of file PyClical.pyx.

#### 6.3.2.23 __pow__()

```
def PyClical.clifford.__pow__ (
              self,
              m,
              dummy )
```

```
Power: self to the m.
```

```
>>> x=clifford("{1}"); print x ** 2
1
>>> x=clifford("2"); print x ** 2
4
>>> x=clifford("2+{1}"); print x ** 0
1
>>> x=clifford("2+{1}"); print x ** 1
2+{1}
>>> x=clifford("2+{1}"); print x ** 2
5+4{1}
>>> i=clifford("{1,2}");print exp(pi/2) * (i ** i)
1
```

Definition at line 960 of file PyClical.pyx.

References PyClical.clifford.pow().

#### 6.3.2.24 __repr__()

```
def PyClical.clifford.__repr__ (
              self )
```

```
The "official" string representation of self.
```

```
>>> clifford("1+3{-1}+2{1,2}+4{-2,7}").__repr__()
'clifford("1+3{-1}+2{1,2}+4{-2,7}")'
```

Definition at line 1225 of file PyClical.pyx.

References clifford_to_repr().

#### 6.3.2.25 __richcmp__()

```
def PyClical.clifford.__richcmp__ (
              lhs,
              rhs,
              int,
              op )
```

```
Compare objects of type clifford.
```

```
>>> clifford("{1}") == clifford("1{1}")
True
>>> clifford("{1}") != clifford("1.0{1}")
False
>>> clifford("{1}") != clifford("1.0")
True
>>> clifford("{1,2}") == None
False
>>> clifford("{1,2}") != None
True
>>> None == clifford("{1,2}")
False
>>> None != clifford("{1,2}")
True
```

Definition at line 671 of file PyClical.pyx.

#### 6.3.2.26 __str__()

```
def PyClical.clifford.__str__ (
              self )
```

```
The "informal" string representation of self.
```

```
>>> clifford("1+3{-1}+2{1,2}+4{-2,7}").__str__()
'1+3{-1}+2{1,2}+4{-2,7}'
```

Definition at line 1234 of file PyClical.pyx.

References clifford_to_str().

#### 6.3.2.27 __sub__()

```
def PyClical.clifford.__sub__ (
              lhs,
              rhs )
```

```
Geometric difference.
```

```
>>> print clifford(1) - clifford("{2}")
1-{2}
>>> print clifford("{1}") - clifford("{2}")
{1}-{2}
```

Definition at line 759 of file PyClical.pyx.

#### 6.3.2.28 __xor__()

```
def PyClical.clifford.__xor__ (
              lhs,
              rhs )
```

Outer product.

```
>>> print clifford("{1}") ^ clifford("{2}")
{1,2}
>>> print clifford(2) ^ clifford("{2}")
2{2}
>>> print clifford("{1}") ^ clifford("{1}")
0
>>> print clifford("{1}") ^ clifford("{1,2}")
0
```

Definition at line 865 of file PyClical.pyx.

#### 6.3.2.29 abs()

```
def PyClical.clifford.abs (
              self )
```

Absolute value: square root of norm.

```
>>> clifford("1+{-1}+{1,2}+{1,2,3}").abs()
2.0
```

Definition at line 1174 of file PyClical.pyx.

References glucat.abs().

#### 6.3.2.30 conj()

```
def PyClical.clifford.conj (
              self )
```

Conjugation, reverse o involute == involute o reverse.

```
>>> print (clifford("{1}")).conj()
-{1}
>>> print (clifford("{2}") * clifford("{1}")).conj()
{1,2}
>>> print (clifford("{1}") * clifford("{2}")).conj()
-{1,2}
>>> print clifford("1+{1}+{1,2}").conj()
1-{1}-{1,2}
```

Definition at line 1137 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.31 even()

```
def PyClical.clifford.even (
              self )
```

```
Even part of multivector, sum of even grade terms.

>>> print clifford("1+{1}+{1,2}").even()
1+{1,2}
```

Definition at line 1060 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.32 frame()

```
def PyClical.clifford.frame (
              self )
```

```
Subalgebra generated by all generators of terms of given multivector.

>>> print clifford("1+3{-1}+2{1,2}+4{-2,7}").frame()
{-2,-1,1,2,7}
>>> s=clifford("1+3{-1}+2{1,2}+4{-2,7}").frame(); type(s)
<type 'PyClical.index_set'>
```

Definition at line 1214 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.33 inv()

```
def PyClical.clifford.inv (
              self )
```

```
Geometric multiplicative inverse.

>>> x = clifford("{1}"); print x.inv()
{1}
>>> x = clifford(2); print x.inv()
0.5
>>> x = clifford("{1,2}"); print x.inv()
-{1,2}
```

Definition at line 925 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.34 involute()

```
def PyClical.clifford.involute (
              self )
```

```
Main involution, each {i} is replaced by -{i} in each term,
eg. clifford("{1}") -> -clifford("{1}").

>>> print clifford("{1}").involute()
-{1}
>>> print (clifford("{2}") * clifford("{1}")).involute()
-{1,2}
>>> print (clifford("{1}") * clifford("{2}")).involute()
{1,2}
>>> print clifford("1+{1}+{1,2}").involute()
1-{1}+{1,2}
```

Definition at line 1106 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.35 isnan()

```
def PyClical.clifford.isnan (
              self )
```

```
Check if a multivector contains any IEEE NaN values.

>>> clifford().isnan()
False
```

Definition at line 1205 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.36 max_abs()

```
def PyClical.clifford.max_abs (
              self )
```

```
Maximum of absolute values of components of multivector: multivector infinity norm.

>>> clifford("1+{-1}+{1,2}+{1,2,3}").max_abs()
1.0
>>> clifford("3+2{1}+{1,2}").max_abs()
3.0
```

Definition at line 1183 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.37 norm()

```
def PyClical.clifford.norm (
              self )
```

```
Norm == sum of squares of coordinates.
```

```
>>> clifford("1+{1}+{1,2}").norm()
3.0
>>> clifford("1+{-1}+{1,2}+{1,2,3}").norm()
4.0
```

Definition at line 1163 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.38 odd()

```
def PyClical.clifford.odd (
              self )
```

```
Odd part of multivector, sum of odd grade terms.
```

```
>>> print clifford("1+{1}+{1,2}").odd()
{1}
```

Definition at line 1069 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.39 outer_pow()

```
def PyClical.clifford.outer_pow (
              self,
              m )
```

```
Outer product power.
```

```
>>> x=clifford("2+{1}"); print x.outer_pow(0)
1
>>> x=clifford("2+{1}"); print x.outer_pow(1)
2+{1}
>>> x=clifford("2+{1}"); print x.outer_pow(2)
4+4{1}
>>> print clifford("1+{1}+{1,2}").outer_pow(3)
1+3{1}+3{1,2}
```

Definition at line 1003 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.40 pow()

```
def PyClical.clifford.pow (
              self,
              m )
```

```
Power: self to the m.
```

```
>>> x=clifford("{1}"); print x.pow(2)
1
>>> x=clifford("2"); print x.pow(2)
4
>>> x=clifford("2+{1}"); print x.pow(0)
1
>>> x=clifford("2+{1}"); print x.pow(1)
2+{1}
>>> x=clifford("2+{1}"); print x.pow(2)
5+4{1}
>>> print clifford("1+{1}+{1,2}").pow(3)
1+3{1}+3{1,2}
>>> i=clifford("{1,2}");print exp(pi/2) * i.pow(i)
1
```

Definition at line 979 of file PyClical.pyx.

References glucat.exp(), PyClical.index_set.instance, PyClical.clifford.instance, and glucat.log().

Referenced by PyClical.clifford.__pow__().

#### 6.3.2.41 pure()

```
def PyClical.clifford.pure (
              self )
```

```
Pure part.
```

```
>>> print clifford("1+{1}+{1,2}").pure()
{1}+{1,2}
>>> print clifford("{1,2}").pure()
{1,2}
```

Definition at line 1049 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.42 quad()

```
def PyClical.clifford.quad (
              self )
```

```
Quadratic form == (rev(x)*x)(0).
```

```
>>> print clifford("1+{1}+{1,2}").quad()
3.0
>>> print clifford("1+{-1}+{1,2}+{1,2,3}").quad()
2.0
```

Definition at line 1152 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.43 reframe()

```
def PyClical.clifford.reframe (
              self,
              ixt )
```

```
Put self into a larger frame, containing the union of self.frame() and index set ixt.
This can be used to make multiplication faster, by multiplying within a common frame.

>>> clifford("2+3{1}").reframe(index_set({1,2,3}))
clifford("2+3{1}")
>>> s=index_set({1,2,3});t=index_set({-3,-2,-1});x=random_clifford(s); x.reframe(t).frame() == (s|t);
True
```

Definition at line 648 of file PyClical.pyx.

#### 6.3.2.44 reverse()

```
def PyClical.clifford.reverse (
              self )
```

```
Reversion, eg. clifford("{1}")*clifford("{2}") -> clifford("{2}")*clifford("{1}").

>>> print clifford("{1}").reverse()
{1}
>>> print (clifford("{2}") * clifford("{1}")).reverse()
{1,2}
>>> print (clifford("{1}") * clifford("{2}")).reverse()
-{1,2}
>>> print clifford("1+{1}+{1,2}").reverse()
1+{1}-{1,2}
```

Definition at line 1122 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.45 scalar()

```
def PyClical.clifford.scalar (
              self )
```

```
Scalar part.

>>> clifford("1+{1}+{1,2}").scalar()
1.0
>>> clifford("{1,2}").scalar()
0.0
```

Definition at line 1038 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.46 truncated()

```
def PyClical.clifford.truncated (
              self,
              limit )
```

```
Remove all terms of self with relative size smaller than limit.
```

```
>>> clifford("1e8+{1}+1e-8{1,2}").truncated(1.0e-6)
clifford("100000000")
>>> clifford("1e4+{1}+1e-4{1,2}").truncated(1.0e-6)
clifford("10000+{1}")
```

Definition at line 1194 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

#### 6.3.2.47 vector_part()

```
def PyClical.clifford.vector_part (
              self,
              frm = None )
```

```
Vector part of multivector, as a Python list, with respect to frm.
```

```
>>> print clifford("1+2{1}+3{2}+4{1,2}").vector_part()
[2.0, 3.0]
>>> print clifford("1+2{1}+3{2}+4{1,2}").vector_part(index_set({-1,1,2}))
[0.0, 2.0, 3.0]
```

Definition at line 1078 of file PyClical.pyx.

References PyClical.index_set.instance, and PyClical.clifford.instance.

### 6.3.3 Member Data Documentation

#### 6.3.3.1 instance

```
PyClical.clifford.instance
```

Definition at line 592 of file PyClical.pyx.

Referenced by PyClical.clifford.__call__(), PyClical.clifford.__dealloc__(), PyClical.clifford.__getitem__(), PyClical.clifford.__neg__(), PyClical.clifford.conj(), PyClical.clifford.even(), PyClical.clifford.frame(), PyClical.clifford.inv(), PyClical.clifford.involute(), PyClical.clifford.isnan(), PyClical.clifford.max_abs(), PyClical.clifford.norm(), PyClical.clifford.odd(), PyClical.clifford.outer_pow(), PyClical.clifford.pow(), PyClical.clifford.pure(), PyClical.clifford.quad(), PyClical.clifford.reverse(), PyClical.clifford.scalar(), PyClical.clifford.truncated(), and PyClical.clifford.vector_part().

The documentation for this class was generated from the following file:

- pyclical/PyClical.pyx

## 6.4 glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T > Class Template Reference

clifford_algebra<> declares the operations of a Clifford algebra

`#include <clifford_algebra.h>`

### Public Types

- typedef Scalar_T scalar_t
- typedef Index_Set_T index_set_t
- typedef Multivector_T multivector_t
- typedef std::pair< const index_set_t, Scalar_T > pair_t
- typedef std::vector< Scalar_T > vector_t

### Public Member Functions

- virtual ~clifford_algebra ()
- virtual bool operator== (const multivector_t &val) const =0

  *Test for equality of multivectors.*
- virtual bool operator== (const Scalar_T &scr) const =0

  *Test for equality of multivector and scalar.*
- virtual multivector_t & operator+= (const multivector_t &rhs)=0

  *Geometric sum.*
- virtual multivector_t & operator+= (const Scalar_T &scr)=0

  *Geometric sum of multivector and scalar.*
- virtual multivector_t & operator-= (const multivector_t &rhs)=0

  *Geometric difference.*
- virtual const multivector_t operator- () const =0

  *Unary -.*
- virtual multivector_t & operator*= (const Scalar_T &scr)=0

  *Product of multivector and scalar.*
- virtual multivector_t & operator*= (const multivector_t &rhs)=0

  *Geometric product.*
- virtual multivector_t & operator%= (const multivector_t &rhs)=0

  *Contraction.*
- virtual multivector_t & operator &= (const multivector_t &rhs)=0

  *Inner product.*
- virtual multivector_t & operator^= (const multivector_t &rhs)=0

  *Outer product.*
- virtual multivector_t & operator/= (const Scalar_T &scr)=0

  *Quotient of multivector and scalar.*
- virtual multivector_t & operator/= (const multivector_t &rhs)=0

  *Geometric quotient.*
- virtual multivector_t & operator|= (const multivector_t &rhs)=0

  *Transformation via twisted adjoint action.*
- virtual const multivector_t inv () const =0

  *Geometric multiplicative inverse.*
- virtual const multivector_t pow (int m) const =0

*this to the m

- virtual const multivector_t outer_pow (int m) const =0

  *Outer product power.*
- virtual const index_set_t frame () const =0

  *Subalgebra generated by all generators of terms of given multivector.*
- virtual index_t grade () const =0

  *Maximum of the grades of each term.*
- virtual Scalar_T operator[ ] (const index_set_t ist) const =0

  *Subscripting: map from index set to scalar coordinate.*
- virtual const multivector_t operator() (index_t grade) const =0

  *Pure grade-vector part.*
- virtual Scalar_T scalar () const =0

  *Scalar part.*
- virtual const multivector_t pure () const =0

  *Pure part.*
- virtual const multivector_t even () const =0

  *Even part of multivector, sum of even grade terms.*
- virtual const multivector_t odd () const =0

  *Odd part of multivector, sum of odd grade terms.*
- virtual const vector_t vector_part () const =0

  *Vector part of multivector, as a vector_t with respect to frame()*
- virtual const vector_t vector_part (const index_set_t frm, const bool prechecked) const =0

  *Vector part of multivector, as a vector_t with respect to frm.*
- virtual const multivector_t involute () const =0

  *Main involution, each {i} is replaced by -{i} in each term, eg. {1} -> -{1}.*
- virtual const multivector_t reverse () const =0

  *Reversion, eg. {1}*{2} -> {2}*{1}.*
- virtual const multivector_t conj () const =0

  *Conjugation, reverse o involute == involute o reverse.*
- virtual Scalar_T quad () const =0

  *Scalar_T quadratic form == (rev(x)*x)(0)*
- virtual Scalar_T norm () const =0

  *Scalar_T norm == sum of norm of coordinates.*
- virtual Scalar_T max_abs () const =0

  *Maximum of absolute values of components of multivector: multivector infinity norm.*
- virtual const multivector_t truncated (const Scalar_T &limit=Scalar_T(DEFAULT_TRUNCATION)) const =0

  *Remove all terms with relative size smaller than limit.*
- virtual bool isnan () const =0

  *Check if a multivector contains any IEEE NaN values.*
- virtual void write (const std::string &msg="") const =0

  *Write formatted multivector to output.*
- virtual void write (std::ofstream &ofile, const std::string &msg="") const =0

  *Write formatted multivector to file.*

## Static Public Member Functions

- static const std::string classname ()

### 6.4.1 Detailed Description

**template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>**
**class glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >**

clifford_algebra<> declares the operations of a Clifford algebra

Definition at line 42 of file clifford_algebra.h.

### 6.4.2 Member Typedef Documentation

#### 6.4.2.1 index_set_t

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
typedef Index_Set_T glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::index_set_t
```

Definition at line 46 of file clifford_algebra.h.

#### 6.4.2.2 multivector_t

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
typedef Multivector_T glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::multivector_t
```

Definition at line 47 of file clifford_algebra.h.

#### 6.4.2.3 pair_t

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
typedef std::pair< const index_set_t, Scalar_T > glucat::clifford_algebra< Scalar_T, Index_↩
Set_T, Multivector_T >::pair_t
```

Definition at line 48 of file clifford_algebra.h.

#### 6.4.2.4 scalar_t

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
typedef Scalar_T glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::scalar_t
```

Definition at line 45 of file clifford_algebra.h.

#### 6.4.2.5 vector_t

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
typedef std::vector<Scalar_T> glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T
>::vector_t
```

Definition at line 49 of file clifford_algebra.h.

### 6.4.3 Constructor & Destructor Documentation

#### 6.4.3.1 ~clifford_algebra()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::~clifford_algebra (
) [inline], [virtual]
```

Definition at line 53 of file clifford_algebra.h.

### 6.4.4 Member Function Documentation

#### 6.4.4.1 classname()

```
template<typename Scalar_T , typename Index_Set_T , typename Multivector_T >
const std::string glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::classname
( ) [static]
```

Definition at line 66 of file clifford_algebra_imp.h.

#### 6.4.4.2 conj()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const multivector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::conj ( ) const [pure virtual]
```

Conjugation, reverse o involute == involute o reverse.

#### 6.4.4.3 even()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const multivector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::even ( ) const  [pure virtual]
```

Even part of multivector, sum of even grade terms.

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::fast_matrix_multi().

#### 6.4.4.4 frame()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const index_set_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::frame ( ) const  [pure virtual]
```

Subalgebra generated by all generators of terms of given multivector.

#### 6.4.4.5 grade()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual index_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::grade ( )
const  [pure virtual]
```

Maximum of the grades of each term.

#### 6.4.4.6 inv()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const multivector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::inv ( ) const  [pure virtual]
```

Geometric multiplicative inverse.

#### 6.4.4.7 involute()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const multivector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::involute ( ) const  [pure virtual]
```

Main involution, each {i} is replaced by -{i} in each term, eg. {1} -> -{1}.

#### 6.4.4.8 isnan()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual bool glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::isnan ( ) const
[pure virtual]
```

Check if a multivector contains any IEEE NaN values.

#### 6.4.4.9 max_abs()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual Scalar_T glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::max_abs ( )
const  [pure virtual]
```

Maximum of absolute values of components of multivector: multivector infinity norm.

#### 6.4.4.10 norm()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual Scalar_T glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::norm ( )
const  [pure virtual]
```

Scalar_T norm == sum of norm of coordinates.

#### 6.4.4.11 odd()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const multivector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::odd ( ) const  [pure virtual]
```

Odd part of multivector, sum of odd grade terms.

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::fast_matrix_multi().

#### 6.4.4.12 operator &=()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual multivector_t& glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::operator&= (
            const multivector_t & rhs )  [pure virtual]
```

Inner product.

#### 6.4.4.13 operator%=()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual multivector_t& glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::operator%= (
            const multivector_t & rhs )  [pure virtual]
```

Contraction.

#### 6.4.4.14 operator()()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const multivector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::operator() (
            index_t grade ) const  [pure virtual]
```

Pure grade-vector part.

#### 6.4.4.15 operator*=() [1/2]

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual multivector_t& glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::operator*= (
            const Scalar_T & scr )  [pure virtual]
```

Product of multivector and scalar.

#### 6.4.4.16 operator*=() [2/2]

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual multivector_t& glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::operator*= (
            const multivector_t & rhs )  [pure virtual]
```

Geometric product.

#### 6.4.4.17 operator+=() [1/2]

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual multivector_t& glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::operator+= (
            const multivector_t & rhs )  [pure virtual]
```

Geometric sum.

#### 6.4.4.18 operator+=() [2/2]

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual multivector_t& glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::operator+= (
            const Scalar_T & scr )  [pure virtual]
```

Geometric sum of multivector and scalar.

#### 6.4.4.19 operator-()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const multivector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::operator- ( ) const  [pure virtual]
```

Unary -.

#### 6.4.4.20 operator-=()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual multivector_t& glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::operator-= (
            const multivector_t & rhs )  [pure virtual]
```

Geometric difference.

#### 6.4.4.21 operator/=() [1/2]

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual multivector_t& glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::operator/= (
            const Scalar_T & scr )  [pure virtual]
```

Quotient of multivector and scalar.

#### 6.4.4.22 operator/=() [2/2]

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual multivector_t& glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::operator/= (
            const multivector_t & rhs )  [pure virtual]
```

Geometric quotient.

#### 6.4.4.23 operator==() [1/2]

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual bool glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::operator== (
            const multivector_t & val ) const  [pure virtual]
```

Test for equality of multivectors.

#### 6.4.4.24 operator==() [2/2]

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual bool glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::operator== (
            const Scalar_T & scr ) const  [pure virtual]
```

Test for equality of multivector and scalar.

#### 6.4.4.25 operator[]()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual Scalar_T glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::operator[]
(
            const index_set_t ist ) const  [pure virtual]
```

Subscripting: map from index set to scalar coordinate.

#### 6.4.4.26 operator^=()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual multivector_t& glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::operator^= (
            const multivector_t & rhs )  [pure virtual]
```

Outer product.

#### 6.4.4.27 operator"|=()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual multivector_t& glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::operator|= (
            const multivector_t & rhs )  [pure virtual]
```

Transformation via twisted adjoint action.

#### 6.4.4.28 outer_pow()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const multivector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::outer_pow (
            int m ) const  [pure virtual]
```

Outer product power.

#### 6.4.4.29 pow()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const multivector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::pow (
            int m ) const  [pure virtual]
```

∗this to the m

#### 6.4.4.30 pure()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const multivector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::pure ( ) const  [pure virtual]
```

Pure part.

#### 6.4.4.31 quad()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual Scalar_T glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::quad ( )
const  [pure virtual]
```

Scalar_T quadratic form == (rev(x)∗x)(0)

#### 6.4.4.32 reverse()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const multivector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::reverse ( ) const  [pure virtual]
```

Reversion, eg. {1}∗{2} -> {2}∗{1}.

#### 6.4.4.33 scalar()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual Scalar_T glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::scalar ( )
const  [pure virtual]
```

Scalar part.

#### 6.4.4.34 truncated()

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const multivector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::truncated (
            const Scalar_T & limit = Scalar_T(DEFAULT_TRUNCATION) ) const  [pure virtual]
```

Remove all terms with relative size smaller than limit.

#### 6.4.4.35 vector_part() [1/2]

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const vector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::vector_part ( ) const  [pure virtual]
```

Vector part of multivector, as a vector_t with respect to frame()

#### 6.4.4.36 vector_part() [2/2]

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual const vector_t glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >↩
::vector_part (
            const index_set_t frm,
            const bool prechecked ) const  [pure virtual]
```

Vector part of multivector, as a vector_t with respect to frm.

#### 6.4.4.37 write() [1/2]

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual void glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::write (
            const std::string & msg = "" ) const  [pure virtual]
```

Write formatted multivector to output.

#### 6.4.4.38 write() [2/2]

```
template<typename Scalar_T, typename Index_Set_T, typename Multivector_T>
virtual void glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::write (
            std::ofstream & ofile,
            const std::string & msg = "" ) const  [pure virtual]
```

Write formatted multivector to file.

The documentation for this class was generated from the following files:

- glucat/clifford_algebra.h
- glucat/clifford_algebra_imp.h

## 6.5 glucat::compare_types< LHS_T, RHS_T > Class Template Reference

Type comparison.

`#include <global.h>`

### Public Types

- enum { are_same = false }

### 6.5.1 Detailed Description

**template<typename LHS_T, typename RHS_T>**
**class glucat::compare_types< LHS_T, RHS_T >**

Type comparison.

Definition at line 54 of file global.h.

### 6.5.2 Member Enumeration Documentation

#### 6.5.2.1 anonymous enum

```
template<typename LHS_T , typename RHS_T >
anonymous enum
```

**Enumerator**

| | |
|---|---|
| are_same | |

Definition at line 57 of file global.h.

The documentation for this class was generated from the following file:

- glucat/global.h

## 6.6 glucat::compare_types< T, T > Class Template Reference

`#include <global.h>`

### Public Types

- enum { are_same = true }

#### 6.6.1 Detailed Description

**template<typename T>**
**class glucat::compare_types< T, T >**

Definition at line 60 of file global.h.

#### 6.6.2 Member Enumeration Documentation

##### 6.6.2.1 anonymous enum

```
template<typename T >
anonymous enum
```

**Enumerator**

| | |
|---|---|
| are_same | |

Definition at line 63 of file global.h.

The documentation for this class was generated from the following file:

- glucat/global.h

## 6.7 glucat::control_t Class Reference

Parameters to control tests.

`#include <control.h>`

### Public Member Functions

- int call (intfn f) const

  *Call a function that returns int.*
- int call (intintfn f, int arg) const

  *Call a function of int that returns int.*

### Static Public Member Functions

- static const control_t & control (int argc, char **argv)
- static bool verbose ()

  *Produce more detailed output from tests.*

### Private Member Functions

- bool valid () const
- bool catch_exceptions () const
- control_t (int argc, char **argv)

  *Constructor from program arguments.*
- control_t ()
- ~control_t ()
- control_t (const control_t &)
- control_t & operator= (const control_t &)

### Private Attributes

- bool m_valid

  *Test parameters are valid.*
- bool m_catch_exceptions

  *Catch exceptions.*

### Static Private Attributes

- static bool m_verbose_output = false

  *Produce more detailed output from tests.*

### Friends

- class friend_for_private_destructor

### 6.7.1 Detailed Description

Parameters to control tests.

Definition at line 39 of file control.h.

### 6.7.2 Constructor & Destructor Documentation

#### 6.7.2.1 control_t() [1/3]

```
glucat::control_t::control_t (
            int argc,
            char ** argv )  [private]
```

Constructor from program arguments.

Test control constructor from program arguments.

Definition at line 89 of file control.h.

References GLUCAT_PACKAGE_NAME, GLUCAT_VERSION, m_catch_exceptions, m_valid, m_verbose_output, and valid().

#### 6.7.2.2 control_t() [2/3]

```
glucat::control_t::control_t ( )  [inline], [private]
```

Definition at line 59 of file control.h.

#### 6.7.2.3 ~control_t()

```
glucat::control_t::~control_t ( )  [inline], [private]
```

Definition at line 60 of file control.h.

#### 6.7.2.4 control_t() [3/3]

```
glucat::control_t::control_t (
            const control_t &  )  [private]
```

### 6.7.3 Member Function Documentation

#### 6.7.3.1 call() [1/2]

```
int glucat::control_t::call (
            intfn f ) const  [inline]
```

Call a function that returns int.

Definition at line 137 of file control.h.

References catch_exceptions(), glucat::try_catch(), and valid().

#### 6.7.3.2 call() [2/2]

```
int glucat::control_t::call (
            intintfn f,
            int arg ) const  [inline]
```

Call a function of int that returns int.

Definition at line 151 of file control.h.

References catch_exceptions(), glucat::try_catch(), and valid().

#### 6.7.3.3 catch_exceptions()

```
bool glucat::control_t::catch_exceptions ( ) const  [inline], [private]
```

Definition at line 49 of file control.h.

References m_catch_exceptions.

Referenced by call().

#### 6.7.3.4 control()

```
static const control_t& glucat::control_t::control (
            int argc,
            char ** argv )  [inline], [static]
```

Single instance Ref: Scott Meyers, "Effective C++" Second Edition, Addison-Wesley, 1998.

Definition at line 71 of file control.h.

#### 6.7.3.5 operator=()

```
control_t& glucat::control_t::operator= (
            const control_t &  )  [private]
```

#### 6.7.3.6 valid()

```
bool glucat::control_t::valid ( ) const  [inline], [private]
```

Definition at line 44 of file control.h.

References m_valid.

Referenced by call(), and control_t().

#### 6.7.3.7 verbose()

```
static bool glucat::control_t::verbose ( )  [inline], [static]
```

Produce more detailed output from tests.

Definition at line 80 of file control.h.

References m_verbose_output.

### 6.7.4 Friends And Related Function Documentation

#### 6.7.4.1 friend_for_private_destructor

```
friend class friend_for_private_destructor  [friend]
```

Friend declaration to avoid compiler warning: "... only defines a private destructor and has no friends" Ref: Carlos O'Ryan, ACE http://doc.ece.uci.edu

Definition at line 67 of file control.h.

### 6.7.5 Member Data Documentation

#### 6.7.5.1 m_catch_exceptions

```
bool glucat::control_t::m_catch_exceptions  [private]
```

Catch exceptions.

Definition at line 48 of file control.h.

Referenced by catch_exceptions(), and control_t().

#### 6.7.5.2 m_valid

```
bool glucat::control_t::m_valid  [private]
```

Test parameters are valid.

Definition at line 43 of file control.h.

Referenced by control_t(), and valid().

#### 6.7.5.3 m_verbose_output

```
bool glucat::control_t::m_verbose_output = false  [static], [private]
```

Produce more detailed output from tests.

Definition at line 53 of file control.h.

Referenced by control_t(), and verbose().

The documentation for this class was generated from the following file:

- test/control.h

## 6.8 glucat::CTAssertion< bool > Struct Template Reference

Compile time assertion.

```
#include <global.h>
```

### 6.8.1 Detailed Description

**template<bool>**
**struct glucat::CTAssertion< bool >**

Compile time assertion.

Definition at line 46 of file global.h.

The documentation for this struct was generated from the following file:

- glucat/global.h

## 6.9 glucat::CTAssertion< true > Struct Template Reference

`#include <global.h>`

### 6.9.1 Detailed Description

**template<>**
**struct glucat::CTAssertion< true >**

Definition at line 47 of file global.h.

The documentation for this struct was generated from the following file:

- glucat/global.h

## 6.10 glucat::numeric_traits< Scalar_T >::demoted<> Struct Template Reference

Demoted type for long double.

`#include <long_double.h>`

### Public Types

- typedef long double type
- typedef float type

### 6.10.1 Detailed Description

**template<typename Scalar_T>**
**template<>**
**struct glucat::numeric_traits< Scalar_T >::demoted<>**

Demoted type for long double.

Demoted type.

Definition at line 47 of file long_double.h.

### 6.10.2 Member Typedef Documentation

#### 6.10.2.1 type [1/2]

```
template<typename Scalar_T >
typedef long double glucat::numeric_traits< Scalar_T >::demoted<>::type
```

Definition at line 49 of file long_double.h.

#### 6.10.2.2 type [2/2]

```
template<typename Scalar_T >
typedef float glucat::numeric_traits< Scalar_T >::demoted<>::type
```

Definition at line 147 of file scalar.h.

The documentation for this struct was generated from the following files:

- glucat/long_double.h
- glucat/scalar.h

## 6.11 glucat::matrix::eig_genus< Matrix_T > Struct Template Reference

Structure containing classification of eigenvalues.

```
#include <matrix.h>
```

### Public Types

- typedef Matrix_T::value_type Scalar_T

### Public Attributes

- eig_case_t m_eig_case

  *What kind of eigenvalues does the matrix contain?*
- Scalar_T m_safe_arg

  *Argument such that exp(pi-m_safe_arg) lies between arguments of eigenvalues.*

### 6.11.1 Detailed Description

**template<typename Matrix_T>**
**struct glucat::matrix::eig_genus< Matrix_T >**

Structure containing classification of eigenvalues.

Definition at line 131 of file matrix.h.

### 6.11.2 Member Typedef Documentation

#### 6.11.2.1 Scalar_T

```
template<typename Matrix_T>
typedef Matrix_T::value_type glucat::matrix::eig_genus< Matrix_T >::Scalar_T
```

Definition at line 133 of file matrix.h.

### 6.11.3 Member Data Documentation

#### 6.11.3.1 m_eig_case

```
template<typename Matrix_T>
eig_case_t glucat::matrix::eig_genus< Matrix_T >::m_eig_case
```

What kind of eigenvalues does the matrix contain?

Definition at line 135 of file matrix.h.

Referenced by glucat::matrix::classify_eigenvalues(), glucat::matrix_log(), and glucat::matrix_sqrt().

#### 6.11.3.2 m_safe_arg

```
template<typename Matrix_T>
Scalar_T glucat::matrix::eig_genus< Matrix_T >::m_safe_arg
```

Argument such that exp(pi-m_safe_arg) lies between arguments of eigenvalues.

Definition at line 137 of file matrix.h.

Referenced by glucat::matrix::classify_eigenvalues(), glucat::matrix_log(), and glucat::matrix_sqrt().

The documentation for this struct was generated from the following file:

- glucat/matrix.h

## 6.12 glucat::error< Class_T > Class Template Reference

Specific exception class.

`#include <errors.h>`

Inheritance diagram for glucat::error< Class_T >:




Collaboration diagram for glucat::error< Class_T >:




### Public Member Functions

- error (const std::string &msg)
  *Specific exception class.*
- error (const std::string &context, const std::string &msg)
- virtual const std::string heading () const throw ()
- virtual const std::string classname () const throw ()
- virtual void print_error_msg () const

## Additional Inherited Members

### 6.12.1 Detailed Description

**template<class Class_T>**
**class glucat::error< Class_T >**

Specific exception class.

Definition at line 57 of file errors.h.

### 6.12.2 Constructor & Destructor Documentation

#### 6.12.2.1 error() [1/2]

```
template<class Class_T >
glucat::error< Class_T >::error (
            const std::string & msg )
```

Specific exception class.

Definition at line 39 of file errors_imp.h.

#### 6.12.2.2 error() [2/2]

```
template<class Class_T >
glucat::error< Class_T >::error (
            const std::string & context,
            const std::string & msg )
```

Definition at line 45 of file errors_imp.h.

### 6.12.3 Member Function Documentation

#### 6.12.3.1 classname()

```
template<class Class_T >
const std::string glucat::error< Class_T >::classname ( ) const throw )   [virtual]
```

Implements glucat::glucat_error.

Definition at line 58 of file errors_imp.h.

#### 6.12.3.2 heading()

```
template<class Class_T >
const std::string glucat::error< Class_T >::heading ( ) const throw )   [virtual]
```

Implements glucat::glucat_error.

Definition at line 52 of file errors_imp.h.

#### 6.12.3.3 print_error_msg()

```
template<class Class_T >
void glucat::error< Class_T >::print_error_msg ( ) const  [virtual]
```

Implements glucat::glucat_error.

Definition at line 64 of file errors_imp.h.

The documentation for this class was generated from the following files:

- glucat/errors.h
- glucat/errors_imp.h

## 6.13 glucat::framed_multi< Scalar_T, LO, HI > Class Template Reference

A framed_multi<Scalar_T,LO,HI> is a framed approximation to a multivector.

```
#include <framed_multi.h>
```

Inheritance diagram for glucat::framed_multi< Scalar_T, LO, HI >:



Collaboration diagram for glucat::framed_multi< Scalar_T, LO, HI >:




## Classes

- class hash_size_t
- class var_term

  *Variable term.*

## Public Types

- typedef framed_multi multivector_t
- typedef multivector_t framed_multi_t
- typedef Scalar_T scalar_t
- typedef index_set< LO, HI > index_set_t
- typedef std::pair< const index_set_t, Scalar_T > term_t
- typedef std::vector< Scalar_T > vector_t
- typedef error< multivector_t > error_t
- typedef matrix_multi< Scalar_T, LO, HI > matrix_multi_t

## Public Member Functions

- ~framed_multi ()

  *Destructor.*
- framed_multi ()

  *Default constructor.*
- template<typename Other_Scalar_T >
  framed_multi (const framed_multi< Other_Scalar_T, LO, HI > &val)

  *Construct a multivector from a multivector with a different scalar type.*
- template<typename Other_Scalar_T >
  framed_multi (const framed_multi< Other_Scalar_T, LO, HI > &val, const index_set_t frm, const bool prechecked=false)

  *Construct a multivector, within a given frame, from a given multivector.*
- framed_multi (const framed_multi_t &val, const index_set_t frm, const bool prechecked=false)

*Construct a multivector, within a given frame, from a given multivector.*

- framed_multi (const index_set_t ist, const Scalar_T &crd=Scalar_T(1))

  *Construct a multivector from an index set and a scalar coordinate.*
- framed_multi (const index_set_t ist, const Scalar_T &crd, const index_set_t frm, const bool prechecked=false)

  *Construct a multivector, within a given frame, from an index set and a scalar coordinate.*
- framed_multi (const Scalar_T &scr, const index_set_t frm=index_set_t())

  *Construct a multivector from a scalar (within a frame, if given)*
- framed_multi (const int scr, const index_set_t frm=index_set_t())

  *Construct a multivector from an int (within a frame, if given)*
- framed_multi (const vector_t &vec, const index_set_t frm, const bool prechecked=false)

  *Construct a multivector, within a given frame, from a given vector.*
- framed_multi (const std::string &str)

  *Construct a multivector from a string: eg: "3+2{1,2}-6.1e-2{2,3}".*
- framed_multi (const std::string &str, const index_set_t frm, const bool prechecked=false)

  *Construct a multivector, within a given frame, from a string: eg: "3+2{1,2}-6.1e-2{2,3}".*
- framed_multi (const char ∗str)

  *Construct a multivector from a char∗: eg: "3+2{1,2}-6.1e-2{2,3}".*
- framed_multi (const char ∗str, const index_set_t frm, const bool prechecked=false)

  *Construct a multivector, within a given frame, from a char∗: eg: "3+2{1,2}-6.1e-2{2,3}".*
- template<typename Other_Scalar_T >
  framed_multi (const matrix_multi< Other_Scalar_T, LO, HI > &val)

  *Construct a multivector from a matrix_multi_t.*
- template<typename Other_Scalar_T >
  const matrix_multi< Other_Scalar_T, LO, HI > fast_matrix_multi (const index_set_t frm) const

  *Use generalized FFT to construct a matrix_multi_t.*
- const framed_multi_t fast_framed_multi () const

  *Use inverse generalized FFT to construct a framed_multi_t.*
- _GLUCAT_CLIFFORD_ALGEBRA_OPERATIONS unsigned long nbr_terms () const

  *Number of terms.*
- multivector_t & operator+= (const term_t &term)

  *Add a term, if non-zero.*

## Static Public Member Functions

- static const std::string classname ()

  *Class name used in messages.*
- static const framed_multi_t random (const index_set_t frm, Scalar_T fill=Scalar_T(1))

  *Random multivector within a frame.*

## Private Types

- typedef class var_term var_term_t
- typedef matrix_multi_t::matrix_t matrix_t
- typedef std::map< index_set_t, Scalar_T, std::less< const index_set_t > > sorted_map_t
- typedef std::unordered_map< index_set_t, Scalar_T, index_set_hash< LO, HI > > map_t
- typedef std::pair< const multivector_t, const multivector_t > framed_pair_t
- typedef map_t::size_type size_type
- typedef map_t::iterator iterator
- typedef map_t::const_iterator const_iterator

### Private Member Functions

- framed_multi (const hash_size_t &hash_size)

  *Private constructor using hash_size.*
- multivector_t fold (const index_set_t frm) const

  *Subalgebra isomorphism: fold each term within the given frame.*
- multivector_t unfold (const index_set_t frm) const

  *Subalgebra isomorphism: unfold each term within the given frame.*
- multivector_t & centre_pm4_qp4 (index_t &p, index_t &q)

  *Subalgebra isomorphism: R_{p,q} to R_{p-4,q+4}.*
- multivector_t & centre_pp4_qm4 (index_t &p, index_t &q)

  *Subalgebra isomorphism: R_{p,q} to R_{p+4,q-4}.*
- multivector_t & centre_qp1_pm1 (index_t &p, index_t &q)

  *Subalgebra isomorphism: R_{p,q} to R_{q+1,p-1}.*
- const framed_pair_t divide (const index_set_t ist) const

  *Divide multivector into part divisible by index_set and remainder.*
- const matrix_t fast (const index_t level, const bool odd) const

  *Generalized FFT from framed_multi_t to matrix_t.*

### Friends

- template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
  class matrix_multi
- template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
  class framed_multi
- const framed_multi_t operator* (const framed_multi_t &lhs, const framed_multi_t &rhs)
- const framed_multi_t operator^ (const framed_multi_t &lhs, const framed_multi_t &rhs)
- const framed_multi_t operator & (const framed_multi_t &lhs, const framed_multi_t &rhs)
- const framed_multi_t operator% (const framed_multi_t &lhs, const framed_multi_t &rhs)
- Scalar_T star (const framed_multi_t &lhs, const framed_multi_t &rhs)
- const framed_multi_t operator/ (const framed_multi_t &lhs, const framed_multi_t &rhs)
- const framed_multi_t operator| (const framed_multi_t &lhs, const framed_multi_t &rhs)
- std::istream & operator>> (std::istream &s, multivector_t &val)
- std::ostream & operator<< (std::ostream &os, const multivector_t &val)
- std::ostream & operator<< (std::ostream &os, const term_t &term)
- const framed_multi_t exp (const framed_multi_t &val)

### 6.13.1 Detailed Description

**template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAULT_HI>**
**class glucat::framed_multi< Scalar_T, LO, HI >**

A framed_multi<Scalar_T,LO,HI> is a framed approximation to a multivector.

Definition at line 65 of file framed_multi.h.

### 6.13.2 Member Typedef Documentation

#### 6.13.2.1 const_iterator

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef map_t::const_iterator glucat::framed_multi< Scalar_T, LO, HI >::const_iterator  [private]
```

Definition at line 196 of file framed_multi.h.

#### 6.13.2.2 error_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef error<multivector_t> glucat::framed_multi< Scalar_T, LO, HI >::error_t
```

Definition at line 155 of file framed_multi.h.

#### 6.13.2.3 framed_multi_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef multivector_t glucat::framed_multi< Scalar_T, LO, HI >::framed_multi_t
```

Definition at line 150 of file framed_multi.h.

#### 6.13.2.4 framed_pair_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef std::pair< const multivector_t, const multivector_t > glucat::framed_multi< Scalar_T,
LO, HI >::framed_pair_t  [private]
```

Definition at line 193 of file framed_multi.h.

#### 6.13.2.5 index_set_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef index_set<LO,HI> glucat::framed_multi< Scalar_T, LO, HI >::index_set_t
```

Definition at line 152 of file framed_multi.h.

#### 6.13.2.6 iterator

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef map_t::iterator glucat::framed_multi< Scalar_T, LO, HI >::iterator  [private]
```

Definition at line 195 of file framed_multi.h.

#### 6.13.2.7 map_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef std::unordered_map< index_set_t, Scalar_T, index_set_hash<LO,HI> > glucat::framed_multi<
Scalar_T, LO, HI >::map_t  [private]
```

Definition at line 175 of file framed_multi.h.

#### 6.13.2.8 matrix_multi_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef matrix_multi<Scalar_T,LO,HI> glucat::framed_multi< Scalar_T, LO, HI >::matrix_multi_t
```

Definition at line 156 of file framed_multi.h.

#### 6.13.2.9 matrix_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef matrix_multi_t::matrix_t glucat::framed_multi< Scalar_T, LO, HI >::matrix_t  [private]
```

Definition at line 165 of file framed_multi.h.

#### 6.13.2.10 multivector_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef framed_multi glucat::framed_multi< Scalar_T, LO, HI >::multivector_t
```

Definition at line 149 of file framed_multi.h.

#### 6.13.2.11 scalar_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef Scalar_T glucat::framed_multi< Scalar_T, LO, HI >::scalar_t
```

Definition at line 151 of file framed_multi.h.

#### 6.13.2.12 size_type

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef map_t::size_type glucat::framed_multi< Scalar_T, LO, HI >::size_type  [private]
```

Definition at line 194 of file framed_multi.h.

#### 6.13.2.13 sorted_map_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef std::map< index_set_t, Scalar_T, std::less<const index_set_t> > glucat::framed_multi<
Scalar_T, LO, HI >::sorted_map_t  [private]
```

Definition at line 172 of file framed_multi.h.

#### 6.13.2.14 term_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef std::pair<const index_set_t, Scalar_T> glucat::framed_multi< Scalar_T, LO, HI >↩
::term_t
```

Definition at line 153 of file framed_multi.h.

#### 6.13.2.15 var_term_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef class var_term glucat::framed_multi< Scalar_T, LO, HI >::var_term_t  [private]
```

Definition at line 164 of file framed_multi.h.

#### 6.13.2.16 vector_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef std::vector<Scalar_T> glucat::framed_multi< Scalar_T, LO, HI >::vector_t
```

Definition at line 154 of file framed_multi.h.

### 6.13.3 Constructor & Destructor Documentation

#### 6.13.3.1 ~framed_multi()

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
glucat::framed_multi< Scalar_T, LO, HI >::~framed_multi ( )  [inline]
```

Destructor.

Definition at line 202 of file framed_multi.h.

#### 6.13.3.2 framed_multi() [1/15]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi ( )
```

Default constructor.

Definition at line 67 of file framed_multi_imp.h.

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::framed_multi().

#### 6.13.3.3 framed_multi() [2/15]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const hash_size_t & hash_size )  [private]
```

Private constructor using hash_size.

Definition at line 74 of file framed_multi_imp.h.

#### 6.13.3.4 framed_multi() [3/15]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
template<typename Other_Scalar_T >
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const framed_multi< Other_Scalar_T, LO, HI > & val )
```

Construct a multivector from a multivector with a different scalar type.

Definition at line 82 of file framed_multi_imp.h.

#### 6.13.3.5 framed_multi() [4/15]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
template<typename Other_Scalar_T >
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const framed_multi< Other_Scalar_T, LO, HI > & val,
            const index_set_t frm,
            const bool prechecked = false )
```

Construct a multivector, within a given frame, from a given multivector.

Definition at line 97 of file framed_multi_imp.h.

#### 6.13.3.6 framed_multi() [5/15]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const framed_multi_t & val,
            const index_set_t frm,
            const bool prechecked = false )
```

Construct a multivector, within a given frame, from a given multivector.

Definition at line 112 of file framed_multi_imp.h.

#### 6.13.3.7 framed_multi() [6/15]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const index_set_t ist,
            const Scalar_T & crd = Scalar_T(1) )
```

Construct a multivector from an index set and a scalar coordinate.

Definition at line 120 of file framed_multi_imp.h.

References PyClical::ist.

#### 6.13.3.8 framed_multi() [7/15]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const index_set_t ist,
            const Scalar_T & crd,
            const index_set_t frm,
            const bool prechecked = false )
```

Construct a multivector, within a given frame, from an index set and a scalar coordinate.

Definition at line 130 of file framed_multi_imp.h.

References PyClical::ist.

#### 6.13.3.9 framed_multi() [8/15]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const Scalar_T & scr,
            const index_set_t frm = index_set_t() )
```

Construct a multivector from a scalar (within a frame, if given)

Definition at line 143 of file framed_multi_imp.h.

#### 6.13.3.10 framed_multi() [9/15]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const int scr,
            const index_set_t frm = index_set_t() )
```

Construct a multivector from an int (within a frame, if given)

Definition at line 153 of file framed_multi_imp.h.

#### 6.13.3.11 framed_multi() [10/15]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const vector_t & vec,
            const index_set_t frm,
            const bool prechecked = false )
```

Construct a multivector, within a given frame, from a given vector.

Definition at line 163 of file framed_multi_imp.h.

References glucat::index_set< LO, HI >::count(), glucat::index_set< LO, HI >::max(), and glucat::index_set< LO, HI >::min().

#### 6.13.3.12 framed_multi() [11/15]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const std::string & str )
```

Construct a multivector from a string: eg: "3+2{1,2}-6.1e-2{2,3}".

Definition at line 186 of file framed_multi_imp.h.

#### 6.13.3.13 framed_multi() [12/15]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const std::string & str,
            const index_set_t frm,
            const bool prechecked = false )
```

Construct a multivector, within a given frame, from a string: eg: "3+2{1,2}-6.1e-2{2,3}".

Definition at line 202 of file framed_multi_imp.h.

#### 6.13.3.14 framed_multi() [13/15]

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const char * str )  [inline]
```

Construct a multivector from a char*: eg: "3+2{1,2}-6.1e-2{2,3}".

Definition at line 238 of file framed_multi.h.

References glucat::framed_multi< Scalar_T, LO, HI >::framed_multi().

#### 6.13.3.15 framed_multi() [14/15]

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const char * str,
            const index_set_t frm,
            const bool prechecked = false )  [inline]
```

Construct a multivector, within a given frame, from a char*: eg: "3+2{1,2}-6.1e-2{2,3}".

Definition at line 241 of file framed_multi.h.

References glucat::framed_multi< Scalar_T, LO, HI >::framed_multi().

#### 6.13.3.16 framed_multi() [15/15]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
template<typename Other_Scalar_T >
glucat::framed_multi< Scalar_T, LO, HI >::framed_multi (
            const matrix_multi< Other_Scalar_T, LO, HI > & val )
```

Construct a multivector from a matrix_multi_t.

Definition at line 215 of file framed_multi_imp.h.

References _GLUCAT_HASH_SIZE_T, glucat::abs(), glucat::matrix_multi< Scalar_T, LO, HI >::basis_element(), glucat::index_set< LO, HI >::count(), PyClical::e(), glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::frame(), glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_↩ Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast↩ _Dim_Threshold, Products_Size_Threshold, Function_Precision >::inv_fast_dim_threshold, PyClical::ist, glucat↩ ::matrix_multi< Scalar_T, LO, HI >::m_matrix, glucat::matrix::nnz(), and glucat::clifford_algebra< Scalar_T, index↩ _set< LO, HI >, matrix_multi< Scalar_T, LO, HI > >::norm().

### 6.13.4 Member Function Documentation

#### 6.13.4.1 centre_pm4_qp4()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
framed_multi< Scalar_T, LO, HI > & glucat::framed_multi< Scalar_T, LO, HI >::centre_pm4_qp4 (
            index_t & p,
            index_t & q )  [private]
```

Subalgebra isomorphism: R_{p,q} to R_{p-4,q+4}.

Definition at line 1655 of file framed_multi_imp.h.

References PyClical::ist.

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >::fast_framed_multi(), and glucat::framed_multi< Scalar_T, LO, HI >::fast_matrix_multi().

#### 6.13.4.2 centre_pp4_qm4()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
framed_multi< Scalar_T, LO, HI > & glucat::framed_multi< Scalar_T, LO, HI >::centre_pp4_qm4 (
            index_t & p,
            index_t & q )  [private]
```

Subalgebra isomorphism: R_{p,q} to R_{p+4,q-4}.

Definition at line 1700 of file framed_multi_imp.h.

References PyClical::ist.

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >::fast_framed_multi(), and glucat::framed_multi< Scalar_T, LO, HI >::fast_matrix_multi().

#### 6.13.4.3 centre_qp1_pm1()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
framed_multi< Scalar_T, LO, HI > & glucat::framed_multi< Scalar_T, LO, HI >::centre_qp1_pm1 (
            index_t & p,
            index_t & q )  [private]
```

Subalgebra isomorphism: R_{p,q} to R_{q+1,p-1}.

Definition at line 1745 of file framed_multi_imp.h.

References PyClical::ist.

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >::fast_framed_multi(), and glucat::framed_multi< Scalar_T, LO, HI >::fast_matrix_multi().

#### 6.13.4.4 classname()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const std::string glucat::framed_multi< Scalar_T, LO, HI >::classname ( )  [static]
```

Class name used in messages.

Definition at line 53 of file framed_multi_imp.h.

#### 6.13.4.5 divide()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const std::pair< const framed_multi< Scalar_T, LO, HI >, const framed_multi< Scalar_T, LO, HI
> > glucat::framed_multi< Scalar_T, LO, HI >::divide (
            const index_set_t ist ) const  [private]
```

Divide multivector into part divisible by index_set and remainder.

Divide multivector into quotient with terms divisible by index set, and remainder.

Definition at line 1781 of file framed_multi_imp.h.

References PyClical::ist.

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::fast().

#### 6.13.4.6 fast()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const framed_multi< Scalar_T, LO, HI >::matrix_t glucat::framed_multi< Scalar_T, LO, HI >↩
::fast (
            const index_t level,
            const bool odd ) const  [private]
```

Generalized FFT from framed_multi_t to matrix_t.

Definition at line 1800 of file framed_multi_imp.h.

References glucat::framed_multi< Scalar_T, LO, HI >::divide(), glucat::framed_multi< Scalar_T, LO, HI >::fast(), glucat::matrix::kron(), glucat::odd(), and glucat::scalar().

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::fast(), and glucat::framed_multi< Scalar_T, LO, HI >↩
::fast_matrix_multi().

#### 6.13.4.7 fast_framed_multi()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const framed_multi< Scalar_T, LO, HI > glucat::framed_multi< Scalar_T, LO, HI >::fast_↩
framed_multi ( ) const  [inline]
```

Use inverse generalized FFT to construct a framed_multi_t.

Definition at line 1898 of file framed_multi_imp.h.

#### 6.13.4.8 fast_matrix_multi()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
template<typename Other_Scalar_T >
const matrix_multi< Other_Scalar_T, LO, HI > glucat::framed_multi< Scalar_T, LO, HI >::fast↩
_matrix_multi (
            const index_set_t frm ) const
```

Use generalized FFT to construct a matrix_multi_t.

Definition at line 1866 of file framed_multi_imp.h.

References glucat::framed_multi< Scalar_T, LO, HI >::centre_pm4_qp4(), glucat::framed_multi< Scalar_T, LO, HI >::centre_pp4_qm4(), glucat::framed_multi< Scalar_T, LO, HI >::centre_qp1_pm1(), glucat::index_set< L↩
O, HI >::count_neg(), glucat::index_set< LO, HI >::count_pos(), glucat::clifford_algebra< Scalar_T, Index_Set↩
_T, Multivector_T >::even(), glucat::framed_multi< Scalar_T, LO, HI >::fast(), glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >::odd(), glucat::gen::offset_to_super, and glucat::pos_mod().

#### 6.13.4.9 fold()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
framed_multi< Scalar_T, LO, HI > glucat::framed_multi< Scalar_T, LO, HI >::fold (
            const index_set_t frm ) const  [private]
```

Subalgebra isomorphism: fold each term within the given frame.

Definition at line 1614 of file framed_multi_imp.h.

References glucat::index_set< LO, HI >::is_contiguous().

#### 6.13.4.10 nbr_terms()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
unsigned long glucat::framed_multi< Scalar_T, LO, HI >::nbr_terms ( ) const
```

Number of terms.

Definition at line 1545 of file framed_multi_imp.h.

#### 6.13.4.11 operator+=()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
framed_multi< Scalar_T, LO, HI > & glucat::framed_multi< Scalar_T, LO, HI >::operator+= (
            const term_t & term )  [inline]
```

Add a term, if non-zero.

Insert a term into a multivector, add terms with same index set.

Geometric sum.

Geometric sum of multivector and scalar.

Definition at line 329 of file framed_multi_imp.h.

#### 6.13.4.12 random()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const framed_multi< Scalar_T, LO, HI > glucat::framed_multi< Scalar_T, LO, HI >::random (
            const index_set_t frm,
            Scalar_T fill = Scalar_T(1) )  [static]
```

Random multivector within a frame.

Definition at line 1273 of file framed_multi_imp.h.

References glucat::index_set< LO, HI >::count(), PyClical::fill, and glucat::sqrt().

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >::random().

#### 6.13.4.13 unfold()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
framed_multi< Scalar_T, LO, HI > glucat::framed_multi< Scalar_T, LO, HI >::unfold (
            const index_set_t frm ) const  [private]
```

Subalgebra isomorphism: unfold each term within the given frame.

Definition at line 1634 of file framed_multi_imp.h.

References glucat::index_set< LO, HI >::is_contiguous().

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >::fast_framed_multi().

### 6.13.5 Friends And Related Function Documentation

#### 6.13.5.1 exp

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
const framed_multi_t exp (
            const framed_multi_t & val )  [friend]
```

#### 6.13.5.2 framed_multi

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
friend class framed_multi  [friend]
```

Definition at line 160 of file framed_multi.h.

#### 6.13.5.3 matrix_multi

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
friend class matrix_multi  [friend]
```

Definition at line 158 of file framed_multi.h.

#### 6.13.5.4 operator &

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
const framed_multi_t operator& (
            const framed_multi_t & lhs,
            const framed_multi_t & rhs )  [friend]
```

#### 6.13.5.5 operator%

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
const framed_multi_t operator% (
            const framed_multi_t & lhs,
            const framed_multi_t & rhs )  [friend]
```

#### 6.13.5.6 operator∗

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
const framed_multi_t operator* (
            const framed_multi_t & lhs,
            const framed_multi_t & rhs )  [friend]
```

#### 6.13.5.7 operator/

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
const framed_multi_t operator/ (
            const framed_multi_t & lhs,
            const framed_multi_t & rhs )  [friend]
```

#### 6.13.5.8 operator<< [1/2]

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
std::ostream& operator<< (
            std::ostream & os,
            const multivector_t & val )  [friend]
```

#### 6.13.5.9 operator<< [2/2]

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
std::ostream& operator<< (
            std::ostream & os,
            const term_t & term )  [friend]
```

#### 6.13.5.10 operator>>

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
std::istream& operator>> (
            std::istream & s,
            multivector_t & val )  [friend]
```

#### 6.13.5.11 operator^

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
const framed_multi_t operator^ (
            const framed_multi_t & lhs,
            const framed_multi_t & rhs )  [friend]
```

#### 6.13.5.12 operator"|

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
const framed_multi_t operator| (
            const framed_multi_t & lhs,
            const framed_multi_t & rhs )  [friend]
```

#### 6.13.5.13 star

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
Scalar_T star (
            const framed_multi_t & lhs,
            const framed_multi_t & rhs )  [friend]
```

The documentation for this class was generated from the following files:

- glucat/framed_multi.h
- glucat/framed_multi_imp.h

## 6.14 glucat::gen::generator_table< Matrix_T > Class Template Reference

Table of generators for specific signatures.

`#include <generation.h>`

Inheritance diagram for glucat::gen::generator_table< Matrix_T >:




Collaboration diagram for glucat::gen::generator_table< Matrix_T >:




### Public Member Functions

- const Matrix_T * operator() (const index_t p, const index_t q)

  *Pointer to generators for a specific signature.*

### Static Public Member Functions

- static generator_table< Matrix_T > & generator ()

  *Single instance of generator table.*

### Private Member Functions

- const std::vector< Matrix_T > & gen_vector (const index_t p, const index_t q)

  *Construct a vector of generators for a specific signature.*
- void gen_from_pm1_qm1 (const std::vector< Matrix_T > &old, const signature_t sig)

  *Construct generators for p,q given generators for p-1,q-1.*
- void gen_from_pm4_qp4 (const std::vector< Matrix_T > &old, const signature_t sig)

  *Construct generators for p,q given generators for p-4,q+4.*
- void gen_from_pp4_qm4 (const std::vector< Matrix_T > &old, const signature_t sig)

  *Construct generators for p,q given generators for p+4,q-4.*
- void gen_from_qp1_pm1 (const std::vector< Matrix_T > &old, const signature_t sig)

  *Construct generators for p,q given generators for q+1,p-1.*
- generator_table ()
- ~generator_table ()
- generator_table (const generator_table &)
- generator_table & operator= (const generator_table &)

### Friends

- class friend_for_private_destructor

## 6.14.1 Detailed Description

**template<class Matrix_T>**
**class glucat::gen::generator_table< Matrix_T >**

Table of generators for specific signatures.

Definition at line 47 of file generation.h.

## 6.14.2 Constructor & Destructor Documentation

### 6.14.2.1 generator_table() [1/2]

```
template<class Matrix_T>
glucat::gen::generator_table< Matrix_T >::generator_table ( )  [inline], [private]
```

Definition at line 69 of file generation.h.

### 6.14.2.2 ~generator_table()

```
template<class Matrix_T>
glucat::gen::generator_table< Matrix_T >::~generator_table ( )  [inline], [private]
```

Definition at line 70 of file generation.h.

#### 6.14.2.3 generator_table() [2/2]

```
template<class Matrix_T>
glucat::gen::generator_table< Matrix_T >::generator_table (
            const generator_table< Matrix_T > &  )  [private]
```

### 6.14.3 Member Function Documentation

#### 6.14.3.1 gen_from_pm1_qm1()

```
template<class Matrix_T >
void glucat::gen::generator_table< Matrix_T >::gen_from_pm1_qm1 (
            const std::vector< Matrix_T > & old,
            const signature_t sig )  [private]
```

Construct generators for p,q given generators for p-1,q-1.

Definition at line 127 of file generation_imp.h.

References glucat::matrix::mono_kron().

#### 6.14.3.2 gen_from_pm4_qp4()

```
template<class Matrix_T >
void glucat::gen::generator_table< Matrix_T >::gen_from_pm4_qp4 (
            const std::vector< Matrix_T > & old,
            const signature_t sig )  [private]
```

Construct generators for p,q given generators for p-4,q+4.

Definition at line 164 of file generation_imp.h.

References glucat::matrix::mono_prod().

#### 6.14.3.3 gen_from_pp4_qm4()

```
template<class Matrix_T >
void glucat::gen::generator_table< Matrix_T >::gen_from_pp4_qm4 (
            const std::vector< Matrix_T > & old,
            const signature_t sig )  [private]
```

Construct generators for p,q given generators for p+4,q-4.

Definition at line 195 of file generation_imp.h.

References glucat::matrix::mono_prod().

#### 6.14.3.4 gen_from_qp1_pm1()

```
template<class Matrix_T >
void glucat::gen::generator_table< Matrix_T >::gen_from_qp1_pm1 (
            const std::vector< Matrix_T > & old,
            const signature_t sig )  [private]
```

Construct generators for p,q given generators for q+1,p-1.

Definition at line 225 of file generation_imp.h.

References glucat::matrix::mono_prod().

#### 6.14.3.5 gen_vector()

```
template<class Matrix_T >
const std::vector< Matrix_T > & glucat::gen::generator_table< Matrix_T >::gen_vector (
            const index_t p,
            const index_t q )  [private]
```

Construct a vector of generators for a specific signature.

Definition at line 80 of file generation_imp.h.

References glucat::pos_mod().

#### 6.14.3.6 generator()

```
template<class Matrix_T >
generator_table< Matrix_T > & glucat::gen::generator_table< Matrix_T >::generator ( )  [static]
```

Single instance of generator table.

Definition at line 50 of file generation_imp.h.

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >::basis_element().

#### 6.14.3.7 operator()()

```
template<class Matrix_T >
const Matrix_T * glucat::gen::generator_table< Matrix_T >::operator() (
            const index_t p,
            const index_t q )  [inline]
```

Pointer to generators for a specific signature.

Definition at line 59 of file generation_imp.h.

References glucat::gen::offset_to_super, and glucat::pos_mod().

#### 6.14.3.8 operator=()

```
template<class Matrix_T>
generator_table& glucat::gen::generator_table< Matrix_T >::operator= (
            const generator_table< Matrix_T > &  )  [private]
```

### 6.14.4 Friends And Related Function Documentation

#### 6.14.4.1 friend_for_private_destructor

```
template<class Matrix_T>
friend class friend_for_private_destructor  [friend]
```

Friend declaration to avoid compiler warning: "... only defines a private destructor and has no friends" Ref: Carlos O'Ryan, ACE http://doc.ece.uci.edu

Definition at line 77 of file generation.h.

The documentation for this class was generated from the following files:

- glucat/generation.h
- glucat/generation_imp.h

## 6.15 glucat::glucat_error Class Reference

Abstract exception class.

`#include <errors.h>`

Inheritance diagram for glucat::glucat_error:



Collaboration diagram for glucat::glucat_error:




### Public Member Functions

- glucat_error (const std::string &context, const std::string &msg)
- ~glucat_error () throw ()
- virtual const std::string heading () const =0 throw ()
- virtual const std::string classname () const =0 throw ()
- virtual void print_error_msg () const =0

### Public Attributes

- std::string name

## 6.15.1 Detailed Description

Abstract exception class.

Definition at line 41 of file errors.h.

## 6.15.2 Constructor & Destructor Documentation

### 6.15.2.1 glucat_error()

```
glucat::glucat_error::glucat_error (
            const std::string & context,
            const std::string & msg )  [inline]
```

Definition at line 44 of file errors.h.

#### 6.15.2.2 ~glucat_error()

```
glucat::glucat_error::~glucat_error ( ) throw )   [inline]
```

Definition at line 47 of file errors.h.

### 6.15.3 Member Function Documentation

#### 6.15.3.1 classname()

```
virtual const std::string glucat::glucat_error::classname ( ) const throw )   [pure virtual]
```

Implemented in glucat::error< Class_T >.

#### 6.15.3.2 heading()

```
virtual const std::string glucat::glucat_error::heading ( ) const throw )   [pure virtual]
```

Implemented in glucat::error< Class_T >.

#### 6.15.3.3 print_error_msg()

```
virtual void glucat::glucat_error::print_error_msg ( ) const  [pure virtual]
```

Implemented in glucat::error< Class_T >.

### 6.15.4 Member Data Documentation

#### 6.15.4.1 name

```
std::string glucat::glucat_error::name
```

Definition at line 52 of file errors.h.

The documentation for this class was generated from the following file:

- glucat/errors.h

## 6.16 glucat::framed_multi< Scalar_T, LO, HI >::hash_size_t Class Reference

### Public Member Functions

- hash_size_t (size_t hash_size)
- size_t operator() () const

### Private Attributes

- size_t n

### 6.16.1 Detailed Description

**template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAULT_HI>**
**class glucat::framed_multi< Scalar_T, LO, HI >::hash_size_t**

Definition at line 180 of file framed_multi.h.

### 6.16.2 Constructor & Destructor Documentation

#### 6.16.2.1 hash_size_t()

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
glucat::framed_multi< Scalar_T, LO, HI >::hash_size_t::hash_size_t (
            size_t hash_size )  [inline]
```

Definition at line 183 of file framed_multi.h.

### 6.16.3 Member Function Documentation

#### 6.16.3.1 operator()()

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
size_t glucat::framed_multi< Scalar_T, LO, HI >::hash_size_t::operator() ( ) const  [inline]
```

Definition at line 186 of file framed_multi.h.

References glucat::framed_multi< Scalar_T, LO, HI >::hash_size_t::n.

### 6.16.4 Member Data Documentation

#### 6.16.4.1 n

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
size_t glucat::framed_multi< Scalar_T, LO, HI >::hash_size_t::n  [private]
```

Definition at line 189 of file framed_multi.h.

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::hash_size_t::operator()().

The documentation for this class was generated from the following file:

- glucat/framed_multi.h

## 6.17 glucat::index_set< LO, HI > Class Template Reference

Index set class based on std::bitset<> in Gnu standard C++ library.

`#include <index_set.h>`

Inheritance diagram for glucat::index_set< LO, HI >:




Collaboration diagram for glucat::index_set< LO, HI >:



## Classes

- class reference

  *Index set member reference.*

## Public Types

- typedef index_set index_set_t
- typedef std::pair< index_t, index_t > index_pair_t

## Public Member Functions

- index_set ()

  *Default constructor creates an empty set.*
- index_set (const bitset_t bst)

  *Constructor from bitset_t.*
- index_set (const index_t idx)

  *Constructor from index.*
- index_set (const set_value_t folded_val, const index_set_t frm, const bool prechecked=false)

  *Constructor from set value of an index set folded within the given frame.*
- index_set (const index_pair_t &range, const bool prechecked=false)

  *Constructor from range of indices from range.first to range.second.*
- index_set (const std::string &str)

  *Constructor from string.*
- bool operator== (const index_set_t rhs) const

  *Equality.*
- bool operator!= (const index_set_t rhs) const

  *Inequality.*
- index_set_t operator~ () const

  *Set complement: not.*
- index_set_t & operator^= (const index_set_t rhs)

  *Symmetric set difference: exclusive or.*
- index_set_t & operator &= (const index_set_t rhs)

  *Set intersection: and.*
- index_set_t & operator|= (const index_set_t rhs)

  *Set union: or.*
- bool operator[ ] (const index_t idx) const

  *Subscripting: Test idx for membership: test value of bit idx.*
- bool test (const index_t idx) const

  *Test idx for membership: test value of bit idx.*
- index_set_t & set ()

  *Include all indices except 0: set all bits except 0.*
- index_set_t & set (const index_t idx)

  *Include idx: Set bit at idx if idx != 0.*
- index_set_t & set (const index_t idx, const int val)

  *Set membership of idx to val if idx != 0: Set bit at idx to val if idx != 0.*
- index_set_t & reset ()

  *Make set empty: Set all bits to 0.*
- index_set_t & reset (const index_t idx)

  *Exclude idx: Set bit at idx to 0.*

- index_set_t & flip ()

  *Set complement, except 0: flip all bits, except 0.*
- index_set_t & flip (const index_t idx)

  *Complement membership of idx if idx != 0: flip bit at idx if idx != 0.*
- index_t count () const

  *Cardinality: Number of indices included in set.*
- index_t count_neg () const

  *Number of negative indices included in set.*
- index_t count_pos () const

  *Number of positive indices included in set.*
- index_t min () const

  *Minimum member.*
- index_t max () const

  *Maximum member.*
- bool operator< (const index_set_t rhs) const

  *Less than operator used for comparisons, map, etc.*
- bool is_contiguous () const

  *Determine if the index set is contiguous, ie. has no gaps.*
- const index_set_t fold () const

  *Fold this index set within itself as a frame.*
- const index_set_t fold (const index_set_t frm, const bool prechecked=false) const

  *Fold this index set within the given frame.*
- const index_set_t unfold (const index_set_t frm, const bool prechecked=false) const

  *Unfold this index set within the given frame.*
- set_value_t value_of_fold (const index_set_t frm) const

  *The set value of the fold of this index set within the given frame.*
- int sign_of_mult (const index_set_t ist) const

  *Sign of geometric product of two Clifford basis elements.*
- int sign_of_square () const

  *Sign of geometric square of a Clifford basis element.*
- size_t hash_fn () const

  *Hash function.*
- reference operator[ ] (index_t idx)

  *Subscripting: Element access.*

## Static Public Member Functions

- static const std::string classname ()

## Static Public Attributes

- static const index_t v_lo = LO
- static const index_t v_hi = HI

## Private Types

- typedef std::bitset< HI-LO > bitset_t
- typedef error< index_set > error_t

### Private Member Functions

- BOOST_STATIC_ASSERT ((LO<=0) &&(0<=HI) &&(LO< HI) &&(-LO< _GLUCAT_BITS_PER_ULONG) &&(HI< _GLUCAT_BITS_PER_ULONG) &&(HI-LO<=_GLUCAT_BITS_PER_ULONG))
- bool lex_less_than (const index_set_t rhs) const

  *Lexicographic ordering of two sets: ∗this < rhs.*

### Friends

- class reference
- const index_set_t operator^ (const index_set_t &lhs, const index_set_t &rhs)
- const index_set_t operator & (const index_set_t &lhs, const index_set_t &rhs)
- const index_set_t operator| (const index_set_t &lhs, const index_set_t &rhs)
- int compare (const index_set_t &lhs, const index_set_t &rhs)

## 6.17.1 Detailed Description

**template<const index_t LO, const index_t HI>**
**class glucat::index_set< LO, HI >**

Index set class based on std::bitset<> in Gnu standard C++ library.

Definition at line 45 of file index_set.h.

## 6.17.2 Member Typedef Documentation

### 6.17.2.1 bitset_t

```
template<const index_t LO, const index_t HI>
typedef std::bitset<HI-LO> glucat::index_set< LO, HI >::bitset_t  [private]
```

Definition at line 81 of file index_set.h.

### 6.17.2.2 error_t

```
template<const index_t LO, const index_t HI>
typedef error<index_set> glucat::index_set< LO, HI >::error_t  [private]
```

Definition at line 82 of file index_set.h.

#### 6.17.2.3 index_pair_t

```
template<const index_t LO, const index_t HI>
typedef std::pair<index_t,index_t> glucat::index_set< LO, HI >::index_pair_t
```

Definition at line 85 of file index_set.h.

#### 6.17.2.4 index_set_t

```
template<const index_t LO, const index_t HI>
typedef index_set glucat::index_set< LO, HI >::index_set_t
```

Definition at line 84 of file index_set.h.

### 6.17.3 Constructor & Destructor Documentation

#### 6.17.3.1 index_set() [1/6]

```
template<const index_t LO, const index_t HI>
glucat::index_set< LO, HI >::index_set ( )  [inline]
```

Default constructor creates an empty set.

Definition at line 92 of file index_set.h.

#### 6.17.3.2 index_set() [2/6]

```
template<const index_t LO, const index_t HI>
glucat::index_set< LO, HI >::index_set (
            const bitset_t bst )
```

Constructor from bitset_t.

Definition at line 61 of file index_set_imp.h.

#### 6.17.3.3 index_set() [3/6]

```
template<const index_t LO, const index_t HI>
glucat::index_set< LO, HI >::index_set (
            const index_t idx )
```

Constructor from index.

Constructor from index value.

Definition at line 55 of file index_set_imp.h.

#### 6.17.3.4 index_set() [4/6]

```
template<const index_t LO, const index_t HI>
glucat::index_set< LO, HI >::index_set (
            const set_value_t folded_val,
            const index_set_t frm,
            const bool prechecked = false )
```

Constructor from set value of an index set folded within the given frame.

Definition at line 68 of file index_set_imp.h.

References glucat::index_set< LO, HI >::count(), glucat::index_set< LO, HI >::fold(), glucat::index_set< LO, HI >::min(), and glucat::index_set< LO, HI >::unfold().

#### 6.17.3.5 index_set() [5/6]

```
template<const index_t LO, const index_t HI>
glucat::index_set< LO, HI >::index_set (
            const index_pair_t & range,
            const bool prechecked = false )
```

Constructor from range of indices from range.first to range.second.

Definition at line 82 of file index_set_imp.h.

#### 6.17.3.6 index_set() [6/6]

```
template<const index_t LO, const index_t HI>
glucat::index_set< LO, HI >::index_set (
            const std::string & str )
```

Constructor from string.

Definition at line 102 of file index_set_imp.h.

### 6.17.4 Member Function Documentation

#### 6.17.4.1 BOOST_STATIC_ASSERT()

```
template<const index_t LO, const index_t HI>
glucat::index_set< LO, HI >::BOOST_STATIC_ASSERT (
             (LO<=0) &&(0<=HI) &&(LO< HI) &&(-LO< _GLUCAT_BITS_PER_ULONG) &&(HI< _GLUCAT_BI↩
TS_PER_ULONG) &&(HI-LO<=_GLUCAT_BITS_PER_ULONG)  )  [private]
```

#### 6.17.4.2 classname()

```
template<const index_t LO, const index_t HI>
const std::string glucat::index_set< LO, HI >::classname ( )  [inline], [static]
```

Definition at line 49 of file index_set_imp.h.

#### 6.17.4.3 count()

```
template<const index_t LO, const index_t HI>
index_t glucat::index_set< LO, HI >::count ( ) const  [inline]
```

Cardinality: Number of indices included in set.

Definition at line 344 of file index_set_imp.h.

Referenced by glucat::index_set< LO, HI >::count_neg(), glucat::index_set< LO, HI >::count_pos(), glucat↩
::framed_multi< Scalar_T, LO, HI >::framed_multi(), glucat::index_set< LO, HI >::index_set(), glucat::matrix_↩
multi< Scalar_T, LO, HI >::matrix_multi(), glucat::index_set< LO, HI >::operator<(), and glucat::framed_multi<
Scalar_T, LO, HI >::random().

#### 6.17.4.4 count_neg()

```
template<const index_t LO, const index_t HI>
index_t glucat::index_set< LO, HI >::count_neg ( ) const  [inline]
```

Number of negative indices included in set.

Definition at line 364 of file index_set_imp.h.

References glucat::index_set< LO, HI >::count().

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::fast_matrix_multi(), and glucat::folded_dim().

#### 6.17.4.5 count_pos()

```
template<const index_t LO, const index_t HI>
index_t glucat::index_set< LO, HI >::count_pos ( ) const  [inline]
```

Number of positive indices included in set.

Definition at line 376 of file index_set_imp.h.

References glucat::index_set< LO, HI >::count().

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::fast_matrix_multi(), and glucat::folded_dim().

#### 6.17.4.6 flip() [1/2]

```
template<const index_t LO, const index_t HI>
index_set< LO, HI > & glucat::index_set< LO, HI >::flip ( )  [inline]
```

Set complement, except 0: flip all bits, except 0.

Definition at line 319 of file index_set_imp.h.

#### 6.17.4.7 flip() [2/2]

```
template<const index_t LO, const index_t HI>
index_set< LO, HI > & glucat::index_set< LO, HI >::flip (
            const index_t idx )  [inline]
```

Complement membership of idx if idx != 0: flip bit at idx if idx != 0.

Definition at line 330 of file index_set_imp.h.

#### 6.17.4.8 fold() [1/2]

```
template<const index_t LO, const index_t HI>
const index_set< LO, HI > glucat::index_set< LO, HI >::fold ( ) const  [inline]
```

Fold this index set within itself as a frame.

Definition at line 748 of file index_set_imp.h.

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >::basis_element(), glucat::index_set< LO, HI >::index_↩ set(), and glucat::index_set< LO, HI >::value_of_fold().

#### 6.17.4.9 fold() [2/2]

```
template<const index_t LO, const index_t HI>
const index_set< LO, HI > glucat::index_set< LO, HI >::fold (
            const index_set_t frm,
            const bool prechecked = false ) const
```

Fold this index set within the given frame.

Definition at line 756 of file index_set_imp.h.

References glucat::index_set< LO, HI >::max(), glucat::index_set< LO, HI >::min(), glucat::index_set< LO, HI >::set(), and glucat::index_set< LO, HI >::test().

#### 6.17.4.10 hash_fn()

```
template<const index_t LO, const index_t HI>
size_t glucat::index_set< LO, HI >::hash_fn ( ) const  [inline]
```

Hash function.

Definition at line 948 of file index_set_imp.h.

Referenced by glucat::index_set_hash< LO, HI >::operator()().

#### 6.17.4.11 is_contiguous()

```
template<const index_t LO, const index_t HI>
bool glucat::index_set< LO, HI >::is_contiguous ( ) const  [inline]
```

Determine if the index set is contiguous, ie. has no gaps.

Determine if the index set is contiguous, ie. has no gaps when 0 is included.

Definition at line 732 of file index_set_imp.h.

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::fold(), and glucat::framed_multi< Scalar_T, LO, HI >::unfold().

#### 6.17.4.12 lex_less_than()

```
template<const index_t LO, const index_t HI>
bool glucat::index_set< LO, HI >::lex_less_than (
            const index_set_t rhs ) const  [inline], [private]
```

Lexicographic ordering of two sets: $*$this $<$ rhs.

Definition at line 588 of file index_set_imp.h.

Referenced by glucat::compare().

#### 6.17.4.13 max()

```
template<const index_t LO, const index_t HI>
index_t glucat::index_set< LO, HI >::max ( ) const
```

Maximum member.

Maximum member, or 0 if none.

Definition at line 550 of file index_set_imp.h.

Referenced by PyClical.index_set::__iter__(), glucat::matrix_multi< Scalar_T, LO, HI >::basis_element(), glucat::index_set< LO, HI >::fold(), glucat::framed_multi< Scalar_T, LO, HI >::framed_multi(), glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi(), and glucat::index_set< LO, HI >::unfold().

#### 6.17.4.14 min()

```
template<const index_t LO, const index_t HI>
index_t glucat::index_set< LO, HI >::min ( ) const
```

Minimum member.

Minimum member, or 0 if none.

Definition at line 461 of file index_set_imp.h.

Referenced by PyClical.index_set::__iter__(), glucat::matrix_multi< Scalar_T, LO, HI >::basis_element(), glucat::index_set< LO, HI >::fold(), glucat::framed_multi< Scalar_T, LO, HI >::framed_multi(), glucat::index_set< LO, HI >::index_set(), glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi(), glucat::index_set< LO, HI >::unfold(), and glucat::index_set< LO, HI >::value_of_fold().

#### 6.17.4.15 operator &=()

```
template<const index_t LO, const index_t HI>
index_set_t& glucat::index_set< LO, HI >::operator&= (
            const index_set_t rhs )
```

Set intersection: and.

#### 6.17.4.16 operator"!=()

```
template<const index_t LO, const index_t HI>
bool glucat::index_set< LO, HI >::operator!= (
            const index_set_t rhs ) const  [inline]
```

Inequality.

Definition at line 130 of file index_set_imp.h.

#### 6.17.4.17 operator<()

```
template<const index_t LO, const index_t HI>
bool glucat::index_set< LO, HI >::operator< (
            const index_set_t rhs ) const  [inline]
```

Less than operator used for comparisons, map, etc.

Definition at line 597 of file index_set_imp.h.

References glucat::index_set< LO, HI >::count().

#### 6.17.4.18 operator==()

```
template<const index_t LO, const index_t HI>
bool glucat::index_set< LO, HI >::operator== (
            const index_set_t rhs ) const  [inline]
```

Equality.

Definition at line 119 of file index_set_imp.h.

#### 6.17.4.19 operator[]() [1/2]

```
template<const index_t LO, const index_t HI>
bool glucat::index_set< LO, HI >::operator[] (
            const index_t idx ) const  [inline]
```

Subscripting: Test idx for membership: test value of bit idx.

Definition at line 232 of file index_set_imp.h.

#### 6.17.4.20 operator[]() [2/2]

```
template<const index_t LO, const index_t HI>
index_set< LO, HI >::reference glucat::index_set< LO, HI >::operator[] (
            index_t idx )  [inline]
```

Subscripting: Element access.

Definition at line 224 of file index_set_imp.h.

#### 6.17.4.21 operator^=()

```
template<const index_t LO, const index_t HI>
index_set< LO, HI > & glucat::index_set< LO, HI >::operator^= (
            const index_set_t rhs )  [inline]
```

Symmetric set difference: exclusive or.

Definition at line 149 of file index_set_imp.h.

#### 6.17.4.22 operator"" |=()

```
template<const index_t LO, const index_t HI>
index_set< LO, HI > & glucat::index_set< LO, HI >::operator|= (
            const index_set_t rhs )  [inline]
```

Set union: or.

Definition at line 199 of file index_set_imp.h.

#### 6.17.4.23 operator~()

```
template<const index_t LO, const index_t HI>
index_set< LO, HI > glucat::index_set< LO, HI >::operator~ ( ) const  [inline]
```

Set complement: not.

Definition at line 141 of file index_set_imp.h.

#### 6.17.4.24 reset() [1/2]

```
template<const index_t LO, const index_t HI>
index_set< LO, HI > & glucat::index_set< LO, HI >::reset ( )  [inline]
```

Make set empty: Set all bits to 0.

Definition at line 294 of file index_set_imp.h.

#### 6.17.4.25 reset() [2/2]

```
template<const index_t LO, const index_t HI>
index_set< LO, HI > & glucat::index_set< LO, HI >::reset (
            const index_t idx )  [inline]
```

Exclude idx: Set bit at idx to 0.

Definition at line 305 of file index_set_imp.h.

#### 6.17.4.26 set() [1/3]

```
template<const index_t LO, const index_t HI>
index_set< LO, HI > & glucat::index_set< LO, HI >::set ( )  [inline]
```

Include all indices except 0: set all bits except 0.

Definition at line 255 of file index_set_imp.h.

Referenced by glucat::index_set< LO, HI >::fold(), glucat::operator>>(), and glucat::index_set< LO, HI >::unfold().

#### 6.17.4.27 set() [2/3]

```
template<const index_t LO, const index_t HI>
index_set< LO, HI > & glucat::index_set< LO, HI >::set (
            const index_t idx )  [inline]
```

Include idx: Set bit at idx if idx != 0.

Definition at line 266 of file index_set_imp.h.

#### 6.17.4.28 set() [3/3]

```
template<const index_t LO, const index_t HI>
index_set< LO, HI > & glucat::index_set< LO, HI >::set (
            const index_t idx,
            const int val )  [inline]
```

Set membership of idx to val if idx != 0: Set bit at idx to val if idx != 0.

Definition at line 280 of file index_set_imp.h.

#### 6.17.4.29 sign_of_mult()

```
template<const index_t LO, const index_t HI>
int glucat::index_set< LO, HI >::sign_of_mult (
            const index_set_t ist ) const
```

Sign of geometric product of two Clifford basis elements.

Definition at line 879 of file index_set_imp.h.

References glucat::inverse_gray(), and glucat::inverse_reversed_gray().

#### 6.17.4.30 sign_of_square()

```
template<const index_t LO, const index_t HI>
int glucat::index_set< LO, HI >::sign_of_square ( ) const  [inline]
```

Sign of geometric square of a Clifford basis element.

Definition at line 928 of file index_set_imp.h.

#### 6.17.4.31 test()

```
template<const index_t LO, const index_t HI>
bool glucat::index_set< LO, HI >::test (
            const index_t idx ) const  [inline]
```

Test idx for membership: test value of bit idx.

Definition at line 240 of file index_set_imp.h.

Referenced by glucat::index_set< LO, HI >::fold(), and glucat::index_set< LO, HI >::unfold().

#### 6.17.4.32 unfold()

```
template<const index_t LO, const index_t HI>
const index_set< LO, HI > glucat::index_set< LO, HI >::unfold (
            const index_set_t frm,
            const bool prechecked = false ) const
```

Unfold this index set within the given frame.

Definition at line 794 of file index_set_imp.h.

References glucat::index_set< LO, HI >::max(), glucat::index_set< LO, HI >::min(), glucat::index_set< LO, HI >::set(), and glucat::index_set< LO, HI >::test().

Referenced by glucat::index_set< LO, HI >::index_set().

#### 6.17.4.33 value_of_fold()

```
template<const index_t LO, const index_t HI>
set_value_t glucat::index_set< LO, HI >::value_of_fold (
            const index_set_t frm ) const  [inline]
```

The set value of the fold of this index set within the given frame.

Definition at line 828 of file index_set_imp.h.

References glucat::index_set< LO, HI >::fold(), and glucat::index_set< LO, HI >::min().

### 6.17.5 Friends And Related Function Documentation

#### 6.17.5.1 compare

```
template<const index_t LO, const index_t HI>
int compare (
            const index_set_t & lhs,
            const index_set_t & rhs )  [friend]
```

#### 6.17.5.2 operator &

```
template<const index_t LO, const index_t HI>
const index_set_t operator& (
            const index_set_t & lhs,
            const index_set_t & rhs )  [friend]
```

#### 6.17.5.3 operator^

```
template<const index_t LO, const index_t HI>
const index_set_t operator^ (
            const index_set_t & lhs,
            const index_set_t & rhs )  [friend]
```

#### 6.17.5.4 operator" |

```
template<const index_t LO, const index_t HI>
const index_set_t operator| (
            const index_set_t & lhs,
            const index_set_t & rhs )  [friend]
```

#### 6.17.5.5 reference

```
template<const index_t LO, const index_t HI>
friend class reference  [friend]
```

Definition at line 173 of file index_set.h.

### 6.17.6 Member Data Documentation

#### 6.17.6.1 v_hi

```
template<const index_t LO, const index_t HI>
const index_t glucat::index_set< LO, HI >::v_hi = HI  [static]
```

Definition at line 88 of file index_set.h.

#### 6.17.6.2 v_lo

```
template<const index_t LO, const index_t HI>
const index_t glucat::index_set< LO, HI >::v_lo = LO  [static]
```

Definition at line 87 of file index_set.h.

The documentation for this class was generated from the following files:

- glucat/index_set.h
- glucat/index_set_imp.h

## 6.18 PyClical.index_set Class Reference

Inheritance diagram for PyClical.index_set:



Collaboration diagram for PyClical.index_set:




### Public Member Functions

- def __cinit__ (self, other=0)
- def __dealloc__ (self)
- def __richcmp__ (lhs, rhs, int, op)
- def __setitem__ (self, idx, val)
- def __getitem__ (self, idx)
- def __contains__ (self, idx)
- def __iter__ (self)
- def __invert__ (self)
- def __xor__ (lhs, rhs)
- def __ixor__ (self, rhs)
- def __and__ (lhs, rhs)
- def __iand__ (self, rhs)
- def __or__ (lhs, rhs)
- def __ior__ (self, rhs)
- def count (self)
- def count_neg (self)
- def count_pos (self)
- def min (self)
- def max (self)
- def hash_fn (self)
- def sign_of_mult (self, rhs)
- def sign_of_square (self)
- def __repr__ (self)
- def __str__ (self)

### Public Attributes

- instance

#### 6.18.1 Detailed Description

```
Return the C++ IndexSet instance wrapped by index_set(obj).

Python class index_set wraps C++ class IndexSet.
```

Definition at line 39 of file PyClical.pyx.

### 6.18.2 Member Function Documentation

#### 6.18.2.1 __and__()

```
def PyClical.index_set.__and__ (
              lhs,
              rhs )
```

```
Set intersection: and.

>>> print index_set({1}) & index_set({2})
{}
>>> print index_set({1,2}) & index_set({2})
{2}
```

Definition at line 269 of file PyClical.pyx.

#### 6.18.2.2 __cinit__()

```
def PyClical.index_set.__cinit__ (
              self,
              other = 0 )
```

```
Construct an object of type index_set.

>>> print index_set(1)
{1}
>>> print index_set({1,2})
{1,2}
>>> print index_set(index_set({1,2}))
{1,2}
>>> print index_set({1,2})
{1,2}
>>> print index_set({1,2,1})
{1,2}
>>> print index_set("{1,2,1}")
{1,2}
>>> print index_set("")
{}
```

Definition at line 73 of file PyClical.pyx.

#### 6.18.2.3 __contains__()

```
def PyClical.index_set.__contains__ (
              self,
              idx )
```

```
Check that an index_set object contains the index idx: idx in self.
```

```
>>> 1 in index_set({1})
True
>>> 2 in index_set({1})
False
>>> -1 in index_set({2})
False
>>> 1 in index_set({2})
False
>>> 2 in index_set({2})
True
>>> 33 in index_set({2})
False
```

Definition at line 208 of file PyClical.pyx.

References PyClical.index_set.instance.

#### 6.18.2.4 __dealloc__()

```
def PyClical.index_set.__dealloc__ (
              self )
```

```
Clean up by deallocating the instance of C++ class IndexSet.
```

Definition at line 114 of file PyClical.pyx.

References PyClical.index_set.instance.

#### 6.18.2.5 __getitem__()

```
def PyClical.index_set.__getitem__ (
              self,
              idx )
```

```
Get the value of an index_set object at an index.
```

```
>>> index_set({1})[1]
True
>>> index_set({1})[2]
False
>>> index_set({2})[-1]
False
>>> index_set({2})[1]
False
>>> index_set({2})[2]
True
>>> index_set({2})[33]
False
```

Definition at line 189 of file PyClical.pyx.

References PyClical.index_set.instance.

#### 6.18.2.6 __iand__()

```
def PyClical.index_set.__iand__ (
              self,
              rhs )
```

Set intersection: and.

```
>>> x = index_set({1}); x &= index_set({2}); print x
{}
>>> x = index_set({1,2}); x &= index_set({2}); print x
{2}
```

Definition at line 280 of file PyClical.pyx.

#### 6.18.2.7 __invert__()

```
def PyClical.index_set.__invert__ (
              self )
```

Set complement: not.

```
>>> print ~index_set({-16,-15,-14,-13,-12,-11,-10,-9,-8,-7,-6,-5,-4,-3,-2,-1,1,2,3,4,5,6,7,8,9,10,11,12,13,14,
{-32,-31,-30,-29,-28,-27,-26,-25,-24,-23,-22,-21,-20,-19,-18,-17,17,18,19,20,21,22,23,24,25,26,27,28,29,30,31,
```

Definition at line 238 of file PyClical.pyx.

References PyClical.index_set.instance.

#### 6.18.2.8 __ior__()

```
def PyClical.index_set.__ior__ (
              self,
              rhs )
```

Set union: or.

```
>>> x = index_set({1}); x |= index_set({2}); print x
{1,2}
>>> x = index_set({1,2}); x |= index_set({2}); print x
{1,2}
```

Definition at line 302 of file PyClical.pyx.

#### 6.18.2.9 __iter__()

```
def PyClical.index_set.__iter__ (
              self )
```

```
Iterate over the indices of an index_set.

>>> for i in index_set({-3,4,7}): print i,
-3 4 7
```

Definition at line 227 of file PyClical.pyx.

References glucat::index_set< LO, HI >.max(), PyClical.index_set.max(), glucat::index_set< LO, HI >.min(), and PyClical.index_set.min().

#### 6.18.2.10 __ixor__()

```
def PyClical.index_set.__ixor__ (
              self,
              rhs )
```

```
Symmetric set difference: exclusive or.

>>> x = index_set({1}); x ^= index_set({2}); print x
{1,2}
>>> x = index_set({1,2}); x ^= index_set({2}); print x
{1}
```

Definition at line 258 of file PyClical.pyx.

#### 6.18.2.11 __or__()

```
def PyClical.index_set.__or__ (
              lhs,
              rhs )
```

```
Set union: or.

>>> print index_set({1}) | index_set({2})
{1,2}
>>> print index_set({1,2}) | index_set({2})
{1,2}
```

Definition at line 291 of file PyClical.pyx.

#### 6.18.2.12 __repr__()

```
def PyClical.index_set.__repr__ (
              self )
```

```
The "official" string representation of self.

>>> index_set({1,2}).__repr__()
'index_set({1,2})'
>>> repr(index_set({1,2}))
'index_set({1,2})'
```

Definition at line 382 of file PyClical.pyx.

References index_set_to_repr().

#### 6.18.2.13 __richcmp__()

```
def PyClical.index_set.__richcmp__ (
              lhs,
              rhs,
              int,
              op )
```

```
Compare two objects of class index_set.

>>> index_set(1) == index_set({1})
True
>>> index_set({1}) != index_set({1})
False
>>> index_set({1}) != index_set({2})
True
>>> index_set({1}) == index_set({2})
False
>>> index_set({1}) < index_set({2})
True
>>> index_set({1}) <= index_set({2})
True
>>> index_set({1}) > index_set({2})
False
>>> index_set({1}) >= index_set({2})
False
```

Definition at line 120 of file PyClical.pyx.

#### 6.18.2.14 __setitem__()

```
def PyClical.index_set.__setitem__ (
              self,
              idx,
              val )
```

```
Set the value of an index_set object at index idx to value val.

>>> s=index_set({1}); s[2] = True; print s
{1,2}
>>> s=index_set({1,2}); s[1] = False; print s
{2}
```

Definition at line 177 of file PyClical.pyx.

References PyClical.index_set.instance.

#### 6.18.2.15 __str__()

```
def PyClical.index_set.__str__ (
              self )
```

```
The "informal" string representation of self.

>>> index_set({1,2}).__str__()
'{1,2}'
>>> str(index_set({1,2}))
'{1,2}'
```

Definition at line 393 of file PyClical.pyx.

References index_set_to_str().

#### 6.18.2.16 __xor__()

```
def PyClical.index_set.__xor__ (
              lhs,
              rhs )
```

```
Symmetric set difference: exclusive or.

>>> print index_set({1}) ^ index_set({2})
{1,2}
>>> print index_set({1,2}) ^ index_set({2})
{1}
```

Definition at line 247 of file PyClical.pyx.

#### 6.18.2.17 count()

```
def PyClical.index_set.count (
              self )
```

```
Cardinality: Number of indices included in set.

>>> index_set({-1,1,2}).count()
3
```

Definition at line 313 of file PyClical.pyx.

References PyClical.index_set.instance.

#### 6.18.2.18 count_neg()

```
def PyClical.index_set.count_neg (
              self )
```

Number of negative indices included in set.

```
>>> index_set({-1,1,2}).count_neg()
1
```

Definition at line 322 of file PyClical.pyx.

References PyClical.index_set.instance.

#### 6.18.2.19 count_pos()

```
def PyClical.index_set.count_pos (
              self )
```

Number of positive indices included in set.

```
>>> index_set({-1,1,2}).count_pos()
2
```

Definition at line 331 of file PyClical.pyx.

References PyClical.index_set.instance.

#### 6.18.2.20 hash_fn()

```
def PyClical.index_set.hash_fn (
              self )
```

Hash function.

Definition at line 358 of file PyClical.pyx.

References PyClical.index_set.instance.

#### 6.18.2.21 max()

```
def PyClical.index_set.max (
              self )
```

```
Maximum member.

>>> index_set({-1,1,2}).max()
2
```

Definition at line 349 of file PyClical.pyx.

References PyClical.index_set.instance.

Referenced by PyClical.index_set.__iter__().

#### 6.18.2.22 min()

```
def PyClical.index_set.min (
              self )
```

```
Minimum member.

>>> index_set({-1,1,2}).min()
-1
```

Definition at line 340 of file PyClical.pyx.

References PyClical.index_set.instance.

Referenced by PyClical.index_set.__iter__().

#### 6.18.2.23 sign_of_mult()

```
def PyClical.index_set.sign_of_mult (
              self,
              rhs )
```

```
Sign of geometric product of two Clifford basis elements.

>>> s = index_set({1,2}); t=index_set({-1}); s.sign_of_mult(t)
1
```

Definition at line 364 of file PyClical.pyx.

References PyClical.index_set.instance.

#### 6.18.2.24 sign_of_square()

```
def PyClical.index_set.sign_of_square (
              self )
```

```
Sign of geometric square of a Clifford basis element.

>>> s = index_set({1,2}); s.sign_of_square()
-1
```

Definition at line 373 of file PyClical.pyx.

References PyClical.index_set.instance.

### 6.18.3 Member Data Documentation

#### 6.18.3.1 instance

```
PyClical.index_set.instance
```

Definition at line 94 of file PyClical.pyx.

Referenced by PyClical.clifford.__call__(), PyClical.index_set.__contains__(), PyClical.index_set.__dealloc__(), PyClical.clifford.__dealloc__(), PyClical.index_set.__getitem__(), PyClical.clifford.__getitem__(), PyClical.index_set.__invert__(), PyClical.clifford.__neg__(), PyClical.index_set.__setitem__(), PyClical.clifford.conj(), PyClical.index_set.count(), PyClical.index_set.count_neg(), PyClical.index_set.count_pos(), PyClical.clifford.even(), PyClical.clifford.frame(), PyClical.index_set.hash_fn(), PyClical.clifford.inv(), PyClical.clifford.involute(), PyClical.clifford.isnan(), PyClical.index_set.max(), PyClical.clifford.max_abs(), PyClical.index_set.min(), PyClical.clifford.norm(), PyClical.clifford.odd(), PyClical.clifford.outer_pow(), PyClical.clifford.pow(), PyClical.clifford.pure(), PyClical.clifford.quad(), PyClical.clifford.reverse(), PyClical.clifford.scalar(), PyClical.index_set.sign_of_mult(), PyClical.index_set.sign_of_square(), PyClical.clifford.truncated(), and PyClical.clifford.vector_part().

The documentation for this class was generated from the following file:

- pyclical/PyClical.pyx

## 6.19 glucat::index_set_hash< LO, HI > Class Template Reference

```
#include <framed_multi.h>
```

### Public Types

- typedef index_set< LO, HI > index_set_t

### Public Member Functions

- size_t operator() (index_set_t val) const

## 6.19.1 Detailed Description

**template<const index_t LO, const index_t HI>**
**class glucat::index_set_hash< LO, HI >**

Definition at line 126 of file framed_multi.h.

## 6.19.2 Member Typedef Documentation

### 6.19.2.1 index_set_t

```
template<const index_t LO, const index_t HI>
typedef index_set<LO,HI> glucat::index_set_hash< LO, HI >::index_set_t
```

Definition at line 129 of file framed_multi.h.

## 6.19.3 Member Function Documentation

### 6.19.3.1 operator()()

```
template<const index_t LO, const index_t HI>
size_t glucat::index_set_hash< LO, HI >::operator() (
            index_set_t val ) const  [inline]
```

Definition at line 130 of file framed_multi.h.

References glucat::index_set< LO, HI >::hash_fn().

The documentation for this class was generated from the following file:

- glucat/framed_multi.h

## 6.20 glucat::matrix_multi< Scalar_T, LO, HI > Class Template Reference

A matrix_multi<Scalar_T,LO,HI> is a matrix approximation to a multivector.

`#include <framed_multi.h>`

Inheritance diagram for glucat::matrix_multi< Scalar_T, LO, HI >:




Collaboration diagram for glucat::matrix_multi< Scalar_T, LO, HI >:




### Public Types

- typedef matrix_multi multivector_t
- typedef multivector_t matrix_multi_t
- typedef Scalar_T scalar_t
- typedef index_set< LO, HI > index_set_t
- typedef std::pair< const index_set_t, Scalar_T > term_t
- typedef std::vector< Scalar_T > vector_t
- typedef error< multivector_t > error_t
- typedef framed_multi< Scalar_T, LO, HI > framed_multi_t

## Public Member Functions

- ~matrix_multi ()

  *Destructor.*
- matrix_multi ()

  *Default constructor.*
- template<typename Other_Scalar_T >
  matrix_multi (const matrix_multi< Other_Scalar_T, LO, HI > &val)

  *Construct a multivector from a multivector with a different scalar type.*
- template<typename Other_Scalar_T >
  matrix_multi (const matrix_multi< Other_Scalar_T, LO, HI > &val, const index_set_t frm, const bool prechecked=false)

  *Construct a multivector, within a given frame, from a given multivector.*
- matrix_multi (const multivector_t &val, const index_set_t frm, const bool prechecked=false)

  *Construct a multivector, within a given frame, from a given multivector.*
- matrix_multi (const index_set_t ist, const Scalar_T &crd=Scalar_T(1))

  *Construct a multivector from an index set and a scalar coordinate.*
- matrix_multi (const index_set_t ist, const Scalar_T &crd, const index_set_t frm, const bool prechecked=false)

  *Construct a multivector, within a given frame, from an index set and a scalar coordinate.*
- matrix_multi (const Scalar_T &scr, const index_set_t frm=index_set_t())

  *Construct a multivector from a scalar (within a frame, if given)*
- matrix_multi (const int scr, const index_set_t frm=index_set_t())

  *Construct a multivector from an int (within a frame, if given)*
- matrix_multi (const vector_t &vec, const index_set_t frm, const bool prechecked=false)

  *Construct a multivector, within a given frame, from a given vector.*
- matrix_multi (const std::string &str)

  *Construct a multivector from a string: eg: "3+2{1,2}-6.1e-2{2,3}".*
- matrix_multi (const std::string &str, const index_set_t frm, const bool prechecked=false)

  *Construct a multivector, within a given frame, from a string: eg: "3+2{1,2}-6.1e-2{2,3}".*
- matrix_multi (const char *str)

  *Construct a multivector from a char*: eg: "3+2{1,2}-6.1e-2{2,3}".*
- matrix_multi (const char *str, const index_set_t frm, const bool prechecked=false)

  *Construct a multivector, within a given frame, from a char*: eg: "3+2{1,2}-6.1e-2{2,3}".*
- template<typename Other_Scalar_T >
  matrix_multi (const framed_multi< Other_Scalar_T, LO, HI > &val)

  *Construct a multivector from a framed_multi_t.*
- template<typename Other_Scalar_T >
  matrix_multi (const framed_multi< Other_Scalar_T, LO, HI > &val, const index_set_t frm, const bool prechecked=false)

  *Construct a multivector, within a given frame, from a framed_multi_t.*
- const matrix_multi_t fast_matrix_multi (const index_set_t frm) const

  *Use generalized FFT to construct a matrix_multi_t.*
- template<typename Other_Scalar_T >
  const framed_multi< Other_Scalar_T, LO, HI > fast_framed_multi () const

  *Use inverse generalized FFT to construct a framed_multi_t.*
- _GLUCAT_CLIFFORD_ALGEBRA_OPERATIONS multivector_t & operator= (const multivector_t &rhs)

  *Assignment operator.*
- multivector_t & operator+= (const term_t &rhs)

  *Add a term, if non-zero.*

### Static Public Member Functions

- static const std::string classname ()

  *Class name used in messages.*
- static const matrix_multi_t random (const index_set_t frm, Scalar_T fill=Scalar_T(1))

  *Random multivector within a frame.*

### Private Types

- typedef ublas::row_major orientation_t
- typedef ublas::compressed_matrix< int, orientation_t > basis_matrix_t
- typedef ublas::compressed_matrix< Scalar_T, orientation_t > matrix_t
- typedef matrix_t::size_type matrix_index_t

### Private Member Functions

- template<typename Matrix_T >
  matrix_multi (const Matrix_T &mtx, const index_set_t frm)

  *Construct a multivector within a given frame from a given matrix.*
- matrix_multi (const matrix_t &mtx, const index_set_t frm)

  *Construct a multivector within a given frame from a given matrix.*
- const basis_matrix_t basis_element (const index_set< LO, HI > &ist) const

  *Create a basis element matrix within the current frame.*

### Private Attributes

- index_set_t m_frame

  *Index set representing the frame for the subalgebra which contains the multivector.*
- matrix_t m_matrix

  *Matrix value representing the multivector within the folded frame.*

### Friends

- template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
  class framed_multi
- template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
  class matrix_multi
- const matrix_multi_t operator* (const matrix_multi_t &lhs, const matrix_multi_t &rhs)
- const matrix_multi_t operator^ (const matrix_multi_t &lhs, const matrix_multi_t &rhs)
- const matrix_multi_t operator & (const matrix_multi_t &lhs, const matrix_multi_t &rhs)
- const matrix_multi_t operator% (const matrix_multi_t &lhs, const matrix_multi_t &rhs)
- Scalar_T star (const matrix_multi_t &lhs, const matrix_multi_t &rhs)
- const matrix_multi_t operator/ (const matrix_multi_t &lhs, const matrix_multi_t &rhs)
- const matrix_multi_t operator| (const matrix_multi_t &lhs, const matrix_multi_t &rhs)
- std::istream & operator>> (std::istream &s, multivector_t &val)
- std::ostream & operator<< (std::ostream &os, const multivector_t &val)
- std::ostream & operator<< (std::ostream &os, const term_t &term)

- template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
  const index_set< Other_LO, Other_HI > reframe (const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > &lhs, const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > &rhs, matrix_multi< Other_Scalar_T, Other_LO, Other_HI > &lhs_reframed, matrix_multi< Other_Scalar_T, Other_LO, Other_HI > &rhs_reframed)
- template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
  const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > matrix_sqrt (const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > &val, const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > &i)
- template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
  const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > matrix_log (const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > &val, const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > &i)

### 6.20.1 Detailed Description

**template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAULT_HI>**
**class glucat::matrix_multi< Scalar_T, LO, HI >**

A matrix_multi<Scalar_T,LO,HI> is a matrix approximation to a multivector.

Definition at line 68 of file framed_multi.h.

### 6.20.2 Member Typedef Documentation

#### 6.20.2.1 basis_matrix_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef ublas::compressed_matrix< int, orientation_t > glucat::matrix_multi< Scalar_T, LO, HI
>::basis_matrix_t  [private]
```

Definition at line 152 of file matrix_multi.h.

#### 6.20.2.2 error_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef error<multivector_t> glucat::matrix_multi< Scalar_T, LO, HI >::error_t
```

Definition at line 142 of file matrix_multi.h.

#### 6.20.2.3 framed_multi_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef framed_multi<Scalar_T,LO,HI> glucat::matrix_multi< Scalar_T, LO, HI >::framed_multi_t
```

Definition at line 143 of file matrix_multi.h.

#### 6.20.2.4 index_set_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef index_set<LO,HI> glucat::matrix_multi< Scalar_T, LO, HI >::index_set_t
```

Definition at line 139 of file matrix_multi.h.

#### 6.20.2.5 matrix_index_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef matrix_t::size_type glucat::matrix_multi< Scalar_T, LO, HI >::matrix_index_t  [private]
```

Definition at line 159 of file matrix_multi.h.

#### 6.20.2.6 matrix_multi_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef multivector_t glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi_t
```

Definition at line 137 of file matrix_multi.h.

#### 6.20.2.7 matrix_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef ublas::compressed_matrix< Scalar_T, orientation_t > glucat::matrix_multi< Scalar_T,
LO, HI >::matrix_t  [private]
```

Definition at line 157 of file matrix_multi.h.

#### 6.20.2.8 multivector_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef matrix_multi glucat::matrix_multi< Scalar_T, LO, HI >::multivector_t
```

Definition at line 136 of file matrix_multi.h.

#### 6.20.2.9 orientation_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef ublas::row_major glucat::matrix_multi< Scalar_T, LO, HI >::orientation_t  [private]
```

Definition at line 150 of file matrix_multi.h.

#### 6.20.2.10 scalar_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef Scalar_T glucat::matrix_multi< Scalar_T, LO, HI >::scalar_t
```

Definition at line 138 of file matrix_multi.h.

#### 6.20.2.11 term_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef std::pair<const index_set_t, Scalar_T> glucat::matrix_multi< Scalar_T, LO, HI >↩
::term_t
```

Definition at line 140 of file matrix_multi.h.

#### 6.20.2.12 vector_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef std::vector<Scalar_T> glucat::matrix_multi< Scalar_T, LO, HI >::vector_t
```

Definition at line 141 of file matrix_multi.h.

### 6.20.3 Constructor & Destructor Documentation

#### 6.20.3.1 ~matrix_multi()

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
glucat::matrix_multi< Scalar_T, LO, HI >::~matrix_multi ( )  [inline]
```

Destructor.

Definition at line 165 of file matrix_multi.h.

#### 6.20.3.2 matrix_multi() [1/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi ( )
```

Default constructor.

Definition at line 97 of file matrix_multi_imp.h.

References glucat::matrix_multi< Scalar_T, LO, HI >::m_matrix.

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi().

#### 6.20.3.3 matrix_multi() [2/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
template<typename Other_Scalar_T >
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const matrix_multi< Other_Scalar_T, LO, HI > & val )
```

Construct a multivector from a multivector with a different scalar type.

Definition at line 106 of file matrix_multi_imp.h.

References glucat::matrix_multi< Scalar_T, LO, HI >::m_matrix.

#### 6.20.3.4 matrix_multi() [3/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
template<typename Other_Scalar_T >
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const matrix_multi< Other_Scalar_T, LO, HI > & val,
            const index_set_t frm,
            const bool prechecked = false )
```

Construct a multivector, within a given frame, from a given multivector.

Definition at line 128 of file matrix_multi_imp.h.

References glucat::matrix_multi< Scalar_T, LO, HI >::m_frame, and glucat::matrix_multi< Scalar_T, LO, HI >::m_matrix.

#### 6.20.3.5 matrix_multi() [4/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const multivector_t & val,
            const index_set_t frm,
            const bool prechecked = false )
```

Construct a multivector, within a given frame, from a given multivector.

Definition at line 156 of file matrix_multi_imp.h.

References glucat::matrix_multi< Scalar_T, LO, HI >::m_frame, and glucat::matrix_multi< Scalar_T, LO, HI >::m_matrix.

#### 6.20.3.6 matrix_multi() [5/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const index_set_t ist,
            const Scalar_T & crd = Scalar_T(1) )
```

Construct a multivector from an index set and a scalar coordinate.

Definition at line 168 of file matrix_multi_imp.h.

References glucat::matrix_multi< Scalar_T, LO, HI >::m_frame, and glucat::matrix_multi< Scalar_T, LO, HI >::m_matrix.

#### 6.20.3.7 matrix_multi() [6/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const index_set_t ist,
            const Scalar_T & crd,
            const index_set_t frm,
            const bool prechecked = false )
```

Construct a multivector, within a given frame, from an index set and a scalar coordinate.

Definition at line 180 of file matrix_multi_imp.h.

References PyClical::ist, and glucat::matrix_multi< Scalar_T, LO, HI >::m_matrix.

#### 6.20.3.8 matrix_multi() [7/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const Scalar_T & scr,
            const index_set_t frm = index_set_t() )
```

Construct a multivector from a scalar (within a frame, if given)

Definition at line 194 of file matrix_multi_imp.h.

References glucat::matrix_multi< Scalar_T, LO, HI >::m_matrix.

#### 6.20.3.9 matrix_multi() [8/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const int scr,
            const index_set_t frm = index_set_t() )
```

Construct a multivector from an int (within a frame, if given)

Definition at line 206 of file matrix_multi_imp.h.

#### 6.20.3.10 matrix_multi() [9/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const vector_t & vec,
            const index_set_t frm,
            const bool prechecked = false )
```

Construct a multivector, within a given frame, from a given vector.

Definition at line 212 of file matrix_multi_imp.h.

References glucat::index_set< LO, HI >::count(), glucat::matrix_multi< Scalar_T, LO, HI >::m_matrix, glucat::index_set< LO, HI >::max(), and glucat::index_set< LO, HI >::min().

#### 6.20.3.11 matrix_multi() [10/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const std::string & str )
```

Construct a multivector from a string: eg: "3+2{1,2}-6.1e-2{2,3}".

Definition at line 239 of file matrix_multi_imp.h.

#### 6.20.3.12 matrix_multi() [11/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const std::string & str,
            const index_set_t frm,
            const bool prechecked = false )
```

Construct a multivector, within a given frame, from a string: eg: "3+2{1,2}-6.1e-2{2,3}".

Definition at line 245 of file matrix_multi_imp.h.

#### 6.20.3.13 matrix_multi() [12/17]

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const char * str )  [inline]
```

Construct a multivector from a char*: eg: "3+2{1,2}-6.1e-2{2,3}".

Definition at line 196 of file matrix_multi.h.

References glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi().

#### 6.20.3.14 matrix_multi() [13/17]

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const char * str,
            const index_set_t frm,
            const bool prechecked = false )  [inline]
```

Construct a multivector, within a given frame, from a char*: eg: "3+2{1,2}-6.1e-2{2,3}".

Definition at line 199 of file matrix_multi.h.

References glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi().

#### 6.20.3.15 matrix_multi() [14/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
template<typename Other_Scalar_T >
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const framed_multi< Other_Scalar_T, LO, HI > & val )
```

Construct a multivector from a framed_multi_t.

Definition at line 252 of file matrix_multi_imp.h.

References PyClical::e(), glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_↩ Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >::fast_size_threshold, glucat::matrix_multi< Scalar_T, LO, HI >::m_frame, and glucat::matrix_multi< Scalar_T, LO, HI >::m_matrix.

#### 6.20.3.16 matrix_multi() [15/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
template<typename Other_Scalar_T >
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const framed_multi< Other_Scalar_T, LO, HI > & val,
            const index_set_t frm,
            const bool prechecked = false )
```

Construct a multivector, within a given frame, from a framed_multi_t.

Definition at line 279 of file matrix_multi_imp.h.

References PyClical::e(), glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_↩ Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >::fast_size_threshold, and glucat::clifford_algebra< Scalar_T, index_set< LO, HI >, framed_multi< Scalar_T, LO, HI > >::frame().

#### 6.20.3.17 matrix_multi() [16/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
template<typename Matrix_T >
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const Matrix_T & mtx,
            const index_set_t frm )  [private]
```

Construct a multivector within a given frame from a given matrix.

Definition at line 307 of file matrix_multi_imp.h.

References glucat::matrix_multi< Scalar_T, LO, HI >::m_matrix.

#### 6.20.3.18 matrix_multi() [17/17]

```
template<typename Scalar_T , const index_t LO, const index_t HI>
glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi (
            const matrix_t & mtx,
            const index_set_t frm )  [private]
```

Construct a multivector within a given frame from a given matrix.

Definition at line 328 of file matrix_multi_imp.h.

### 6.20.4 Member Function Documentation

#### 6.20.4.1 basis_element()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI >::basis_matrix_t glucat::matrix_multi< Scalar_T, LO, HI
>::basis_element (
            const index_set< LO, HI > & ist ) const  [private]
```

Create a basis element matrix within the current frame.

Definition at line 1243 of file matrix_multi_imp.h.

References glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_↩ Threshold, Function_Precision >::basis_max_count, PyClical::e(), glucat::index_set< LO, HI >::fold(), glucat↩ ::gen::generator_table< Matrix_T >::generator(), PyClical::ist, glucat::index_set< LO, HI >::max(), glucat::index↩ _set< LO, HI >::min(), glucat::matrix::mono_prod(), and glucat::offset_level().

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::framed_multi().

#### 6.20.4.2 classname()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const std::string glucat::matrix_multi< Scalar_T, LO, HI >::classname ( )  [static]
```

Class name used in messages.

Definition at line 69 of file matrix_multi_imp.h.

#### 6.20.4.3 fast_framed_multi()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
template<typename Other_Scalar_T >
const framed_multi< Other_Scalar_T, LO, HI > glucat::matrix_multi< Scalar_T, LO, HI >::fast↩
_framed_multi ( ) const
```

Use inverse generalized FFT to construct a framed_multi_t.

Definition at line 1166 of file matrix_multi_imp.h.

References glucat::framed_multi< Scalar_T, LO, HI >::centre_pm4_qp4(), glucat::framed_multi< Scalar_T, LO, HI >::centre_pp4_qm4(), glucat::framed_multi< Scalar_T, LO, HI >::centre_qp1_pm1(), glucat::gen::offset_to_↩ super, glucat::pos_mod(), and glucat::framed_multi< Scalar_T, LO, HI >::unfold().

#### 6.20.4.4 fast_matrix_multi()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::matrix_multi< Scalar_T, LO, HI >::fast_↩
matrix_multi (
             const index_set_t frm ) const  [inline]
```

Use generalized FFT to construct a matrix_multi_t.

Definition at line 1153 of file matrix_multi_imp.h.

#### 6.20.4.5 operator+=()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
matrix_multi< Scalar_T, LO, HI > & glucat::matrix_multi< Scalar_T, LO, HI >::operator+= (
             const term_t & rhs )  [inline]
```

Add a term, if non-zero.

Geometric sum.

Geometric sum of multivector and scalar.

Definition at line 470 of file matrix_multi_imp.h.

#### 6.20.4.6 operator=()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
matrix_multi< Scalar_T, LO, HI > & glucat::matrix_multi< Scalar_T, LO, HI >::operator= (
             const multivector_t & rhs )
```

Assignment operator.

Definition at line 336 of file matrix_multi_imp.h.

References glucat::matrix_multi< Scalar_T, LO, HI >::m_frame, and glucat::matrix_multi< Scalar_T, LO, HI >↩ ::m_matrix.

#### 6.20.4.7 random()

```
template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::matrix_multi< Scalar_T, LO, HI >::random (
            const index_set_t frm,
            Scalar_T fill = Scalar_T(1) )  [static]
```

Random multivector within a frame.

Definition at line 996 of file matrix_multi_imp.h.

References PyClical::fill, and glucat::framed_multi< Scalar_T, LO, HI >::random().

### 6.20.5 Friends And Related Function Documentation

#### 6.20.5.1 framed_multi

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
friend class framed_multi  [friend]
```

Definition at line 145 of file matrix_multi.h.

#### 6.20.5.2 matrix_log

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
const matrix_multi<Other_Scalar_T,Other_LO,Other_HI> matrix_log (
            const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > & val,
            const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > & i )  [friend]
```

#### 6.20.5.3 matrix_multi

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
friend class matrix_multi  [friend]
```

Definition at line 147 of file matrix_multi.h.

#### 6.20.5.4 matrix_sqrt

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
const matrix_multi<Other_Scalar_T,Other_LO,Other_HI> matrix_sqrt (
            const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > & val,
            const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > & i )  [friend]
```

#### 6.20.5.5 operator &

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
const matrix_multi_t operator& (
            const matrix_multi_t & lhs,
            const matrix_multi_t & rhs )  [friend]
```

#### 6.20.5.6 operator%

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
const matrix_multi_t operator% (
            const matrix_multi_t & lhs,
            const matrix_multi_t & rhs )  [friend]
```

#### 6.20.5.7 operator∗

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
const matrix_multi_t operator* (
            const matrix_multi_t & lhs,
            const matrix_multi_t & rhs )  [friend]
```

#### 6.20.5.8 operator/

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
const matrix_multi_t operator/ (
            const matrix_multi_t & lhs,
            const matrix_multi_t & rhs )  [friend]
```

#### 6.20.5.9 operator<< [1/2]

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
std::ostream& operator<< (
            std::ostream & os,
            const multivector_t & val )  [friend]
```

#### 6.20.5.10 operator<< [2/2]

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
std::ostream& operator<< (
            std::ostream & os,
            const term_t & term )  [friend]
```

#### 6.20.5.11 operator>>

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
std::istream& operator>> (
            std::istream & s,
            multivector_t & val )  [friend]
```

#### 6.20.5.12 operator^

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
const matrix_multi_t operator^ (
            const matrix_multi_t & lhs,
            const matrix_multi_t & rhs )  [friend]
```

#### 6.20.5.13 operator"|

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
const matrix_multi_t operator| (
            const matrix_multi_t & lhs,
            const matrix_multi_t & rhs )  [friend]
```

#### 6.20.5.14 reframe

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
template<typename Other_Scalar_T , const index_t Other_LO, const index_t Other_HI>
const index_set<Other_LO,Other_HI> reframe (
            const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > & lhs,
            const matrix_multi< Other_Scalar_T, Other_LO, Other_HI > & rhs,
            matrix_multi< Other_Scalar_T, Other_LO, Other_HI > & lhs_reframed,
            matrix_multi< Other_Scalar_T, Other_LO, Other_HI > & rhs_reframed )  [friend]
```

#### 6.20.5.15 star

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
Scalar_T star (
            const matrix_multi_t & lhs,
            const matrix_multi_t & rhs )  [friend]
```

### 6.20.6 Member Data Documentation

#### 6.20.6.1 m_frame

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
index_set_t glucat::matrix_multi< Scalar_T, LO, HI >::m_frame  [private]
```

Index set representing the frame for the subalgebra which contains the multivector.

Definition at line 275 of file matrix_multi.h.

Referenced by glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi(), glucat::operator*(), glucat::operator/(), glucat::matrix_multi< Scalar_T, LO, HI >::operator=(), and glucat::reframe().

#### 6.20.6.2 m_matrix

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
matrix_t glucat::matrix_multi< Scalar_T, LO, HI >::m_matrix  [private]
```

Matrix value representing the multivector within the folded frame.

Definition at line 277 of file matrix_multi.h.

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::framed_multi(), glucat::matrix_multi< Scalar_T, LO, HI >::matrix_multi(), glucat::operator*(), and glucat::matrix_multi< Scalar_T, LO, HI >::operator=().

The documentation for this class was generated from the following files:

- glucat/framed_multi.h
- glucat/matrix_multi.h
- glucat/matrix_multi_imp.h

## 6.21 std::numeric_limits< glucat::framed_multi< Scalar_T, LO, HI > > Struct Template Reference

Numeric limits for framed_multi inherit limits for the corresponding scalar type.

`#include <framed_multi.h>`

Inheritance diagram for std::numeric_limits< glucat::framed_multi< Scalar_T, LO, HI > >:




Collaboration diagram for std::numeric_limits< glucat::framed_multi< Scalar_T, LO, HI > >:




### 6.21.1 Detailed Description

**template<typename Scalar_T, const glucat::index_t LO, const glucat::index_t HI>**
**struct std::numeric_limits< glucat::framed_multi< Scalar_T, LO, HI > >**

Numeric limits for framed_multi inherit limits for the corresponding scalar type.

Definition at line 374 of file framed_multi.h.

The documentation for this struct was generated from the following file:

- glucat/framed_multi.h

## 6.22 std::numeric_limits< glucat::matrix_multi< Scalar_T, LO, HI > > Struct Template Reference

Numeric limits for matrix_multi inherit limits for the corresponding scalar type.

`#include <matrix_multi.h>`

Inheritance diagram for std::numeric_limits< glucat::matrix_multi< Scalar_T, LO, HI > >:




Collaboration diagram for std::numeric_limits< glucat::matrix_multi< Scalar_T, LO, HI > >:




### 6.22.1 Detailed Description

**template<typename Scalar_T, const glucat::index_t LO, const glucat::index_t HI>**
**struct std::numeric_limits< glucat::matrix_multi< Scalar_T, LO, HI > >**

Numeric limits for matrix_multi inherit limits for the corresponding scalar type.

Definition at line 293 of file matrix_multi.h.

The documentation for this struct was generated from the following file:

- glucat/matrix_multi.h

## 6.23 glucat::numeric_traits< Scalar_T > Class Template Reference

Extra traits which extend numeric limits.

`#include <scalar.h>`

### Classes

- struct demoted

  *Demoted type for long double.*
- struct promoted

  *Promoted type.*

### Public Member Functions

- template<>
  long double pi ()

  *Pi for long double.*
- template<>
  long double ln_2 ()

  *log(2) for long double*
- template<>
  float to_scalar_t (const Other_Scalar_T &val)

  *Extra traits which extend numeric limits.*
- template<>
  double to_scalar_t (const Other_Scalar_T &val)

  *Cast to double.*
- template<>
  long double to_scalar_t (const dd_real &val)

  *Cast to long double.*
- template<>
  long double to_scalar_t (const qd_real &val)

  *Cast to long double.*
- template<>
  dd_real to_scalar_t (const long double &val)

  *Cast to dd_real.*
- template<>
  dd_real to_scalar_t (const qd_real &val)

  *Cast to dd_real.*
- template<>
  qd_real to_scalar_t (const long double &val)

  *Cast to qd_real.*
- template<>
  qd_real to_scalar_t (const dd_real &val)

  *Cast to qd_real.*

### Static Public Member Functions

- static bool isInf (const Scalar_T &val)
  *Smart isinf.*
- static bool isNaN (const Scalar_T &val)
  *Smart isnan.*
- static bool isNaN_or_isInf (const Scalar_T &val)
  *Smart isnan or isinf.*
- static Scalar_T NaN ()
  *Smart NaN.*
- static int to_int (const Scalar_T &val)
  *Cast to int.*
- static double to_double (const Scalar_T &val)
  *Cast to double.*
- template<typename Other_Scalar_T >
  static Scalar_T to_scalar_t (const Other_Scalar_T &val)
  *Cast to Scalar_T.*
- static Scalar_T fmod (const Scalar_T &lhs, const Scalar_T &rhs)
  *Modulo function for scalar.*
- static Scalar_T conj (const Scalar_T &val)
  *Complex conjugate of scalar.*
- static Scalar_T real (const Scalar_T &val)
  *Real part of scalar.*
- static Scalar_T imag (const Scalar_T &val)
  *Imaginary part of scalar.*
- static Scalar_T abs (const Scalar_T &val)
  *Absolute value of scalar.*
- static Scalar_T pi ()
  *Pi.*
- static Scalar_T ln_2 ()
  *log(2)*
- static Scalar_T pow (const Scalar_T &val, int n)
  *Integer power.*
- static Scalar_T sqrt (const Scalar_T &val)
  *Square root of scalar.*
- static Scalar_T exp (const Scalar_T &val)
  *Exponential.*
- static Scalar_T log (const Scalar_T &val)
  *Logarithm of scalar.*
- static Scalar_T log2 (const Scalar_T &val)
  *Log base 2.*
- static Scalar_T cos (const Scalar_T &val)
  *Cosine of scalar.*
- static Scalar_T acos (const Scalar_T &val)
  *Inverse cosine of scalar.*
- static Scalar_T cosh (const Scalar_T &val)
  *Hyperbolic cosine of scalar.*
- static Scalar_T sin (const Scalar_T &val)
  *Sine of scalar.*
- static Scalar_T asin (const Scalar_T &val)
  *Inverse sine of scalar.*

- static Scalar_T sinh (const Scalar_T &val)

  *Hyperbolic sine of scalar.*
- static Scalar_T tan (const Scalar_T &val)

  *Tangent of scalar.*
- static Scalar_T atan (const Scalar_T &val)

  *Inverse tangent of scalar.*
- static Scalar_T tanh (const Scalar_T &val)

  *Hyperbolic tangent of scalar.*

### Static Private Member Functions

- static bool isInf (const Scalar_T &val, bool_to_type< false >)

  *Smart isinf specialised for Scalar_T without infinity.*
- static bool isInf (const Scalar_T &val, bool_to_type< true >)

  *Smart isinf specialised for Scalar_T with infinity.*
- static bool isNaN (const Scalar_T &val, bool_to_type< false >)

  *Smart isnan specialised for Scalar_T without quiet NaN.*
- static bool isNaN (const Scalar_T &val, bool_to_type< true >)

  *Smart isnan specialised for Scalar_T with quiet NaN.*

## 6.23.1 Detailed Description

**template<typename Scalar_T>**
**class glucat::numeric_traits< Scalar_T >**

Extra traits which extend numeric limits.

Definition at line 46 of file scalar.h.

## 6.23.2 Member Function Documentation

### 6.23.2.1 abs()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::abs (
            const Scalar_T & val )  [inline], [static]
```

Absolute value of scalar.

Definition at line 181 of file scalar.h.

References UBLAS_ABS.

#### 6.23.2.2 acos()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::acos (
            const Scalar_T & val )  [inline], [static]
```

Inverse cosine of scalar.

Definition at line 244 of file scalar.h.

References glucat::acos().

#### 6.23.2.3 asin()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::asin (
            const Scalar_T & val )  [inline], [static]
```

Inverse sine of scalar.

Definition at line 265 of file scalar.h.

References glucat::asin().

#### 6.23.2.4 atan()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::atan (
            const Scalar_T & val )  [inline], [static]
```

Inverse tangent of scalar.

Definition at line 286 of file scalar.h.

References glucat::atan().

#### 6.23.2.5 conj()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::conj (
            const Scalar_T & val )  [inline], [static]
```

Complex conjugate of scalar.

Definition at line 160 of file scalar.h.

#### 6.23.2.6 cos()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::cos (
            const Scalar_T & val )  [inline], [static]
```

Cosine of scalar.

Definition at line 237 of file scalar.h.

References glucat::cos().

#### 6.23.2.7 cosh()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::cosh (
            const Scalar_T & val )  [inline], [static]
```

Hyperbolic cosine of scalar.

Definition at line 251 of file scalar.h.

References glucat::cosh().

#### 6.23.2.8 exp()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::exp (
            const Scalar_T & val )  [inline], [static]
```

Exponential.

Definition at line 216 of file scalar.h.

References glucat::exp().

#### 6.23.2.9 fmod()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::fmod (
            const Scalar_T & lhs,
            const Scalar_T & rhs )  [inline], [static]
```

Modulo function for scalar.

Definition at line 153 of file scalar.h.

#### 6.23.2.10 imag()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::imag (
            const Scalar_T & val )  [inline], [static]
```

Imaginary part of scalar.

Definition at line 174 of file scalar.h.

#### 6.23.2.11 isInf() [1/3]

```
template<typename Scalar_T >
static bool glucat::numeric_traits< Scalar_T >::isInf (
            const Scalar_T & val,
            bool_to_type< false >  )  [inline], [static], [private]
```

Smart isinf specialised for Scalar_T without infinity.

Definition at line 53 of file scalar.h.

Referenced by glucat::numeric_traits< Scalar_T >::isInf(), and glucat::numeric_traits< Scalar_T >::isNaN_or_↩ isInf().

#### 6.23.2.12 isInf() [2/3]

```
template<typename Scalar_T >
static bool glucat::numeric_traits< Scalar_T >::isInf (
            const Scalar_T & val,
            bool_to_type< true >  )  [inline], [static], [private]
```

Smart isinf specialised for Scalar_T with infinity.

Definition at line 60 of file scalar.h.

References _GLUCAT_ISINF.

#### 6.23.2.13 isInf() [3/3]

```
template<typename Scalar_T >
static bool glucat::numeric_traits< Scalar_T >::isInf (
            const Scalar_T & val )  [inline], [static]
```

Smart isinf.

Definition at line 82 of file scalar.h.

References glucat::numeric_traits< Scalar_T >::isInf().

#### 6.23.2.14 isNaN() [1/3]

```
template<typename Scalar_T >
static bool glucat::numeric_traits< Scalar_T >::isNaN (
            const Scalar_T & val,
            bool_to_type< false >  )  [inline], [static], [private]
```

Smart isnan specialised for Scalar_T without quiet NaN.

Definition at line 67 of file scalar.h.

Referenced by glucat::numeric_traits< Scalar_T >::isNaN(), and glucat::numeric_traits< Scalar_T >::isNaN_or↩ _isInf().

#### 6.23.2.15 isNaN() [2/3]

```
template<typename Scalar_T >
static bool glucat::numeric_traits< Scalar_T >::isNaN (
            const Scalar_T & val,
            bool_to_type< true >  )  [inline], [static], [private]
```

Smart isnan specialised for Scalar_T with quiet NaN.

Definition at line 74 of file scalar.h.

References _GLUCAT_ISNAN.

#### 6.23.2.16 isNaN() [3/3]

```
template<typename Scalar_T >
static bool glucat::numeric_traits< Scalar_T >::isNaN (
            const Scalar_T & val )  [inline], [static]
```

Smart isnan.

Definition at line 92 of file scalar.h.

References glucat::numeric_traits< Scalar_T >::isNaN().

#### 6.23.2.17 isNaN_or_isInf()

```
template<typename Scalar_T >
static bool glucat::numeric_traits< Scalar_T >::isNaN_or_isInf (
            const Scalar_T & val )  [inline], [static]
```

Smart isnan or isinf.

Definition at line 102 of file scalar.h.

References glucat::numeric_traits< Scalar_T >::isInf(), and glucat::numeric_traits< Scalar_T >::isNaN().

#### 6.23.2.18 ln_2() [1/2]

```
template<>
long double glucat::numeric_traits< long double >::ln_2 ( )  [inline]
```

log(2) for long double

Definition at line 83 of file long_double.h.

References glucat::l_ln2.

#### 6.23.2.19 ln_2() [2/2]

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::ln_2 ( )  [inline], [static]
```

log(2)

Definition at line 195 of file scalar.h.

Referenced by glucat::numeric_traits< Scalar_T >::log2().

#### 6.23.2.20 log()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::log (
            const Scalar_T & val )  [inline], [static]
```

Logarithm of scalar.

Definition at line 223 of file scalar.h.

References glucat::log().

Referenced by glucat::numeric_traits< Scalar_T >::log2().

#### 6.23.2.21 log2()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::log2 (
            const Scalar_T & val )  [inline], [static]
```

Log base 2.

Definition at line 230 of file scalar.h.

References glucat::numeric_traits< Scalar_T >::ln_2(), and glucat::numeric_traits< Scalar_T >::log().

Referenced by glucat::log2().

#### 6.23.2.22 NaN()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::NaN ( )  [inline], [static]
```

Smart NaN.

Definition at line 114 of file scalar.h.

References glucat::log().

Referenced by glucat::matrix::trace().

#### 6.23.2.23 pi() [1/2]

```
template<>
long double glucat::numeric_traits< long double >::pi ( )  [inline]
```

Pi for long double.

Definition at line 75 of file long_double.h.

References glucat::l_pi.

#### 6.23.2.24 pi() [2/2]

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::pi ( )  [inline], [static]
```

Pi.

Definition at line 188 of file scalar.h.

Referenced by glucat::matrix::classify_eigenvalues().

#### 6.23.2.25 pow()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::pow (
            const Scalar_T & val,
            int n )  [inline], [static]
```

Integer power.

Definition at line 202 of file scalar.h.

References glucat::pow().

#### 6.23.2.26 real()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::real (
            const Scalar_T & val )  [inline], [static]
```

Real part of scalar.

Definition at line 167 of file scalar.h.

#### 6.23.2.27 sin()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::sin (
            const Scalar_T & val )  [inline], [static]
```

Sine of scalar.

Definition at line 258 of file scalar.h.

References glucat::sin().

#### 6.23.2.28 sinh()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::sinh (
            const Scalar_T & val )  [inline], [static]
```

Hyperbolic sine of scalar.

Definition at line 272 of file scalar.h.

References glucat::sinh().

#### 6.23.2.29 sqrt()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::sqrt (
            const Scalar_T & val )  [inline], [static]
```

Square root of scalar.

Definition at line 209 of file scalar.h.

References UBLAS_SQRT.

Referenced by glucat::abs().

#### 6.23.2.30 tan()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::tan (
            const Scalar_T & val )  [inline], [static]
```

Tangent of scalar.

Definition at line 279 of file scalar.h.

References glucat::tan().

#### 6.23.2.31 tanh()

```
template<typename Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::tanh (
            const Scalar_T & val )  [inline], [static]
```

Hyperbolic tangent of scalar.

Definition at line 293 of file scalar.h.

References glucat::tanh().

#### 6.23.2.32 to_double()

```
template<typename Scalar_T >
static double glucat::numeric_traits< Scalar_T >::to_double (
            const Scalar_T & val )  [inline], [static]
```

Cast to double.

Definition at line 132 of file scalar.h.

Referenced by glucat::operator<<(), and glucat::numeric_traits< Scalar_T >::to_scalar_t().

#### 6.23.2.33 to_int()

```
template<typename Scalar_T >
static int glucat::numeric_traits< Scalar_T >::to_int (
            const Scalar_T & val )  [inline], [static]
```

Cast to int.

Definition at line 125 of file scalar.h.

#### 6.23.2.34 to_scalar_t() [1/9]

```
template<>
float glucat::numeric_traits< float >::to_scalar_t (
            const Other_Scalar_T & val )  [inline]
```

Extra traits which extend numeric limits.

Cast to float

Definition at line 52 of file scalar_imp.h.

References glucat::numeric_traits< Scalar_T >::to_double().

#### 6.23.2.35 to_scalar_t() [2/9]

```
template<>
double glucat::numeric_traits< double >::to_scalar_t (
            const Other_Scalar_T & val )  [inline]
```

Cast to double.

Definition at line 61 of file scalar_imp.h.

References glucat::numeric_traits< Scalar_T >::to_double().

#### 6.23.2.36 to_scalar_t() [3/9]

```
template<>
long double glucat::numeric_traits< long double >::to_scalar_t (
            const dd_real & val )  [inline]
```

Cast to long double.

Definition at line 71 of file scalar_imp.h.

#### 6.23.2.37 to_scalar_t() [4/9]

```
template<>
long double glucat::numeric_traits< long double >::to_scalar_t (
            const qd_real & val )  [inline]
```

Cast to long double.

Definition at line 80 of file scalar_imp.h.

#### 6.23.2.38 to_scalar_t() [5/9]

```
template<>
dd_real glucat::numeric_traits< dd_real >::to_scalar_t (
            const long double & val )  [inline]
```

Cast to dd_real.

Definition at line 89 of file scalar_imp.h.

#### 6.23.2.39 to_scalar_t() [6/9]

```
template<>
dd_real glucat::numeric_traits< dd_real >::to_scalar_t (
            const qd_real & val )  [inline]
```

Cast to dd_real.

Definition at line 98 of file scalar_imp.h.

#### 6.23.2.40 to_scalar_t() [7/9]

```
template<>
qd_real glucat::numeric_traits< qd_real >::to_scalar_t (
            const long double & val )  [inline]
```

Cast to qd_real.

Definition at line 107 of file scalar_imp.h.

#### 6.23.2.41 to_scalar_t() [8/9]

```
template<>
qd_real glucat::numeric_traits< qd_real >::to_scalar_t (
            const dd_real & val )  [inline]
```

Cast to qd_real.

Definition at line 116 of file scalar_imp.h.

#### 6.23.2.42 to_scalar_t() [9/9]

```
template<typename Scalar_T >
template<typename Other_Scalar_T >
static Scalar_T glucat::numeric_traits< Scalar_T >::to_scalar_t (
            const Other_Scalar_T & val )  [inline], [static]
```

Cast to Scalar_T.

Definition at line 140 of file scalar.h.

Referenced by glucat::matrix::nork_range(), glucat::to_demote(), and glucat::to_promote().

The documentation for this class was generated from the following file:

- glucat/scalar.h

## 6.24 glucat::numeric_traits< Scalar_T >::promoted Struct Reference

Promoted type.

```
#include <scalar.h>
```

### Public Types

- typedef double type

### 6.24.1 Detailed Description

**template<typename Scalar_T>**
**struct glucat::numeric_traits< Scalar_T >::promoted**

Promoted type.

Definition at line 144 of file scalar.h.

### 6.24.2 Member Typedef Documentation

#### 6.24.2.1 type

```
template<typename Scalar_T >
typedef double glucat::numeric_traits< Scalar_T >::promoted::type
```

Definition at line 144 of file scalar.h.

The documentation for this struct was generated from the following file:

- glucat/scalar.h

## 6.25 glucat::random_generator< Scalar_T > Class Template Reference

Random number generator with single instance per Scalar_T.

`#include <random.h>`

### Public Member Functions

- Scalar_T uniform ()
- Scalar_T normal ()

### Static Public Member Functions

- static random_generator & generator ()

  *Single instance of Random number generator.*

### Private Member Functions

- random_generator (const random_generator &)
- random_generator & operator= (const random_generator &)
- random_generator ()
- ~random_generator ()

### Private Attributes

- std::mt19937 uint_gen
- std::uniform_real_distribution< double > uniform_dist
- std::normal_distribution< double > normal_dist

### Static Private Attributes

- static const unsigned long seed = 19590921UL

### Friends

- class friend_for_private_destructor

### 6.25.1 Detailed Description

**template<typename Scalar_T>**
**class glucat::random_generator< Scalar_T >**

Random number generator with single instance per Scalar_T.

Definition at line 47 of file random.h.

### 6.25.2 Constructor & Destructor Documentation

#### 6.25.2.1 random_generator() [1/2]

```
template<typename Scalar_T >
glucat::random_generator< Scalar_T >::random_generator (
            const random_generator< Scalar_T > & ) [private]
```

#### 6.25.2.2 random_generator() [2/2]

```
template<typename Scalar_T >
glucat::random_generator< Scalar_T >::random_generator ( ) [inline], [private]
```

Definition at line 83 of file random.h.

References glucat::random_generator< Scalar_T >::seed.

#### 6.25.2.3 ~random_generator()

```
template<typename Scalar_T >
glucat::random_generator< Scalar_T >::~random_generator ( ) [inline], [private]
```

Definition at line 87 of file random.h.

### 6.25.3 Member Function Documentation

#### 6.25.3.1 generator()

```
template<typename Scalar_T >
static random_generator& glucat::random_generator< Scalar_T >::generator ( ) [inline], [static]
```

Single instance of Random number generator.

Definition at line 51 of file random.h.

#### 6.25.3.2 normal()

```
template<typename Scalar_T >
Scalar_T glucat::random_generator< Scalar_T >::normal ( )  [inline]
```

Definition at line 93 of file random.h.

References glucat::random_generator< Scalar_T >::normal_dist.

#### 6.25.3.3 operator=()

```
template<typename Scalar_T >
random_generator& glucat::random_generator< Scalar_T >::operator= (
            const random_generator< Scalar_T > &  )  [private]
```

#### 6.25.3.4 uniform()

```
template<typename Scalar_T >
Scalar_T glucat::random_generator< Scalar_T >::uniform ( )  [inline]
```

Definition at line 91 of file random.h.

References glucat::random_generator< Scalar_T >::uniform_dist.

### 6.25.4 Friends And Related Function Documentation

#### 6.25.4.1 friend_for_private_destructor

```
template<typename Scalar_T >
friend class friend_for_private_destructor  [friend]
```

Friend declaration to avoid compiler warning: "... only defines a private destructor and has no friends" Ref: Carlos O'Ryan, ACE http://doc.ece.uci.edu

Definition at line 56 of file random.h.

### 6.25.5 Member Data Documentation

#### 6.25.5.1 normal_dist

```
template<typename Scalar_T >
std::normal_distribution<double> glucat::random_generator< Scalar_T >::normal_dist  [private]
```

Definition at line 81 of file random.h.

Referenced by glucat::random_generator< Scalar_T >::normal().

#### 6.25.5.2 seed

```
template<typename Scalar_T >
const unsigned long glucat::random_generator< Scalar_T >::seed = 19590921UL  [static], [private]
```

Definition at line 59 of file random.h.

Referenced by glucat::random_generator< Scalar_T >::random_generator().

#### 6.25.5.3 uint_gen

```
template<typename Scalar_T >
std::mt19937 glucat::random_generator< Scalar_T >::uint_gen  [private]
```

Definition at line 79 of file random.h.

#### 6.25.5.4 uniform_dist

```
template<typename Scalar_T >
std::uniform_real_distribution<double> glucat::random_generator< Scalar_T >::uniform_dist
[private]
```

Definition at line 80 of file random.h.

Referenced by glucat::random_generator< Scalar_T >::uniform().

The documentation for this class was generated from the following file:

- glucat/random.h

## 6.26 glucat::index_set< LO, HI >::reference Class Reference

Index set member reference.

`#include <index_set.h>`

Collaboration diagram for glucat::index_set< LO, HI >::reference:




### Public Member Functions

- reference (index_set_t &ist, index_t idx)
  *index_set reference*
- ~reference ()
- reference & operator= (const bool x)
  *for b[i] = x;*
- reference & operator= (const reference &j)
  *for b[i] = b[j];*
- bool operator~ () const
  *Flips a bit.*
- operator bool () const
  *for x = b[i];*
- reference & flip ()
  *for b[i].flip();*

### Private Member Functions

- reference ()
  *Private default constructor is left undefined.*

### Private Attributes

- index_set_t * m_pst
- index_t m_idx

### Friends

- class index_set

## 6.26.1 Detailed Description

**template<const index_t LO, const index_t HI>**
**class glucat::index_set< LO, HI >::reference**

Index set member reference.

Definition at line 177 of file index_set.h.

## 6.26.2 Constructor & Destructor Documentation

### 6.26.2.1 reference() [1/2]

```
template<const index_t LO, const index_t HI>
glucat::index_set< LO, HI >::reference::reference ( )  [private]
```

Private default constructor is left undefined.

### 6.26.2.2 reference() [2/2]

```
template<const index_t LO, const index_t HI>
glucat::index_set< LO, HI >::reference::reference (
            index_set_t & ist,
            index_t idx )  [inline]
```

index_set reference

Definition at line 983 of file index_set_imp.h.

#### 6.26.2.3 ~reference()

```
template<const index_t LO, const index_t HI>
glucat::index_set< LO, HI >::reference::~reference ( )  [inline]
```

Definition at line 184 of file index_set.h.

### 6.26.3 Member Function Documentation

#### 6.26.3.1 flip()

```
template<const index_t LO, const index_t HI>
index_set< LO, HI >::reference & glucat::index_set< LO, HI >::reference::flip ( )  [inline]
```

for b[i].flip();

Definition at line 1036 of file index_set_imp.h.

References glucat::index_set< LO, HI >::reference::flip().

Referenced by glucat::index_set< LO, HI >::reference::flip().

#### 6.26.3.2 operator bool()

```
template<const index_t LO, const index_t HI>
glucat::index_set< LO, HI >::reference::operator bool ( ) const  [inline]
```

for x = b[i];

Definition at line 1028 of file index_set_imp.h.

#### 6.26.3.3 operator=() [1/2]

```
template<const index_t LO, const index_t HI>
index_set< LO, HI >::reference & glucat::index_set< LO, HI >::reference::operator= (
            const bool x )  [inline]
```

for b[i] = x;

Definition at line 993 of file index_set_imp.h.

#### 6.26.3.4 operator=() [2/2]

```
template<const index_t LO, const index_t HI>
index_set< LO, HI >::reference & glucat::index_set< LO, HI >::reference::operator= (
            const reference & j )  [inline]
```

for b[i] = b[j];

Definition at line 1007 of file index_set_imp.h.

References glucat::index_set< LO, HI >::reference::m_idx, and glucat::index_set< LO, HI >::reference::m_pst.

#### 6.26.3.5 operator~()

```
template<const index_t LO, const index_t HI>
bool glucat::index_set< LO, HI >::reference::operator~ ( ) const  [inline]
```

Flips a bit.

flips the bit

Definition at line 1021 of file index_set_imp.h.

### 6.26.4 Friends And Related Function Documentation

#### 6.26.4.1 index_set

```
template<const index_t LO, const index_t HI>
friend class index_set  [friend]
```

Definition at line 178 of file index_set.h.

### 6.26.5 Member Data Documentation

#### 6.26.5.1 m_idx

```
template<const index_t LO, const index_t HI>
index_t glucat::index_set< LO, HI >::reference::m_idx  [private]
```

Definition at line 198 of file index_set.h.

Referenced by glucat::index_set< LO, HI >::reference::operator=().

#### 6.26.5.2 m_pst

```
template<const index_t LO, const index_t HI>
index_set_t* glucat::index_set< LO, HI >::reference::m_pst  [private]
```

Definition at line 197 of file index_set.h.

Referenced by glucat::index_set< LO, HI >::reference::operator=().

The documentation for this class was generated from the following files:

- glucat/index_set.h
- glucat/index_set_imp.h

## 6.27 glucat::sorted_range< Map_T, Sorted_Map_T > Class Template Reference

Sorted range for use with output.

```
#include <framed_multi_imp.h>
```

### Public Types

- typedef Map_T map_t
- typedef Sorted_Map_T sorted_map_t
- typedef Sorted_Map_T::const_iterator sorted_iterator

### Public Member Functions

- sorted_range (Sorted_Map_T &sorted_val, const Map_T &val)

### Public Attributes

- sorted_iterator sorted_begin
- sorted_iterator sorted_end

### 6.27.1 Detailed Description

**template<typename Map_T, typename Sorted_Map_T>**
**class glucat::sorted_range< Map_T, Sorted_Map_T >**

Sorted range for use with output.

Definition at line 1326 of file framed_multi_imp.h.

### 6.27.2 Member Typedef Documentation

#### 6.27.2.1 map_t

```
template<typename Map_T, typename Sorted_Map_T>
typedef Map_T glucat::sorted_range< Map_T, Sorted_Map_T >::map_t
```

Definition at line 1329 of file framed_multi_imp.h.

#### 6.27.2.2 sorted_iterator

```
template<typename Map_T, typename Sorted_Map_T>
typedef Sorted_Map_T::const_iterator glucat::sorted_range< Map_T, Sorted_Map_T >::sorted_iterator
```

Definition at line 1331 of file framed_multi_imp.h.

#### 6.27.2.3 sorted_map_t

```
template<typename Map_T, typename Sorted_Map_T>
typedef Sorted_Map_T glucat::sorted_range< Map_T, Sorted_Map_T >::sorted_map_t
```

Definition at line 1330 of file framed_multi_imp.h.

### 6.27.3 Constructor & Destructor Documentation

#### 6.27.3.1 sorted_range()

```
template<typename Map_T, typename Sorted_Map_T>
glucat::sorted_range< Map_T, Sorted_Map_T >::sorted_range (
            Sorted_Map_T & sorted_val,
            const Map_T & val )  [inline]
```

Definition at line 1333 of file framed_multi_imp.h.

References glucat::sorted_range< Map_T, Sorted_Map_T >::sorted_begin, and glucat::sorted_range< Map_T, Sorted_Map_T >::sorted_end.

### 6.27.4 Member Data Documentation

#### 6.27.4.1 sorted_begin

```
template<typename Map_T, typename Sorted_Map_T>
sorted_iterator glucat::sorted_range< Map_T, Sorted_Map_T >::sorted_begin
```

Definition at line 1343 of file framed_multi_imp.h.

Referenced by glucat::operator<<(), and glucat::sorted_range< Map_T, Sorted_Map_T >::sorted_range().

#### 6.27.4.2 sorted_end

```
template<typename Map_T, typename Sorted_Map_T>
sorted_iterator glucat::sorted_range< Map_T, Sorted_Map_T >::sorted_end
```

Definition at line 1344 of file framed_multi_imp.h.

Referenced by glucat::operator<<(), and glucat::sorted_range< Map_T, Sorted_Map_T >::sorted_range().

The documentation for this class was generated from the following file:

- glucat/framed_multi_imp.h

## 6.28 glucat::sorted_range< Sorted_Map_T, Sorted_Map_T > Class Template Reference

```
#include <framed_multi_imp.h>
```

### Public Types

- typedef Sorted_Map_T map_t
- typedef Sorted_Map_T sorted_map_t
- typedef Sorted_Map_T::const_iterator sorted_iterator

### Public Member Functions

- sorted_range (Sorted_Map_T &sorted_val, const Sorted_Map_T &val)

### Public Attributes

- sorted_iterator sorted_begin
- sorted_iterator sorted_end

### 6.28.1 Detailed Description

**template<typename Sorted_Map_T>**
**class glucat::sorted_range< Sorted_Map_T, Sorted_Map_T >**

Definition at line 1348 of file framed_multi_imp.h.

## 6.28.2 Member Typedef Documentation

### 6.28.2.1 map_t

```
template<typename Sorted_Map_T >
typedef Sorted_Map_T glucat::sorted_range< Sorted_Map_T, Sorted_Map_T >::map_t
```

Definition at line 1351 of file framed_multi_imp.h.

### 6.28.2.2 sorted_iterator

```
template<typename Sorted_Map_T >
typedef Sorted_Map_T::const_iterator glucat::sorted_range< Sorted_Map_T, Sorted_Map_T >↩
::sorted_iterator
```

Definition at line 1353 of file framed_multi_imp.h.

### 6.28.2.3 sorted_map_t

```
template<typename Sorted_Map_T >
typedef Sorted_Map_T glucat::sorted_range< Sorted_Map_T, Sorted_Map_T >::sorted_map_t
```

Definition at line 1352 of file framed_multi_imp.h.

## 6.28.3 Constructor & Destructor Documentation

### 6.28.3.1 sorted_range()

```
template<typename Sorted_Map_T >
glucat::sorted_range< Sorted_Map_T, Sorted_Map_T >::sorted_range (
            Sorted_Map_T & sorted_val,
            const Sorted_Map_T & val )  [inline]
```

Definition at line 1355 of file framed_multi_imp.h.

## 6.28.4 Member Data Documentation

#### 6.28.4.1 sorted_begin

```
template<typename Sorted_Map_T >
sorted_iterator glucat::sorted_range< Sorted_Map_T, Sorted_Map_T >::sorted_begin
```

Definition at line 1359 of file framed_multi_imp.h.

#### 6.28.4.2 sorted_end

```
template<typename Sorted_Map_T >
sorted_iterator glucat::sorted_range< Sorted_Map_T, Sorted_Map_T >::sorted_end
```

Definition at line 1360 of file framed_multi_imp.h.

The documentation for this class was generated from the following file:

- glucat/framed_multi_imp.h

## 6.29 glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision > Struct Template Reference

Tuning policy.

```
#include <global.h>
```

### Public Types

- enum { mult_matrix_threshold = Mult_Matrix_Threshold }
  *Minimum index count needed to invoke matrix multiplication algorithm.*
- enum { div_max_steps = Div_Max_Steps }
  *Maximum steps of iterative refinement in division algorithm.*
- enum { sqrt_max_steps = Sqrt_Max_Steps }
  *Maximum number of steps in square root iteration.*
- enum { log_max_outer_steps = Log_Max_Outer_Steps }
  *Maximum number of incomplete square roots in cascade log algorithm.*
- enum { log_max_inner_steps = Log_Max_Inner_Steps }
  *Maximum number of steps in incomplete square root within cascade log algorithm.*
- enum { basis_max_count = Basis_Max_Count }
  *Maximum index count of folded frames in basis cache.*
- enum { fast_size_threshold = Fast_Size_Threshold }
  *Minimum map size needed to invoke generalized FFT.*
- enum { inv_fast_dim_threshold = Inv_Fast_Dim_Threshold }
  *Minimum matrix dimension needed to invoke inverse generalized FFT.*
- enum { products_size_threshold = Products_Size_Threshold }
  *Minimum size needed for to invoke faster products algorithms.*

**Static Public Attributes**

- static const precision_t function_precision = Function_Precision

  *Precision used for exp, log and sqrt functions.*

### 6.29.1 Detailed Description

**template<unsigned int Mult_Matrix_Threshold = DEFAULT_Mult_Matrix_Threshold, unsigned int Div_Max_Steps = DEFAULT_↩ Div_Max_Steps, unsigned int Sqrt_Max_Steps = DEFAULT_Sqrt_Max_Steps, unsigned int Log_Max_Outer_Steps = DEFAULT_↩ Log_Max_Outer_Steps, unsigned int Log_Max_Inner_Steps = DEFAULT_Log_Max_Inner_Steps, unsigned int Basis_Max_Count = DEFAULT_Basis_Max_Count, unsigned int Fast_Size_Threshold = DEFAULT_Fast_Size_Threshold, unsigned int Inv_Fast_Dim↩ _Threshold = DEFAULT_Inv_Fast_Dim_Threshold, unsigned int Products_Size_Threshold = DEFAULT_Products_Size_Threshold, precision_t Function_Precision = DEFAULT_Function_Precision>**
**struct glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >**

Tuning policy.

Definition at line 151 of file global.h.

### 6.29.2 Member Enumeration Documentation

#### 6.29.2.1 anonymous enum

```
template<unsigned int Mult_Matrix_Threshold = DEFAULT_Mult_Matrix_Threshold, unsigned int
Div_Max_Steps = DEFAULT_Div_Max_Steps, unsigned int Sqrt_Max_Steps = DEFAULT_Sqrt_Max_Steps,
unsigned int Log_Max_Outer_Steps = DEFAULT_Log_Max_Outer_Steps, unsigned int Log_Max_Inner_↩
Steps = DEFAULT_Log_Max_Inner_Steps, unsigned int Basis_Max_Count = DEFAULT_Basis_Max_Count,
unsigned int Fast_Size_Threshold = DEFAULT_Fast_Size_Threshold, unsigned int Inv_Fast_Dim_↩
Threshold = DEFAULT_Inv_Fast_Dim_Threshold, unsigned int Products_Size_Threshold = DEFAULT_↩
Products_Size_Threshold, precision_t Function_Precision = DEFAULT_Function_Precision>
anonymous enum
```

Minimum matrix dimension needed to invoke inverse generalized FFT.

**Enumerator**

| | |
|---|---|
| inv_fast_dim_threshold | |

Definition at line 174 of file global.h.

#### 6.29.2.2 anonymous enum

```
template<unsigned int Mult_Matrix_Threshold = DEFAULT_Mult_Matrix_Threshold, unsigned int
Div_Max_Steps = DEFAULT_Div_Max_Steps, unsigned int Sqrt_Max_Steps = DEFAULT_Sqrt_Max_Steps,
```

```
unsigned int Log_Max_Outer_Steps = DEFAULT_Log_Max_Outer_Steps, unsigned int Log_Max_Inner_↩
Steps = DEFAULT_Log_Max_Inner_Steps, unsigned int Basis_Max_Count = DEFAULT_Basis_Max_Count,
unsigned int Fast_Size_Threshold = DEFAULT_Fast_Size_Threshold, unsigned int Inv_Fast_Dim_↩
Threshold = DEFAULT_Inv_Fast_Dim_Threshold, unsigned int Products_Size_Threshold = DEFAULT_↩
Products_Size_Threshold, precision_t Function_Precision = DEFAULT_Function_Precision>
anonymous enum
```

Minimum size needed for to invoke faster products algorithms.

**Enumerator**

| | |
|---|---|
| products_size_threshold | |

Definition at line 177 of file global.h.

#### 6.29.2.3 anonymous enum

```
template<unsigned int Mult_Matrix_Threshold = DEFAULT_Mult_Matrix_Threshold, unsigned int
Div_Max_Steps = DEFAULT_Div_Max_Steps, unsigned int Sqrt_Max_Steps = DEFAULT_Sqrt_Max_Steps,
unsigned int Log_Max_Outer_Steps = DEFAULT_Log_Max_Outer_Steps, unsigned int Log_Max_Inner_↩
Steps = DEFAULT_Log_Max_Inner_Steps, unsigned int Basis_Max_Count = DEFAULT_Basis_Max_Count,
unsigned int Fast_Size_Threshold = DEFAULT_Fast_Size_Threshold, unsigned int Inv_Fast_Dim_↩
Threshold = DEFAULT_Inv_Fast_Dim_Threshold, unsigned int Products_Size_Threshold = DEFAULT_↩
Products_Size_Threshold, precision_t Function_Precision = DEFAULT_Function_Precision>
anonymous enum
```

Minimum index count needed to invoke matrix multiplication algorithm.

**Enumerator**

| | |
|---|---|
| mult_matrix_threshold | |

Definition at line 155 of file global.h.

#### 6.29.2.4 anonymous enum

```
template<unsigned int Mult_Matrix_Threshold = DEFAULT_Mult_Matrix_Threshold, unsigned int
Div_Max_Steps = DEFAULT_Div_Max_Steps, unsigned int Sqrt_Max_Steps = DEFAULT_Sqrt_Max_Steps,
unsigned int Log_Max_Outer_Steps = DEFAULT_Log_Max_Outer_Steps, unsigned int Log_Max_Inner_↩
Steps = DEFAULT_Log_Max_Inner_Steps, unsigned int Basis_Max_Count = DEFAULT_Basis_Max_Count,
unsigned int Fast_Size_Threshold = DEFAULT_Fast_Size_Threshold, unsigned int Inv_Fast_Dim_↩
Threshold = DEFAULT_Inv_Fast_Dim_Threshold, unsigned int Products_Size_Threshold = DEFAULT_↩
Products_Size_Threshold, precision_t Function_Precision = DEFAULT_Function_Precision>
anonymous enum
```

Maximum steps of iterative refinement in division algorithm.

**Enumerator**

| |
|---|
| div_max_steps | |

Definition at line 158 of file global.h.

#### 6.29.2.5 anonymous enum

```
template<unsigned int Mult_Matrix_Threshold = DEFAULT_Mult_Matrix_Threshold, unsigned int
Div_Max_Steps = DEFAULT_Div_Max_Steps, unsigned int Sqrt_Max_Steps = DEFAULT_Sqrt_Max_Steps,
unsigned int Log_Max_Outer_Steps = DEFAULT_Log_Max_Outer_Steps, unsigned int Log_Max_Inner_↩
Steps = DEFAULT_Log_Max_Inner_Steps, unsigned int Basis_Max_Count = DEFAULT_Basis_Max_Count,
unsigned int Fast_Size_Threshold = DEFAULT_Fast_Size_Threshold, unsigned int Inv_Fast_Dim_↩
Threshold = DEFAULT_Inv_Fast_Dim_Threshold, unsigned int Products_Size_Threshold = DEFAULT_↩
Products_Size_Threshold, precision_t Function_Precision = DEFAULT_Function_Precision>
anonymous enum
```

Maximum number of steps in square root iteration.

**Enumerator**

| |
|---|
| sqrt_max_steps | |

Definition at line 161 of file global.h.

#### 6.29.2.6 anonymous enum

```
template<unsigned int Mult_Matrix_Threshold = DEFAULT_Mult_Matrix_Threshold, unsigned int
Div_Max_Steps = DEFAULT_Div_Max_Steps, unsigned int Sqrt_Max_Steps = DEFAULT_Sqrt_Max_Steps,
unsigned int Log_Max_Outer_Steps = DEFAULT_Log_Max_Outer_Steps, unsigned int Log_Max_Inner_↩
Steps = DEFAULT_Log_Max_Inner_Steps, unsigned int Basis_Max_Count = DEFAULT_Basis_Max_Count,
unsigned int Fast_Size_Threshold = DEFAULT_Fast_Size_Threshold, unsigned int Inv_Fast_Dim_↩
Threshold = DEFAULT_Inv_Fast_Dim_Threshold, unsigned int Products_Size_Threshold = DEFAULT_↩
Products_Size_Threshold, precision_t Function_Precision = DEFAULT_Function_Precision>
anonymous enum
```

Maximum number of incomplete square roots in cascade log algorithm.

**Enumerator**

| |
|---|
| log_max_outer_steps | |

Definition at line 164 of file global.h.

#### 6.29.2.7 anonymous enum

```
template<unsigned int Mult_Matrix_Threshold = DEFAULT_Mult_Matrix_Threshold, unsigned int
Div_Max_Steps = DEFAULT_Div_Max_Steps, unsigned int Sqrt_Max_Steps = DEFAULT_Sqrt_Max_Steps,
unsigned int Log_Max_Outer_Steps = DEFAULT_Log_Max_Outer_Steps, unsigned int Log_Max_Inner_↩
Steps = DEFAULT_Log_Max_Inner_Steps, unsigned int Basis_Max_Count = DEFAULT_Basis_Max_Count,
unsigned int Fast_Size_Threshold = DEFAULT_Fast_Size_Threshold, unsigned int Inv_Fast_Dim_↩
Threshold = DEFAULT_Inv_Fast_Dim_Threshold, unsigned int Products_Size_Threshold = DEFAULT_↩
Products_Size_Threshold, precision_t Function_Precision = DEFAULT_Function_Precision>
anonymous enum
```

Maximum number of steps in incomplete square root within cascade log algorithm.

**Enumerator**

| | |
|---|---|
| log_max_inner_steps | |

Definition at line 166 of file global.h.

#### 6.29.2.8 anonymous enum

```
template<unsigned int Mult_Matrix_Threshold = DEFAULT_Mult_Matrix_Threshold, unsigned int
Div_Max_Steps = DEFAULT_Div_Max_Steps, unsigned int Sqrt_Max_Steps = DEFAULT_Sqrt_Max_Steps,
unsigned int Log_Max_Outer_Steps = DEFAULT_Log_Max_Outer_Steps, unsigned int Log_Max_Inner_↩
Steps = DEFAULT_Log_Max_Inner_Steps, unsigned int Basis_Max_Count = DEFAULT_Basis_Max_Count,
unsigned int Fast_Size_Threshold = DEFAULT_Fast_Size_Threshold, unsigned int Inv_Fast_Dim_↩
Threshold = DEFAULT_Inv_Fast_Dim_Threshold, unsigned int Products_Size_Threshold = DEFAULT_↩
Products_Size_Threshold, precision_t Function_Precision = DEFAULT_Function_Precision>
anonymous enum
```

Maximum index count of folded frames in basis cache.

**Enumerator**

| | |
|---|---|
| basis_max_count | |

Definition at line 169 of file global.h.

#### 6.29.2.9 anonymous enum

```
template<unsigned int Mult_Matrix_Threshold = DEFAULT_Mult_Matrix_Threshold, unsigned int
Div_Max_Steps = DEFAULT_Div_Max_Steps, unsigned int Sqrt_Max_Steps = DEFAULT_Sqrt_Max_Steps,
unsigned int Log_Max_Outer_Steps = DEFAULT_Log_Max_Outer_Steps, unsigned int Log_Max_Inner_↩
Steps = DEFAULT_Log_Max_Inner_Steps, unsigned int Basis_Max_Count = DEFAULT_Basis_Max_Count,
unsigned int Fast_Size_Threshold = DEFAULT_Fast_Size_Threshold, unsigned int Inv_Fast_Dim_↩
Threshold = DEFAULT_Inv_Fast_Dim_Threshold, unsigned int Products_Size_Threshold = DEFAULT_↩
Products_Size_Threshold, precision_t Function_Precision = DEFAULT_Function_Precision>
anonymous enum
```

Minimum map size needed to invoke generalized FFT.

**Enumerator**

| | |
|---|---|
| fast_size_threshold | |

Definition at line 172 of file global.h.

### 6.29.3 Member Data Documentation

#### 6.29.3.1 function_precision

```
template<unsigned int Mult_Matrix_Threshold = DEFAULT_Mult_Matrix_Threshold, unsigned int
Div_Max_Steps = DEFAULT_Div_Max_Steps, unsigned int Sqrt_Max_Steps = DEFAULT_Sqrt_Max_Steps,
unsigned int Log_Max_Outer_Steps = DEFAULT_Log_Max_Outer_Steps, unsigned int Log_Max_Inner_↩
Steps = DEFAULT_Log_Max_Inner_Steps, unsigned int Basis_Max_Count = DEFAULT_Basis_Max_Count,
unsigned int Fast_Size_Threshold = DEFAULT_Fast_Size_Threshold, unsigned int Inv_Fast_Dim_↩
Threshold = DEFAULT_Inv_Fast_Dim_Threshold, unsigned int Products_Size_Threshold = DEFAULT_↩
Products_Size_Threshold, precision_t Function_Precision = DEFAULT_Function_Precision>
const precision_t glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log↩
_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim↩
_Threshold, Products_Size_Threshold, Function_Precision >::function_precision = Function_↩
Precision  [static]
```

Precision used for exp, log and sqrt functions.

Definition at line 180 of file global.h.

Referenced by glucat::exp(), glucat::log(), and glucat::sqrt().

The documentation for this struct was generated from the following file:

- glucat/global.h

## 6.30 glucat::framed_multi< Scalar_T, LO, HI >::var_term Class Reference

Variable term.

Inheritance diagram for glucat::framed_multi< Scalar_T, LO, HI >::var_term:



Collaboration diagram for glucat::framed_multi< Scalar_T, LO, HI >::var_term:




## Public Types

- typedef std::pair< index_set< LO, HI >, Scalar_T > var_pair_t

## Public Member Functions

- ~var_term ()

  *Destructor.*
- var_term ()

  *Default constructor.*
- var_term (const index_set_t ist, const Scalar_T &crd=Scalar_T(1))

  *Construct a variable term from an index set and a scalar coordinate.*
- var_term_t & operator*= (const term_t &rhs)

  *Product of variable term and term.*

## Static Public Member Functions

- static const std::string classname ()

  *Class name used in messages.*

### 6.30.1 Detailed Description

**template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAULT_HI>**
**class glucat::framed_multi< Scalar_T, LO, HI >::var_term**

Variable term.

Definition at line 308 of file framed_multi.h.

### 6.30.2 Member Typedef Documentation

#### 6.30.2.1 var_pair_t

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
typedef std::pair<index_set<LO,HI>, Scalar_T> glucat::framed_multi< Scalar_T, LO, HI ><↩
::var_term::var_pair_t
```

Definition at line 312 of file framed_multi.h.

### 6.30.3 Constructor & Destructor Documentation

#### 6.30.3.1 ~var_term()

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
glucat::framed_multi< Scalar_T, LO, HI >::var_term::~var_term ( )  [inline]
```

Destructor.

Definition at line 318 of file framed_multi.h.

#### 6.30.3.2 var_term() [1/2]

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
glucat::framed_multi< Scalar_T, LO, HI >::var_term::var_term ( )  [inline]
```

Default constructor.

Definition at line 320 of file framed_multi.h.

#### 6.30.3.3 var_term() [2/2]

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
glucat::framed_multi< Scalar_T, LO, HI >::var_term::var_term (
            const index_set_t ist,
            const Scalar_T & crd = Scalar_T(1) )  [inline]
```

Construct a variable term from an index set and a scalar coordinate.

Definition at line 324 of file framed_multi.h.

### 6.30.4 Member Function Documentation

#### 6.30.4.1 classname()

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
static const std::string glucat::framed_multi< Scalar_T, LO, HI >::var_term::classname ( )
[inline], [static]
```

Class name used in messages.

Definition at line 315 of file framed_multi.h.

#### 6.30.4.2 operator*=()

```
template<typename Scalar_T = double, const index_t LO = DEFAULT_LO, const index_t HI = DEFAU↩
LT_HI>
var_term_t& glucat::framed_multi< Scalar_T, LO, HI >::var_term::operator*= (
            const term_t & rhs )  [inline]
```

Product of variable term and term.

Definition at line 328 of file framed_multi.h.

The documentation for this class was generated from the following file:

- glucat/framed_multi.h

# Chapter 7

# File Documentation

## 7.1 glucat/clifford_algebra.h File Reference

```
#include <string>
#include <utility>
#include <vector>
```

Include dependency graph for clifford_algebra.h:



This graph shows which files directly or indirectly include this file:




## Classes

- class glucat::clifford_algebra< Scalar_T, Index_Set_T, Multivector_T >

  *clifford_algebra<> declares the operations of a Clifford algebra*

## Namespaces

- glucat

## Macros

- #define _GLUCAT_CLIFFORD_ALGEBRA_OPERATIONS

## Functions

- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  bool glucat::operator!= (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Test for inequality of multivectors.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  bool glucat::operator!= (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar_T &scr)

  *Test for inequality of multivector and scalar.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  bool glucat::operator!= (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)

  *Test for inequality of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator+ (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar_T &scr)

  *Geometric sum of multivector and scalar.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator+ (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)

  *Geometric sum of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator+ (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Geometric sum.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator- (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar_T &scr)

  *Geometric difference of multivector and scalar.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator- (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)

  *Geometric difference of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator- (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Geometric difference.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator* (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar_T &scr)

  *Product of multivector and scalar.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator* (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)

  *Product of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator* (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Geometric product.*

- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator^ (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Outer product.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator & (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Inner product.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator% (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Left contraction.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::star (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Hestenes scalar product.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator/ (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar_T &scr)

  *Quotient of multivector and scalar.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator/ (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)

  *Quotient of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator/ (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Geometric quotient.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator| (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Transformation via twisted adjoint action.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::inv (const Multivector< Scalar_T, LO, HI > &val)

  *Geometric multiplicative inverse.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::pow (const Multivector< Scalar_T, LO, HI > &lhs, int rhs)

  *Integer power of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::pow (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Multivector power of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::outer_pow (const Multivector< Scalar_T, LO, HI > &lhs, int rhs)

*Outer product power of multivector.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::scalar (const Multivector< Scalar_T, LO, HI > &val)

  *Scalar part.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::real (const Multivector< Scalar_T, LO, HI > &val)

  *Real part: synonym for scalar part.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::imag (const Multivector< Scalar_T, LO, HI > &val)

  *Imaginary part: deprecated (always 0)*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::pure (const Multivector< Scalar_T, LO, HI > &val)

  *Pure part.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::even (const Multivector< Scalar_T, LO, HI > &val)

  *Even part.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::odd (const Multivector< Scalar_T, LO, HI > &val)

  *Odd part.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const std::vector< Scalar_T > glucat::vector_part (const Multivector< Scalar_T, LO, HI > &val)

  *Vector part of multivector, as a vector_t with respect to frame()*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::involute (const Multivector< Scalar_T, LO, HI > &val)

  *Main involution, each {i} is replaced by -{i} in each term, eg. {1}∗{2} -> (-{2})∗(-{1})*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::reverse (const Multivector< Scalar_T, LO, HI > &val)

  *Reversion, eg. {1}∗{2} -> {2}∗{1}.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::conj (const Multivector< Scalar_T, LO, HI > &val)

  *Conjugation, rev o invo == invo o rev.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::quad (const Multivector< Scalar_T, LO, HI > &val)

  *Scalar_T quadratic form == (rev(x)∗x)(0)*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::norm (const Multivector< Scalar_T, LO, HI > &val)

  *Scalar_T norm == sum of norm of coordinates.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::abs (const Multivector< Scalar_T, LO, HI > &val)

  *Absolute value == sqrt(norm)*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::max_abs (const Multivector< Scalar_T, LO, HI > &val)

  *Maximum of absolute values of components of multivector: multivector infinity norm.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::complexifier (const Multivector< Scalar_T, LO, HI > &val)

  *Square root of -1 which commutes with all members of the frame of the given multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::elliptic (const Multivector< Scalar_T, LO, HI > &val)
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::sqrt (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Square root of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::sqrt (const Multivector< Scalar_T, LO, HI > &val)

  *Square root of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::clifford_exp (const Multivector< Scalar_T, LO, HI > &val)

  *Exponential of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::log (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Natural logarithm of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::log (const Multivector< Scalar_T, LO, HI > &val)

  *Natural logarithm of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::cos (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Cosine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::cos (const Multivector< Scalar_T, LO, HI > &val)

  *Cosine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::acos (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse cosine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::acos (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse cosine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::cosh (const Multivector< Scalar_T, LO, HI > &val)

  *Hyperbolic cosine of multivector.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::acosh (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse hyperbolic cosine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::acosh (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse hyperbolic cosine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::sin (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Sine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::sin (const Multivector< Scalar_T, LO, HI > &val)

  *Sine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::asin (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse sine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::asin (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse sine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::sinh (const Multivector< Scalar_T, LO, HI > &val)

  *Hyperbolic sine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::asinh (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse hyperbolic sine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::asinh (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse hyperbolic sine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::tan (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Tangent of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::tan (const Multivector< Scalar_T, LO, HI > &val)

  *Tangent of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::atan (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse tangent of multivector with specified complexifier.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::atan (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse tangent of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::tanh (const Multivector< Scalar_T, LO, HI > &val)

  *Hyperbolic tangent of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::atanh (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse hyperbolic tangent of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::atanh (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse hyperbolic tangent of multivector.*

### 7.1.1 Macro Definition Documentation

#### 7.1.1.1 _GLUCAT_CLIFFORD_ALGEBRA_OPERATIONS

```
#define _GLUCAT_CLIFFORD_ALGEBRA_OPERATIONS
```

Definition at line 134 of file clifford_algebra.h.

## 7.2 glucat/clifford_algebra_imp.h File Reference

```
#include <glucat/clifford_algebra.h>
#include <glucat/scalar.h>
```

Include dependency graph for clifford_algebra_imp.h:



This graph shows which files directly or indirectly include this file:




## Namespaces

- glucat

## Functions

- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  bool glucat::operator!= (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)
  *Test for inequality of multivectors.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  bool glucat::operator!= (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar_T &scr)
  *Test for inequality of multivector and scalar.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  bool glucat::operator!= (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)
  *Test for inequality of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator+ (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar_T &scr)
  *Geometric sum of multivector and scalar.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator+ (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)
  *Geometric sum of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator+ (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

*Geometric sum.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator- (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar_T &scr)

  *Geometric difference of multivector and scalar.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator- (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)

  *Geometric difference of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator- (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Geometric difference.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator* (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar_T &scr)

  *Product of multivector and scalar.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator* (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)

  *Product of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator* (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Geometric product.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator^ (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Outer product.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator & (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Inner product.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator% (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Left contraction.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::star (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Hestenes scalar product.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator/ (const Multivector< Scalar_T, LO, HI > &lhs, const Scalar_T &scr)

  *Quotient of multivector and scalar.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator/ (const Scalar_T &scr, const Multivector< Scalar_T, LO, HI > &rhs)

  *Quotient of scalar and multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator/ (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Geometric quotient.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::operator| (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Transformation via twisted adjoint action.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::inv (const Multivector< Scalar_T, LO, HI > &val)

  *Geometric multiplicative inverse.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::pow (const Multivector< Scalar_T, LO, HI > &lhs, int rhs)

  *Integer power of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, template< typename, const index_t, const index_t > class RHS, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::pow (const Multivector< Scalar_T, LO, HI > &lhs, const RHS< Scalar_T, LO, HI > &rhs)

  *Multivector power of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::outer_pow (const Multivector< Scalar_T, LO, HI > &lhs, int rhs)

  *Outer product power of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::scalar (const Multivector< Scalar_T, LO, HI > &val)

  *Scalar part.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::real (const Multivector< Scalar_T, LO, HI > &val)

  *Real part: synonym for scalar part.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::imag (const Multivector< Scalar_T, LO, HI > &val)

  *Imaginary part: deprecated (always 0)*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::pure (const Multivector< Scalar_T, LO, HI > &val)

  *Pure part.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::even (const Multivector< Scalar_T, LO, HI > &val)

  *Even part.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::odd (const Multivector< Scalar_T, LO, HI > &val)

  *Odd part.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const std::vector< Scalar_T > glucat::vector_part (const Multivector< Scalar_T, LO, HI > &val)

  *Vector part of multivector, as a vector_t with respect to frame()*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::involute (const Multivector< Scalar_T, LO, HI > &val)

  *Main involution, each {i} is replaced by -{i} in each term, eg. {1}*{2} -> (-{2})*(-{1})*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::reverse (const Multivector< Scalar_T, LO, HI > &val)

  *Reversion, eg. {1}*{2} -> {2}*{1}.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::conj (const Multivector< Scalar_T, LO, HI > &val)

  *Conjugation, rev o invo == invo o rev.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::quad (const Multivector< Scalar_T, LO, HI > &val)

  *Scalar_T quadratic form == (rev(x)*x)(0)*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::norm (const Multivector< Scalar_T, LO, HI > &val)

  *Scalar_T norm == sum of norm of coordinates.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::abs (const Multivector< Scalar_T, LO, HI > &val)

  *Absolute value == sqrt(norm)*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::max_abs (const Multivector< Scalar_T, LO, HI > &val)

  *Maximum of absolute values of components of multivector: multivector infinity norm.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::complexifier (const Multivector< Scalar_T, LO, HI > &val)

  *Square root of -1 which commutes with all members of the frame of the given multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::elliptic (const Multivector< Scalar_T, LO, HI > &val)
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  static void glucat::check_complex (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Check that i is a valid complexifier for val.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::sqrt (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Square root of multivector with specified complexifier.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::sqrt (const Multivector< Scalar_T, LO, HI > &val)

  *Square root of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::clifford_exp (const Multivector< Scalar_T, LO, HI > &val)

  *Exponential of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::log (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Natural logarithm of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::log (const Multivector< Scalar_T, LO, HI > &val)

  *Natural logarithm of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::cosh (const Multivector< Scalar_T, LO, HI > &val)

  *Hyperbolic cosine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::acosh (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse hyperbolic cosine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::acosh (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse hyperbolic cosine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::cos (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Cosine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::cos (const Multivector< Scalar_T, LO, HI > &val)

  *Cosine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::acos (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse cosine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::acos (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse cosine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::sinh (const Multivector< Scalar_T, LO, HI > &val)

  *Hyperbolic sine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::asinh (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

*Inverse hyperbolic sine of multivector with specified complexifier.*

- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::asinh (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse hyperbolic sine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::sin (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Sine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::sin (const Multivector< Scalar_T, LO, HI > &val)

  *Sine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::asin (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse sine of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::asin (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse sine of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::tanh (const Multivector< Scalar_T, LO, HI > &val)

  *Hyperbolic tangent of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::atanh (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse hyperbolic tangent of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::atanh (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse hyperbolic tangent of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::tan (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Tangent of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::tan (const Multivector< Scalar_T, LO, HI > &val)

  *Tangent of multivector.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::atan (const Multivector< Scalar_T, LO, HI > &val, const Multivector< Scalar_T, LO, HI > &i, const bool prechecked=false)

  *Inverse tangent of multivector with specified complexifier.*
- template<template< typename, const index_t, const index_t > class Multivector, typename Scalar_T , const index_t LO, const index_t HI>
  const Multivector< Scalar_T, LO, HI > glucat::atan (const Multivector< Scalar_T, LO, HI > &val)

  *Inverse tangent of multivector.*

## 7.3 glucat/errors.h File Reference

```
#include <string>
#include <exception>
#include <stdexcept>
```

Include dependency graph for errors.h:




This graph shows which files directly or indirectly include this file:




### Classes

- class glucat::glucat_error
  *Abstract exception class.*
- class glucat::error< Class_T >
  *Specific exception class.*

### Namespaces

- glucat

## 7.4 glucat/errors_imp.h File Reference

This graph shows which files directly or indirectly include this file:




### Namespaces

- glucat

## 7.5 glucat/framed_multi.h File Reference

```
#include "glucat/global.h"
#include "glucat/errors.h"
#include "glucat/clifford_algebra.h"
#include <string>
#include <utility>
#include <map>
#include <vector>
#include <unordered_map>
```

Include dependency graph for framed_multi.h:



This graph shows which files directly or indirectly include this file:




## Classes

- class glucat::framed_multi< Scalar_T, LO, HI >

  *A framed_multi<Scalar_T,LO,HI> is a framed approximation to a multivector.*
- class glucat::matrix_multi< Scalar_T, LO, HI >

  *A matrix_multi<Scalar_T,LO,HI> is a matrix approximation to a multivector.*
- class glucat::index_set_hash< LO, HI >
- class glucat::framed_multi< Scalar_T, LO, HI >

  *A framed_multi<Scalar_T,LO,HI> is a framed approximation to a multivector.*
- class glucat::framed_multi< Scalar_T, LO, HI >::hash_size_t
- class glucat::framed_multi< Scalar_T, LO, HI >::var_term

  *Variable term.*
- struct std::numeric_limits< glucat::framed_multi< Scalar_T, LO, HI > >

  *Numeric limits for framed_multi inherit limits for the corresponding scalar type.*

## Namespaces

- glucat
- std

## Macros

- #define _GLUCAT_MAP_IS_HASH

## Functions

- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::operator* (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Geometric product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::operator^ (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Outer product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::operator & (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Inner product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::operator% (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Left contraction.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::star (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Hestenes scalar product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::operator/ (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Geometric quotient.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::operator| (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Transformation via twisted adjoint action.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  std::istream & glucat::operator>> (std::istream &s, framed_multi< Scalar_T, LO, HI > &val)

  *Read multivector from input.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  std::ostream & glucat::operator<< (std::ostream &os, const framed_multi< Scalar_T, LO, HI > &val)

  *Write multivector to output.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  std::ostream & glucat::operator<< (std::ostream &os, const std::pair< const index_set< LO, HI >, Scalar_T > &term)

  *Write term to output.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::exp (const framed_multi< Scalar_T, LO, HI > &val)

  *Exponential of multivector.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  static Scalar_T glucat::crd_of_mult (const std::pair< const index_set< LO, HI >, Scalar_T > &lhs, const std::pair< const index_set< LO, HI >, Scalar_T > &rhs)

  *Coordinate of product of terms.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const std::pair< const index_set< LO, HI >, Scalar_T > glucat::operator* (const std::pair< const index_set< LO, HI >, Scalar_T > &lhs, const std::pair< const index_set< LO, HI >, Scalar_T > &rhs)

*Product of terms.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::sqrt (const framed_multi< Scalar_T, LO, HI > &val, const framed_multi< Scalar_T, LO, HI > &i, bool prechecked)

  *Square root of multivector with specified complexifier.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::log (const framed_multi< Scalar_T, LO, HI > &val, const framed_multi< Scalar_T, LO, HI > &i, bool prechecked)

  *Natural logarithm of multivector with specified complexifier.*

### 7.5.1 Macro Definition Documentation

#### 7.5.1.1 _GLUCAT_MAP_IS_HASH

```
#define _GLUCAT_MAP_IS_HASH
```

Definition at line 55 of file framed_multi.h.

## 7.6 glucat/framed_multi_imp.h File Reference

```
#include "glucat/framed_multi.h"
#include "glucat/random.h"
#include <sstream>
#include <fstream>
```

Include dependency graph for framed_multi_imp.h:



This graph shows which files directly or indirectly include this file:




## Classes

- class glucat::sorted_range< Map_T, Sorted_Map_T >

  *Sorted range for use with output.*
- class glucat::sorted_range< Sorted_Map_T, Sorted_Map_T >

## Namespaces

- glucat

## Macros

- #define _GLUCAT_HASH_N(x)
- #define _GLUCAT_HASH_SIZE_T(x)

## Functions

- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::operator* (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Geometric product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::operator^ (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Outer product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::operator & (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Inner product.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::operator% (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Left contraction.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::star (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Hestenes scalar product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::operator/ (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Geometric quotient.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::operator| (const framed_multi< Scalar_T, LO, HI > &lhs, const framed_multi< Scalar_T, LO, HI > &rhs)

  *Transformation via twisted adjoint action.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  std::ostream & glucat::operator<< (std::ostream &os, const framed_multi< Scalar_T, LO, HI > &val)

  *Write multivector to output.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  std::ostream & glucat::operator<< (std::ostream &os, const std::pair< const index_set< LO, HI >, Scalar_T > &term)

  *Write term to output.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  std::istream & glucat::operator>> (std::istream &s, framed_multi< Scalar_T, LO, HI > &val)

  *Read multivector from input.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  static Scalar_T glucat::crd_of_mult (const std::pair< const index_set< LO, HI >, Scalar_T > &lhs, const std::pair< const index_set< LO, HI >, Scalar_T > &rhs)

  *Coordinate of product of terms.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const std::pair< const index_set< LO, HI >, Scalar_T > glucat::operator* (const std::pair< const index_set< LO, HI >, Scalar_T > &lhs, const std::pair< const index_set< LO, HI >, Scalar_T > &rhs)

  *Product of terms.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::sqrt (const framed_multi< Scalar_T, LO, HI > &val, const framed_multi< Scalar_T, LO, HI > &i, bool prechecked)

  *Square root of multivector with specified complexifier.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::exp (const framed_multi< Scalar_T, LO, HI > &val)

  *Exponential of multivector.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const framed_multi< Scalar_T, LO, HI > glucat::log (const framed_multi< Scalar_T, LO, HI > &val, const framed_multi< Scalar_T, LO, HI > &i, bool prechecked)

  *Natural logarithm of multivector with specified complexifier.*

### 7.6.1 Macro Definition Documentation

#### 7.6.1.1 _GLUCAT_HASH_N

```
#define _GLUCAT_HASH_N(
              x )
```

Definition at line 60 of file framed_multi_imp.h.

#### 7.6.1.2 _GLUCAT_HASH_SIZE_T

```
#define _GLUCAT_HASH_SIZE_T(
              x )
```

Definition at line 61 of file framed_multi_imp.h.

Referenced by glucat::framed_multi< Scalar_T, LO, HI >::framed_multi(), glucat::operator &(), glucat::operator%(), glucat::operator*(), and glucat::operator^().

## 7.7 glucat/generation.h File Reference

```
#include <utility>
#include <map>
#include <vector>
```

Include dependency graph for generation.h:



This graph shows which files directly or indirectly include this file:




## Classes

- class glucat::gen::generator_table< Matrix_T >

  *Table of generators for specific signatures.*

## Namespaces

- glucat
- glucat::gen

## Typedefs

- typedef std::pair< index_t, index_t > glucat::gen::signature_t

  *A signature is a pair of indices, p, q, with p == frame.max(), q == -frame.min()*

## Variables

- static const index_t glucat::gen::offset_to_super [ ] = {0,-1, 0,-1,-2, 3, 2, 1}

  *Offsets between the current signature and that of the real superalgebra.*

## 7.8 glucat/generation_imp.h File Reference

```
#include "glucat/generation.h"
#include "glucat/matrix.h"
```

Include dependency graph for generation_imp.h:




This graph shows which files directly or indirectly include this file:




### Namespaces

- glucat
- glucat::gen

## 7.9 glucat/global.h File Reference

```
#include "glucat/portability.h"
#include <limits>
```

`#include <climits>`
Include dependency graph for global.h:




This graph shows which files directly or indirectly include this file:




## Classes

- struct glucat::CTAssertion< bool >

  *Compile time assertion.*
- struct glucat::CTAssertion< true >

- class glucat::compare_types< LHS_T, RHS_T >

  *Type comparison.*
- class glucat::compare_types< T, T >
- class glucat::bool_to_type< truth_value >

  *Bool to type.*
- struct glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Ste

  *Tuning policy.*

## Namespaces

- glucat

## Macros

- #define _GLUCAT_CTAssert(expr, msg) namespace { struct msg { glucat::CTAssertion<(expr)> ERROR↩ _##msg; }; }

## Typedefs

- typedef int glucat::index_t

  *Size of index_t should be enough to represent LO, HI.*
- typedef unsigned long glucat::set_value_t

  *Size of set_value_t should be enough to contain index_set<LO,HI>*

## Enumerations

- enum glucat::precision_t { glucat::precision_demoted, glucat::precision_same, glucat::precision_promoted }

  *Precision policy.*

## Functions

- glucat::_GLUCAT_CTAssert (std::numeric_limits< unsigned char >::radix==2, CannotDetermineBitsPer↩ Char) const index_t BITS_PER_CHAR

  *If radix of unsigned char is not 2, we can't easily determine number of bits from sizeof.*
- glucat::_GLUCAT_CTAssert (_GLUCAT_BITS_PER_ULONG==BITS_PER_SET_VALUE, BitsPerULong↩ DoesNotMatchSetValueT) const index_t DEFAULT_LO

  *Default lowest index in an index set.*
- template<typename LHS_T , typename RHS_T >
  LHS_T glucat::pos_mod (LHS_T lhs, RHS_T rhs)

  *Modulo function which works reliably for lhs < 0.*

### Variables

- const double glucat::MS_PER_S = 1000.0

  *Timing constant: deprecated here - moved to test/timing.h.*
- const index_t glucat::BITS_PER_SET_VALUE = std::numeric_limits<set_value_t>::digits

  *Number of bits in set_value_t.*
- const index_t glucat::DEFAULT_HI = index_t(BITS_PER_SET_VALUE / 2)

  *Default highest index in an index set.*
- const double glucat::DEFAULT_TRUNCATION = std::numeric_limits<float>::epsilon()

  *Default for truncation.*
- const unsigned int glucat::DEFAULT_Mult_Matrix_Threshold = 8
- const unsigned int glucat::DEFAULT_Div_Max_Steps = 4
- const unsigned int glucat::DEFAULT_Sqrt_Max_Steps = 256
- const unsigned int glucat::DEFAULT_Log_Max_Outer_Steps = 256
- const unsigned int glucat::DEFAULT_Log_Max_Inner_Steps = 32
- const unsigned int glucat::DEFAULT_Basis_Max_Count = 12
- const unsigned int glucat::DEFAULT_Fast_Size_Threshold = 1 << 6
- const unsigned int glucat::DEFAULT_Inv_Fast_Dim_Threshold = 1 << 3
- const unsigned int glucat::DEFAULT_Products_Size_Threshold = 1 << 22
- const precision_t glucat::DEFAULT_Function_Precision = precision_same

### 7.9.1 Macro Definition Documentation

#### 7.9.1.1 _GLUCAT_CTAssert

```
#define _GLUCAT_CTAssert(
              expr,
              msg ) namespace { struct msg { glucat::CTAssertion<(expr)> ERROR_##msg; }; }
```

Definition at line 48 of file global.h.

## 7.10 glucat/glucat.h File Reference

```
#include "glucat/portability.h"
#include "glucat/global.h"
#include "glucat/errors.h"
#include "glucat/index_set.h"
#include "glucat/scalar.h"
#include "glucat/long_double.h"
#include "glucat/qd.h"
#include "glucat/clifford_algebra.h"
#include "glucat/framed_multi.h"
#include "glucat/generation.h"
#include "glucat/matrix.h"
```

```
#include "glucat/matrix_multi.h"
```

Include dependency graph for glucat.h:




This graph shows which files directly or indirectly include this file:




## 7.11 glucat/glucat_config.h File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- #define GLUCAT_HAVE_INTTYPES_H 1
- #define GLUCAT_HAVE_MEMORY_H 1
- #define GLUCAT_HAVE_STDINT_H 1
- #define GLUCAT_HAVE_STDLIB_H 1
- #define GLUCAT_HAVE_STRINGS_H 1
- #define GLUCAT_HAVE_STRING_H 1
- #define GLUCAT_HAVE_SYS_STAT_H 1
- #define GLUCAT_HAVE_SYS_TYPES_H 1
- #define GLUCAT_HAVE_UNISTD_H 1
- #define GLUCAT_PACKAGE "glucat"
- #define GLUCAT_PACKAGE_BUGREPORT ""
- #define GLUCAT_PACKAGE_NAME "glucat"
- #define GLUCAT_PACKAGE_STRING "glucat 0.8.2"
- #define GLUCAT_PACKAGE_TARNAME "glucat"
- #define GLUCAT_PACKAGE_URL ""
- #define GLUCAT_PACKAGE_VERSION "0.8.2"
- #define GLUCAT_STDC_HEADERS 1
- #define GLUCAT_VERSION "0.8.2"

## 7.11.1 Macro Definition Documentation

### 7.11.1.1 GLUCAT_HAVE_INTTYPES_H

```
#define GLUCAT_HAVE_INTTYPES_H 1
```

Definition at line 10 of file glucat_config.h.

### 7.11.1.2 GLUCAT_HAVE_MEMORY_H

```
#define GLUCAT_HAVE_MEMORY_H 1
```

Definition at line 18 of file glucat_config.h.

### 7.11.1.3 GLUCAT_HAVE_STDINT_H

```
#define GLUCAT_HAVE_STDINT_H 1
```

Definition at line 23 of file glucat_config.h.

#### 7.11.1.4 GLUCAT_HAVE_STDLIB_H

```
#define GLUCAT_HAVE_STDLIB_H 1
```

Definition at line 28 of file glucat_config.h.

#### 7.11.1.5 GLUCAT_HAVE_STRING_H

```
#define GLUCAT_HAVE_STRING_H 1
```

Definition at line 38 of file glucat_config.h.

#### 7.11.1.6 GLUCAT_HAVE_STRINGS_H

```
#define GLUCAT_HAVE_STRINGS_H 1
```

Definition at line 33 of file glucat_config.h.

#### 7.11.1.7 GLUCAT_HAVE_SYS_STAT_H

```
#define GLUCAT_HAVE_SYS_STAT_H 1
```

Definition at line 43 of file glucat_config.h.

#### 7.11.1.8 GLUCAT_HAVE_SYS_TYPES_H

```
#define GLUCAT_HAVE_SYS_TYPES_H 1
```

Definition at line 48 of file glucat_config.h.

#### 7.11.1.9 GLUCAT_HAVE_UNISTD_H

```
#define GLUCAT_HAVE_UNISTD_H 1
```

Definition at line 53 of file glucat_config.h.

#### 7.11.1.10 GLUCAT_PACKAGE

```
#define GLUCAT_PACKAGE "glucat"
```

Definition at line 58 of file glucat_config.h.

#### 7.11.1.11 GLUCAT_PACKAGE_BUGREPORT

```
#define GLUCAT_PACKAGE_BUGREPORT ""
```

Definition at line 63 of file glucat_config.h.

#### 7.11.1.12 GLUCAT_PACKAGE_NAME

```
#define GLUCAT_PACKAGE_NAME "glucat"
```

Definition at line 68 of file glucat_config.h.

Referenced by glucat::control_t::control_t().

#### 7.11.1.13 GLUCAT_PACKAGE_STRING

```
#define GLUCAT_PACKAGE_STRING "glucat 0.8.2"
```

Definition at line 73 of file glucat_config.h.

#### 7.11.1.14 GLUCAT_PACKAGE_TARNAME

```
#define GLUCAT_PACKAGE_TARNAME "glucat"
```

Definition at line 78 of file glucat_config.h.

#### 7.11.1.15 GLUCAT_PACKAGE_URL

```
#define GLUCAT_PACKAGE_URL ""
```

Definition at line 83 of file glucat_config.h.

#### 7.11.1.16 GLUCAT_PACKAGE_VERSION

```
#define GLUCAT_PACKAGE_VERSION "0.8.2"
```

Definition at line 88 of file glucat_config.h.

#### 7.11.1.17 GLUCAT_STDC_HEADERS

```
#define GLUCAT_STDC_HEADERS 1
```

Definition at line 93 of file glucat_config.h.

#### 7.11.1.18 GLUCAT_VERSION

```
#define GLUCAT_VERSION "0.8.2"
```

Definition at line 98 of file glucat_config.h.

Referenced by glucat::control_t::control_t().

## 7.12 glucat/glucat_imp.h File Reference

```
#include "glucat/errors_imp.h"
#include "glucat/index_set_imp.h"
#include "glucat/scalar_imp.h"
#include "glucat/clifford_algebra_imp.h"
#include "glucat/random.h"
#include "glucat/framed_multi_imp.h"
#include "glucat/matrix_imp.h"
#include "glucat/generation_imp.h"
#include "glucat/matrix_multi_imp.h"
```

Include dependency graph for glucat_imp.h:



This graph shows which files directly or indirectly include this file:



## 7.13 glucat/index_set.h File Reference

```
#include "glucat/global.h"
#include "glucat/errors.h"
#include <boost/static_assert.hpp>
#include <bitset>
#include <utility>
```

Include dependency graph for index_set.h:




This graph shows which files directly or indirectly include this file:




### Classes

- class glucat::index_set< LO, HI >

  *Index set class based on std::bitset<> in Gnu standard C++ library.*

- class glucat::index_set< LO, HI >

  *Index set class based on std::bitset<> in Gnu standard C++ library.*

- class glucat::index_set< LO, HI >::reference

  *Index set member reference.*

## Namespaces

- glucat

## Functions

- template<const index_t LO, const index_t HI>
  const index_set< LO, HI > glucat::operator^ (const index_set< LO, HI > &lhs, const index_set< LO, HI > &rhs)

  *Symmetric set difference: exclusive or.*

- template<const index_t LO, const index_t HI>
  const index_set< LO, HI > glucat::operator & (const index_set< LO, HI > &lhs, const index_set< LO, HI > &rhs)

  *Set intersection: and.*

- template<const index_t LO, const index_t HI>
  const index_set< LO, HI > glucat::operator| (const index_set< LO, HI > &lhs, const index_set< LO, HI > &rhs)

  *Set union: or.*

- template<const index_t LO, const index_t HI>
  int glucat::compare (const index_set< LO, HI > &a, const index_set< LO, HI > &b)

  *"lexicographic compare" eg. {3,4,5} is less than {3,7,8}*

- glucat::_GLUCAT_CTAssert (sizeof(set_value_t) >=sizeof(std::bitset< DEFAULT_HI-DEFAULT_LO >), Default_index_set_too_big_for_value) template< const index_t LO

  *Size of set_value_t should be enough to contain bitset<DEFAULT_HI-DEFAULT_LO>*

- const index_t HI std::ostream & glucat::operator<< (std::ostream &os, const index_set< LO, HI > &ist)

  *Write out index set.*

- template<const index_t LO, const index_t HI>
  std::istream & glucat::operator>> (std::istream &s, index_set< LO, HI > &ist)

  *Read in index set.*

- int glucat::sign_of_square (index_t j)

  *Square of generator {j}.*

- template<const index_t LO, const index_t HI>
  index_t glucat::min_neg (const index_set< LO, HI > &ist)

  *Minimum negative index, or 0 if none.*

- template<const index_t LO, const index_t HI>
  index_t glucat::max_pos (const index_set< LO, HI > &ist)

  *Maximum positive index, or 0 if none.*

## 7.14 glucat/index_set_imp.h File Reference

```
#include "glucat/index_set.h"
#include <sstream>
```

Include dependency graph for index_set_imp.h:




This graph shows which files directly or indirectly include this file:




### Namespaces

- glucat

### Functions

- template<const index_t LO, const index_t HI>
  const index_set< LO, HI > glucat::operator^ (const index_set< LO, HI > &lhs, const index_set< LO, HI > &rhs)

  *Symmetric set difference: exclusive or.*

- template<const index_t LO, const index_t HI>
  const index_set< LO, HI > glucat::operator & (const index_set< LO, HI > &lhs, const index_set< LO, HI > &rhs)

  *Set intersection: and.*
- template<const index_t LO, const index_t HI>
  const index_set< LO, HI > glucat::operator| (const index_set< LO, HI > &lhs, const index_set< LO, HI > &rhs)

  *Set union: or.*
- template<const index_t LO, const index_t HI>
  int glucat::compare (const index_set< LO, HI > &a, const index_set< LO, HI > &b)

  *"lexicographic compare" eg. {3,4,5} is less than {3,7,8}*
- const index_t HI std::ostream & glucat::operator<< (std::ostream &os, const index_set< LO, HI > &ist)

  *Write out index set.*
- template<const index_t LO, const index_t HI>
  std::istream & glucat::operator>> (std::istream &s, index_set< LO, HI > &ist)

  *Read in index set.*
- static unsigned long glucat::inverse_reversed_gray (unsigned long x)

  *Inverse reversed Gray code.*
- static unsigned long glucat::inverse_gray (unsigned long x)

  *Inverse Gray code.*
- int glucat::sign_of_square (index_t j)

  *Square of generator {j}.*
- template<const index_t LO, const index_t HI>
  index_t glucat::min_neg (const index_set< LO, HI > &ist)

  *Minimum negative index, or 0 if none.*
- template<const index_t LO, const index_t HI>
  index_t glucat::max_pos (const index_set< LO, HI > &ist)

  *Maximum positive index, or 0 if none.*

## 7.15 glucat/long_double.h File Reference

This graph shows which files directly or indirectly include this file:



### Classes

- struct glucat::numeric_traits< Scalar_T >::demoted<>

  *Demoted type for long double.*

### Namespaces

- glucat

### Variables

- static const long double glucat::l_pi = 3.14159265358979323846264338327950 29L
- static const long double glucat::l_ln2 = 0.69314718055994530941723212145817 66L

## 7.16 glucat/matrix.h File Reference

```
#include <boost/numeric/ublas/fwd.hpp>
#include <complex>
```

Include dependency graph for matrix.h:




This graph shows which files directly or indirectly include this file:



## Classes

- struct glucat::matrix::eig_genus< Matrix_T >

  *Structure containing classification of eigenvalues.*

## Namespaces

- glucat
- glucat::matrix

## Enumerations

- enum glucat::matrix::eig_case_t { glucat::matrix::safe_eig_case, glucat::matrix::negative_eig_case, glucat::matrix::both_eig_case }

  *Classification of eigenvalues of a matrix.*

## Functions

- template<typename LHS_T , typename RHS_T >
  const RHS_T glucat::matrix::kron (const LHS_T &lhs, const RHS_T &rhs)

  *Kronecker tensor product of matrices - as per Matlab kron.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T glucat::matrix::mono_kron (const LHS_T &lhs, const RHS_T &rhs)

  *Sparse Kronecker tensor product of monomial matrices.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T glucat::matrix::nork (const LHS_T &lhs, const RHS_T &rhs, const bool mono=true)

  *Left inverse of Kronecker product.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T glucat::matrix::signed_perm_nork (const LHS_T &lhs, const RHS_T &rhs)

  *Left inverse of Kronecker product where lhs is a signed permutation matrix.*
- template<typename Matrix_T >
  Matrix_T::size_type glucat::matrix::nnz (const Matrix_T &m)

  *Number of non-zeros.*
- template<typename Matrix_T >
  bool glucat::matrix::isnan (const Matrix_T &m)

  *Not a Number.*
- template<typename Matrix_T >
  const Matrix_T glucat::matrix::unit (const typename Matrix_T::size_type n)

  *Unit matrix - as per Matlab eye.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T::expression_type glucat::matrix::mono_prod (const ublas::matrix_expression< LHS_T > &lhs, const ublas::matrix_expression< RHS_T > &rhs)

  *Product of monomial matrices.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T::expression_type glucat::matrix::sparse_prod (const ublas::matrix_expression< LHS_T > &lhs, const ublas::matrix_expression< RHS_T > &rhs)

  *Product of sparse matrices.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T::expression_type glucat::matrix::prod (const ublas::matrix_expression< LHS_T > &lhs, const ublas::matrix_expression< RHS_T > &rhs)

  *Product of matrices.*

- template<typename Scalar_T , typename LHS_T , typename RHS_T >
  Scalar_T glucat::matrix::inner (const LHS_T &lhs, const RHS_T &rhs)

  *Inner product: sum(x(i,j)∗y(i,j))/x.nrows()*

- template<typename Matrix_T >
  Matrix_T::value_type glucat::matrix::norm_frob2 (const Matrix_T &val)

  *Square of Frobenius norm.*

- template<typename Matrix_T >
  Matrix_T::value_type glucat::matrix::trace (const Matrix_T &val)

  *Matrix trace.*

- template<typename Matrix_T >
  ublas::vector< std::complex< double > > glucat::matrix::eigenvalues (const Matrix_T &val)

  *Eigenvalues of a matrix.*

- template<typename Matrix_T >
  eig_genus< Matrix_T > glucat::matrix::classify_eigenvalues (const Matrix_T &val)

  *Classify the eigenvalues of a matrix.*

## 7.17 glucat/matrix_imp.h File Reference

```
#include "glucat/matrix.h"
#include <boost/numeric/ublas/vector.hpp>
#include <boost/numeric/ublas/vector_proxy.hpp>
#include <boost/numeric/ublas/matrix.hpp>
#include <boost/numeric/ublas/matrix_expression.hpp>
#include <boost/numeric/ublas/matrix_proxy.hpp>
#include <boost/numeric/ublas/matrix_sparse.hpp>
#include <boost/numeric/ublas/operation.hpp>
#include <boost/numeric/ublas/operation_sparse.hpp>
#include <boost/numeric/bindings/lapack/driver/gees.hpp>
#include <boost/numeric/bindings/ublas.hpp>
#include <set>
```

Include dependency graph for matrix_imp.h:



This graph shows which files directly or indirectly include this file:




## Namespaces

- glucat
- glucat::matrix

## Functions

- template<typename LHS_T , typename RHS_T >
  const RHS_T glucat::matrix::kron (const LHS_T &lhs, const RHS_T &rhs)

  *Kronecker tensor product of matrices - as per Matlab kron.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T glucat::matrix::mono_kron (const LHS_T &lhs, const RHS_T &rhs)

  *Sparse Kronecker tensor product of monomial matrices.*
- template<typename LHS_T , typename RHS_T >
  void glucat::matrix::nork_range (RHS_T &result, const typename LHS_T::const_iterator2 lhs_it2, const RH↩
  S_T &rhs, const typename RHS_T::size_type res_s1, const typename RHS_T::size_type res_s2)

  *Utility routine for nork: calculate result for a range of indices.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T glucat::matrix::nork (const LHS_T &lhs, const RHS_T &rhs, const bool mono=true)

  *Left inverse of Kronecker product.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T glucat::matrix::signed_perm_nork (const LHS_T &lhs, const RHS_T &rhs)

  *Left inverse of Kronecker product where lhs is a signed permutation matrix.*
- template<typename Matrix_T >
  Matrix_T::size_type glucat::matrix::nnz (const Matrix_T &m)

  *Number of non-zeros.*
- template<typename Matrix_T >
  bool glucat::matrix::isnan (const Matrix_T &m)

  *Not a Number.*
- template<typename Matrix_T >
  const Matrix_T glucat::matrix::unit (const typename Matrix_T::size_type n)

*Unit matrix - as per Matlab eye.*

- template<typename LHS_T , typename RHS_T >
  const RHS_T::expression_type glucat::matrix::mono_prod (const ublas::matrix_expression< LHS_T > &lhs, const ublas::matrix_expression< RHS_T > &rhs)

  *Product of monomial matrices.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T::expression_type glucat::matrix::sparse_prod (const ublas::matrix_expression< LHS_T > &lhs, const ublas::matrix_expression< RHS_T > &rhs)

  *Product of sparse matrices.*
- template<typename LHS_T , typename RHS_T >
  const RHS_T::expression_type glucat::matrix::prod (const ublas::matrix_expression< LHS_T > &lhs, const ublas::matrix_expression< RHS_T > &rhs)

  *Product of matrices.*
- template<typename Scalar_T , typename LHS_T , typename RHS_T >
  Scalar_T glucat::matrix::inner (const LHS_T &lhs, const RHS_T &rhs)

  *Inner product: sum(x(i,j)∗y(i,j))/x.nrows()*
- template<typename Matrix_T >
  Matrix_T::value_type glucat::matrix::norm_frob2 (const Matrix_T &val)

  *Square of Frobenius norm.*
- template<typename Matrix_T >
  Matrix_T::value_type glucat::matrix::trace (const Matrix_T &val)

  *Matrix trace.*
- template<typename Matrix_T >
  static ublas::matrix< double, ublas::column_major > glucat::matrix::to_lapack (const Matrix_T &val)

  *Convert matrix to LAPACK format.*
- template<typename Matrix_T >
  ublas::vector< std::complex< double > > glucat::matrix::eigenvalues (const Matrix_T &val)

  *Eigenvalues of a matrix.*
- template<typename Matrix_T >
  eig_genus< Matrix_T > glucat::matrix::classify_eigenvalues (const Matrix_T &val)

  *Classify the eigenvalues of a matrix.*

## 7.18 glucat/matrix_multi.h File Reference

```
#include "glucat/global.h"
#include "glucat/errors.h"
#include "glucat/index_set.h"
#include "glucat/clifford_algebra.h"
#include "glucat/framed_multi.h"
#include <boost/numeric/ublas/fwd.hpp>
#include <fstream>
#include <string>
#include <utility>
#include <vector>
```

Include dependency graph for matrix_multi.h:



This graph shows which files directly or indirectly include this file:




## Classes

- class glucat::framed_multi< Scalar_T, LO, HI >

  *A framed_multi<Scalar_T,LO,HI> is a framed approximation to a multivector.*
- class glucat::matrix_multi< Scalar_T, LO, HI >

  *A matrix_multi<Scalar_T,LO,HI> is a matrix approximation to a multivector.*
- class glucat::matrix_multi< Scalar_T, LO, HI >

  *A matrix_multi<Scalar_T,LO,HI> is a matrix approximation to a multivector.*
- struct std::numeric_limits< glucat::matrix_multi< Scalar_T, LO, HI > >

  *Numeric limits for matrix_multi inherit limits for the corresponding scalar type.*

## Namespaces

- glucat
- std

## Functions

- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > glucat::operator* (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Geometric product.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > glucat::operator^ (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

*Outer product.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::operator & (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Inner product.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::operator% (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Left contraction.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
Scalar_T glucat::star (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Hestenes scalar product.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::operator/ (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Geometric quotient.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::operator| (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Transformation via twisted adjoint action.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
std::istream & glucat::operator>> (std::istream &s, matrix_multi< Scalar_T, LO, HI > &val)

  *Read multivector from input.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
std::ostream & glucat::operator<< (std::ostream &os, const matrix_multi< Scalar_T, LO, HI > &val)

  *Write multivector to output.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
const index_set< LO, HI > glucat::reframe (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs, matrix_multi< Scalar_T, LO, HI > &lhs_reframed, matrix_multi< Scalar_T, LO, HI > &rhs_reframed)

  *Find a common frame for operands of a binary operator.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::sqrt (const matrix_multi< Scalar_T, LO, HI > &val, const matrix_multi< Scalar_T, LO, HI > &i, bool prechecked)

  *Square root of multivector with specified complexifier.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::matrix_sqrt (const matrix_multi< Scalar_T, LO, HI > &val, const matrix_multi< Scalar_T, LO, HI > &i)

  *Square root of multivector with specified complexifier.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::log (const matrix_multi< Scalar_T, LO, HI > &val, const matrix_multi< Scalar_T, LO, HI > &i, bool prechecked)

  *Natural logarithm of multivector with specified complexifier.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::matrix_log (const matrix_multi< Scalar_T, LO, HI > &val, const matrix_multi< Scalar_T, LO, HI > &i)

  *Natural logarithm of multivector with specified complexifier.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
const matrix_multi< Scalar_T, LO, HI > glucat::exp (const matrix_multi< Scalar_T, LO, HI > &val)

  *Exponential of multivector.*

## 7.19 glucat/matrix_multi_imp.h File Reference

```
#include "glucat/matrix_multi.h"
#include "glucat/matrix.h"
#include "glucat/generation.h"
#include <boost/numeric/ublas/matrix.hpp>
#include <boost/numeric/ublas/matrix_expression.hpp>
#include <boost/numeric/ublas/matrix_proxy.hpp>
#include <boost/numeric/ublas/matrix_sparse.hpp>
#include <boost/numeric/ublas/operation.hpp>
#include <boost/numeric/ublas/operation_sparse.hpp>
#include <boost/numeric/ublas/triangular.hpp>
#include <boost/numeric/ublas/lu.hpp>
#include <fstream>
#include <iomanip>
```

Include dependency graph for matrix_multi_imp.h:



This graph shows which files directly or indirectly include this file:




### Classes

- class glucat::basis_table< Scalar_T, LO, HI, Matrix_T >

  *Table of basis elements used as a cache by basis_element()*

### Namespaces

- glucat

## Functions

- index_t glucat::offset_level (const index_t p, const index_t q)

  *Determine the log2 dim corresponding to signature p, q.*

- template<typename Matrix_Index_T , const index_t LO, const index_t HI>
  static Matrix_Index_T glucat::folded_dim (const index_set< LO, HI > &sub)

  *Determine the matrix dimension of the fold of a subalegbra.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  const index_set< LO, HI > glucat::reframe (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_↩ multi< Scalar_T, LO, HI > &rhs, matrix_multi< Scalar_T, LO, HI > &lhs_reframed, matrix_multi< Scalar_T, LO, HI > &rhs_reframed)

  *Find a common frame for operands of a binary operator.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > glucat::operator* (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Geometric product.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > glucat::operator^ (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Outer product.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > glucat::operator & (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Inner product.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > glucat::operator% (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Left contraction.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  Scalar_T glucat::star (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Hestenes scalar product.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > glucat::operator/ (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Geometric quotient.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > glucat::operator| (const matrix_multi< Scalar_T, LO, HI > &lhs, const matrix_multi< Scalar_T, LO, HI > &rhs)

  *Transformation via twisted adjoint action.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  std::ostream & glucat::operator<< (std::ostream &os, const matrix_multi< Scalar_T, LO, HI > &val)

  *Write multivector to output.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  std::istream & glucat::operator>> (std::istream &s, matrix_multi< Scalar_T, LO, HI > &val)

  *Read multivector from input.*

- template<typename Multivector_T , typename Matrix_T , typename Basis_Matrix_T >
  static Multivector_T glucat::fast (const Matrix_T &X, index_t level)

  *Inverse generalized Fast Fourier Transform.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  static const matrix_multi< Scalar_T, LO, HI > glucat::pade_approx (const int array_size, const Scalar_T a[ ], const Scalar_T b[ ], const matrix_multi< Scalar_T, LO, HI > &X)

  *Pade' approximation.*

- template<typename Scalar_T , const index_t LO, const index_t HI>
  static void glucat::db_step (matrix_multi< Scalar_T, LO, HI > &M, matrix_multi< Scalar_T, LO, HI > &Y)

  *Single step of product form of Denman-Beavers square root iteration.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  static const matrix_multi< Scalar_T, LO, HI > glucat::db_sqrt (const matrix_multi< Scalar_T, LO, HI > &val)

  *Product form of Denman-Beavers square root iteration.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > glucat::sqrt (const matrix_multi< Scalar_T, LO, HI > &val, const matrix_multi< Scalar_T, LO, HI > &i, bool prechecked)

  *Square root of multivector with specified complexifier.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > glucat::matrix_sqrt (const matrix_multi< Scalar_T, LO, HI > &val, const matrix_multi< Scalar_T, LO, HI > &i)

  *Square root of multivector with specified complexifier.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  static const matrix_multi< Scalar_T, LO, HI > glucat::pade_log (const matrix_multi< Scalar_T, LO, HI > &val)

  *Pade' approximation of log.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  static const matrix_multi< Scalar_T, LO, HI > glucat::cascade_log (const matrix_multi< Scalar_T, LO, HI > &val)

  *Incomplete square root cascade and Pade' approximation of log.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > glucat::log (const matrix_multi< Scalar_T, LO, HI > &val, const matrix_multi< Scalar_T, LO, HI > &i, bool prechecked)

  *Natural logarithm of multivector with specified complexifier.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > glucat::matrix_log (const matrix_multi< Scalar_T, LO, HI > &val, const matrix_multi< Scalar_T, LO, HI > &i)

  *Natural logarithm of multivector with specified complexifier.*
- template<typename Scalar_T , const index_t LO, const index_t HI>
  const matrix_multi< Scalar_T, LO, HI > glucat::exp (const matrix_multi< Scalar_T, LO, HI > &val)

  *Exponential of multivector.*

## 7.20 glucat/portability.h File Reference

```
#include <boost/version.hpp>
#include <cmath>
```

Include dependency graph for portability.h:



This graph shows which files directly or indirectly include this file:




## Macros

- #define _GLUCAT_ISNAN(x) (x != x)
- #define _GLUCAT_ISINF(x) (!_GLUCAT_ISNAN(x) && _GLUCAT_ISNAN(x-x))
- #define UBLAS_ABS abs
- #define UBLAS_SQRT sqrt

### 7.20.1 Macro Definition Documentation

#### 7.20.1.1 _GLUCAT_ISINF

```
#define _GLUCAT_ISINF(
              x ) (!_GLUCAT_ISNAN(x) && _GLUCAT_ISNAN(x-x))
```

Definition at line 48 of file portability.h.

Referenced by glucat::numeric_traits< Scalar_T >::isInf().

#### 7.20.1.2 _GLUCAT_ISNAN

```
#define _GLUCAT_ISNAN(
              x ) (x != x)
```

Definition at line 47 of file portability.h.

Referenced by glucat::numeric_traits< Scalar_T >::isNaN().

#### 7.20.1.3 UBLAS_ABS

```
#define UBLAS_ABS abs
```

Definition at line 56 of file portability.h.

Referenced by glucat::numeric_traits< Scalar_T >::abs().

#### 7.20.1.4 UBLAS_SQRT

```
#define UBLAS_SQRT sqrt
```

Definition at line 57 of file portability.h.

Referenced by glucat::numeric_traits< Scalar_T >::sqrt().

## 7.21 glucat/qd.h File Reference

```
#include "glucat/scalar.h"
#include <qd/qd_real.h>
```

Include dependency graph for qd.h:



This graph shows which files directly or indirectly include this file:




## 7.22 glucat/random.h File Reference

`#include <random>`
Include dependency graph for random.h:



This graph shows which files directly or indirectly include this file:




### Classes

- class glucat::random_generator< Scalar_T >

  *Random number generator with single instance per Scalar_T.*

### Namespaces

- glucat

## 7.23 glucat/scalar.h File Reference

```
#include "glucat/portability.h"
#include <boost/numeric/ublas/traits.hpp>
#include <cmath>
#include <limits>
```

Include dependency graph for scalar.h:




This graph shows which files directly or indirectly include this file:




## Classes

- class glucat::numeric_traits< Scalar_T >

  *Extra traits which extend numeric limits.*
- struct glucat::numeric_traits< Scalar_T >::promoted

  *Promoted type.*
- struct glucat::numeric_traits< Scalar_T >::demoted<>

  *Demoted type for long double.*

### Namespaces

- glucat

### Functions

- template<typename Scalar_T >
  Scalar_T glucat::log2 (const Scalar_T &x)

  *Log base 2 of scalar.*

## 7.24 glucat/scalar_imp.h File Reference

```
#include "glucat/portability.h"
#include <boost/numeric/ublas/traits.hpp>
#include <cmath>
#include <limits>
```

Include dependency graph for scalar_imp.h:




This graph shows which files directly or indirectly include this file:



### Namespaces

- glucat

### Functions

- template<typename Scalar_T >
  numeric_traits< Scalar_T >::promoted::type glucat::to_promote (const Scalar_T &val)

  *Cast to promote.*
- template<typename Scalar_T >
  numeric_traits< Scalar_T >::demoted::type glucat::to_demote (const Scalar_T &val)

  *Cast to demote.*

## 7.25 pyclical/glucat.pxd File Reference

### Namespaces

- glucat

## 7.26 pyclical/PyClical.cpp File Reference

```
#include "Python.h"
```

Include dependency graph for PyClical.cpp:




### Macros

- #define PY_SSIZE_T_CLEAN

### 7.26.1 Macro Definition Documentation

#### 7.26.1.1 PY_SSIZE_T_CLEAN

```
#define PY_SSIZE_T_CLEAN
```

Definition at line 57 of file PyClical.cpp.

## 7.27 pyclical/PyClical.h File Reference

```
#include "glucat/glucat.h"
#include "glucat/glucat_imp.h"
#include <iostream>
#include <sstream>
#include <iomanip>
```

Include dependency graph for PyClical.h:



### Namespaces

- cga3

  *Definitions for 3D Conformal Geometric Algebra [DL].*

### Typedefs

- typedef glucat::tuning< glucat::DEFAULT_Mult_Matrix_Threshold, glucat::DEFAULT_Div_Max_Steps, glucat::DEFAULT_Sqrt_Max_Steps, glucat::DEFAULT_Log_Max_Outer_Steps, glucat::DEFAULT_Log_Max_Inner_Steps, glucat::DEFAULT_Basis_Max_Count, glucat::DEFAULT_Fast_Size_Threshold, glucat::DEFAULT_Inv_Fast_Dim_Threshold, glucat::DEFAULT_Products_Size_Threshold, glucat::precision_promoted > Tune_P
- typedef std::string String
- typedef index_set< lo_ndx, hi_ndx > IndexSet
- typedef double scalar_t
- typedef matrix_multi< scalar_t > Clifford

### Functions

- template<typename Scalar_T >
  PyObject * PyFloat_FromDouble (Scalar_T v)
- template<typename Index_Set_T >
  String index_set_to_repr (const Index_Set_T &ist)

  *The "official" string representation of Index_Set_T ist.*
- template<typename Index_Set_T >
  String index_set_to_str (const Index_Set_T &ist)

  *The "informal" string representation of Index_Set_T ist.*
- template<typename Multivector_T >
  String clifford_to_repr (const Multivector_T &mv)

*The “official” string representation of Multivector_T mv.*

- template<typename Multivector_T >
  String clifford_to_str (const Multivector_T &mv)

  *The "informal" string representation of Multivector_T mv.*
- template<typename Multivector_T >
  Multivector_T cga3::cga3 (const Multivector_T &x)

  *Convert Euclidean 3D vector to Conformal Geometric Algebra null vector [DL (10.50)].*
- template<typename Multivector_T >
  Multivector_T cga3::cga3std (const Multivector_T &X)

  *Convert CGA3 null vector to standard Conformal Geometric Algebra null vector [DL (10.52)].*
- template<typename Multivector_T >
  Multivector_T cga3::agc3 (const Multivector_T &X)

  *Convert CGA3 null vector to Euclidean 3D vector [DL (10.50)].*

## Variables

- const index_t lo_ndx = DEFAULT_LO
- const index_t hi_ndx = DEFAULT_HI

### 7.27.1 Typedef Documentation

#### 7.27.1.1 Clifford

```
typedef matrix_multi<scalar_t> Clifford
```

Definition at line 160 of file PyClical.h.

#### 7.27.1.2 IndexSet

```
typedef index_set<lo_ndx,hi_ndx> IndexSet
```

Definition at line 157 of file PyClical.h.

#### 7.27.1.3 scalar_t

```
typedef double scalar_t
```

Definition at line 159 of file PyClical.h.

#### 7.27.1.4 String

```
typedef std::string String
```

Definition at line 65 of file PyClical.h.

#### 7.27.1.5 Tune_P

```
typedef glucat::tuning< glucat::DEFAULT_Mult_Matrix_Threshold, glucat::DEFAULT_Div_Max_Steps,
glucat::DEFAULT_Sqrt_Max_Steps, glucat::DEFAULT_Log_Max_Outer_Steps, glucat::DEFAULT_Log_Max_Inner_Steps,
glucat::DEFAULT_Basis_Max_Count, glucat::DEFAULT_Fast_Size_Threshold, glucat::DEFAULT_Inv_Fast_Dim_Threshold,
glucat::DEFAULT_Products_Size_Threshold, glucat::precision_promoted > Tune_P
```

Definition at line 49 of file PyClical.h.

### 7.27.2 Function Documentation

#### 7.27.2.1 clifford_to_repr()

```
template<typename Multivector_T >
String clifford_to_repr (
            const Multivector_T & mv )  [inline]
```

The “official” string representation of Multivector_T mv.

Definition at line 87 of file PyClical.h.

Referenced by PyClical.clifford::__repr__().

#### 7.27.2.2 clifford_to_str()

```
template<typename Multivector_T >
String clifford_to_str (
            const Multivector_T & mv )  [inline]
```

The "informal" string representation of Multivector_T mv.

Definition at line 98 of file PyClical.h.

References glucat::abs(), and PyClical::e().

Referenced by PyClical.clifford::__str__().

#### 7.27.2.3 index_set_to_repr()

```
template<typename Index_Set_T >
String index_set_to_repr (
            const Index_Set_T & ist )  [inline]
```

The “official” string representation of Index_Set_T ist.

Definition at line 69 of file PyClical.h.

References PyClical::ist.

Referenced by PyClical.index_set::__repr__().

#### 7.27.2.4 index_set_to_str()

```
template<typename Index_Set_T >
String index_set_to_str (
            const Index_Set_T & ist )  [inline]
```

The "informal" string representation of Index_Set_T ist.

Definition at line 78 of file PyClical.h.

References PyClical::ist.

Referenced by PyClical.index_set::__str__().

#### 7.27.2.5 PyFloat_FromDouble()

```
template<typename Scalar_T >
PyObject* PyFloat_FromDouble (
            Scalar_T v )  [inline]
```

Create a PyFloatObject object from Scalar_T v. Needed because Scalar_T might not be the same as double.

Definition at line 59 of file PyClical.h.

### 7.27.3 Variable Documentation

#### 7.27.3.1 hi_ndx

```
const index_t hi_ndx = DEFAULT_HI
```

Definition at line 156 of file PyClical.h.

#### 7.27.3.2 lo_ndx

```
const index_t lo_ndx = DEFAULT_LO
```

Definition at line 155 of file PyClical.h.

## 7.28 pyclical/PyClical.pxd File Reference

### Namespaces

- PyClical

## 7.29 pyclical/PyClical.pyx File Reference

### Classes

- class PyClical.index_set
- class PyClical.index_set
- class PyClical.clifford
- class PyClical.clifford

### Namespaces

- PyClical

### Functions

- def PyClical.index_set_hidden_doctests ()
- def PyClical.clifford_hidden_doctests ()
- def PyClical.e (obj)
- def PyClical.istpq (p, q)
- def PyClical._test ()

### Variables

- string PyClical.__version__ = "0.8.2"
- PyClical.obj
- PyClical.i
- PyClical.ixt
- PyClical.fill
- float PyClical.tau = atan(clifford(1.0)) ∗ 8.0
- float PyClical.pi = tau / 2.0
- PyClical.cl = clifford
- PyClical.ist = index_set
- def PyClical.ninf3 = e(4) + e(-1)
- def PyClical.nbar3 = e(4) - e(-1)

## 7.30 pyclical/PyClical_nocython.cpp File Reference

```
#include "Python.h"
```

Include dependency graph for PyClical_nocython.cpp:




### Macros

- #define PY_SSIZE_T_CLEAN

### 7.30.1 Macro Definition Documentation

#### 7.30.1.1 PY_SSIZE_T_CLEAN

```
#define PY_SSIZE_T_CLEAN
```

Definition at line 52 of file PyClical_nocython.cpp.

## 7.31 test/control.h File Reference

```
#include "glucat/glucat_config.h"
#include "test/try_catch.h"
```

Include dependency graph for control.h:



This graph shows which files directly or indirectly include this file:




### Classes

- class glucat::control_t

  *Parameters to control tests.*

### Namespaces

- glucat

## 7.32 test/driver.h File Reference

```
#include "glucat/glucat.h"
#include "test/tuning.h"
#include "glucat/glucat_imp.h"
#include "test/try_catch.h"
#include "test/control.h"
#include <cstdio>
```

Include dependency graph for driver.h:



## 7.33 test/timing.h File Reference

### Namespaces

- glucat
- glucat::timing

### Functions

- static double glucat::timing::elapsed (clock_t cpu_time)

  *Elapsed time in milliseconds.*

### Variables

- const double glucat::timing::MS_PER_SEC = 1000.0

  *Timing constant: milliseconds per second.*
- const double glucat::timing::MS_PER_CLOCK = MS_PER_SEC / double(CLOCKS_PER_SEC)

  *Timing constant: milliseconds per clock.*
- const int glucat::timing::EXTRA_TRIALS = 2

  *Timing constant: trial expansion factor.*

## 7.34 test/try_catch.h File Reference

This graph shows which files directly or indirectly include this file:




### Namespaces

- glucat

### Typedefs

- typedef int(∗ glucat::intfn) ()

  *For exception catching: pointer to function returning int.*
- typedef int(∗ glucat::intintfn) (int)

  *For exception catching: pointer to function of int returning int.*

### Functions

- int glucat::try_catch (intfn f)

  *Exception catching for functions returning int.*
- int glucat::try_catch (intintfn f, int arg)

  *Exception catching for functions of int returning int.*

## 7.35 test/tuning.h File Reference

This graph shows which files directly or indirectly include this file:




### Macros

- #define __TEST_TUNING_DEFAULT_CONSTANT(SUFFIX) const unsigned int Test_Tuning_##SUFFIX = glucat::DEFAULT_##SUFFIX

### Typedefs

- typedef glucat::precision_t precision_t
- typedef glucat::tuning< Test_Tuning_Mult_Matrix_Threshold, Test_Tuning_Div_Max_Steps, Test_Tuning_↩ Sqrt_Max_Steps, Test_Tuning_Log_Max_Outer_Steps, Test_Tuning_Log_Max_Inner_Steps, Test_Tuning↩ _Basis_Max_Count, Test_Tuning_Fast_Size_Threshold, Test_Tuning_Inv_Fast_Dim_Threshold, Test_↩ Tuning_Products_Size_Threshold, Test_Tuning_Function_Precision > Tune_P

  *Tuning policy.*

### Functions

- _GLUCAT_CTAssert (std::numeric_limits< unsigned int >::radix==2, CannotSetThresholds) const unsigned int Test_Tuning_Int_Digits
- __TEST_TUNING_DEFAULT_CONSTANT (Mult_Matrix_Threshold)
- __TEST_TUNING_DEFAULT_CONSTANT (Div_Max_Steps)
- __TEST_TUNING_DEFAULT_CONSTANT (Sqrt_Max_Steps)
- __TEST_TUNING_DEFAULT_CONSTANT (Log_Max_Outer_Steps)
- __TEST_TUNING_DEFAULT_CONSTANT (Log_Max_Inner_Steps)
- __TEST_TUNING_DEFAULT_CONSTANT (Basis_Max_Count)
- __TEST_TUNING_DEFAULT_CONSTANT (Fast_Size_Threshold)
- __TEST_TUNING_DEFAULT_CONSTANT (Inv_Fast_Dim_Threshold)
- __TEST_TUNING_DEFAULT_CONSTANT (Products_Size_Threshold)

### Variables

- const unsigned int Test_Tuning_Max_Threshold = 1 << Test_Tuning_Int_Digits
- const precision_t Test_Tuning_Function_Precision = glucat::DEFAULT_Function_Precision

## 7.35.1 Macro Definition Documentation

### 7.35.1.1 __TEST_TUNING_DEFAULT_CONSTANT

```
#define __TEST_TUNING_DEFAULT_CONSTANT(
              SUFFIX ) const unsigned int Test_Tuning_##SUFFIX = glucat::DEFAULT_##SUFFIX
```

Definition at line 41 of file tuning.h.

## 7.35.2 Typedef Documentation

### 7.35.2.1 precision_t

```
typedef glucat::precision_t precision_t
```

Definition at line 39 of file tuning.h.

### 7.35.2.2 Tune_P

```
typedef glucat::tuning< Test_Tuning_Mult_Matrix_Threshold, Test_Tuning_Div_Max_Steps, Test↩
_Tuning_Sqrt_Max_Steps, Test_Tuning_Log_Max_Outer_Steps, Test_Tuning_Log_Max_Inner_Steps,
Test_Tuning_Basis_Max_Count, Test_Tuning_Fast_Size_Threshold, Test_Tuning_Inv_Fast_Dim_↩
Threshold, Test_Tuning_Products_Size_Threshold, Test_Tuning_Function_Precision > Tune_P
```

Tuning policy.

Definition at line 126 of file tuning.h.

## 7.35.3 Function Documentation

#### 7.35.3.1 __TEST_TUNING_DEFAULT_CONSTANT() [1/9]

```
__TEST_TUNING_DEFAULT_CONSTANT (
             Mult_Matrix_Threshold  )
```

#### 7.35.3.2 __TEST_TUNING_DEFAULT_CONSTANT() [2/9]

```
__TEST_TUNING_DEFAULT_CONSTANT (
             Div_Max_Steps  )
```

#### 7.35.3.3 __TEST_TUNING_DEFAULT_CONSTANT() [3/9]

```
__TEST_TUNING_DEFAULT_CONSTANT (
             Sqrt_Max_Steps  )
```

#### 7.35.3.4 __TEST_TUNING_DEFAULT_CONSTANT() [4/9]

```
__TEST_TUNING_DEFAULT_CONSTANT (
             Log_Max_Outer_Steps  )
```

#### 7.35.3.5 __TEST_TUNING_DEFAULT_CONSTANT() [5/9]

```
__TEST_TUNING_DEFAULT_CONSTANT (
             Log_Max_Inner_Steps  )
```

#### 7.35.3.6 __TEST_TUNING_DEFAULT_CONSTANT() [6/9]

```
__TEST_TUNING_DEFAULT_CONSTANT (
             Basis_Max_Count  )
```

#### 7.35.3.7 __TEST_TUNING_DEFAULT_CONSTANT() [7/9]

```
__TEST_TUNING_DEFAULT_CONSTANT (
             Fast_Size_Threshold  )
```

#### 7.35.3.8 __TEST_TUNING_DEFAULT_CONSTANT() [8/9]

```
__TEST_TUNING_DEFAULT_CONSTANT (
             Inv_Fast_Dim_Threshold  )
```

#### 7.35.3.9 __TEST_TUNING_DEFAULT_CONSTANT() [9/9]

```
__TEST_TUNING_DEFAULT_CONSTANT (
             Products_Size_Threshold  )
```

#### 7.35.3.10 _GLUCAT_CTAssert()

```
_GLUCAT_CTAssert (
             std::numeric_limits< unsigned int >::radix  = 2,
             CannotSetThresholds  ) const
```

### 7.35.4 Variable Documentation

#### 7.35.4.1 Test_Tuning_Function_Precision

```
const precision_t Test_Tuning_Function_Precision = glucat::DEFAULT_Function_Precision
```

Definition at line 110 of file tuning.h.

#### 7.35.4.2 Test_Tuning_Max_Threshold

```
const unsigned int Test_Tuning_Max_Threshold = 1 << Test_Tuning_Int_Digits
```

Definition at line 37 of file tuning.h.

## 7.36 test/undefine.h File Reference

# Index


_GLUCAT_CLIFFORD_ALGEBRA_OPERATIONS
clifford_algebra.h, 238
_GLUCAT_CTAssert
global.h, 257
glucat, 23
tuning.h, 295
_GLUCAT_HASH_N
framed_multi_imp.h, 251
_GLUCAT_HASH_SIZE_T
framed_multi_imp.h, 252
_GLUCAT_ISINF
portability.h, 277
_GLUCAT_ISNAN
portability.h, 277
_GLUCAT_MAP_IS_HASH
framed_multi.h, 249
__TEST_TUNING_DEFAULT_CONSTANT
tuning.h, 293–295
__add__
PyClical::clifford, 84
__and__
PyClical::clifford, 85
PyClical::index_set, 167
__call__
PyClical::clifford, 85
__cinit__
PyClical::clifford, 85
PyClical::index_set, 167
__contains__
PyClical::clifford, 86
PyClical::index_set, 167
__dealloc__
PyClical::clifford, 86
PyClical::index_set, 168
__div__
PyClical::clifford, 86
__getitem__
PyClical::clifford, 87
PyClical::index_set, 168
__iadd__
PyClical::clifford, 87
__iand__
PyClical::clifford, 87
PyClical::index_set, 168
__idiv__
PyClical::clifford, 88
__imod__
PyClical::clifford, 88
__imul__
PyClical::clifford, 88
__invert__
PyClical::index_set, 169
__ior__
PyClical::clifford, 89
PyClical::index_set, 169
__isub__
PyClical::clifford, 89
__iter__
PyClical::clifford, 89
PyClical::index_set, 169
__ixor__
PyClical::clifford, 90
PyClical::index_set, 170
__mod__
PyClical::clifford, 90
__mul__
PyClical::clifford, 90
__neg__
PyClical::clifford, 91
__or__
PyClical::clifford, 91
PyClical::index_set, 170
__pos__
PyClical::clifford, 91
__pow__
PyClical::clifford, 92
__repr__
PyClical::clifford, 92
PyClical::index_set, 170
__richcmp__
PyClical::clifford, 92
PyClical::index_set, 171
__setitem__
PyClical::index_set, 171
__str__
PyClical::clifford, 93
PyClical::index_set, 171
__sub__
PyClical::clifford, 93
__version__
PyClical, 76
__xor__
PyClical::clifford, 93
PyClical::index_set, 172
_test
PyClical, 72
~basis_table
glucat::basis_table, 80

~clifford_algebra
glucat::clifford_algebra, 104
~control_t
glucat::control_t, 115
~framed_multi
glucat::framed_multi, 131
~generator_table
glucat::gen::generator_table, 143
~glucat_error
glucat::glucat_error, 147
~matrix_multi
glucat::matrix_multi, 183
~random_generator
glucat::random_generator, 211
~reference
glucat::index_set::reference, 215
~var_term
glucat::framed_multi::var_term, 229

abs
glucat, 23
glucat::numeric_traits, 198
PyClical::clifford, 94
acos
glucat, 23, 24
glucat::numeric_traits, 198
acosh
glucat, 24
agc3
cga3, 9
asin
glucat, 25
glucat::numeric_traits, 199
asinh
glucat, 25, 26
atan
glucat, 26
glucat::numeric_traits, 199
atanh
glucat, 27

BITS_PER_SET_VALUE
glucat, 60
BOOST_STATIC_ASSERT
glucat::index_set, 156
basis
glucat::basis_table, 81
basis_element
glucat::matrix_multi, 188
basis_matrix_t
glucat::matrix_multi, 180
basis_table
glucat::basis_table, 80
bitset_t
glucat::index_set, 153

call
glucat::control_t, 115, 116
cascade_log
glucat, 27
catch_exceptions
glucat::control_t, 116
centre_pm4_qp4
glucat::framed_multi, 135
centre_pp4_qm4
glucat::framed_multi, 135
centre_qp1_pm1
glucat::framed_multi, 135
cga3, 9
agc3, 9
cga3, 9
cga3std, 10
cga3std
cga3, 10
check_complex
glucat, 28
cl
PyClical, 76
classify_eigenvalues
glucat::matrix, 66
classname
glucat::clifford_algebra, 104
glucat::error, 123
glucat::framed_multi, 136
glucat::framed_multi::var_term, 230
glucat::glucat_error, 148
glucat::index_set, 156
glucat::matrix_multi, 188
Clifford
PyClical.h, 285
clifford_algebra.h
_GLUCAT_CLIFFORD_ALGEBRA_OPERATIO↩
NS, 238
clifford_exp
glucat, 28
clifford_hidden_doctests
PyClical, 72
clifford_to_repr
PyClical.h, 286
clifford_to_str
PyClical.h, 286
compare
glucat, 28
glucat::index_set, 164
complexifier
glucat, 29
conj
glucat, 29
glucat::clifford_algebra, 104
glucat::numeric_traits, 199
PyClical::clifford, 94
const_iterator
glucat::framed_multi, 127
control
glucat::control_t, 116
control_t
glucat::control_t, 115

cos
glucat, 29, 30
glucat::numeric_traits, 199
cosh
glucat, 30
glucat::numeric_traits, 200
count
glucat::index_set, 156
PyClical::index_set, 172
count_neg
glucat::index_set, 156
PyClical::index_set, 172
count_pos
glucat::index_set, 156
PyClical::index_set, 173
crd_of_mult
glucat, 30, 31

DEFAULT_Basis_Max_Count
glucat, 60
DEFAULT_Div_Max_Steps
glucat, 60
DEFAULT_Fast_Size_Threshold
glucat, 61
DEFAULT_Function_Precision
glucat, 61
DEFAULT_HI
glucat, 61
DEFAULT_Inv_Fast_Dim_Threshold
glucat, 61
DEFAULT_Log_Max_Inner_Steps
glucat, 61
DEFAULT_Log_Max_Outer_Steps
glucat, 61
DEFAULT_Mult_Matrix_Threshold
glucat, 62
DEFAULT_Products_Size_Threshold
glucat, 62
DEFAULT_Sqrt_Max_Steps
glucat, 62
DEFAULT_TRUNCATION
glucat, 62
db_sqrt
glucat, 31
db_step
glucat, 31
divide
glucat::framed_multi, 136

e
PyClical, 74
EXTRA_TRIALS
glucat::timing, 71
eig_case_t
glucat::matrix, 65
eigenvalues
glucat::matrix, 66
elapsed
glucat::timing, 71
elliptic
glucat, 31
error
glucat::error, 123
error_t
glucat::framed_multi, 128
glucat::index_set, 153
glucat::matrix_multi, 180
even
glucat, 32
glucat::clifford_algebra, 104
PyClical::clifford, 94
exp
glucat, 32
glucat::framed_multi, 139
glucat::numeric_traits, 200

fast
glucat, 33
glucat::framed_multi, 136
fast_framed_multi
glucat::framed_multi, 137
glucat::matrix_multi, 188
fast_matrix_multi
glucat::framed_multi, 137
glucat::matrix_multi, 189
fill
PyClical, 76
flip
glucat::index_set, 157
glucat::index_set::reference, 216
fmod
glucat::numeric_traits, 200
fold
glucat::framed_multi, 137
glucat::index_set, 157
folded_dim
glucat, 33
frame
glucat::clifford_algebra, 105
PyClical::clifford, 95
framed_multi
glucat::framed_multi, 131–134, 139
glucat::matrix_multi, 190
framed_multi.h
_GLUCAT_MAP_IS_HASH, 249
framed_multi_imp.h
_GLUCAT_HASH_N, 251
_GLUCAT_HASH_SIZE_T, 252
framed_multi_t
glucat::framed_multi, 128
glucat::matrix_multi, 180
framed_pair_t
glucat::framed_multi, 128
friend_for_private_destructor
glucat::basis_table, 81
glucat::control_t, 117
glucat::gen::generator_table, 146
glucat::random_generator, 212

function_precision
glucat::tuning, 227

GLUCAT_HAVE_INTTYPES_H
glucat_config.h, 259
GLUCAT_HAVE_MEMORY_H
glucat_config.h, 259
GLUCAT_HAVE_STDINT_H
glucat_config.h, 259
GLUCAT_HAVE_STDLIB_H
glucat_config.h, 259
GLUCAT_HAVE_STRING_H
glucat_config.h, 260
GLUCAT_HAVE_STRINGS_H
glucat_config.h, 260
GLUCAT_HAVE_SYS_STAT_H
glucat_config.h, 260
GLUCAT_HAVE_SYS_TYPES_H
glucat_config.h, 260
GLUCAT_HAVE_UNISTD_H
glucat_config.h, 260
GLUCAT_PACKAGE_BUGREPORT
glucat_config.h, 261
GLUCAT_PACKAGE_NAME
glucat_config.h, 261
GLUCAT_PACKAGE_STRING
glucat_config.h, 261
GLUCAT_PACKAGE_TARNAME
glucat_config.h, 261
GLUCAT_PACKAGE_URL
glucat_config.h, 261
GLUCAT_PACKAGE_VERSION
glucat_config.h, 261
GLUCAT_PACKAGE
glucat_config.h, 260
GLUCAT_STDC_HEADERS
glucat_config.h, 262
GLUCAT_VERSION
glucat_config.h, 262
gen_from_pm1_qm1
glucat::gen::generator_table, 144
gen_from_pm4_qp4
glucat::gen::generator_table, 144
gen_from_pp4_qm4
glucat::gen::generator_table, 144
gen_from_qp1_pm1
glucat::gen::generator_table, 144
gen_vector
glucat::gen::generator_table, 145
generator
glucat::gen::generator_table, 145
glucat::random_generator, 211
generator_table
glucat::gen::generator_table, 143
global.h
_GLUCAT_CTAssert, 257
glucat, 10
_GLUCAT_CTAssert, 23
abs, 23
acos, 23, 24
acosh, 24
asin, 25
asinh, 25, 26
atan, 26
atanh, 27
BITS_PER_SET_VALUE, 60
cascade_log, 27
check_complex, 28
clifford_exp, 28
compare, 28
complexifier, 29
conj, 29
cos, 29, 30
cosh, 30
crd_of_mult, 30, 31
DEFAULT_Basis_Max_Count, 60
DEFAULT_Div_Max_Steps, 60
DEFAULT_Fast_Size_Threshold, 61
DEFAULT_Function_Precision, 61
DEFAULT_HI, 61
DEFAULT_Inv_Fast_Dim_Threshold, 61
DEFAULT_Log_Max_Inner_Steps, 61
DEFAULT_Log_Max_Outer_Steps, 61
DEFAULT_Mult_Matrix_Threshold, 62
DEFAULT_Products_Size_Threshold, 62
DEFAULT_Sqrt_Max_Steps, 62
DEFAULT_TRUNCATION, 62
db_sqrt, 31
db_step, 31
elliptic, 31
even, 32
exp, 32
fast, 33
folded_dim, 33
imag, 33
index_t, 21
intfn, 21
intintfn, 22
inv, 34
inverse_gray, 34
inverse_reversed_gray, 34
involute, 34
l_ln2, 62
l_pi, 62
log, 35, 36
log2, 36
MS_PER_S, 63
matrix_log, 36
matrix_sqrt, 37
max_abs, 37
max_pos, 37
min_neg, 38
norm, 38
odd, 38
offset_level, 38
operator &, 39, 40
operator!=, 41

operator<<, 47, 48
operator>>, 48, 49
operator*, 42–44
operator^, 49, 50
operator+, 44, 45
operator-, 45
operator/, 46, 47
operator%, 41, 42
operator|, 50, 51
outer_pow, 51
pade_approx, 51
pade_log, 51
pos_mod, 52
pow, 52
precision_t, 22
pure, 53
quad, 53
real, 53
reframe, 53
reverse, 54
scalar, 54
set_value_t, 22
sign_of_square, 54
sin, 55
sinh, 55
sqrt, 56, 57
star, 57
tan, 58
tanh, 58
to_demote, 59
to_promote, 59
try_catch, 59
vector_part, 60
glucat/clifford_algebra.h, 231
glucat/clifford_algebra_imp.h, 238
glucat/errors.h, 245
glucat/errors_imp.h, 246
glucat/framed_multi.h, 246
glucat/framed_multi_imp.h, 249
glucat/generation.h, 252
glucat/generation_imp.h, 254
glucat/global.h, 254
glucat/glucat.h, 257
glucat/glucat_config.h, 258
glucat/glucat_imp.h, 262
glucat/index_set.h, 263
glucat/index_set_imp.h, 265
glucat/long_double.h, 266
glucat/matrix.h, 267
glucat/matrix_imp.h, 269
glucat/matrix_multi.h, 271
glucat/matrix_multi_imp.h, 274
glucat/portability.h, 276
glucat/qd.h, 278
glucat/random.h, 279
glucat/scalar.h, 280
glucat/scalar_imp.h, 282
glucat::CTAssertion< bool >, 118
glucat::CTAssertion< true >, 119
glucat::basis_table
~basis_table, 80
basis, 81
basis_table, 80
friend_for_private_destructor, 81
operator=, 81
glucat::basis_table< Scalar_T, LO, HI, Matrix_T >, 79
glucat::bool_to_type< truth_value >, 82
glucat::clifford_algebra
~clifford_algebra, 104
classname, 104
conj, 104
even, 104
frame, 105
grade, 105
index_set_t, 103
inv, 105
involute, 105
isnan, 105
max_abs, 106
multivector_t, 103
norm, 106
odd, 106
operator &=, 106
operator*=, 107
operator^=, 109
operator(), 107
operator+=, 107
operator-, 108
operator-=, 108
operator/=, 108
operator==, 108, 109
operator%=, 106
operator[], 109
operator|=, 109
outer_pow, 109
pair_t, 103
pow, 110
pure, 110
quad, 110
reverse, 110
scalar, 110
scalar_t, 103
truncated, 111
vector_part, 111
vector_t, 103
write, 111
glucat::clifford_algebra< Scalar_T, Index_Set_↩
T, Multivector_T >, 101
glucat::compare_types< LHS_T, RHS_T >, 112
glucat::compare_types< T, T >, 113
glucat::control_t, 113
~control_t, 115
call, 115, 116
catch_exceptions, 116
control, 116
control_t, 115

friend_for_private_destructor, 117
m_catch_exceptions, 117
m_valid, 118
m_verbose_output, 118
operator=, 116
valid, 117
verbose, 117
glucat::error
classname, 123
error, 123
heading, 123
print_error_msg, 124
glucat::error< Class_T >, 122
glucat::framed_multi
~framed_multi, 131
centre_pm4_qp4, 135
centre_pp4_qm4, 135
centre_qp1_pm1, 135
classname, 136
const_iterator, 127
divide, 136
error_t, 128
exp, 139
fast, 136
fast_framed_multi, 137
fast_matrix_multi, 137
fold, 137
framed_multi, 131–134, 139
framed_multi_t, 128
framed_pair_t, 128
index_set_t, 128
iterator, 128
map_t, 129
matrix_multi, 139
matrix_multi_t, 129
matrix_t, 129
multivector_t, 129
nbr_terms, 138
operator &, 139
operator<<, 140
operator>>, 141
operator*, 140
operator^, 141
operator+=, 138
operator/, 140
operator%, 140
operator|, 141
random, 138
scalar_t, 129
size_type, 130
sorted_map_t, 130
star, 141
term_t, 130
unfold, 138
var_term_t, 130
vector_t, 130
glucat::framed_multi< Scalar_T, LO, HI >, 124
glucat::framed_multi< Scalar_T, LO, HI >::hash_size_t, 149
glucat::framed_multi< Scalar_T, LO, HI >::var_term, 227
glucat::framed_multi::hash_size_t
hash_size_t, 149
n, 150
operator(), 149
glucat::framed_multi::var_term
~var_term, 229
classname, 230
operator*=, 230
var_pair_t, 229
var_term, 229
glucat::gen, 63
offset_to_super, 64
signature_t, 63
glucat::gen::generator_table
~generator_table, 143
friend_for_private_destructor, 146
gen_from_pm1_qm1, 144
gen_from_pm4_qp4, 144
gen_from_pp4_qm4, 144
gen_from_qp1_pm1, 144
gen_vector, 145
generator, 145
generator_table, 143
operator(), 145
operator=, 145
glucat::gen::generator_table< Matrix_T >, 142
glucat::glucat_error, 146
~glucat_error, 147
classname, 148
glucat_error, 147
heading, 148
name, 148
print_error_msg, 148
glucat::index_set
BOOST_STATIC_ASSERT, 156
bitset_t, 153
classname, 156
compare, 164
count, 156
count_neg, 156
count_pos, 156
error_t, 153
flip, 157
fold, 157
hash_fn, 158
index_pair_t, 153
index_set, 154, 155
index_set_t, 154
is_contiguous, 158
lex_less_than, 158
max, 158
min, 159
operator &, 164
operator &=, 159

operator!=, 159
operator<, 159
operator~, 161
operator^, 164
operator^=, 160
operator==, 160
operator[], 160
operator|, 164
operator|=, 161
reference, 164
reset, 161
set, 162
sign_of_mult, 162
sign_of_square, 163
test, 163
unfold, 163
v_hi, 165
v_lo, 165
value_of_fold, 163
glucat::index_set< LO, HI >, 150
glucat::index_set< LO, HI >::reference, 214
glucat::index_set::reference
~reference, 215
flip, 216
index_set, 217
m_idx, 217
m_pst, 217
operator bool, 216
operator~, 217
operator=, 216
reference, 215
glucat::index_set_hash
index_set_t, 176
operator(), 176
glucat::index_set_hash< LO, HI >, 175
glucat::matrix, 64
classify_eigenvalues, 66
eig_case_t, 65
eigenvalues, 66
inner, 66
isnan, 66
kron, 67
mono_kron, 67
mono_prod, 67
nnz, 67
nork, 68
nork_range, 68
norm_frob2, 68
prod, 69
signed_perm_nork, 69
sparse_prod, 69
to_lapack, 69
trace, 70
unit, 70
glucat::matrix::eig_genus
m_eig_case, 121
m_safe_arg, 121
Scalar_T, 121
glucat::matrix::eig_genus< Matrix_T >, 120
glucat::matrix_multi
~matrix_multi, 183
basis_element, 188
basis_matrix_t, 180
classname, 188
error_t, 180
fast_framed_multi, 188
fast_matrix_multi, 189
framed_multi, 190
framed_multi_t, 180
index_set_t, 181
m_frame, 193
m_matrix, 193
matrix_index_t, 181
matrix_log, 190
matrix_multi, 183–187, 190
matrix_multi_t, 181
matrix_sqrt, 190
matrix_t, 181
multivector_t, 181
operator &, 191
operator<<, 191, 192
operator>>, 192
operator*, 191
operator^, 192
operator+=, 189
operator/, 191
operator=, 189
operator%, 191
operator|, 192
orientation_t, 182
random, 189
reframe, 192
scalar_t, 182
star, 193
term_t, 182
vector_t, 182
glucat::matrix_multi< Scalar_T, LO, HI >, 177
glucat::numeric_traits
abs, 198
acos, 198
asin, 199
atan, 199
conj, 199
cos, 199
cosh, 200
exp, 200
fmod, 200
imag, 200
isInf, 201
isNaN_or_isInf, 202
isNaN, 201, 202
ln_2, 202, 203
log, 203
log2, 203
NaN, 203
pi, 204

pow, 204
real, 204
sin, 205
sinh, 205
sqrt, 205
tan, 205
tanh, 206
to_double, 206
to_int, 206
to_scalar_t, 206–208
glucat::numeric_traits< Scalar_T >, 196
glucat::numeric_traits< Scalar_T >::demoted<>, 119
glucat::numeric_traits< Scalar_T >::promoted, 209
glucat::numeric_traits::demoted
type, 120
glucat::numeric_traits::promoted
type, 209
glucat::random_generator
~random_generator, 211
friend_for_private_destructor, 212
generator, 211
normal, 211
normal_dist, 212
operator=, 212
random_generator, 211
seed, 213
uint_gen, 213
uniform, 212
uniform_dist, 213
glucat::random_generator< Scalar_T >, 210
glucat::sorted_range
map_t, 218
sorted_begin, 219
sorted_end, 220
sorted_iterator, 219
sorted_map_t, 219
sorted_range, 219
glucat::sorted_range< Map_T, Sorted_Map_T >, 218
glucat::sorted_range< Sorted_Map_T, Sorted_Map_T >, 220
map_t, 221
sorted_begin, 221
sorted_end, 222
sorted_iterator, 221
sorted_map_t, 221
sorted_range, 221
glucat::timing, 70
EXTRA_TRIALS, 71
elapsed, 71
MS_PER_CLOCK, 71
MS_PER_SEC, 71
glucat::tuning
function_precision, 227
glucat::tuning< Mult_Matrix_Threshold, Div_Max_Steps, Sqrt_Max_Steps, Log_Max_Outer_Steps, Log_Max_Inner_Steps, Basis_Max_Count, Fast_Size_Threshold, Inv_Fast_Dim_Threshold, Products_Size_Threshold, Function_Precision >, 222
glucat_config.h
GLUCAT_HAVE_INTTYPES_H, 259
GLUCAT_HAVE_MEMORY_H, 259
GLUCAT_HAVE_STDINT_H, 259
GLUCAT_HAVE_STDLIB_H, 259
GLUCAT_HAVE_STRING_H, 260
GLUCAT_HAVE_STRINGS_H, 260
GLUCAT_HAVE_SYS_STAT_H, 260
GLUCAT_HAVE_SYS_TYPES_H, 260
GLUCAT_HAVE_UNISTD_H, 260
GLUCAT_PACKAGE_BUGREPORT, 261
GLUCAT_PACKAGE_NAME, 261
GLUCAT_PACKAGE_STRING, 261
GLUCAT_PACKAGE_TARNAME, 261
GLUCAT_PACKAGE_URL, 261
GLUCAT_PACKAGE_VERSION, 261
GLUCAT_PACKAGE, 260
GLUCAT_STDC_HEADERS, 262
GLUCAT_VERSION, 262
glucat_error
glucat::glucat_error, 147
grade
glucat::clifford_algebra, 105

hash_fn
glucat::index_set, 158
PyClical::index_set, 173
hash_size_t
glucat::framed_multi::hash_size_t, 149
heading
glucat::error, 123
glucat::glucat_error, 148
hi_ndx
PyClical.h, 287

i
PyClical, 76
imag
glucat, 33
glucat::numeric_traits, 200
index_pair_t
glucat::index_set, 153
index_set
glucat::index_set, 154, 155
glucat::index_set::reference, 217
index_set_hidden_doctests
PyClical, 74
index_set_t
glucat::clifford_algebra, 103
glucat::framed_multi, 128
glucat::index_set, 154
glucat::index_set_hash, 176
glucat::matrix_multi, 181
index_set_to_repr
PyClical.h, 286
index_set_to_str
PyClical.h, 287
index_t

glucat, 21
IndexSet
PyClical.h, 285
inner
glucat::matrix, 66
instance
PyClical::clifford, 100
PyClical::index_set, 175
intfn
glucat, 21
intintfn
glucat, 22
inv
glucat, 34
glucat::clifford_algebra, 105
PyClical::clifford, 95
inverse_gray
glucat, 34
inverse_reversed_gray
glucat, 34
involute
glucat, 34
glucat::clifford_algebra, 105
PyClical::clifford, 95
is_contiguous
glucat::index_set, 158
isInf
glucat::numeric_traits, 201
isNaN_or_isInf
glucat::numeric_traits, 202
isNaN
glucat::numeric_traits, 201, 202
isnan
glucat::clifford_algebra, 105
glucat::matrix, 66
PyClical::clifford, 96
ist
PyClical, 77
istpq
PyClical, 75
iterator
glucat::framed_multi, 128
ixt
PyClical, 77

kron
glucat::matrix, 67

l_ln2
glucat, 62
l_pi
glucat, 62
lex_less_than
glucat::index_set, 158
ln_2
glucat::numeric_traits, 202, 203
lo_ndx
PyClical.h, 287
log
glucat, 35, 36
glucat::numeric_traits, 203
log2
glucat, 36
glucat::numeric_traits, 203

m_catch_exceptions
glucat::control_t, 117
m_eig_case
glucat::matrix::eig_genus, 121
m_frame
glucat::matrix_multi, 193
m_idx
glucat::index_set::reference, 217
m_matrix
glucat::matrix_multi, 193
m_pst
glucat::index_set::reference, 217
m_safe_arg
glucat::matrix::eig_genus, 121
m_valid
glucat::control_t, 118
m_verbose_output
glucat::control_t, 118
MS_PER_CLOCK
glucat::timing, 71
MS_PER_SEC
glucat::timing, 71
MS_PER_S
glucat, 63
map_t
glucat::framed_multi, 129
glucat::sorted_range, 218
glucat::sorted_range< Sorted_Map_T, Sorted_↩
Map_T >, 221
matrix_index_t
glucat::matrix_multi, 181
matrix_log
glucat, 36
glucat::matrix_multi, 190
matrix_multi
glucat::framed_multi, 139
glucat::matrix_multi, 183–187, 190
matrix_multi_t
glucat::framed_multi, 129
glucat::matrix_multi, 181
matrix_sqrt
glucat, 37
glucat::matrix_multi, 190
matrix_t
glucat::framed_multi, 129
glucat::matrix_multi, 181
max
glucat::index_set, 158
PyClical::index_set, 173
max_abs
glucat, 37
glucat::clifford_algebra, 106
PyClical::clifford, 96

max_pos
glucat, 37
min
glucat::index_set, 159
PyClical::index_set, 174
min_neg
glucat, 38
mono_kron
glucat::matrix, 67
mono_prod
glucat::matrix, 67
multivector_t
glucat::clifford_algebra, 103
glucat::framed_multi, 129
glucat::matrix_multi, 181

n
glucat::framed_multi::hash_size_t, 150
name
glucat::glucat_error, 148
NaN
glucat::numeric_traits, 203
nbar3
PyClical, 77
nbr_terms
glucat::framed_multi, 138
ninf3
PyClical, 77
nnz
glucat::matrix, 67
nork
glucat::matrix, 68
nork_range
glucat::matrix, 68
norm
glucat, 38
glucat::clifford_algebra, 106
PyClical::clifford, 96
norm_frob2
glucat::matrix, 68
normal
glucat::random_generator, 211
normal_dist
glucat::random_generator, 212

obj
PyClical, 77
odd
glucat, 38
glucat::clifford_algebra, 106
PyClical::clifford, 97
offset_level
glucat, 38
offset_to_super
glucat::gen, 64
operator &
glucat, 39, 40
glucat::framed_multi, 139
glucat::index_set, 164
glucat::matrix_multi, 191
operator &=
glucat::clifford_algebra, 106
glucat::index_set, 159
operator bool
glucat::index_set::reference, 216
operator!=
glucat, 41
glucat::index_set, 159
operator<
glucat::index_set, 159
operator<<
glucat, 47, 48
glucat::framed_multi, 140
glucat::matrix_multi, 191, 192
operator>>
glucat, 48, 49
glucat::framed_multi, 141
glucat::matrix_multi, 192
operator*
glucat, 42–44
glucat::framed_multi, 140
glucat::matrix_multi, 191
operator*=
glucat::clifford_algebra, 107
glucat::framed_multi::var_term, 230
operator~
glucat::index_set, 161
glucat::index_set::reference, 217
operator^
glucat, 49, 50
glucat::framed_multi, 141
glucat::index_set, 164
glucat::matrix_multi, 192
operator^=
glucat::clifford_algebra, 109
glucat::index_set, 160
operator()
glucat::clifford_algebra, 107
glucat::framed_multi::hash_size_t, 149
glucat::gen::generator_table, 145
glucat::index_set_hash, 176
operator+
glucat, 44, 45
operator+=
glucat::clifford_algebra, 107
glucat::framed_multi, 138
glucat::matrix_multi, 189
operator-
glucat, 45
glucat::clifford_algebra, 108
operator-=
glucat::clifford_algebra, 108
operator/
glucat, 46, 47
glucat::framed_multi, 140
glucat::matrix_multi, 191
operator/=

glucat::clifford_algebra, 108
operator=
glucat::basis_table, 81
glucat::control_t, 116
glucat::gen::generator_table, 145
glucat::index_set::reference, 216
glucat::matrix_multi, 189
glucat::random_generator, 212
operator==
glucat::clifford_algebra, 108, 109
glucat::index_set, 160
operator%
glucat, 41, 42
glucat::framed_multi, 140
glucat::matrix_multi, 191
operator%=
glucat::clifford_algebra, 106
operator[]
glucat::clifford_algebra, 109
glucat::index_set, 160
operator|
glucat, 50, 51
glucat::framed_multi, 141
glucat::index_set, 164
glucat::matrix_multi, 192
operator|=
glucat::clifford_algebra, 109
glucat::index_set, 161
orientation_t
glucat::matrix_multi, 182
outer_pow
glucat, 51
glucat::clifford_algebra, 109
PyClical::clifford, 97

PY_SSIZE_T_CLEAN
PyClical.cpp, 283
PyClical_nocython.cpp, 289
pade_approx
glucat, 51
pade_log
glucat, 51
pair_t
glucat::clifford_algebra, 103
pi
glucat::numeric_traits, 204
PyClical, 78
portability.h
_GLUCAT_ISINF, 277
_GLUCAT_ISNAN, 277
UBLAS_ABS, 277
UBLAS_SQRT, 278
pos_mod
glucat, 52
pow
glucat, 52
glucat::clifford_algebra, 110
glucat::numeric_traits, 204
PyClical::clifford, 97
precision_t
glucat, 22
tuning.h, 293
print_error_msg
glucat::error, 124
glucat::glucat_error, 148
prod
glucat::matrix, 69
pure
glucat, 53
glucat::clifford_algebra, 110
PyClical::clifford, 98
PyClical, 72
__version__, 76
_test, 72
cl, 76
clifford_hidden_doctests, 72
e, 74
fill, 76
i, 76
index_set_hidden_doctests, 74
ist, 77
istpq, 75
ixt, 77
nbar3, 77
ninf3, 77
obj, 77
pi, 78
tau, 78
PyClical.clifford, 83
PyClical.cpp
PY_SSIZE_T_CLEAN, 283
PyClical.h
Clifford, 285
clifford_to_repr, 286
clifford_to_str, 286
hi_ndx, 287
index_set_to_repr, 286
index_set_to_str, 287
IndexSet, 285
lo_ndx, 287
PyFloat_FromDouble, 287
scalar_t, 285
String, 285
Tune_P, 286
PyClical.index_set, 165
PyClical::clifford
__add__, 84
__and__, 85
__call__, 85
__cinit__, 85
__contains__, 86
__dealloc__, 86
__div__, 86
__getitem__, 87
__iadd__, 87
__iand__, 87
__idiv__, 88

__imod__, 88
__imul__, 88
__ior__, 89
__isub__, 89
__iter__, 89
__ixor__, 90
__mod__, 90
__mul__, 90
__neg__, 91
__or__, 91
__pos__, 91
__pow__, 92
__repr__, 92
__richcmp__, 92
__str__, 93
__sub__, 93
__xor__, 93
abs, 94
conj, 94
even, 94
frame, 95
instance, 100
inv, 95
involute, 95
isnan, 96
max_abs, 96
norm, 96
odd, 97
outer_pow, 97
pow, 97
pure, 98
quad, 98
reframe, 98
reverse, 99
scalar, 99
truncated, 99
vector_part, 100
PyClical::index_set
__and__, 167
__cinit__, 167
__contains__, 167
__dealloc__, 168
__getitem__, 168
__iand__, 168
__invert__, 169
__ior__, 169
__iter__, 169
__ixor__, 170
__or__, 170
__repr__, 170
__richcmp__, 171
__setitem__, 171
__str__, 171
__xor__, 172
count, 172
count_neg, 172
count_pos, 173
hash_fn, 173
instance, 175
max, 173
min, 174
sign_of_mult, 174
sign_of_square, 174
PyClical_nocython.cpp
PY_SSIZE_T_CLEAN, 289
PyFloat_FromDouble
PyClical.h, 287
pyclical/PyClical.cpp, 283
pyclical/PyClical.h, 284
pyclical/PyClical.pxd, 288
pyclical/PyClical.pyx, 288
pyclical/PyClical_nocython.cpp, 289
pyclical/glucat.pxd, 283

quad
glucat, 53
glucat::clifford_algebra, 110
PyClical::clifford, 98

random
glucat::framed_multi, 138
glucat::matrix_multi, 189
random_generator
glucat::random_generator, 211
real
glucat, 53
glucat::numeric_traits, 204
reference
glucat::index_set, 164
glucat::index_set::reference, 215
reframe
glucat, 53
glucat::matrix_multi, 192
PyClical::clifford, 98
reset
glucat::index_set, 161
reverse
glucat, 54
glucat::clifford_algebra, 110
PyClical::clifford, 99

scalar
glucat, 54
glucat::clifford_algebra, 110
PyClical::clifford, 99
Scalar_T
glucat::matrix::eig_genus, 121
scalar_t
glucat::clifford_algebra, 103
glucat::framed_multi, 129
glucat::matrix_multi, 182
PyClical.h, 285
seed
glucat::random_generator, 213
set
glucat::index_set, 162
set_value_t

glucat, 22
sign_of_mult
glucat::index_set, 162
PyClical::index_set, 174
sign_of_square
glucat, 54
glucat::index_set, 163
PyClical::index_set, 174
signature_t
glucat::gen, 63
signed_perm_nork
glucat::matrix, 69
sin
glucat, 55
glucat::numeric_traits, 205
sinh
glucat, 55
glucat::numeric_traits, 205
size_type
glucat::framed_multi, 130
sorted_begin
glucat::sorted_range, 219
glucat::sorted_range< Sorted_Map_T, Sorted_↩ Map_T >, 221
sorted_end
glucat::sorted_range, 220
glucat::sorted_range< Sorted_Map_T, Sorted_↩ Map_T >, 222
sorted_iterator
glucat::sorted_range, 219
glucat::sorted_range< Sorted_Map_T, Sorted_↩ Map_T >, 221
sorted_map_t
glucat::framed_multi, 130
glucat::sorted_range, 219
glucat::sorted_range< Sorted_Map_T, Sorted_↩ Map_T >, 221
sorted_range
glucat::sorted_range, 219
glucat::sorted_range< Sorted_Map_T, Sorted_↩ Map_T >, 221
sparse_prod
glucat::matrix, 69
sqrt
glucat, 56, 57
glucat::numeric_traits, 205
star
glucat, 57
glucat::framed_multi, 141
glucat::matrix_multi, 193
std, 78
std::numeric_limits< glucat::framed_multi< Scalar_T, LO, HI > >, 194
std::numeric_limits< glucat::matrix_multi< Scalar_T, LO, HI > >, 195
String
PyClical.h, 285

tan
glucat, 58
glucat::numeric_traits, 205
tanh
glucat, 58
glucat::numeric_traits, 206
tau
PyClical, 78
term_t
glucat::framed_multi, 130
glucat::matrix_multi, 182
test
glucat::index_set, 163
test/control.h, 289
test/driver.h, 290
test/timing.h, 290
test/try_catch.h, 291
test/tuning.h, 292
test/undefine.h, 295
Test_Tuning_Function_Precision
tuning.h, 295
Test_Tuning_Max_Threshold
tuning.h, 295
to_demote
glucat, 59
to_double
glucat::numeric_traits, 206
to_int
glucat::numeric_traits, 206
to_lapack
glucat::matrix, 69
to_promote
glucat, 59
to_scalar_t
glucat::numeric_traits, 206–208
trace
glucat::matrix, 70
truncated
glucat::clifford_algebra, 111
PyClical::clifford, 99
try_catch
glucat, 59
Tune_P
PyClical.h, 286
tuning.h, 293
tuning.h
_GLUCAT_CTAssert, 295
__TEST_TUNING_DEFAULT_CONSTANT, 293–295
precision_t, 293
Test_Tuning_Function_Precision, 295
Test_Tuning_Max_Threshold, 295
Tune_P, 293
type
glucat::numeric_traits::demoted, 120
glucat::numeric_traits::promoted, 209

UBLAS_ABS
portability.h, 277
UBLAS_SQRT

portability.h, 278
uint_gen
glucat::random_generator, 213
unfold
glucat::framed_multi, 138
glucat::index_set, 163
uniform
glucat::random_generator, 212
uniform_dist
glucat::random_generator, 213
unit
glucat::matrix, 70

v_hi
glucat::index_set, 165
v_lo
glucat::index_set, 165
valid
glucat::control_t, 117
value_of_fold
glucat::index_set, 163
var_pair_t
glucat::framed_multi::var_term, 229
var_term
glucat::framed_multi::var_term, 229
var_term_t
glucat::framed_multi, 130
vector_part
glucat, 60
glucat::clifford_algebra, 111
PyClical::clifford, 100
vector_t
glucat::clifford_algebra, 103
glucat::framed_multi, 130
glucat::matrix_multi, 182
verbose
glucat::control_t, 117

write
glucat::clifford_algebra, 111